

HSK – Your partner for plastic welding – and bending technology

Hand welding extruder HSK40 RFX /HSK40 RSX



BASIC EXTRUDER		
<ul style="list-style-type: none"> ▪ Extrusion welding from PEHD, PP, PVDF and PVC* ▪ temperature probe, location in the melt chamber ▪ rod feeding, no additional gearing ▪ Control units for actual / desired mass and air temperature ▪ Cold start protection ▪ Rod diameter 3,4 and 5 mm ▪ 1 pce nozzle blank included 		
		*PVC with special screw
TECHNICAL DATA		
Output	3.8 kg/h (with PEHD rod 5 mm)	
Heating extruder	700 W / air 2200 W	
Drive	1.100 W	
Air requirement	300 l/min.	
Voltage	230 V / 50Hz	
Weight	8 kg	
Guarantee	screw and cylinder 24 months	
HSK40 RSX (WITH HOT AIR BLOWER)		
<ul style="list-style-type: none"> ▪ Works as basic extruder, without external air supply ▪ Hot air blower controlled (air quantity 300 l/min) ▪ Technical data see basic extruder ▪ Heating hot air blower 2200 W 		
ADDITIONAL EQUIPMENT		
<ul style="list-style-type: none"> ▪ Welding nozzles ▪ Transportation box ▪ Welding rod 	<ul style="list-style-type: none"> Extruder nozzle preheating Prolongation Widen 	<ul style="list-style-type: none"> Angle adaptor Air compactor
<p>Technical execution subject to modifications</p>		

Larry Rowold
 PLASTIC FABRICATION CONSULTANT
 1010 VERMONT AVE
 THE VILLAGES, FL 32159

email: larowold@gmail.com
 Cell phone: 630-319-3480