

# Panasonic

## MULTI SPLIT SYSTEM AIR CONDITIONERS



**INVERTER**



## Testing Products to Ensure Reliability & Durability

At Panasonic, we believe that the best air conditioner is one that works quietly and effectively in the background whilst minimising its impact on the environment. People who use our products can look forward to many years of high-quality performance without the need for constant maintenance.

As part of our rigorous design and development process, Panasonic air conditioners undergo a variety of stringent tests to ensure their effectiveness and long-term reliability. Tests for durability, waterproofing, shock resistance and noise are conducted on component parts and on the finished products.

As a result of these painstaking efforts, Panasonic air conditioners meet even the most demanding industrial standards and regulations in every country where they are sold.

Applying advanced technologies that truly make life better, we live by an unparalleled commitment to product quality. Our approach to product development originates in the DNA of Japanese craftsmanship.

Panasonic is building on the Japanese tradition of uncompromising quality control worldwide, developing and manufacturing fine products and delivering them to customers everywhere.

## Durability

At Panasonic we know the importance of a long service life with minimal maintenance. That's why we subject our air conditioners to a wide range of stringent durability tests.



## Long-Term Durability Test

To ensure durability and stable operation for many years, we conduct a long-term, continuous operation test under conditions that are much more severe than actual operating conditions.



## Compressor Reliability Test

After the continuous operation test, we remove the compressor from a selected outdoor unit, disassemble it and examine the internal mechanisms and parts for potential failure. This helps to ensure reliable long-term performance under harsh conditions.



A silicone coated circuit board



## Waterproof Test

The outdoor unit, which is subject to rain and wind, complies with IPX4 waterproof specifications. Contact sections on printed circuit boards are silicone coated to prevent adverse effects caused by exposure to water (an unlikely occurrence).

## Shock Resistance

Impact and vibration tests ensure that the product's quality and performance at the time of final inspection are maintained upon delivery to the end user.



### Drop Test

Packaging has been strengthened to help products withstand large impacts caused by improper handling during transportation. Testing includes conventional vertical drops, along with more severe tests in which the sides, edges, or corners hit the ground first. This ensures that the products' rigidity and shock-absorbing materials are strong enough to prevent damage.

## Comfort

To keep every person in the room comfortable, Panasonic designs its air conditioners to work quietly in the background, without making their presence known.



### Noise Test

The operating noise of the indoor and outdoor units are measured in a high-performance anechoic chamber. These tests verify that operating noise is low enough to allow the user to talk and sleep comfortably whilst the product is operating.

## International Standard Quality

To uphold the company's reputation around the world, Panasonic continuously strives to offer the highest quality with the lowest possible environmental impact.



The strength of the resin material used in a propeller fan is confirmed by a tension test



### Reliable Parts That Meet or Exceed Industrial Standards

In every country where they are sold, Panasonic air conditioners comply with all required industrial standards and regulations. In addition, Panasonic conducts stringent testing to ensure the reliability of parts and materials.



### RoHS/REACH Compliant Parts

All Panasonic parts and materials comply with Europe's strict RoHS/REACH environmental regulations. During the development and production of parts, stringent inspections are conducted on over 100 materials to ensure that no hazardous substances are included.



### Sophisticated Production Process

Panasonic's air conditioner production lines employ state-of-the-art factory automation technologies to ensure products are manufactured efficiently and with uniformly high levels of quality and reliability.



# CLASS LEADING FEATURES

## Energy Saving Technology

Panasonic combines Inverter Technology and Economy Mode\* to create a powerhouse energy saving product. These clever technologies benefit both the environment and your power bill, so your green intentions don't have to prevent you from living a comfortable life.


\*Wall-mounted type only.



## Cleaner, Healthier Air

As well as a cool, comfortable home, a Panasonic air conditioner provides the ultimate peace of mind. The Anti-Bacterial Filter\* eliminates unwanted contaminants to make the air healthier for you and your family.

\*Wall-mounted type only.



## Quiet Operation

Panasonic systems are amongst the quietest in the world, so you can enjoy the comfort of running your air conditioner at night and still have a relaxing sleep. The outdoor unit is also very quiet which means you don't have to worry about keeping your neighbours up either.




\*1 Allergen deactivation was certified by Shinshu University. Allergen: Cider Pollen Allergen Cry j1 \*2 Bacteria deactivation was certified by Boken Quality Evaluation Institute. Test Report No: 10042459-1 and 10042459-2 Bacteria: Staphylococcus aureus NBRC 12732; Escherichia coli NBRC 3972 \*3 Virus deactivation was certified by Osaka Prefectural Institute of Public Health. Test Report No: 313360397 Virus: Influenza (H3N2) A/Hong Kong \*4 Certified by Boken Quality Evaluation Institute. Test Report No: 000366-3 Mould: Aspergillus niger ATCC 6275

## Control, Comfort & Reassurance



### Aussie Temperatures

Our air conditioning systems boast an outstanding operating temperature range. Cooling operation is possible even when it is a scorching +46°C outside, which is perfect for Australia's hot summer days. The heating operation is designed to operate even when it's a freezing -15°C outside, ensuring even the coldest parts of Australia are comfortable.



### Built Tough

Panasonic outdoor units are built to last in the harsh Australian environment. To ensure you will enjoy many years of reliable comfort from your air conditioner, the internal components of the outdoor unit are coated with a special blue coating that protects the unit from the damaging effects of salty air, dust, wind and rain.



### Count on Panasonic

Panasonic air conditioners are manufactured to the highest quality standards to ensure years of reliable comfort. We even back our reliability by offering a full 5-year parts and labour warranty.

# ULTRA SLIM DUCTED



## Ultra Slim Ducted



Wired Remote Controller Included

Model No	CS-E9SD3RW   CS-E12SD3RW   CS-E18SD3RW		
Capacity	2.6kW	3.7kW	5.0kW

- Market-leading Energy Efficiency
- Only 200mm High
- Rear or Bottom Return Air
- Built-in Drain Pump (500mm lift\*)
- -15°C to +46°C Operating Range

\*Refer to Technical Manual for more details



## Specifications

 Cooling  
Heating

240V / 1 Phase / 50 Hz			Ultra Slim Ducted		
			CS-E9SD3RW (CU-E9SD3R)	CS-E12SD3RW (CU-E12SD3R)	CS-E18SD3RW (CU-E18SD3R)
Cooling/Heating Capacity	kW		2.60(0.85-3.20) 3.30(0.85-4.50)	3.70(0.85-4.00) 4.20(0.85-5.10)	5.00(0.90-5.70) 6.10(0.90-7.10)
AEER/EER ACOP/COP	W/W		4.01/4.19 3.80/3.93	3.49/3.59 3.72/3.82	3.26/3.33 3.52/3.59
Electrical Data	Voltage	V	240 240	240 240	240 240
	Running Current	A	2.8 3.8	4.4 4.7	6.5 7.4
	Power Input	kW	0.62(0.23-0.97) 0.84(0.22-1.36)	1.03(0.23-1.15) 1.10(0.22-1.50)	1.50(0.29-1.8) 1.70(0.33-2.05)
Airflow (max @ 10 Pa) - Cooling	L/s		231	241	293
Airflow (max @ 10 Pa) - Heating	L/s		231	241	293
Adjustable Static Pressure Range	Pa		0-78	0-84	0-114
Noise Indoor	dB-A (H/L/Q-Lo)		32/27/24 34/28/25	33/27/24 35/28/25	41/30/27 41/32/29
	Power Level dB		48/43/40 50/44/41	49/43/40 51/44/41	57/46/43 57/48/45
Noise Outdoor	dB-A (H/L/Q-Lo)		46/-/- 46/-/-	49/-/- 50/-/-	48/-/43 49/-/44
	Power Level dB		61/-/- 61/-/-	64/-/- 65/-/-	62/-/57 63/-/58
Dimensions	Height x Width x Depth	mm	200x750x640 (619x824x299)	200x750x640 (619x824x299)	200x750x640 (795x875x320)
Net Weight	kg		19(33)	19(33)	19(52)
Refrigerant Pipe Diameter	Liquid Side	mm/(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Side	mm/(inch)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)
Power Supply			Outdoor	Outdoor	Outdoor
Pipe Length	Min~Max (m)		3-15	3-15	3-30
Pipe Length for Additional Gas	m		7.5	7.5	10
Additional Gas Amount	g/m		20	20	20
Operating Range (Outdoor)	Cooling	Degree (°C)	5-46	5-46	5-46
	Heating	Degree (°C)	-15 -24	-15 -24	-15 -24
Drain Pipe Size	mm		VP-20	VP-20	VP-20

## Outdoor


 CU-E9SD3R  
CU-E12SD3R


CU-E18SD3R



# BULKHEAD DUCTED



## Bulkhead Ducted



Wired Remote  
Controller  
Included

Model No	CS-E9QD3RW	CS-E12QD3RW	CS-E18QD3RW
Capacity	2.5kW	3.4kW	5.0kW

- Market-leading Energy Efficiency
- Only 370mm Deep
- Easy Installation
- Built-in Drain Pump (200mm lift\*)
- -15°C to +46°C Operating Range

\*Refer to Technical Manual for more details





## Specifications

 Cooling  
 Heating

240V / 1 Phase / 50 Hz			Bulkhead Ducted		
			CS-E9QD3RW (CU-E9QD3R)	CS-E12QD3RW (CU-E12QD3R)	CS-E18QD3RW (CU-E18QD3R)
Cooling/Heating Capacity	kW	2.50(0.85-3.10) 3.20(0.85-4.40)	3.40(0.85-4.00) 4.00(0.85-5.10)	5.00(0.90-5.70) 6.10(0.90-7.10)	
AEER/EER ACOP/COP	W/W	3.66/3.85 3.51/3.64	3.47/3.58 3.30/3.39	3.18/3.25 3.24/3.30	
Electrical Data	Voltage	V	240 240	240 240	
	Running Current	A	3.0 3.9	4.1 5.1	
	Power Input	kW	0.65(0.23-0.88) 0.88(0.22-1.36)	0.95(0.23-1.18) 1.18(0.22-1.6)	1.54(0.29-1.84) 1.85(0.33-2.20)
Airflow (max @ 10 Pa) - Cooling	L/s	250	256	286	
Airflow (max @ 10 Pa) - Heating	L/s	259	263	294	
Adjustable Static Pressure	Pa	0-124	0-140	0-147	
Noise Indoor	dB-A (H/L/Q-Lo)	32/27/24 34/28/25	33/27/24 35/28/25	42/30/27 42/32/29	
	Power Level dB	48/43/40 50/44/41	49/43/40 51/44/41	48/46/43 48/48/45	
Noise Outdoor	dB-A (H/L/Q-Lo)	46/-/- 48/-/-	49/-/- 50/-/-	48/43 49/44	
	Power Level dB	61/-/- 63/-/-	64/-/- 65/-/-	62/57 63/58	
Dimensions	Height x Width x Depth	mm	235x750x370 (619x824x299)	235x750x370 (619x824x299)	285x750x370 (795x875x320)
Net Weight	kg	17(33)	17(33)	18(52)	
Refrigerant Pipe Diameter	Liquid Side	mm/(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Side	mm/(inch)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)
Power Supply		Outdoor	Outdoor	Outdoor	
Pipe Length	Min-Max (m)	3-15	3-15	3-30	
Pipe Length for Additional Gas	m	7.5	7.5	10	
Additional Gas Amount	g/m	20	20	20	
Operating Range (Outdoor)	Cooling	Degree (°C)	5-46	5-46	5-46
	Heating	Degree (°C)	-15 -24	-15 -24	-15 -24
Drain Pipe Size	mm	VP-20	VP-20	VP-20	

## Outdoor


 CU-E9QD3R  
 CU-E12QD3R


CU-E18QD3R



# 4-WAY MINI CASSETTE



## 4-Way Mini Cassette



Panel CZ-BT20E



Wireless Remote Controller Included



CZ-RD52CP Wired Remote Controller (Optional)



Model No	CS-E9SB4RW	CS-E12QB4RW	CS-E18QB4RW
Capacity	2.5kW	3.4kW	4.8kW

- Market-leading Energy Efficiency
- Compact Design (260mm High)
- Easy Installation
- Built-in Drain Pump (600mm lift\*)
- -15°C to +46°C Operating Range

\*Refer to Technical Manual for more details



## Specifications

 Cooling  
 Heating

240V / 1 Phase / 50 Hz			4-Way Mini Cassette		
			CS-E9SB4RW (CU-E9SB4R)	CS-E12QB4RW (CU-E12QB4R)	CS-E18QB4RW (CU-E18QB4R)
Cooling/Heating Capacity	kW	2.50(0.85-3.20) 3.20(0.85-4.70)	3.40(0.85-4.00) 4.00(0.85-5.40)	4.80(0.90-5.70) 5.00(0.90-7.10)	
AEER/EER ACOP/COP	W/W	4.29/4.55 3.94/4.10	3.73/3.86 3.70/3.81	3.23/3.31 3.24/3.31	
Electrical Data	Voltage	V	240 240	240 240	
	Running Current	A	2.5 3.5	3.9 4.6	
	Power Input	kW	0.55(0.22-0.9) 0.78(0.21-1.36)	0.88(0.22-1.18) 1.05(0.21-1.68)	1.45(0.29-1.93) 1.51(0.33-2.45)
Star Rating		4.0 3.0	2.5 2.5	1.5 2.0	
Airflow (Indoor/High)	L/s	175 182	175 195	195 208	
Noise Indoor	dB-A (H/L/Q-Lo)	34/26/23 35/28/25	35/26/23 37/28/25	38/28/25 39/29/26	
	Power Level dB	50/42/39 51/44/41	51/42/39 53/44/41	54/44/41 55/45/42	
Noise Outdoor	dB-A (H/L/Q-Lo)	46/-/- 46/-/- 61/-/- 61/-/-	49/- 50/- 64/- 65/-	48/43 49/44 62/57 63/58	
	Power Level dB				
Dimensions	Height x Width x Depth	mm	260x575x575 (619x824x299)	260x575x575 (619x824x299)	260x575x575 (795x875x320)
Net Weight	kg	18(33)	18(33)	18(52)	
Refrigerant Pipe Diameter	Liquid Side	mm/(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Side	mm/(inch)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)
Power Supply		Outdoor	Outdoor	Outdoor	
Pipe Length	Min~Max (m)	3-15	3-15	3-30	
Pipe Length for Additional Gas	m	7.5	7.5	10	
Additional Gas Amount	g/m	20	20	20	
Operating Range (Outdoor)	Cooling	Degree (°C)	5-46	5-46	5-46
	Heating	Degree (°C)	-15 -24	-15 -24	-15 -24
Drain Pipe Size	mm	VP-20/VP-25	VP-20/VP-25	VP-20/VP-25	

## Outdoor


 CU-E9SB4R  
 CU-E12QB4R


CU-E18QB4R



# MULTI SPLIT SYSTEM

## Advantages of the Inverter Multi Split System

Indoor unit

- A variety of indoor units
- Market-leading energy efficiency
- Anti-Bacterial Filter (Wall-mounted type only)
- Precise control of individual room temperature

Outdoor unit

- Space-saving  
52% less space than five single split types.



Single Split Type CU-Z9RKR

CU-5E34QBR

BIG SPACE SAVINGS



With a single outdoor unit, control up to 5 indoor units. (Maximum)

### Inverter control

The inverter offers energy-saving efficiency, quick comfort, and flexible power control. Our compressor saves more energy while reducing vibration, noise and unit size.





## MULTI SPLIT SYSTEM

### Wall-Mounted



Wireless Remote Controller Included



CZ-RD514C  
Wired Remote Controller (Optional)

Reverse cycle models

Model No	CS-MRE7QKR	CS-MRE9QKR	CS-MRE12QKR* <sup>1</sup>
Capacity	2.0kW	2.5kW	3.2kW
Model No	CS-MRE18QKR* <sup>1</sup>	CS-MRE24QKR* <sup>2*3</sup>	
Capacity	5.0kW	7.0kW	

### Ultra Slim Ducted



Wired Remote Controller Included

Model No	CS-ME7SD3R	CS-E9SD3RW	CS-E12SD3RW* <sup>1</sup>	CS-E18SD3RW* <sup>1</sup>
Capacity	2.0kW	2.5kW	3.2kW	5.0kW

### Bulkhead Ducted



Wired Remote Controller Included

Model No	CS-E9QD3RW	CS-E12QD3RW* <sup>1</sup>	CS-E18QD3RW* <sup>1</sup>
Capacity	2.5kW	3.2kW	5.0kW

### 4-Way Mini Cassette



Panel CZ-BT20E



Wireless Remote Controller Included



CZ-RD52CP  
Wired Remote Controller (Optional)

Model No	CS-E9SB4RW	CS-E12QB4RW* <sup>1</sup>	CS-E18QB4RW* <sup>1</sup>
Capacity	2.5kW	3.2kW	5.0kW

### Accessories



CZ-MA1P

\*<sup>1</sup> CZ-MA1P is to be used to reduce the connection size on the indoor unit from 1/2" to 3/8".




CZ-MA2P

\*<sup>2</sup> CZ-MA2P is to be used to increase the connection size on the outdoor unit from 3/8" to 1/2".



CZ-MA3P

\*<sup>3</sup> CZ-MA3P is to be used to reduce the connection size on the indoor unit from 5/8" to 1/2".









CZ-CAP2\*<sup>4</sup>

Demand response module CZ-CAP2.

# SPECIFICATIONS

## Specifications

Models	Indoor Units: Possible Combination Patterns Must be within capacity range	Indoor Units Combination Range	Refrigerant Pipe Diameter			Pipe Extension					Indoor Unit Combinations				
			Indoor Unit	Liquid Side	Gas Side	Maximum Pipe Length (1 room)	Maximum Pipe Length (Total)	Maximum Chargeless Length	Additional Gas	Maximum Height	Type Capacity [kW class]	Wall- Mounted	Cassette [4-Way]	Ultra Slim Ducted	Bulkhead Ducted
<b>Up to 2 rooms</b>  <b>CU-2E18SBR</b>   <b>5.2kW</b> *4  Dimensions (HxWxD): 619 x 924(+70) x 299 mm Weight: 39 kg	 PORT A: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT B: 2.0 or 2.5 or 3.2 or 5.0 * Either unit  * At least two indoor units must be connected.	4.0 to 7.5 kW	Room A	ø 6.35	ø 9.52	20 m	30 m	20 m	15 g/m	10 m	2.0	•		•	
			Room B	ø 6.35	ø 9.52						2.5	•	•	•	•
		Make sure to keep combinations within this range.	Room A	ø 6.35	ø 9.52	3.2	•	•	•	•					
			Room B	ø 6.35	ø 9.52	5.0	•	•	•	•					
<b>Up to 3 rooms</b>  <b>CU-3E18SBR</b>   <b>5.2kW</b> *4  Dimensions (HxWxD): 795 x 875(+95) x 320 mm Weight: 71 kg	 PORT A: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT B: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT C: 2.0 or 2.5 or 3.2 or 5.0 * Either unit  * At least two indoor units must be connected.	4.5 to 9.0 kW	Room A	ø 6.35	ø 9.52	25 m	50 m	30 m	20 g/m	15 m	2.0	•		•	
			Room B	ø 6.35	ø 9.52						2.5	•	•	•	•
		Make sure to keep combinations within this range.	Room A	ø 6.35	ø 9.52	3.2	•	•	•	•					
			Room B	ø 6.35	ø 9.52	5.0	•	•	•	•					
<b>Up to 4 rooms</b>  <b>CU-4E23QBR</b>   <b>6.8kW</b> *4  Dimensions (HxWxD): 795 x 875(+95) x 320 mm Weight: 72 kg	 PORT A: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT B: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT C: 2.0 or 2.5 or 3.2 or 5.0 * Either unit PORT D: 2.0 or 2.5 or 3.2 or 5.0 * Either unit  * At least two indoor units must be connected.	4.5 to 11.0 kW	Room A	ø 6.35	ø 9.52	25 m	60 m	30 m	20 g/m	15 m	2.0	•		•	
			Room B	ø 6.35	ø 9.52						2.5	•	•	•	•
		Make sure to keep combinations within this range.	Room A	ø 6.35	ø 9.52	3.2	•	•	•	•					
			Room B	ø 6.35	ø 9.52	5.0	•	•	•	•					

\*4 To enable demand response management, an optional accessory needs to be installed [CZ-CAP2]

## Outdoor

Up to 2 rooms

Up to 3 rooms

Up to 4 rooms

CU-2E18SBR

Heating Possible  
-15°C  
Cooling Possible  
46°C



CU-3E18SBR

Heating Possible  
-15°C  
Cooling Possible  
46°C







CU-4E23QBR

Heating Possible  
-15°C  
Cooling Possible  
46°C



# Specifications

Models	Indoor Units: Possible Combination Patterns Must be within capacity range	Indoor Units Combination Range	Refrigerant Pipe Diameter			Pipe Extension				Indoor Unit Combinations					
			Indoor Unit	Liquid Side	Gas Side	Maximum Pipe Length (1 room)	Maximum Pipe Length (Total)	Maximum Chargeless Length	Additional Gas	Maximum Height	Type Capacity [kW class]	Wall- Mounted	Cassette [4-Way]	Ultra Slim Ducted	Bulkhead Ducted
<b>Up to 4 rooms</b>  <b>CU-4E27QBR</b>  <b>8.0kW</b> *4  Dimensions (HxWxD): 999 x 940 x 340 mm Weight: 80 kg	 <p>* Either unit</p> <p>* Either unit</p> <p>* Either unit</p> <p>* Either unit</p> <p>* At least two indoor units must be connected.</p>	4.5 to 13.6 kW  Make sure to keep combinations within this range.	Room A	ø 6.35	ø 9.52	25 m	70 m	45 m	20 g/m	15 m	2.0	•		•	
			Room B	ø 6.35	ø 9.52						2.5	•	•	•	•
			Room C	ø 6.35	ø 9.52						3.2	•	•	•	•
			Room D	ø 6.35	ø 9.52						5.0	•	•	•	•
											7.0	•			
<b>Up to 5 rooms</b>  <b>CU-5E34QBR</b>  <b>10.0kW</b> *4  Dimensions (HxWxD): 999 x 940 x 340 mm Weight: 81 kg	 <p>* Either unit</p> <p>* Either unit</p> <p>* Either unit</p> <p>* Either unit</p> <p>* Either unit</p> <p>* At least two indoor units must be connected.</p>	4.5 to 17.5 kW  Make sure to keep combinations within this range.	Room A	ø 6.35	ø 9.52	25 m	80 m	45 m	20 g/m	15 m	2.0	•		•	
			Room B	ø 6.35	ø 9.52						2.5	•	•	•	•
			Room C	ø 6.35	ø 9.52						3.2	•	•	•	•
			Room D	ø 6.35	ø 9.52						5.0	•	•	•	•
											7.0	•			
			Room E	ø 6.35	ø 9.52										

\*4 To enable demand response management, an optional accessory needs to be installed (CZ-CAP2)

## Outdoor

Up to 4 rooms

CU-4E27QBR

Heating Possible  
-15°C

Cooling Possible  
46°C



Up to 5 rooms

CU-5E34QBR

Heating Possible  
-15°C

Cooling Possible  
46°C



# SPECIFICATIONS

## Indoor Units

Cooling  
Heating

Model			Wall-Mounted				
			CS-MRE7QKR	CS-MRE9QKR	CS-MRE12QKR	CS-MRE18QKR	CS-MRE24QKR
Capacity	kW		2.0	2.5	3.2	5.0	7.0
Power Source			Single Phase 240V, 50Hz				
Noise (Hi/Lo/S-Lo)	Sound Pressure Level	dB(A)	40/29/26 40/29/26	40/29/26 40/29/26	44/32/29 44/32/29	46/33/30 46/35/32	47/35/32 47/38/35
	Sound Power Level	dB	56/45/42 56/45/42	56/45/42 56/45/42	60/48/45 60/48/45	62/49/46 62/51/48	63/51/48 63/54/51
Airflow	L/s		168/172	168/173	182/190	275/298	307/325
Dimensions	Height	mm	290	290	290	290	290
	Width	mm	870	870	870	1070	1070
	Depth	mm	214	214	214	240	240
Net Weight	kg		9	9	9	12	12
Refrigerant Pipe Diameter	Liquid Side	mm	6.35	6.35	6.35	6.35	6.35
	Gas Side	mm	9.52	9.52	9.52*1	9.52*1	12.7*2*3

Cooling  
Heating

Model			Ultra Slim Ducted				Bulkhead Ducted			4-Way Mini Cassette		
			CS-ME7SD3R	CS-E9SD3RW	CS-E12SD3RW	CS-E18SD3RW	CS-E9QD3RW	CS-E12QD3RW	CS-E18QD3RW	CS-E9SB4RW	CS-E12QB4RW	CS-E18QB4RW
Capacity	kW		2.0	2.5	3.2	5.0	2.5	3.2	5.0	2.5	3.2	5.0
Power Source			Single Phase 240V, 50Hz									
Noise (Hi/Lo/S-Lo)	Sound Pressure Level	dB(A)	33/29/26 35/30/27	34/29/26 36/30/27	35/29/26 37/30/27	43/32/29 43/34/31	34/29/26 36/30/27	35/29/26 37/30/27	44/32/29 44/34/31	36/28/25 37/30/27	37/28/25 39/30/27	40/30/27 41/31/28
	Sound Power Level	dB	49/45/42 51/46/43	50/45/42 52/46/43	51/45/42 53/46/43	59/48/45 59/50/47	50/45/42 52/46/43	51/45/42 53/46/43	60/48/45 60/50/47	52/44/41 53/46/43	53/44/41 55/46/43	56/46/43 57/47/44
Airflow (Ducted Maximum @ 10 PA) - Cooling	L/s		222	231	241	293	250	256	286	175	175	195
Airflow (Ducted Maximum @ 10 PA) - Heating	L/s		222	231	241	293	259	263	294	182	195	208
Dimensions	Height	mm	200	200	200	200	235	235	285	260	260	260
	Width	mm	750	750	750	750	750	750	750	575	575	575
	Depth	mm	640	640	640	640	370	370	370	575	575	575
Net Weight	kg		19	19	19	19	17	17	18	18	18	18
Refrigerant Pipe Diameter	Liquid Side	mm	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas Side	mm	9.52	9.52	9.52*1	9.52*1	9.52	9.52*1	9.52*1	9.52	9.52*1	9.52*1
Drain Pipe Size	mm		VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20/VP-25	VP-20/VP-25	VP-20/VP-25

\*1 CZ-MA1P is to be used to reduce the connection size on the indoor unit from 1/2" to 3/8".  
 \*2 CZ-MA2P is to be used to increase the connection size on the outdoor unit from 3/8" to 1/2".  
 \*3 CZ-MA3P is to be used to reduce the connection size on the indoor unit from 5/8" to 1/2".



## Outdoor Units

Model			(50Hz)	CU-2E18SBR	CU-3E18SBR	CU-4E23QBR	CU-4E27QBR	CU-5E34QBR
Indoor Units Combination				2.0kW+3.2kW	1.6kW+1.6kW+2.0kW	1.6kW+1.6kW+1.6kW+2.0kW	2.0kW+2.0kW+2.0kW+2.0kW	2.0kW+2.0kW+2.0kW+2.0kW+2.0kW
Power Source				Single Phase 240V, 50Hz				
Cooling Operation	Capacity	kW		5.20(1.50-6.00)	5.20(1.80-7.30)	6.80(1.90-8.80)	8.00(3.00-9.20)	10.00(2.90-11.50)
Maximum Connectable Capacity			kW	7.5	9.0	11.0	13.6	17.5
Maximum Connectable Indoors			Units	2	3	4	4	5
Electrical Data	Running Current	A		6.3	5.5	7.5	9.4	13.2
	Power Input	kW		1.40(0.25-1.85)	1.20(0.36-2.18)	1.68(0.34-2.47)	2.15(0.53-2.87)	2.86(0.55-3.86)
	AEER/EER	W/W		4.19/3.71	3.64/4.33	3.95/4.05	3.65/3.72	3.45/3.50
Noise (Hi/Lo)	Sound Pressure Level	dB(A)		49/-	46/-	48/-	51/-	53/-
	Sound Power Level	dB		64/-	60/-	62/-	67/-	69/-
Heating Operation	Capacity	kW		5.60(1.10-7.20)	6.80(1.60-8.30)	8.50(3.00-10.60)	9.40(4.20-10.60)	12.00(3.40-14.50)
Electrical Data	Running Current	A		5.8	6.8	8.6	9.8	13.2
	Power Input	kW		1.31(0.21-1.8)	1.50(0.32-2.11)	1.95(0.58-2.60)	2.18(0.70-3.06)	2.96(0.53-4.24)
	ACOP/COP	W/W		4.41/4.27	4.19/4.53	4.27/4.36	4.23/4.31	4.00/4.05
Noise (Hi/Lo)	Sound Pressure Level	dB(A)		52/-	48/-	49/-	52/-	54/-
	Sound Power Level	dB		67/-	62/-	63/-	68/-	70/-
Maximum Current			A	12.0	15.2	15.6	19.0	21.3
Starting Current			A	6.5	7.0	8.8	10.2	13.6
Compressor Output			W	900	1300	1300	1700	1700
Dimensions	Height	mm		619	795	795	999	999
	Width	mm		824(+70)	875(+95)	875(+95)	940	940
	Depth	mm		299	320	320	340	340
Net Weight			kg	39	71	72	80	81
Power Supply				Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Pipe Length Range (1 room)			m	3-20	3-25	3-25	3-25	3-25
Maximum Pipe Length (Total) *1			m	30	50	60	70	80
Refrigerant Pipe Diameter	Liquid Side	mm		6.35	6.35	6.35	6.35	6.35
	Gas Side	mm		9.52	9.52	9.52	9.52	9.52
Operating Range	Cooling	Degree (°C)		-10-46	-10-46	-10-46	-10-46	-10-46
	Heating	Degree (°C)		-15-24*1	-15-24*1	-15-24*1	-15-24*1	-15-24*1

\*1 Additional Gas might be required for some models. Refer to Page 15 for information on Additional Gas.

### Rating Conditions

	Cooling	Heating
Inside air temperature	27°C DB /19°C WB	20°C DB
Outside air temperature	35°C DB	7°C DB /6°C WB

# SPECIFICATIONS

## CU-2E18SBR

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
	Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total	
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
2 rooms	20+20	2.00	2.00	-	-	-	4.00(1.5~5.6)	4.67	1010(250~1710)	3.96	2.70	2.70	-	-	-	5.40(1.1~7.0)	5.83	1270(210~1770)	4.25
	20+25	2.00	2.50	-	-	-	4.50(1.5~5.8)	5.26	1140(250~1780)	3.95	2.40	3.00	-	-	-	5.40(1.1~7.0)	5.83	1270(210~1770)	4.25
	20+32	2.00	3.20	-	-	-	5.20(1.5~6.0)	6.50	1400(250~1850)	3.71	2.15	3.45	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27
	20+50	1.50	3.70	-	-	-	5.20(1.5~6.0)	6.50	1400(250~1850)	3.71	1.60	4.00	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27
	25+25	2.50	2.50	-	-	-	5.00(1.5~5.8)	6.13	1330(250~1780)	3.76	2.80	2.80	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27
	25+32	2.30	2.90	-	-	-	5.20(1.5~6.0)	6.50	1400(250~1850)	3.71	2.45	3.15	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27
	25+50	1.75	3.45	-	-	-	5.20(1.5~6.0)	6.50	1400(250~1850)	3.71	1.85	3.75	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27
	32+32	2.60	2.60	-	-	-	5.20(1.5~6.0)	6.50	1400(250~1850)	3.71	2.80	2.80	-	-	-	5.60(1.1~7.2)	6.00	1310(210~1800)	4.27

## CU-3E18SBR

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
	Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total	
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
2 rooms	20+20	2.00	2.00	-	-	-	4.00(1.8~6.2)	4.4	930(330~2010)	4.30	2.90	2.90	-	-	-	5.80(1.4~7.0)	6.7	1430(320~1890)	4.06
	20+25	2.00	2.50	-	-	-	4.50(1.8~6.2)	5.4	1140(330~2010)	3.95	2.84	3.56	-	-	-	6.40(1.4~7.0)	7.7	1660(320~1890)	3.86
	20+32	2.00	3.20	-	-	-	5.20(1.8~6.3)	6.9	1480(330~2020)	3.51	2.62	4.18	-	-	-	6.80(1.4~7.3)	8.1	1740(310~1980)	3.91
	20+50	1.49	3.71	-	-	-	5.20(1.9~6.8)	5.9	1280(340~2040)	4.06	1.94	4.86	-	-	-	6.80(1.4~8.0)	7.4	1590(240~2080)	4.28
	25+25	2.50	2.50	-	-	-	5.00(1.8~6.2)	6.4	1400(330~2010)	3.57	3.40	3.40	-	-	-	6.80(1.4~7.0)	8.4	1790(320~1890)	3.80
	25+32	2.28	2.92	-	-	-	5.20(1.9~6.3)	6.9	1480(350~2020)	3.51	2.98	3.82	-	-	-	6.80(1.4~7.3)	8.1	1740(310~1980)	3.91
	25+50	1.73	3.47	-	-	-	5.20(1.9~6.8)	5.9	1280(340~2040)	4.06	2.27	4.53	-	-	-	6.80(1.4~8.0)	7.4	1590(240~2080)	4.28
	32+32	2.60	2.60	-	-	-	5.20(1.9~6.4)	6.4	1400(350~2020)	3.71	3.40	3.40	-	-	-	6.80(1.4~7.5)	8.0	1730(270~2000)	3.93
	32+50	2.03	3.17	-	-	-	5.20(1.9~6.9)	5.7	1240(360~2040)	4.19	2.65	4.15	-	-	-	6.80(1.4~8.0)	7.3	1570(240~2020)	4.33
3 rooms	20+20+20	1.73	1.73	1.73	-	-	5.19(1.9~7.2)	5.6	1200(390~2040)	4.33	2.26	2.26	2.26	-	-	6.78(1.6~8.3)	6.9	1490(310~2050)	4.55
	20+20+25	1.60	1.60	2.00	-	-	5.20(1.9~7.2)	5.6	1200(390~2040)	4.33	2.09	2.09	2.62	-	-	6.80(1.6~8.3)	6.9	1490(310~2050)	4.56
	20+20+32	1.44	1.44	2.32	-	-	5.20(1.9~7.2)	5.4	1160(390~2000)	4.48	1.89	1.89	3.02	-	-	6.80(1.6~8.3)	6.9	1470(310~2030)	4.63
	20+20+50	1.16	1.16	2.88	-	-	5.20(1.8~7.3)	5.3	1120(420~1860)	4.64	1.51	1.51	3.78	-	-	6.80(1.6~8.3)	6.3	1360(360~1890)	5.00
	20+25+25	1.48	1.86	1.86	-	-	5.20(1.9~7.2)	5.6	1200(390~2040)	4.33	1.94	2.43	2.43	-	-	6.80(1.6~8.3)	6.9	1490(310~2050)	4.56
	20+25+32	1.35	1.69	2.16	-	-	5.20(1.9~7.2)	5.4	1160(390~2000)	4.48	1.76	2.21	2.83	-	-	6.80(1.6~8.3)	6.9	1470(310~2030)	4.63
	20+32+32	1.24	1.98	1.98	-	-	5.20(1.8~7.3)	5.4	1160(390~2000)	4.48	1.62	2.59	2.59	-	-	6.80(1.6~8.3)	6.8	1450(320~2000)	4.69
	25+25+25	1.73	1.73	1.73	-	-	5.19(1.9~7.2)	5.6	1200(390~2040)	4.33	2.26	2.26	2.26	-	-	6.78(1.6~8.3)	6.9	1490(310~2050)	4.55
	25+25+32	1.59	1.59	2.02	-	-	5.20(1.9~7.2)	5.4	1160(390~2000)	4.48	2.07	2.07	2.66	-	-	6.80(1.6~8.3)	6.9	1470(310~2030)	4.63
25+32+32	1.46	1.87	1.87	-	-	5.20(1.8~7.3)	5.4	1160(390~2000)	4.48	1.92	2.44	2.44	-	-	6.80(1.6~8.3)	6.8	1450(320~2000)	4.69	

## CU-4E23QBR

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION							
	Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Total				Room A	Room B	Room C	Room D	Total				
	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W	
2 rooms	20+25	2.00	2.50	-	-	4.50(1.9~6.4)	4.9	1100(270~1940)	4.09	2.71	3.39	-	-	6.10(2.7~9.8)	7.1	1610(640~2930)	3.79
	20+32	2.00	3.20	-	-	5.20(1.9~6.9)	6.4	1440(270~2320)	3.61	2.69	4.31	-	-	7.00(2.7~9.9)	8.4	1910(630~2930)	3.66
	20+50	1.94	4.86	-	-	6.80(2.0~7.5)	9.6	2180(280~2350)	3.12	2.43	6.07	-	-	8.50(2.8~10.2)	10.1	2310(560~2890)	3.68
	25+25	2.50	2.50	-	-	5.00(1.9~6.8)	6.0	1360(270~2310)	3.68	3.20	3.20	-	-	6.40(2.7~9.8)	7.6	1710(640~2930)	3.74
	25+32	2.50	3.20	-	-	5.70(1.9~6.9)	7.6	1720(270~2320)	3.31	3.55	4.55	-	-	8.10(2.7~9.9)	10.1	2310(630~2930)	3.51
	25+50	2.27	4.53	-	-	6.80(1.9~7.5)	9.6	2180(260~2350)	3.12	2.83	5.67	-	-	8.50(2.8~10.2)	10.1	2310(560~2890)	3.68
	32+32	3.20	3.20	-	-	6.40(1.9~7.0)	9.5	2170(270~2280)	2.95	4.25	4.25	-	-	8.50(2.8~10.0)	10.8	2460(640~2930)	3.46
	32+50	2.65	4.15	-	-	6.80(2.0~7.6)	9.2	2090(280~2360)	3.25	3.32	5.18	-	-	8.50(2.8~10.3)	9.9	2250(540~2880)	3.78
	50+50	3.40	3.40	-	-	6.80(2.1~8.1)	8.2	1860(320~2370)	3.66	4.25	4.25	-	-	8.50(2.8~10.5)	9.3	2110(510~2780)	4.03
3 rooms	20+20+20	2.00	2.00	2.00	-	6.00(1.9~8.0)	6.7	1510(270~2410)	3.97	2.83	2.83	2.83	-	8.49(3.3~10.4)	9.5	2160(630~2830)	3.93
	20+20+25	2.00	2.00	2.50	-	6.50(1.9~8.0)	7.8	1770(270~2410)	3.67	2.62	2.62	3.26	-	8.50(3.3~10.4)	9.5	2160(630~2830)	3.94
	20+20+32	1.89	1.89	3.02	-	6.80(1.9~8.0)	8.4	1910(270~2320)	3.56	2.36	2.36	3.78	-	8.50(3.3~10.4)	9.4	2140(620~2770)	3.97
	20+20+50	1.51	1.51	3.78	-	6.80(2.0~8.5)	7.6	1720(340~2380)	3.95	1.89	1.89	4.72	-	8.50(3.2~10.6)	8.7	1990(600~2700)	4.27
	20+25+25	1.94	2.43	2.43	-	6.80(1.9~8.0)	8.4	1910(270~2410)	3.56	2.42	3.04	3.04	-	8.50(3.3~10.4)	9.5	2160(630~2830)	3.94
	20+25+32	1.76	2.21	2.83	-	6.80(1.9~8.0)	8.4	1910(270~2320)	3.56	2.21	2.76	3.53	-	8.50(3.3~10.4)	9.4	2140(620~2770)	3.97
	20+25+50	1.43	1.79	3.58	-	6.80(2.0~8.5)	7.6	1720(340~2380)	3.95	1.79	2.24	4.47	-	8.50(3.2~10.6)	8.7	1990(600~2700)	4.27
	20+32+32	1.62	2.59	2.59	-	6.80(1.9~8.1)	8.2	1860(290~2330)	3.66	2.02	3.24	3.24	-	8.50(3.3~10.5)	9.3	2110(640~2790)	4.03
	20+32+50	1.33	2.13	3.34	-	6.80(2.0~8.5)	7.6	1720(340~2330)	3.95	1.66	2.67	4.17	-	8.50(3.2~10.6)	8.6	1970(600~2670)	4.31
	25+25+25	2.26	2.26	2.26	-	6.78(1.9~8.0)	8.4	1910(270~2410)	3.55	2.83	2.83	2.83	-	8.49(3.3~10.4)	9.5	2160(630~2830)	3.93
	25+25+32	2.07	2.07	2.66	-	6.80(1.9~8.0)	8.4	1910(270~2320)	3.56	2.59	2.59	3.32	-	8.50(3.3~10.4)	9.4	2140(620~2770)	3.97
	25+25+50	1.70	1.70	3.40	-	6.80(2.0~8.5)	7.6	1720(340~2380)	3.95	2.13	2.13	4.24	-	8.50(3.2~10.6)	8.7	1990(600~2700)	4.27
	25+32+32	1.92	2.44	2.44	-	6.80(1.9~8.1)	8.2	1860(290~2330)	3.66	2.38	3.06	3.06	-	8.50(3.3~10.5)	9.3	2110(640~2790)	4.03
	25+32+50	1.59	2.03	3.18	-	6.80(2.0~8.5)	7.6	1720(340~2330)	3.95	1.99	2.54	3.97	-	8.50(3.2~10.6)	8.6	1970(600~2670)	4.31
	32+32+32	2.26	2.26	2.26	-	6.78(1.9~8.2)	7.9	1810(290~2330)	3.75	2.83	2.83	2.83	-	8.49(3.3~10.5)	9.0	2050(630~2760)	4.14
4 rooms	20+20+20+20	1.70	1.70	1.70	1.70	6.80(1.9~8.8)	7.5	1680(340~2380)	4.05	2.12	2.12	2.12	2.12	8.48(3.1~10.6)	8.5	1930(600~2570)	4.39
	20+20+20+25	1.60	1.60	1.60	2.00	6.80(1.9~8.8)	7.5	1680(340~2380)	4.05	2.00	2.00	2.00	2.50	8.50(3.1~10.6)	8.5	1930(600~2570)	4.40
	20+20+20+32	1.48	1.48	1.48	2.36	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.85	1.85	1.85	2.95	8.50(3.0~10.6)	8.4	1910(610~2550)	4.45
	20+20+20+50	1.24	1.24	1.24	3.08	6.80(1.9~8.8)	7.3	1640(420~2200)	4.15	1.55	1.55	1.55	3.85	8.50(3.0~10.6)	8.2	1860(680~2440)	4.57
	20+20+25+25	1.51	1.51	1.89	1.89	6.80(1.9~8.8)	7.5	1680(340~2380)	4.05	1.89	1.89	2.36	2.36	8.50(3.1~10.6)	8.5	1930(600~2570)	4.40
	20+20+25+32	1.40	1.40	1.75	2.25	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.75	1.75	2.19	2.81	8.50(3.0~10.6)	8.4	1910(610~2550)	4.45
	20+20+32+32	1.31	1.31	2.09	2.09	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.63	1.63	2.62	2.62	8.50(3.0~10.6)	8.3	1890(610~2530)	4.50
	20+25+25+25	1.43	1.79	1.79	1.79	6.80(1.9~8.8)	7.5	1680(340~2380)	4.05	1.78	2.24	2.24	2.24	8.50(3.1~10.6)	8.5	1930(600~2570)	4.40
	20+25+25+32	1.33	1.67	1.67	2.13	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.67	2.08	2.08	2.67	8.50(3.0~10.6)	8.4	1910(610~2550)	4.45
	20+25+32+32	1.24	1.56	2.00	2.00	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.55	1.95	2.50	2.50	8.50(3.0~10.6)	8.3	1890(610~2530)	4.50
	25+25+25+25	1.70	1.70	1.70	1.70	6.80(1.9~8.8)	7.5	1680(340~2380)	4.05	2.12	2.12	2.12	2.12	8.48(3.1~10.6)	8.5	1930(600~2570)	4.39
25+25+25+32	1.59	1.59	1.59	2.03	6.80(1.9~8.8)	7.3	1640(370~2330)	4.15	1.99	1.99	1.99	2.53	8.50(3.0~10.6)	8.4	1910(610~2550)	4.45	

# SPECIFICATIONS

## CU-4E27QBR

Indoor Units Capacity	COOLING OPERATION								HEATING OPERATION									
	Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
	Room A	Room B	Room C	Room D	Total				Room A	Room B	Room C	Room D	Total					
kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W			
2 rooms	20+25	2.00	2.50	-	-	4.50(2.4-5.8)	5.8	1320(380-1930)	3.41	2.71	3.39	-	-	6.10(2.2-8.2)	8.5	1890(400-2890)	3.23	
	20+32	2.00	3.20	-	-	5.20(2.4-5.8)	6.8	1540(370-1860)	3.38	2.65	4.25	-	-	6.90(2.2-8.6)	9.1	2030(380-2920)	3.40	
	20+50	2.00	5.00	-	-	7.00(2.4-8.1)	9.8	2250(350-3100)	3.11	2.57	6.43	-	-	9.00(2.2-10.0)	10.9	2430(330-3310)	3.70	
	20+70	1.78	6.22	-	-	8.00(2.5-8.5)	12.1	2770(380-3340)	2.89	2.09	7.31	-	-	9.40(2.2-10.3)	11.5	2570(330-3490)	3.66	
	25+25	2.50	2.50	-	-	5.00(2.4-5.8)	6.6	1490(380-1930)	3.36	3.25	3.25	-	-	6.50(2.2-8.6)	8.5	1910(400-3000)	3.40	
	25+32	2.50	3.20	-	-	5.70(2.4-6.7)	8.0	1840(370-2480)	3.10	3.20	4.10	-	-	7.30(2.2-9.8)	9.8	2180(380-3520)	3.35	
	25+50	2.50	5.00	-	-	7.50(2.4-8.5)	11.3	2590(350-3490)	2.90	3.13	6.27	-	-	9.40(2.2-10.0)	11.8	2630(330-3310)	3.57	
	25+70	2.11	5.89	-	-	8.00(2.5-8.5)	12.1	2770(380-3340)	2.89	2.47	6.93	-	-	9.40(2.2-10.3)	11.5	2570(330-3490)	3.66	
	32+32	3.20	3.20	-	-	6.40(2.4-7.2)	9.7	2220(370-2760)	2.88	4.05	4.05	-	-	8.10(2.2-10.0)	11.0	2460(370-3560)	3.29	
	32+50	3.12	4.88	-	-	8.00(2.5-8.5)	12.1	2770(380-3340)	2.89	3.67	5.73	-	-	9.40(2.2-10.0)	11.4	2550(320-3280)	3.69	
32+70	2.51	5.49	-	-	8.00(2.5-8.6)	11.8	2700(380-3340)	2.96	2.95	6.45	-	-	9.40(2.2-10.3)	11.3	2530(320-3380)	3.72		
50+50	4.00	4.00	-	-	8.00(2.5-8.6)	10.5	2420(380-2950)	3.31	4.70	4.70	-	-	9.40(2.2-10.3)	10.6	2360(320-3170)	3.98		
50+70	3.33	4.67	-	-	8.00(2.5-8.6)	10.2	2350(380-2880)	3.40	3.92	5.48	-	-	9.40(2.2-10.5)	10.5	2340(320-3210)	4.02		
20+20+20	2.00	2.00	2.00	-	6.00(3.0-8.5)	7.2	1630(480-3030)	3.68	2.87	2.87	2.87	-	-	8.61(3.2-10.4)	9.5	2140(500-3320)	4.04	
20+20+25	2.00	2.00	2.50	-	6.50(3.0-8.5)	8.1	1870(480-3030)	3.48	2.77	2.77	3.46	-	-	9.00(3.2-10.4)	10.2	2270(500-3320)	3.96	
20+20+32	2.00	2.00	3.20	-	7.20(3.0-8.5)	9.2	2110(480-2950)	3.41	2.61	2.61	4.18	-	-	9.40(3.2-10.4)	10.7	2400(500-3280)	3.92	
20+20+50	1.78	1.78	4.44	-	8.00(3.0-8.6)	9.7	2220(520-2650)	3.60	2.09	2.09	5.22	-	-	9.40(3.2-10.5)	10.2	2270(520-3110)	4.14	
20+20+70	1.45	1.45	5.10	-	8.00(3.0-8.8)	9.7	2220(520-2720)	3.60	1.71	1.71	5.98	-	-	9.40(3.2-10.5)	10.1	2250(520-3090)	4.18	
20+25+25	2.00	2.50	2.50	-	7.00(3.0-8.5)	8.9	2050(480-3030)	3.41	2.68	3.36	3.36	-	-	9.40(3.2-10.4)	10.9	2430(500-3320)	3.87	
20+25+32	2.00	2.50	3.20	-	7.70(3.0-8.5)	10.0	2290(480-2950)	3.36	2.44	3.05	3.91	-	-	9.40(3.2-10.4)	10.7	2400(500-3280)	3.92	
20+25+50	1.68	2.11	4.21	-	8.00(3.0-8.6)	9.7	2220(520-2650)	3.60	1.98	2.47	4.95	-	-	9.40(3.2-10.5)	10.2	2270(520-3110)	4.14	
20+25+70	1.39	1.74	4.87	-	8.00(3.0-8.8)	9.7	2220(520-2720)	3.60	1.63	2.04	5.73	-	-	9.40(3.2-10.6)	10.1	2250(520-3150)	4.18	
20+32+32	1.90	3.05	3.05	-	8.00(3.0-8.6)	10.5	2420(480-2950)	3.31	2.24	3.58	3.58	-	-	9.40(3.2-10.4)	10.6	2370(490-3240)	3.97	
20+32+50	1.57	2.51	3.92	-	8.00(3.0-8.8)	9.7	2220(520-2800)	3.60	1.84	2.95	4.61	-	-	9.40(3.2-10.5)	10.0	2240(520-3070)	4.20	
20+32+70	1.31	2.10	4.59	-	8.00(3.0-9.0)	9.4	2150(520-2800)	3.72	1.54	2.47	5.39	-	-	9.40(3.2-10.6)	10.0	2230(530-3120)	4.22	
20+50+50	1.34	3.33	3.33	-	8.00(3.0-9.0)	9.1	2090(570-2650)	3.83	1.56	3.92	3.92	-	-	9.40(3.2-10.6)	9.6	2140(600-2990)	4.39	
25+25+25	2.50	2.50	2.50	-	7.50(3.0-8.5)	10.1	2310(480-3030)	3.25	3.13	3.13	3.13	-	-	9.39(3.2-10.4)	10.9	2430(500-3320)	3.86	
25+25+32	2.44	2.44	3.12	-	8.00(3.0-8.6)	10.8	2490(480-3030)	3.21	2.87	2.87	3.66	-	-	9.40(3.2-10.4)	10.7	2400(500-3280)	3.92	
25+25+50	2.00	2.00	4.00	-	8.00(3.0-8.8)	9.7	2220(520-2800)	3.60	2.35	2.35	4.70	-	-	9.40(3.2-10.5)	10.2	2270(520-3110)	4.14	
25+25+70	1.67	1.67	4.66	-	8.00(3.0-9.0)	9.7	2220(520-2870)	3.60	1.96	1.96	5.48	-	-	9.40(3.2-10.6)	10.1	2250(520-3150)	4.18	
25+32+32	2.24	2.88	2.88	-	8.00(3.0-8.6)	10.5	2420(480-2950)	3.31	2.64	3.38	3.38	-	-	9.40(3.2-10.5)	10.6	2370(490-3240)	3.97	
25+32+50	1.87	2.39	3.74	-	8.00(3.0-8.8)	9.7	2220(520-2800)	3.60	2.20	2.81	4.39	-	-	9.40(3.2-10.5)	10.0	2240(520-3070)	4.20	
25+32+70	1.57	2.02	4.41	-	8.00(3.0-9.0)	9.4	2150(520-2800)	3.72	1.85	2.37	5.18	-	-	9.40(3.2-10.6)	10.0	2230(530-3120)	4.22	
25+50+50	1.60	3.20	3.20	-	8.00(3.0-9.0)	9.1	2090(570-2650)	3.83	1.88	3.76	3.76	-	-	9.40(3.2-10.6)	9.6	2140(600-2990)	4.39	
32+32+32	2.66	2.66	2.66	-	7.98(3.0-8.6)	10.2	2350(480-2880)	3.40	3.13	3.13	3.13	-	-	9.39(3.2-10.5)	10.5	2340(490-3200)	4.01	
32+32+50	2.25	2.25	3.50	-	8.00(3.0-8.8)	9.4	2150(520-2720)	3.72	2.64	2.64	4.12	-	-	9.40(3.2-10.6)	9.9	2210(530-3100)	4.25	
32+32+70	1.91	1.91	4.18	-	8.00(3.0-9.0)	9.4	2150(520-2800)	3.72	2.24	2.24	4.92	-	-	9.40(3.2-10.6)	9.8	2200(530-3090)	4.27	
32+50+50	1.94	3.03	3.03	-	8.00(3.0-9.0)	9.1	2090(570-2650)	3.83	2.28	3.56	3.56	-	-	9.40(3.2-10.6)	9.5	2120(620-2960)	4.43	
20+20+20+20	2.00	2.00	2.00	2.00	8.00(3.0-9.2)	9.4	2150(530-2870)	3.72	2.35	2.35	2.35	2.35	-	-	9.40(4.2-10.6)	9.8	2180(700-3060)	4.31
20+20+20+25	1.88	1.88	1.88	2.36	8.00(3.0-9.2)	9.4	2150(530-2870)	3.72	2.21	2.21	2.21	2.77	-	-	9.40(4.2-10.6)	9.8	2180(700-3060)	4.31
20+20+20+32	1.74	1.74	1.74	2.78	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	2.04	2.04	2.04	3.28	-	-	9.40(4.2-10.6)	9.7	2160(730-3030)	4.35
20+20+20+50	1.45	1.45	1.45	3.65	8.00(3.0-9.2)	8.8	2030(620-2650)	3.94	1.71	1.71	1.71	4.27	-	-	9.40(4.2-10.6)	9.5	2130(810-2960)	4.41
20+20+20+70	1.23	1.23	1.23	4.31	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.45	1.45	1.45	5.05	-	-	9.40(4.2-10.6)	9.5	2120(820-2950)	4.43
20+20+25+25	1.78	1.78	2.22	2.22	8.00(3.0-9.2)	9.4	2150(530-2870)	3.72	2.09	2.09	2.61	2.61	-	-	9.40(4.2-10.6)	9.8	2180(700-3060)	4.31
20+20+25+32	1.65	1.65	2.06	2.64	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	1.94	1.94	2.42	3.10	-	-	9.40(4.2-10.6)	9.7	2160(730-3030)	4.35
20+20+25+50	1.39	1.39	1.74	3.48	8.00(3.0-9.2)	8.8	2030(620-2650)	3.94	1.63	1.63	2.04	4.10	-	-	9.40(4.2-10.6)	9.5	2130(810-2960)	4.41
20+20+25+70	1.19	1.19	1.47	4.15	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.39	1.39	1.74	4.88	-	-	9.40(4.2-10.6)	9.5	2120(820-2950)	4.43
20+20+32+32	1.54	1.54	2.46	2.46	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	1.81	1.81	2.89	2.89	-	-	9.40(4.2-10.6)	9.6	2140(740-3000)	4.39
20+20+32+50	1.31	1.31	2.10	3.28	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.54	1.54	2.47	3.85	-	-	9.40(4.2-10.6)	9.4	2110(830-2940)	4.45
20+25+25+25	1.67	2.11	2.11	2.11	8.00(3.0-9.2)	9.4	2150(530-2870)	3.72	1.99	2.47	2.47	2.47	-	-	9.40(4.2-10.6)	9.8	2180(700-3060)	4.31
20+25+25+32	1.57	1.96	1.96	2.51	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	1.84	2.30	2.30	2.96	-	-	9.40(4.2-10.6)	9.7	2160(730-3030)	4.35
20+25+25+50	1.33	1.67	1.67	3.33	8.00(3.0-9.2)	8.8	2030(620-2650)	3.94	1.56	1.96	1.96	3.92	-	-	9.40(4.2-10.6)	9.5	2130(810-2960)	4.41
20+25+32+32	1.47	1.83	2.35	2.35	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	1.72	2.16	2.76	2.76	-	-	9.40(4.2-10.6)	9.6	2140(740-3000)	4.39
20+25+32+50	1.26	1.57	2.02	3.15	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.48	1.85	2.37	3.70	-	-	9.40(4.2-10.6)	9.4	2110(830-2940)	4.45
20+32+32+32	1.37	2.21	2.21	2.21	8.00(3.0-9.2)	9.1	2090(570-2720)	3.83	1.63	2.59	2.59	2.59	-	-	9.40(4.2-10.6)	9.5	2120(770-2970)	4.43
20+32+32+50	1.19	1.91	1.91	2.99	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.40	2.24	2.24	3.52	-	-	9.40(4.2-10.6)	9.6	2140(860-2920)	4.39
25+25+25+25	2.00	2.00	2.00	2.00	8.00(3.0-9.2)	9.4	2150(530-2870)	3.72	2.35	2.35	2.35	2.35	-	-	9.40(4.2-10.6)	9.8	2180(700-3060)	4.31
25+25+25+32	1.87	1.87	1.87	2.39	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	2.20	2.20	2.20	2.80	-	-	9.40(4.2-10.6)	9.7	2160(730-3030)	4.35
25+25+25+50	1.60	1.60	1.60	3.20	8.00(3.0-9.2)	8.8	2030(620-2650)	3.94	1.88	1.88	1.88	3.76	-	-	9.40(4.2-10.6)	9.5	2130(810-2960)	4.41
25+25+32+32	1.75	1.75	2.25	2.25	8.00(3.0-9.2)	9.1	2090(570-2800)	3.83	2.06	2.06	2.64	2.64	-	-	9.40(4.2-10.6)	9.6	2140(740-3000)	4.39
25+25+32+50	1.52	1.52	1.93	3.03	8.00(3.0-9.2)	8.8	2030(630-2660)	3.94	1.78	1.78	2.28	3.56	-	-	9.40(4.2-10.6)	9.4	2110(830-2940)</	



CU-5E34QBR

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION										
	Cooling Capacity						Running Current	Power Input	EER	Heating Capacity						Running Current	Power Input	COP		
	Room A	Room B	Room C	Room D	Room E	Total				Room A	Room B	Room C	Room D	Room E	Total					
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
2 rooms	20+25	2.00	2.50	-	-	-	4.50(2.4-5.8)	5.8	1240(300-1860)	3.63	2.71	3.39	-	-	-	6.10(2.0-8.2)	8.6	1940(250-2760)	3.14	
	20+32	2.00	3.20	-	-	-	5.20(2.4-5.8)	6.8	1460(300-1800)	3.56	2.65	4.25	-	-	-	6.90(2.0-8.6)	9.6	2160(240-2800)	3.19	
	20+50	2.00	5.00	-	-	-	7.00(2.4-8.1)	9.9	2160(280-2890)	3.24	2.57	6.43	-	-	-	9.00(2.0-11.0)	12.0	2700(190-3440)	3.33	
	20+70	2.00	7.00	-	-	-	9.00(2.5-10.0)	15.9	3460(310-4460)	2.60	2.38	8.32	-	-	-	10.70(2.0-13.0)	14.7	3300(190-4410)	3.24	
	25+25	2.50	2.50	-	-	-	5.00(2.4-5.8)	6.6	1410(300-1860)	3.55	3.25	3.25	-	-	-	6.50(2.0-8.6)	9.0	2030(250-2880)	3.20	
	25+32	2.50	3.20	-	-	-	5.70(2.4-6.7)	8.1	1740(300-2360)	3.28	3.20	4.10	-	-	-	7.30(2.0-11.0)	10.3	2320(240-3490)	3.15	
	25+50	2.50	5.00	-	-	-	7.50(2.4-8.6)	11.5	2490(280-3330)	3.01	3.13	6.27	-	-	-	9.40(2.0-11.0)	13.0	2930(190-3440)	3.21	
	25+70	2.50	7.00	-	-	-	9.50(2.5-10.1)	17.8	3880(310-4620)	2.45	2.92	8.18	-	-	-	11.10(2.0-13.0)	15.0	3370(190-4410)	3.29	
	32+32	3.20	3.20	-	-	-	6.40(2.4-7.2)	9.7	2100(290-2620)	3.05	4.05	4.05	-	-	-	8.10(2.0-11.0)	11.6	2620(230-3710)	3.20	
	32+50	3.20	5.00	-	-	-	8.20(2.5-9.1)	13.3	2890(310-3490)	2.84	3.98	6.22	-	-	-	10.20(2.0-11.9)	13.8	3100(180-3750)	3.29	
	32+70	3.14	6.86	-	-	-	10.00(2.5-10.4)	19.4	4220(310-4800)	2.37	3.76	8.24	-	-	-	12.00(2.0-13.8)	16.1	3630(180-4780)	3.31	
	50+50	5.00	5.00	-	-	-	10.00(2.5-10.4)	16.6	3610(300-4000)	2.77	6.00	6.00	-	-	-	12.00(2.0-13.8)	15.0	3370(200-4500)	3.56	
	50+70	4.17	5.83	-	-	-	10.00(2.5-10.4)	16.0	3470(300-3850)	2.88	5.00	7.00	-	-	-	12.00(2.0-13.8)	14.9	3360(200-4480)	3.57	
	70+70	5.00	5.00	-	-	-	10.00(2.5-10.4)	15.3	3320(330-3690)	3.01	6.00	6.00	-	-	-	12.00(2.0-13.8)	14.8	3340(200-4460)	3.59	
3 rooms	20+20+20	2.00	2.00	2.00	-	-	6.00(2.9-8.5)	7.2	1540(360-2820)	3.90	2.87	2.87	2.87	-	-	8.61(2.7-12.3)	10.5	2370(270-3860)	3.63	
	20+20+25	2.00	2.00	2.50	-	-	6.50(2.9-8.5)	8.2	1780(360-2820)	3.65	2.77	2.77	3.46	-	-	9.00(2.7-12.3)	11.2	2530(270-3860)	3.56	
	20+20+32	2.00	2.00	3.20	-	-	7.20(2.9-8.5)	9.3	2030(390-2750)	3.55	2.72	2.72	4.36	-	-	9.80(2.7-12.3)	12.6	2840(270-3760)	3.45	
	20+20+50	2.00	2.00	5.00	-	-	9.00(2.9-9.6)	12.3	2670(390-2900)	3.37	2.64	2.64	6.62	-	-	11.90(2.7-13.6)	14.2	3200(290-4170)	3.72	
	20+20+70	1.82	1.82	6.36	-	-	10.00(2.9-10.7)	14.3	3110(390-3620)	3.22	2.18	2.18	7.64	-	-	12.00(2.7-13.8)	14.2	3100(290-4290)	3.76	
	20+25+25	2.00	2.50	2.50	-	-	7.00(2.9-8.5)	9.1	1970(360-2820)	3.55	2.68	3.36	3.36	-	-	9.40(2.7-12.3)	12.0	2700(270-3860)	3.48	
	20+25+32	2.00	2.50	3.20	-	-	7.70(2.9-8.5)	10.2	2220(390-2750)	3.47	2.65	3.31	4.24	-	-	10.20(2.7-12.9)	13.0	2920(270-4080)	3.49	
	20+25+50	2.00	2.50	5.00	-	-	9.50(2.9-10.1)	13.4	2920(390-3250)	3.25	2.52	3.16	6.32	-	-	12.00(2.7-13.6)	14.5	3260(290-4170)	3.68	
	20+25+70	1.74	2.17	6.09	-	-	10.00(2.9-10.7)	14.3	3110(390-3620)	3.22	2.09	2.61	7.30	-	-	12.00(2.7-13.8)	14.2	3190(290-4290)	3.76	
	20+32+32	2.00	3.20	3.20	-	-	8.40(2.9-8.7)	12.0	2610(390-2740)	3.22	2.62	4.19	4.19	-	-	11.00(2.7-12.9)	13.5	3030(280-4050)	3.63	
	20+32+50	1.96	3.14	4.90	-	-	10.00(2.9-10.7)	14.3	3110(390-3700)	3.22	2.35	3.76	5.89	-	-	12.00(2.7-13.6)	14.1	3170(310-4130)	3.79	
	20+32+70	1.64	2.62	5.74	-	-	10.00(2.9-10.7)	14.0	3040(420-3540)	3.29	1.96	3.15	6.89	-	-	12.00(2.7-13.8)	14.0	3150(310-4250)	3.81	
	20+50+50	1.66	4.17	4.17	-	-	10.00(2.9-10.7)	13.0	2830(430-3250)	3.53	2.00	5.00	5.00	-	-	12.00(2.7-13.8)	13.5	3030(350-4020)	3.96	
	20+50+70	1.43	3.57	5.00	-	-	10.00(2.9-10.7)	12.7	2760(460-3180)	3.62	1.71	4.29	6.00	-	-	12.00(2.7-14.1)	13.4	3010(370-4200)	3.99	
	20+70+70	1.24	4.38	4.38	-	-	10.00(2.9-10.7)	12.4	2690(460-3110)	3.72	1.50	5.25	5.25	-	-	12.00(2.7-14.4)	13.6	3050(380-4310)	3.93	
	25+25+25	2.50	2.50	2.50	-	-	7.50(2.9-8.5)	10.2	2220(360-2820)	3.38	3.23	3.23	3.23	-	-	9.69(2.7-12.3)	12.8	2870(270-3860)	3.38	
	25+25+32	2.50	2.50	3.20	-	-	8.20(2.9-8.7)	11.7	2550(390-2810)	3.22	3.20	3.20	4.10	-	-	10.50(2.7-12.9)	13.3	3000(270-4080)	3.50	
	25+25+50	2.50	2.50	5.00	-	-	10.00(2.9-10.7)	14.6	3180(390-3770)	3.14	3.00	3.00	6.00	-	-	12.00(2.7-13.6)	14.5	3260(290-4170)	3.68	
	25+25+70	2.08	2.08	5.84	-	-	10.00(2.9-10.7)	14.3	3110(390-3620)	3.22	2.50	5.00	7.00	-	-	12.00(2.7-13.8)	14.2	3190(290-4290)	3.76	
	25+32+32	2.50	3.20	3.20	-	-	8.90(2.9-9.6)	13.2	2880(390-3250)	3.09	3.18	4.06	4.06	-	-	11.30(2.7-13.6)	13.8	3100(280-4450)	3.65	
	25+32+50	2.34	2.99	4.67	-	-	10.00(2.9-10.7)	14.3	3110(390-3700)	3.22	2.80	3.59	5.61	-	-	12.00(2.7-13.8)	14.1	3170(310-4270)	3.79	
	25+32+70	1.97	2.52	5.51	-	-	10.00(2.9-10.7)	14.0	3040(420-3540)	3.29	2.36	3.02	6.62	-	-	12.00(2.7-14.1)	14.0	3150(310-4380)	3.81	
	25+50+50	2.00	4.00	4.00	-	-	10.00(2.9-10.7)	13.0	2830(430-3250)	3.53	2.40	4.80	4.80	-	-	12.00(2.7-13.8)	13.5	3030(350-4020)	3.96	
	25+50+70	1.72	3.45	4.83	-	-	10.00(2.9-10.7)	12.7	2760(460-3180)	3.62	2.07	4.14	5.79	-	-	12.00(2.7-14.1)	13.4	3010(370-4200)	3.99	
	25+70+70	1.52	4.24	4.24	-	-	10.00(2.9-10.7)	12.4	2690(460-3110)	3.72	1.82	5.09	5.09	-	-	12.00(2.7-14.4)	13.6	3050(380-4310)	3.93	
	32+32+32	3.20	3.20	3.20	-	-	9.60(2.9-10.1)	14.3	3110(390-3540)	3.09	4.00	4.00	4.00	-	-	12.00(2.7-13.6)	14.9	3350(280-4340)	3.58	
	32+32+50	2.81	2.81	4.38	-	-	10.00(2.9-10.7)	14.0	3040(390-3540)	3.29	3.37	3.37	5.26	-	-	12.00(2.7-13.8)	14.0	3140(310-4230)	3.82	
	32+32+70	2.39	2.39	5.22	-	-	10.00(2.9-10.7)	13.7	2970(420-3470)	3.37	2.87	2.87	6.26	-	-	12.00(2.7-14.1)	13.9	3120(320-4340)	3.85	
	32+50+50	2.42	3.79	3.79	-	-	10.00(2.9-10.7)	12.7	2760(460-3180)	3.62	2.90	4.55	4.55	-	-	12.00(2.7-14.1)	13.6	3050(380-4180)	3.93	
	32+50+70	2.10	3.29	4.61	-	-	10.00(2.9-10.7)	12.4	2690(460-3110)	3.72	2.52	3.95	5.53	-	-	12.00(2.7-14.4)	13.5	3040(380-4290)	3.95	
	32+70+70	1.86	4.07	4.07	-	-	10.00(2.9-10.7)	12.4	2700(470-3110)	3.70	2.24	4.88	4.88	-	-	12.00(2.7-14.4)	13.4	3020(390-4270)	3.97	
	50+50+50	3.33	3.33	3.33	-	-	9.99(2.9-10.7)	11.8	2570(510-2970)	3.89	4.00	4.00	4.00	-	-	12.00(2.7-14.4)	13.2	2980(460-4200)	4.03	
	50+50+70	2.94	2.94	4.12	-	-	10.00(2.9-10.7)	11.8	2570(510-2970)	3.89	3.53	3.53	4.94	-	-	12.00(2.7-14.4)	13.2	2970(480-4190)	4.04	
	4 rooms	20+20+20+20	2.00	2.00	2.00	2.00	-	8.00(2.9-10.6)	10.0	2180(420-3770)	3.67	2.88	2.88	2.88	-	-	11.52(3.4-14.2)	13.0	2930(390-4380)	3.93
		20+20+20+25	2.00	2.00	2.00	2.50	-	8.50(2.9-10.6)	10.9	2380(420-3770)	3.57	2.80	2.80	3.50	-	-	11.90(3.4-14.2)	13.8	3100(390-4380)	3.84
		20+20+20+32	2.00	2.00	2.00	3.20	-	9.20(2.9-10.6)	12.3	2670(420-3680)	3.45	2.61	2.61	2.61	4.17	-	12.00(3.4-14.2)	13.6	3060(400-4340)	3.92
		20+20+20+50	1.82	1.82	1.82	4.54	-	10.00(2.9-10.6)	13.5	2930(470-3360)	3.41	2.18	2.18	5.46	-	-	12.00(3.4-14.2)	13.3	2990(480-4160)	4.01
		20+20+20+70	1.54	1.54	1.54	5.38	-	10.00(2.9-10.8)	13.5	2930(500-3450)	3.41	1.85	1.85	6.45	-	-	12.00(3.4-14.4)	13.2	2980(480-4200)	4.03
		20+20+25+25	2.00	2.00	2.50	2.50	-	9.00(2.9-10.6)	12.1	2630(420-3770)	3.62	2.67	2.67	3.33	3.33	-	12.00(3.4-14.2)	13.8	3100(390-4380)	3.87
		20+20+25+32	2.00	2.00	2.50	3.20	-	9.70(2.9-10.6)	13.4	2920(420-3680)	3.32	2.47	2.47	3.09						

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity						Running Current	Power Input	EER	Heating Capacity						Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E	Total				Room A	Room B	Room C	Room D	Room E	Total				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
4 rooms	25+25+32+32	2.19	2.19	2.81	2.81	-	10.00(2.9-10.6)	14.1	3070(430-3600)	3.26	2.63	2.63	3.37	3.37	-	12.00(3.4-14.2)	13.5	3030(420-4230)	3.96
	25+25+32+50	1.89	1.89	2.42	2.42	-	10.00(2.9-10.8)	13.5	2930(500-3440)	3.41	2.27	2.27	2.91	4.55	-	12.00(3.4-14.4)	13.2	2960(490-4190)	4.05
	25+25+32+70	1.64	1.64	2.11	4.61	-	10.00(2.9-11.0)	13.2	2860(510-3530)	3.50	1.97	1.97	2.53	5.53	-	12.00(3.4-14.4)	13.1	2950(500-4170)	4.07
	25+25+50+50	1.67	1.67	3.33	3.33	-	10.00(2.9-11.0)	12.9	2800(560-3460)	3.57	2.00	2.00	4.00	4.00	-	12.00(3.4-14.4)	13.2	2970(590-4160)	4.04
	25+25+50+70	1.47	1.47	2.94	4.12	-	10.00(2.9-11.2)	12.9	2800(560-3540)	3.57	1.76	1.76	3.53	4.95	-	12.00(3.4-14.4)	13.2	2960(600-4140)	4.05
	25+32+32+32	2.08	2.64	2.64	2.64	-	10.00(2.9-10.8)	14.1	3070(460-3680)	3.26	2.49	3.17	3.17	3.17	-	12.00(3.4-14.2)	13.4	3010(430-4190)	3.99
	25+32+32+50	1.80	2.30	2.30	3.60	-	10.00(2.9-10.8)	13.2	2860(510-3450)	3.50	2.16	2.76	2.76	4.32	-	12.00(3.4-14.4)	13.1	2940(510-4220)	4.03
	25+32+32+70	1.57	2.01	4.41	4.41	-	10.00(2.9-11.2)	13.2	2860(510-3690)	3.50	1.88	2.42	2.42	5.28	-	12.00(3.4-14.4)	13.2	2980(520-4200)	4.08
	25+32+50+50	1.59	2.05	3.18	3.18	-	10.00(2.9-11.0)	12.9	2800(560-3380)	3.57	1.91	2.45	3.82	3.82	-	12.00(3.4-14.4)	13.1	2950(620-4130)	4.07
	25+50+50+50	1.42	2.86	2.86	2.86	-	10.00(2.9-11.2)	12.7	2750(660-3480)	3.64	1.71	3.43	3.43	3.43	-	12.00(3.4-14.4)	13.4	3020(730-4120)	3.97
	32+32+32+32	2.50	2.50	2.50	2.50	-	10.00(2.9-10.8)	13.8	3000(460-3600)	3.33	3.00	3.00	3.00	3.00	-	12.00(3.4-14.4)	13.5	3030(450-4280)	3.96
	32+32+32+50	2.19	2.19	2.19	3.43	-	10.00(2.9-11.0)	13.2	2860(510-3530)	3.50	2.63	2.63	2.63	4.11	-	12.00(3.4-14.4)	13.2	2970(530-4180)	4.04
	32+32+32+70	1.93	1.93	1.93	4.21	-	10.00(2.9-11.2)	13.2	2860(520-3610)	3.50	2.31	2.31	2.31	5.07	-	12.00(3.4-14.4)	13.2	2960(550-4160)	4.05
	32+32+50+50	1.95	1.95	3.05	3.05	-	10.00(2.9-11.2)	12.9	2800(600-3540)	3.57	2.34	2.34	3.66	3.66	-	12.00(3.4-14.4)	13.2	2980(630-4100)	4.03
	20+20+20+20+20	2.00	2.00	2.00	2.00	2.00	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.40	2.40	2.40	2.40	2.40	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05
	20+20+20+20+25	1.90	1.90	1.90	1.90	2.40	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.29	2.29	2.29	2.29	2.84	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05
	20+20+20+20+32	1.79	1.79	1.79	1.79	2.84	10.00(2.9-11.5)	12.9	2800(550-3780)	3.57	2.14	2.14	2.14	2.14	3.44	12.00(3.4-14.5)	13.1	2940(560-4200)	4.08
	20+20+20+20+50	1.54	1.54	1.54	1.54	3.84	10.00(2.9-11.5)	12.9	2810(610-3630)	3.56	1.85	1.85	1.85	1.85	4.60	12.00(3.4-14.5)	13.2	2960(670-4180)	4.05
	20+20+20+20+70	1.33	1.33	1.33	1.33	4.68	10.00(2.9-11.5)	12.7	2750(650-3640)	3.64	1.60	1.60	1.60	1.60	5.60	12.00(3.4-14.5)	13.3	3000(680-4170)	4.00
	20+20+20+25+25	1.82	1.82	1.82	2.27	2.27	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.18	2.18	2.18	2.73	2.73	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05
20+20+20+25+32	1.71	1.71	1.71	2.13	2.74	10.00(2.9-11.5)	12.9	2800(550-3780)	3.57	2.05	2.05	2.05	2.56	3.29	12.00(3.4-14.5)	13.1	2940(560-4200)	4.08	
20+20+20+25+50	1.48	1.48	1.48	1.85	3.71	10.00(2.9-11.5)	12.9	2810(610-3630)	3.56	1.78	1.78	1.78	2.22	4.44	12.00(3.4-14.5)	13.2	2960(670-4180)	4.05	
20+20+20+25+70	1.29	1.29	1.29	1.61	4.52	10.00(2.9-11.5)	12.7	2750(650-3640)	3.64	1.55	1.55	1.55	1.93	5.42	12.00(3.4-14.5)	13.3	3000(680-4170)	4.00	
20+20+20+32+32	1.60	1.60	1.60	2.60	2.60	10.00(2.9-11.5)	12.9	2800(560-3780)	3.57	1.94	1.94	1.94	3.09	3.09	12.00(3.4-14.5)	13.2	2970(580-4170)	4.04	
20+20+20+32+50	1.41	1.41	1.41	2.25	3.52	10.00(2.9-11.5)	12.7	2750(650-3630)	3.64	1.69	1.69	1.69	2.70	4.23	12.00(3.4-14.5)	13.3	2990(690-4150)	4.01	
20+20+20+32+70	1.23	1.23	1.23	1.98	4.33	10.00(2.9-11.5)	12.7	2760(660-3640)	3.62	1.48	1.48	1.48	2.37	5.19	12.00(3.4-14.5)	13.3	2990(710-4140)	4.01	
20+20+20+50+50	1.24	1.24	1.24	3.14	3.14	10.00(2.9-11.5)	12.8	2780(750-3580)	3.60	1.50	1.50	1.50	3.75	3.75	12.00(3.4-14.5)	13.7	3080(830-4220)	3.90	
20+20+25+25+25	1.73	1.73	2.18	2.18	2.18	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.10	2.10	2.60	2.60	2.60	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05	
20+20+25+25+32	1.64	1.64	2.05	2.05	2.62	10.00(2.9-11.5)	12.9	2800(550-3780)	3.57	1.97	1.97	2.46	2.46	3.14	12.00(3.4-14.5)	13.1	2940(560-4200)	4.08	
20+20+25+25+50	1.43	1.43	1.79	1.79	3.56	10.00(2.9-11.5)	12.9	2810(610-3630)	3.56	1.71	1.71	2.14	2.14	4.30	12.00(3.4-14.5)	13.2	2960(670-4180)	4.05	
20+20+25+25+70	1.25	1.25	1.56	1.56	4.38	10.00(2.9-11.5)	12.7	2750(650-3640)	3.64	1.50	1.50	1.88	1.88	5.24	12.00(3.4-14.5)	13.3	3000(680-4170)	4.00	
20+20+25+32+32	1.55	1.55	1.94	2.48	2.48	10.00(2.9-11.5)	12.9	2800(560-3780)	3.57	1.86	1.86	2.32	2.98	2.98	12.00(3.4-14.5)	13.2	2970(580-4170)	4.04	
20+20+25+32+50	1.36	1.36	1.70	2.18	3.40	10.00(2.9-11.5)	12.7	2750(650-3630)	3.64	1.63	1.63	2.04	2.61	4.09	12.00(3.4-14.5)	13.3	2990(690-4150)	4.01	
20+20+25+32+70	1.20	1.20	1.49	1.92	4.19	10.00(2.9-11.5)	12.7	2760(660-3640)	3.62	1.44	1.44	1.79	2.30	5.03	12.00(3.4-14.5)	13.3	2990(710-4140)	4.01	
20+20+25+50+50	1.21	1.21	1.52	3.03	3.03	10.00(2.9-11.5)	12.8	2780(750-3580)	3.60	1.45	1.45	1.82	3.64	3.64	12.00(3.4-14.5)	13.7	3080(830-4220)	3.90	
20+20+32+32+32	1.46	1.46	2.36	2.36	2.36	10.00(2.9-11.5)	12.9	2800(560-3700)	3.57	1.77	1.77	2.82	2.82	2.82	12.00(3.4-14.5)	13.1	2950(600-4200)	4.07	
20+20+32+32+50	1.30	1.30	2.08	2.08	3.24	10.00(2.9-11.5)	12.7	2750(660-3640)	3.64	1.56	1.56	2.49	2.49	3.90	12.00(3.4-14.5)	13.5	3030(720-4190)	3.96	
20+20+32+32+70	1.15	1.15	1.84	1.84	4.02	10.00(2.9-11.5)	12.7	2760(700-3640)	3.62	1.38	1.38	2.21	2.21	4.82	12.00(3.4-14.5)	13.4	3020(730-4180)	3.97	
20+20+32+50+50	1.16	1.16	1.86	2.91	2.91	10.00(2.9-11.5)	12.8	2790(760-3590)	3.58	1.40	1.40	2.22	3.49	3.49	12.00(3.4-14.5)	13.9	3120(860-4200)	3.85	
20+25+25+25+25	1.68	2.08	2.08	2.08	2.08	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.00	2.50	2.50	2.50	2.50	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05	
20+25+25+25+32	1.57	1.97	1.97	2.52	2.52	10.00(2.9-11.5)	12.9	2800(550-3780)	3.57	1.89	2.36	2.36	2.36	3.03	12.00(3.4-14.5)	13.1	2940(560-4200)	4.08	
20+25+25+25+50	1.38	1.72	1.72	1.72	3.46	10.00(2.9-11.5)	12.9	2810(610-3630)	3.56	1.65	2.07	2.07	2.07	4.14	12.00(3.4-14.5)	13.2	2960(670-4180)	4.05	
20+25+25+25+70	1.20	1.52	1.52	1.52	4.24	10.00(2.9-11.5)	12.7	2750(650-3640)	3.64	1.45	1.82	1.82	1.82	5.09	12.00(3.4-14.5)	13.3	3000(680-4170)	4.00	
20+25+25+32+32	1.48	1.87	1.87	2.39	2.39	10.00(2.9-11.5)	12.9	2800(560-3780)	3.57	1.78	2.24	2.24	2.87	2.87	12.00(3.4-14.5)	13.2	2970(580-4170)	4.04	
20+25+25+32+50	1.32	1.64	1.64	2.11	3.29	10.00(2.9-11.5)	12.7	2750(650-3630)	3.64	1.58	1.97	1.97	2.53	3.95	12.00(3.4-14.5)	13.3	2990(690-4150)	4.01	
20+25+25+32+70	1.16	1.45	1.45	1.86	4.08	10.00(2.9-11.5)	12.7	2760(660-3640)	3.62	1.40	1.74	1.74	2.23	4.89	12.00(3.4-14.5)	13.3	2990(710-4140)	4.01	
20+25+25+50+50	1.18	1.47	1.47	2.94	2.94	10.00(2.9-11.5)	12.8	2780(750-3580)	3.60	1.42	1.76	1.76	3.53	3.53	12.00(3.4-14.5)	13.7	3080(830-4220)	3.90	
20+25+32+32+32	1.42	1.77	2.27	2.27	2.27	10.00(2.9-11.5)	12.9	2800(560-3700)	3.57	1.70	2.14	2.72	2.72	2.72	12.00(3.4-14.5)	13.1	2950(600-4200)	4.07	
20+25+32+32+50	1.26	1.57	2.01	2.01	3.15	10.00(2.9-11.5)	12.7	2750(660-3640)	3.64	1.50	1.89	2.42	2.42	3.77	12.00(3.4-14.5)	13.5	3030(720-4190)	3.96	
20+32+32+32+32	1.36	2.16	2.16	2.16	2.16	10.00(2.9-11.5)	12.9	2810(600-3700)	3.56	1.64	2.59	2.59	2.59	2.59	12.00(3.4-14.5)	13.2	2980(630-4170)	4.03	
20+32+32+32+50	1.20	1.93	1.93	1.93	3.01	10.00(2.9-11.5)	12.7	2760(670-3640)	3.62	1.45	2.31	2.31	2.31	3.62	12.00(3.4-14.5)	13.4	3010(750-4160)	3.99	
25+25+25+25+25	2.00	2.00	2.00	2.00	2.00	10.00(2.9-11.5)	13.2	2860(550-3860)	3.50	2.40	2.40	2.40	2.40	2.40	12.00(3.4-14.5)	13.2	2960(530-4240)	4.05	
25+25+25+25+32	1.89	1.89	1.89	2.44	2.44	10.00(2.9-11.5)	12.9	2800(550-3780)	3.57	2.27	2.27	2.27	2.27	2.92	12.00(3.4-14.5)	13.1	2940(560-4200)		



# ONLY PANASONIC HAS 5 STARS



Overall Satisfaction



Reliability



Value for Money



Ease of Use



Functionality



Quietness



After Sales Service

Your local Panasonic specialist



**SANDCASTLE**  
AIR CONDITIONING & REFRIGERATION

[sales@sandcastleair.com.au](mailto:sales@sandcastleair.com.au)

[www.sandcastleair.com.au](http://www.sandcastleair.com.au)

## Panasonic

Panasonic Australia Pty. Limited.

ACN 001 592 187 ABN 83 001 592 187

[www.panasonic.com.au](http://www.panasonic.com.au)

• Specifications are subject to change without prior notice for further improvement • The contents of this catalogue are effective as of February 2017.  
• Due to printing considerations, the actual colours may vary slightly from those shown • All graphics are provided merely for the purpose of illustrating a point.

MULTI-AUS-FEB-2017