

GLAZE GLOSS CLEAR COAT



GLAZE is a water-based clear coat formulated with nano particles that cures on its own and is non-toxic. It offers remarkable hardness and scratch resistance, making it ideal for wall applications. Once completely dried, GLAZE achieves a high-gloss, durable finish. Additionally, it can be sanded and polished to achieve a smooth and uniform surface. This product can be applied on all polymeric base products including Velur and Luxor.



Key Features:

- full gloss
- Hard finish
- Chemical resistance
- UV resistance
- Durable
- Sandable and polishable

Benefits:

Ease of application (Roll, brush, and spray)
Excellent adhesion
Can be applied previously painted surfaces
Easy water wash up
Can be sanded easily

Application Guide:



Surface Preparation and Application:

Comprehensive precautions must be taken to ensure the desired outcome on both newly constructed and previously painted surfaces. All cracks, joints, and nail holes should be filled, cured, and finely sanded in accordance with the manufacturer's specifications. The surface must be thoroughly cleaned and dried, free from dust, peeling, mold, or any loose materials. In the presence of stains, it is essential to clean or wash the affected areas. If necessary, a suitable stain blocker should be applied based on the type of stain encountered. Previously painted surfaces may require light sanding as needed. Utilise fine-grit sandpaper or a sanding block (180 grit or higher) and conduct surface preparation to assess the painting area. For new surfaces that have been finely prepared, it is advisable to apply a single coat of PRIMA across the entire area to enhance coverage and final properties.

Once all surfaces are prepared and done properly, apply first coat of Glaze using roller, brush or spray. Let it dry for 2 hr and re-apply the second coat. If required the 3rd coat can be applied in the same way. Once finished, let it dry for 48-72 hrs before sanding and polishing. Use fine grit sand # 500 or higher, then gradually increase to #5000.

Area of use: all internal and external walls. Plasterboard, FCS, Timber, Brick, Block, Masonry, Previously Painted Surfaces, Splashback Wall, bathroom Walls (not shower area).

Handling, Health and Environment, Storage:

This product is not classified as a dangerous good. Keep it out of children's reach. Store at a temperature between 10-30°C, avoiding frost. Do not stack more than three pails at once. Ensure the lid is securely fastened after each use. For comprehensive safety precautions, please consult the Material Safety Data Sheet (MSDS) accessible via the QR code. Avoid contact with eyes and ingestion. In the event of poisoning, contact the Poison Information Centre at 131 126 or seek immediate medical assistance. For eye contact: rinse with running water. For skin contact: remove contaminated clothing and gently wash the affected skin. If ingested: do not induce vomiting; rinse the mouth with water and seek medical advice. For complete safety precautions, refer to the MSDS via the QR code or contact Chemro Pty Ltd.

Maintenance:

Regular maintenance cleaning is crucial for the longevity of a painted surface. When choosing a cleaner, mild soapy water is typically sufficient. Avoid abrasive, harsh cleaners and strong alkaline or acidic solutions. It is advisable to test the cleaning solution on a small area first to ensure it does not harm the paint film.

Pack Size:

15L, 4L, 0.5L

Disclaimer

Chemro Pty Ltd will not accept responsibility for any colour or look differences. In purchasing from Chemro Pty Ltd, you agree to accept the small risk that there will be a slight variation between the actual colour and pattern amongst different batches, pails and or sample products. In addition, please be aware that colours and textured finishes often vary between batches; for example slightly different shades of 'White', different degrees of shininess, and different looks and feel for material.

The data provided within this article is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems. All recommendations, information, advice, assistance or service for the use of our products, whether given by us in writing, oral, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Under no circumstances shall Chemro Pty Ltd be liable for incidental, consequential or indirect damage for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with product(s). Chemro Pty Ltd sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use.