



# LED 2FT Linear High Bay Multi Wattage 5000K



## FEATURES

- IP40 Rated
- DC 12V auxiliary
- 50,000 hours lifetime

## APPLICATIONS

- Warehouses
- Stadium
- Factories
- Supermarkets
- Logistic Centers
- Exhibition Halls

CONSTRUCTION	CONTROLS AND DIMMING
Die formed galvanized steel, white paint. Isolated driver with wide voltage input option. Frosted PMMA lens. Clear lens special order.	Standard 1-10V dimming. Suitable for use with LED dimmers.
OPTICAL SYSTEM	INSTALLATION
Lumileds 2835 LED chips. 120° beam angle options.	Hanging chain hook (included) or pendant mount.
ELECTRICAL	WARRANTY
Available as 120-277V input. -20°C to 40°C (-4°F to 104°F).	5-year limited warranty. Actual performance may differ as a result of environment and application.



## OPTIONAL ACCESSORIES



Emergency Back-up Driver  
120-EMBU-25WHV



Non-Dimming Motion Sensor  
120-MS-2LHB-ND



Dimming Motion Sensor  
120-MS-2LHB-DIM



Remote Control  
120-RCU-100

## MOUNTING OPTIONS



Chain and Hook (included)



Pendant  
120-MT-2LHB-P



# LED 2FT Linear High Bay Multi Wattage 5000K

## 120-2LHBX-T160-50-DIM

WATTAGE	SIZE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
110W	2 Foot	5000K	14,850lm	135lm/W	120-277V	80	.9	20%	400W HID
135W	2 Foot	5000K	18,225lm	135lm/W	120-277V	80	.9	20%	400W HID
160W	2 Foot	5000K	21,600lm	135lm/W	120-277V	80	.9	20%	400W HID

### PRODUCT MEASUREMENTS

