



LED T8 4FT 10W & 15W TYPE C (EXTERNAL) TUBE SERIES 120



FEATURES

- Single ended Type C
- Wide beam full directional lighting
- IP40 rated
- Low thermal decay & maintenance
- No mercury
- 50,000 hours lifetime

APPLICATIONS

- Limitless
- Commercial Buildings
- Conference rooms
- Hotels
- Office Buildings
- Schools

CONSTRUCTION

Glass body and frosted lens.

ELECTRICAL

Universal voltage 120-277V. 4°F to 122°F (-20°C to 50°C)

OPTICAL SYSTEM

120° beam angle.

INSTALLATION AND MOUNTING

Type C single ended.

CONTROLS AND DIMMING

Non-dimming.

CERTIFICATION AND WARRANTY

IP40 Rated. 3-month limited warranty.

ORDERING EXAMPLE: 120-4T8C-15-50

FORM FACTOR	WATTAGE	VOLTAGE	CCT
120-4T8C=4FT T8 C	10=10W	Blank=120-277V	4,000K
	15=15W		5,000K

TECHNICAL PARAMETERS

TUBE	120-4T8C-10-40	120-4T8C-10-50	120-4T8C-15-50
Wattage	10W	10W	15W
Delivered Lumens (lm)	1,258.3	1,311.1	1,919.4
Efficacy (lm/W)	123.3	129.8	127.9
CRI	82.5	82.7	82.4
Lifespan (Hours)	50,000		
Operating Temperature	4°F to 122°F (-20°C to 50°C)		
Power Factor	.91	.92	.92
THD	12.6%	13.2%	13.4%
REPLACES	25W	25W	32W