



LED 18W TYPE C (EXTERNAL) 5000K TUBE



FEATURES

- IP40 Rated
- Low thermal decay & maintenance
- No mercury
- 50,000 hours lifetime

APPLICATIONS

- Limitless
- Commercial Buildings
- Conference rooms
- Hotels
- Office Buildings
- Schools

CONSTRUCTION

Aluminum body with frosted lens.

ELECTRICAL

Universal voltage 120-277V. 4°F to 122°F (-20°C to 50°C).

OPTICAL SYSTEM

120° beam angle.

INSTALLATION AND MOUNTING

G13 base. Type C.

CONTROLS AND DIMMING

Non-dimming.

CERTIFICATION AND WARRANTY

IP40 Rated. 5-month limited warranty.

ORDERING EXAMPLE: 120-4T8C-18-50

FORM FACTOR	WATTAGE	VOLTAGE	CCT
120-4T8C=4FT Type C	18=18W	Blank=120-277V	5,000K

TECHNICAL PARAMETERS

TUBE	120-4T8C-18-50
Wattage	18W
Delivered Lumens (lm)	2,100lm
Efficacy (lm/W)	110lm/W
CRI	80
Lifespan (Hours)	50,000
Operating Temperature	4°F to 122°F (-20°C to 50°C)
Power Factor	.9
THD	20%
IP40 Rated	Protected from tools and small wires greater than 1mm.
REPLACES	32W