



# LED Vapor Tight High Bay Multi Wattage Multi CCT



4FT – 60W / 75W / 90W  
or  
4FT – 120W / 150W / 180W



## FEATURES

- IK10 and IP66 rated
- NSF rated for splash zone and non-food zone
- Dust tight
- Linkable design (see page 2 for details)
- 100,000 hours lifetime

## APPLICATIONS

- Food / Beverage Factories
- Heavy Manufacturing Facilities
- Underground Parking
- Refrigerated Storage Room
- Shopping Malls
- Supermarkets
- Warehouse
- Tunnel



<b>CONSTRUCTION</b> Polycarbonate housing and white cover with stainless steel clips.	<b>CONTROLS AND DIMMING</b> 0-10V dimming. Suitable to use with LED dimmers. Auxiliary 12V output.
<b>OPTICAL SYSTEM</b> Lumiled 2835 LED chips. 110° beam angle.	<b>INSTALLATION AND MOUNTING</b> Surface mount or suspension mount.
<b>ELECTRICAL</b> 120-277V input. -20°C to 40°C (-4°F to 104°F).	<b>WARRANTY</b> 5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

## OPTIONAL ACCESSORIES



Emergency Back-up Driver  
120-EMBU-15W-050



Motion Sensor-Microwave  
(Internal)  
120-MSU-CP/VT-BMD



Remote Control  
120-RCU-100



Surface Mount  
(included)



Suspension Kit  
120-MT-VT-SK

## MOUNTING OPTIONS



# LED Vapor Tight High Bay Multi Wattage Multi CCT

## Part Number 120-4VLXX-90-50-DIM

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
60W	3500K/4000K/5000K	8,916LM	148.6lm/W	120-277V	80	.9	20%	4.32W LED Tube
75W	3500K/4000K/5000K	11,145LM	148.6lm/W	120-277V	80	.9	20%	4.32W LED Tube
90W	3500K/4000K/5000K	13,374LM	148.6lm/W	120-277V	80	.9	20%	4.32W LED Tube

## Part Number 120-4VTLXX-180-50-DIM

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
120W	3500K/4000K/5000K	17,772LM	148lm/W	120-277V	80	.9	20%	250W MH
150W	3500K/4000K/5000K	22,215LM	148lm/W	120-277V	80	.9	20%	250W MH
180W	3500K/4000K/5000K	26,658LM	148lm/W	120-277V	80	.9	20%	250W MH

### LINKING TOGETHER TABLE

Form Factor	Voltage (18AWG)	Linkable Qty	Voltage (16AWG)	Linkable Qty
120-4VTLXX-90	120V	10	120V	15
	240V	20	240V	30
	277V	24	277V	35
120-4VTLXX-180	120V	5	120V	8
	240V	10	240V	16
	277V	12	277V	18

### PRODUCT DIMENSIONS

