



# LED Vapor Tight Multi Wattage Multi CCT Linkable



20W / 25W / 30W



25W / 35W / 50W



60W / 75W / 90W

## FEATURES

- IK10 and IP66 rated
- NSF rated for splash zone and non-food zone
- Glare-free / flicker-free
- Linkable design (see page 2 for details)
- 100,000 hours lifetime

## APPLICATIONS

- Auto Dealerships
- Commercial/Industrial
- Factories
- Schools
- Shopping Malls
- Supermarkets
- Warehouses
- Logistic Centers



|  |  |
|--|--|
| <b>CONSTRUCTION</b><br>Polycarbonate housing and white cover with stainless steel clips. | <b>CONTROLS AND DIMMING</b><br>0-10V dimming. Suitable to use with LED dimmers. Auxiliary 12V output.                          |
| <b>OPTICAL SYSTEM</b><br>Lumiled 2835 LED chips. 110° beam angle.                        | <b>INSTALLATION AND MOUNTING</b><br>Surface mount or suspension mount.   |
| <b>ELECTRICAL</b><br>120-277V input. -20°C to 40°C (-4°F to 104°F).                      | <b>WARRANTY</b><br>5-year limited warranty. Actual performance may differ as a result of end-user environment and application. |

## OPTIONAL ACCESSORIES



Emergency Back-up Driver  
120-EMBU-15W-050



Motion Sensor-Microwave  
(Internal)  
120-MSU-CP/VT-BMD



Remote Control  
120-RCU-100

## MOUNTING OPTIONS



Surface Mount  
(included)



Suspension Kit  
120-MT-VT-SK



# LED Vapor Tight Multi Wattage Multi CCT Linkable

## Part Number 120-VT2XX-30-50-DIM

| WATTAGE SELECTABLE | CCT SELECTABLE    | LUMENS     | EFFICACY   | VOLTAGE  | CRI  | POWER FACTOR | THD    | REPLACES       |
|--------------------|-------------------|------------|------------|----------|------|--------------|--------|----------------|
| 20W                | 3500K/4000K/5000K | 2,738.2LM  | 136.91lm/W | 120-277V | 81.7 | .9049        | 15.76% | 2.17W LED Tube |
| 25W                | 3500K/4000K/5000K | 3,422.75LM | 136.91lm/W | 120-277V | 81.7 | .9049        | 15.76% | 2.17W LED Tube |
| 30W                | 3500K/4000K/5000K | 4,086.6LM  | 136.91lm/W | 120-277V | 81.7 | .9049        | 15.76% | 2.17W LED Tube |

## Part Number 120-VT4XX-50W-DIM

| WATTAGE SELECTABLE | CCT               | LUMENS     | EFFICACY   | VOLTAGE  | CRI  | POWER FACTOR | THD   | REPLACES       |
|--------------------|-------------------|------------|------------|----------|------|--------------|-------|----------------|
| 25W                | 3500K/4000K/5000K | 3,395.75LM | 135.83lm/W | 120-277V | 81.7 | .9154        | 9.68% | 2.17W LED Tube |
| 35W                | 3500K/4000K/5000K | 4,754.05LM | 135.83lm/W | 120-277V | 81.7 | .9154        | 9.68% | 2.17W LED Tube |
| 50W                | 3500K/4000K/5000K | 6,775.3LM  | 135.83lm/W | 120-277V | 81.7 | .9154        | 9.68% | 2.17W LED Tube |

## Part Number 120-VT8XX-90-50W-DIM

| WATTAGE SELECTABLE | CCT               | LUMENS     | EFFICACY  | VOLTAGE  | CRI | POWER FACTOR | THD | *REPLACES      |
|--------------------|-------------------|------------|-----------|----------|-----|--------------|-----|----------------|
| 60W                | 3500K/4000K/5000K | 8,340LM    | 135.5lm/W | 120-277V | 80  | .9           | 15% | 2.32W LED Tube |
| 75W                | 3500K/4000K/5000K | 10,162.5LM | 135.5lm/W | 120-277V | 80  | .9           | 15% | see below      |
| 90W                | 3500K/4000K/5000K | 12,870LM   | 135.5lm/W | 120-277V | 80  | .9           | 15% | see below      |

\*4.32W or 2.59W LED Tube

### LINKING TOGETHER TABLE

| Form Factor | Voltage (18AWG) | Linkable Qty | Voltage (16AWG) | Linkable Qty |
|-------------|-----------------|--------------|-----------------|--------------|
| 120-VT2-XX  | 120V            | 30           | 120V            | 45           |
|             | 240V            | 60           | 240V            | 90           |
|             | 277V            | 70           | 277V            | 110          |
| 120-VT4-XX  | 120V            | 18           | 120V            | 25           |
|             | 240V            | 35           | 240V            | 50           |
|             | 277V            | 40           | 277V            | 60           |
| 120-VT8-XX  | 120V            | 10           | 120V            | 15           |
|             | 240V            | 21           | 240V            | 30           |
|             | 277V            | 24           | 277V            | 35           |



# LED Vapor Tight Multi Wattage Multi CCT Linkable

## PRODUCT DIMENSIONS

