



**FEATURES**

- IP20 rated
- (4) wattages to choose from
- Multi CCT
- Linkable design – 4 foot can link up to 10 fixtures
- ABS endcap for easy install and removal of lens
- 50,000 hours lifetime

**APPLICATIONS**

- *Limitless*
- Commercial/Industrial/Retail
- Aisles
- Corridors
- Distribution Centers
- Hallways
- Restrooms
- Stairwells
- Storage Closets



22W / 28W / 34W / 44W  
3500K / 4000K / 5000K

<b>CONSTRUCTION</b>	<b>CONTROLS AND DIMMING</b>
22-gauge metal housing with matte white finish. PMMA cover lens.	0-10V dimming.
<b>OPTICAL SYSTEM</b>	<b>INSTALLATION AND MOUNTING</b>
Samsung 2835 LED chips. Frosted lens. 110° beam angle.	Surface mount or suspension mount.
<b>ELECTRICAL</b>	<b>WARRANTY</b>
120-277V input. -20°C to 50°C (-4°F to 122°F).	5-year limited warranty. Actual performance may differ as a result of end-user environment and application.



**OPTIONAL ACCESSORIES**



Emergency Back-up Driver  
120-EMBU-15W-050



Suspension Kit  
120-MTU-VT/WL-SK



Metal Joiner Bracket  
120-MT-WL-JB



**Part Number 1201-WL4XX-44-50-DIM**

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
22W	3500K/4000K/5000K	3,031.6LM	137.8lm/W	120-277V	80	.9	20%	
28W	3500K/4000K/5000K	3,858.4LM	137.8lm/W	120-277V	80	.9	20%	
34W	3500K/4000K/5000K	4,685.2LM	137.8lm/W	120-277V	80	.9	20%	
44W	3500K/4000K/5000K	6,063.2LM	137.8lm/W	120-277V	80	.9	20%	

**PRODUCT DIMENSIONS**

