



Name of chiller:	Plate-tube Direct Evaporative Cool VSD Centrifugal Chiller		
Model:	WCTZ750CPA		
Performance:	Nominal Cooling Capacity	<i>kW</i>	745
	Nominal Cooling Capacity	<i>RT</i>	212
	Nominal Input power	<i>kW</i>	121
	COP (min at full load)	<i>W/W</i>	6.2
	IPLV		8.1
Noise Level	Within 1 meter	<i>dB</i>	72
	Within 10 meters	<i>dB</i>	< 65
Power:	Max operating current	<i>A</i>	245.7
	Power Supply	<i>Ph/V/Hz</i>	3/380/50
Chiller:	Refrigerant		R134a
	Compressor brand		Midea
	Compressor type		VSD Centrifugal
	Compressor adjustable range		10% to 100%
Evaporator:	Type		Flooded
	Water flow	<i>m³/h</i>	128.1
	Internal diameter of water pipe	<i>mm</i>	DN150
	Water pressure drop	<i>kPa</i>	≤70
Condenser:	Type		Plate-tube direct evaporative
	Exhaust static pressure	<i>Pa</i>	10
	Water consumption	<i>m³/h</i>	1.49
	No. of fan		4
	Fan input power	<i>kW</i>	12
	No. of pump		2
	Input power of pump	<i>kW</i>	6.0
Dimension:	Length	<i>mm</i>	7040
	Width	<i>mm</i>	2300
	Height	<i>mm</i>	3150
Weight:	Shipping	<i>kg</i>	11000
	Operating	<i>kg</i>	12400

Notes:-

- Rated conditions for cooling operation:
 - temperature of inlet/outlet chilled water: 12°C/7°C;
 - Ambient dry/wet bulb temperature: 35°C/24°C
- Temperature of supply cooling water is 30°C.
- Supply cooling water pressure is 0.06~0.15 Mpa.
- Chiller electric supply base on maximum load.
- If the chiller is installed indoor, the indoor air flow should be less than 2 m/s.
- If the local water hardness is higher than 400mg/L, water softener is required.
- Minimum refrigerated operating environment temperature is 15°C, or lower on request.
- Chiller water flow range is 50% - 130% of nominal chilled water flow in cooling mode.
- Standard of chiller is GB/T 18430.1 JB/T12323-2015
- 28 °C wet bulb correction factor is 0.98
- All above specifications are subject to change from to time without notice