



Name of chiller:	Plate-tube Direct Evaporative Cool VSD Centrifugal Chiller		
Model:	WCTZ1260CPA		
Performance:	Nominal Cooling Capacity	<i>kW</i>	1260
	Nominal Cooling Capacity	<i>RT</i>	358
	Nominal Input power	<i>kW</i>	210
	COP (min at full load)	<i>W/W</i>	6.0
	IPLV		8.4
Noise Level	Within 1 meter	<i>dB</i>	75
	Within 10 meters	<i>dB</i>	< 66
Power:	Max operating current	<i>A</i>	419.0
	Power Supply	<i>Ph/V/Hz</i>	3/380/50
Chiller:	Refrigerant		R134a
	Compressor brand		Midea
	Compressor type		VSD Centrifugal
	Compressor adjustable range		10% to 100%
Evaporator:	Type		Flooded
	Water flow	<i>m<sup>3</sup>/h</i>	216.7
	Internal diameter of water pipe	<i>mm</i>	DN200
	Water pressure drop	<i>kPa</i>	≤70
Condenser:	Type		Plate-tube direct evaporative
	Exhaust static pressure	<i>Pa</i>	10
	Water consumption	<i>m<sup>3</sup>/h</i>	2.52
	No. of fan		6
	Fan input power	<i>kW</i>	18
	No. of pump		2
	Input power of pump	<i>kW</i>	6.0
Dimension:	Length	<i>mm</i>	9600
	Width	<i>mm</i>	2300
	Height	<i>mm</i>	3150
Weight:	Shipping	<i>kg</i>	16400
	Operating	<i>kg</i>	18500

**Notes:-**

- Rated conditions for cooling operation:
  - temperature of inlet/outlet chilled water: 12°C/7°C;
  - Ambient dry/wet bulb temperature: 35°C/24°C
- Temperature of supply cooling water is 30°C.
- Supply cooling water pressure is 0.06~0.15 Mpa.
- Chiller electric supply base on maximum load.
- If the chiller is installed indoor, the indoor air flow should be less than 2 m/s.
- If the local water hardness is higher than 400mg/L, water softener is required.
- Minimum refrigerated operating environment temperature is 15°C, or lower on request.
- Chiller water flow range is 50% - 130% of nominal chilled water flow in cooling mode.
- Standard of chiller is GB/T 18430.1 JB/T12323-2015
- 28 °C wet bulb correction factor is 0.98
- All above specifications are subject to change from to time without notice