



| | | | |
|------------------|--|------------------------|-------------------------------|
| Name of chiller: | Plate-tube Direct Evaporative Cool Chiller | | |
| Model: | WLSZ400CHG | | |
| Performance: | Nominal Cooling Capacity | <i>kW</i> | 400 |
| | Ton of Refrigeration | <i>Ton</i> | 114 |
| | Nominal Input power (note 4) | <i>kW</i> | 87 |
| | System COP | <i>W/W</i> | 4.60 |
| | COP | <i>W/W</i> | 5.08 |
| Noise Level | Within 1 meter | <i>dB</i> | 80 |
| | Within 10 meters | <i>dB</i> | 68 |
| Power: | Max operating current | <i>A</i> | 200 |
| | Power Supply | <i>Ph/V/Hz</i> | 3/380/50 |
| Chiller: | Refrigerant | | R410A |
| | Refrigerant system | | 1 |
| | Number of compressors | | 3 |
| | Compressor brand | | Danfoss |
| Evaporator: | Compressor type | | Full-Hermetic Scroll |
| | Type | | Shell & Plate |
| | Water flow | <i>m³/h</i> | 68.8 |
| | Internal diameter of water pipe | <i>mm</i> | DN125 |
| Condenser: | Water pressure drop | <i>kPa</i> | ≤70 |
| | Type | | Plate-tube direct evaporative |
| | Exhaust static pressure | <i>Pa</i> | 10 |
| | Water consumption | <i>m³/h</i> | 0.56 |
| | No. of fan | | 2 |
| | Fan input power | <i>kW</i> | 6 |
| | No. of pump | | 1 |
| Dimension: | Input power of pump | <i>kW</i> | 2.2 |
| | Length | <i>mm</i> | 3,480 |
| | Width | <i>mm</i> | 2,300 |
| Weight: | Height | <i>mm</i> | 3,150 |
| | Shipping | <i>kg</i> | 6,600 |
| | Operating | <i>kg</i> | 7,200 |

Notes:-

1. Rated conditions for cooling operation:
 - (a) temperature of inlet/outlet chilled water: 12°C/7°C;
 - (b) Ambient dry/wet bulb temperature: 35°C/26°C
2. Temperature of supply cooling water is 30°C.
3. Supply cooling water pressure is 0.06~0.15 Mpa.
4. Nominal Input power includes power consumption of compressors, cooling water pump and condenser fan
5. Chiller electric supply base on maximum load.
6. If the chiller is installed indoor, the indoor air flow should be less than 2 m/s.
7. If the local water hardness is above Class I, water softener is needed.
8. Minimum refrigerated operating environment temperature is 15°C, or lower on request.
9. Chiller water flow range is 50% - 130% of nominal chilled water flow in cooling mode.
10. Standard of chiller is GB/T 18430.1 & JB/T12323-2015
11. 28°C wet bulb correction factor is 0.98
12. All above specifications are subject to change from to time without notice