



Name of chiller:	Plate-tube Direct Evaporative Cool Chiller		
Model:	WLSZ640CHG		
Performance:	Nominal Cooling Capacity	<i>kW</i>	640
	Ton of Refrigeration (TR)	<i>Ton</i>	182
	Nominal Input power (note 4)	<i>kW</i>	139
	COP	<i>W/W</i>	5.1
Noise Level	Within 1 meter	<i>dB</i>	81
	Within 10 meters	<i>dB</i>	69
Power:	Max operating current	<i>A</i>	320
	Power Supply	<i>Ph/V/Hz</i>	3/380/50
Chiller:	Refrigerant		R410A
	Refrigerant system		2
	Number of compressors		6
	Compressor brand		Danfoss
	Compressor type		Full-Hermetic Scroll
Evaporator:	Type		Shell & Tube
	Water flow	<i>m³/h</i>	110.1
	Internal diameter of water pipe	<i>mm</i>	DN200
	Water pressure drop	<i>kPa</i>	≤70
Condenser:	Type		Plate-tube direct evaporative
	Exhaust static pressure	<i>Pa</i>	10
	Water consumption	<i>m³/h</i>	0.90
	No. of fan		3
	Fan input power	<i>kW</i>	9
	No. of pump		1
	Input power of pump	<i>kW</i>	3.0
Dimension:	Length	<i>mm</i>	5,510
	Width	<i>mm</i>	2,300
	Height	<i>mm</i>	3,150
Weight:	Shipping	<i>kg</i>	9,300
	Operating	<i>kg</i>	10,100

Notes:-

- Rated conditions for cooling operation:
 - temperature of inlet/outlet chilled water: 12°C/7°C;
 - Ambient dry/wet bulb temperature: 35°C/26°C
- Temperature of supply cooling water is 30°C.
- Supply cooling water pressure is 0.06~0.15 Mpa.
- Nominal Input power includes power consumption of compressors, cooling water pump and condenser fan
- Chiller electric supply base on maximum load.
- If the chiller is installed indoor, the indoor air flow should be less than 2 m/s.
- If the local water hardness is higher than 400mg/L, water softener is required.
- Minimum refrigerated operating environment temperature is 15°C, or lower on request.
- Chiller water flow range is 50% - 130% of nominal chilled water flow in cooling mode.
- Standard of chiller is GB/T 18430.1 & JB/T12323-2015
- 28°C wet bulb correction factor is 0.98
- All above specifications are subject to change from to time without notice