Town of Norquay 2024 Drinking Water Quality and Compliance Annual Notice to Consumers

Introduction

The Water Security Agency and the Ministry of Environment requires that at least once each year waterworks owners provide notification to consumers of the quality of water produced and supplied as well as information on the performance of the waterworks in submitting samples as required by a Minister's Order or Permit to Operate a waterworks. The following is a summary of the Town of Norquay water quality and sample submission compliance record for the 2024 time period. This report was completed on January 29, 2025. Readers should refer to Water Security Agency's Municipal Drinking Water Quality Monitoring Guidelines, June 2015, EPB 502 for more information on minimum sample submission requirements and the meaning of type of sample. Permit requirements for a specific waterworks may require more sampling than outlined in the department's monitoring guidelines. If consumers need more information on the nature and significance of specific water tests, for example, "what is the significance of Selenium in a water supply", more detailed information is available from: http://www.hc-sc.gc.ca/ewh-semt/pubs/water-eau/index e.html .

Water Quality Standards Bacteriological Quality

Parameter/Location	Limit	Regular Samples Required	Regular Samples Submitted	# of Positive Regular Submitted (%)
Total Coliform	0 Organisms/100 mL	26	27	0
E. coli	0 Organisms/100 mL	26	27	0

Water Disinfection -

Chlorine Residual in Distribution System for Test Results Submitted with Bacteriological Samples						
	Minimum	Total Chlorine	Free Chlorine	# Tests	# Tests	# Adequate
Parameter	Limit	Residual Range	Residual Range	Required	Submitted	Chlorine (%)
Chlorine	0.1 mg/L free OR					
Residual	0.5 mg/L total	0.24-0.98	0.19-0.87	26	27	100%

Water Disinfection - Free Chlorine Residual for Water Entering Distribution System from Waterworks Records-

From water Treatment F	riant Records	Test Level	# Tests	# Tests Not Meeting	
Parameter	Limit (mg/L)	Range	Performed	Requirements	
Free Chlorine Residual	at least 0.1	0.22-1.02	366	0	

A minimum of 0.1 milligrams per litre (mg/L) free chlorine residual is required for water entering the distribution system. Tests are normally performed on a daily basis by the waterworks operator and are to be recorded in operation records. This data includes the number of free chlorine residual tests performed, the overall range of free chlorine residual (highest and lowest recorded values) and the number of tests and percentage of results not meeting the minimum requirement of 0.1 mg/L free chlorine residual.

<u>Turbidity - From Water Treatment Plant Records</u>

Parameter	Limit (NTU)	Test Level Range	# Tests Not Meeting Requirements	Maximum Turbidity (NTU)	# Tests Required	# Tests Performed	
Turbidity	_1.00	0.09-0.98_	0	0.98	366	366	

More information on water quality and sample submission performance may be obtained from:

Town of Norquay Box 327 Norquay, SK S0A 2V0 306-594-2101 norquay@sasktel.net



