



APU SC10-4 Series (small)

Portable	Yes
Frame	Stainless steel
Pressure gauge	Glycerine filled
Reduction unit air control	Easy control of outgoing pressure
Ratio	5:1 t/m 220:1
Max working pressure	35 bar t/m 1540 bar
Volume per stroke	42,44 t/m 1 cc
Flow rate	12 t/m 0,35 l/min

Options:

Portable	Extra handles
	Wheels
Test certificate	Option
Digital display	Option
Pressure transmitter	Option

Model	Ratio	Maximum working pressure		Volume per stroke		Flow rate	
		Bar	PSI	Cc	in3	l/min	US gpm
APU SC10-4-5	5:1	35	464	42.44	2.59	12	3.17
APU SC10-4-10	10:1	70	1015	22.77	1.39	8.5	2.25
APU SC10-4-15	15:1	105	1523	12.3	0.751	4.7	1.24
APU SC10-4-30	30:1	210	3045	7.6	0.464	2.7	0.71
APU SC10-4-35	35:1	245	3553	6.29	0.384	2.6	0.69
APU SC10-4-55	55:1	385	5583	4.01	0.245	1.6	0.42
APU SC10-4-100	100:1	700	10152	2.26	0.138	0.75	0.2
APU SC10-4-140	140:1	980	14213	1.57	0.096	0.6	0.16
APU SC10-4-220	220:1	1540	22335	1	0.061	0.35	0.09