



### APU SC10-5 Series (medium)

<b>Portable</b>	Yes
<b>Frame</b>	Stainless steel
<b>Pressure gauge</b>	Glycerine filled
<b>Reduction unit air control</b>	Easy control of outgoing pressure
<b>Ratio</b>	5:1 t/m 555:1
<b>Max working pressure</b>	35 bar t/m 3.850 bar
<b>Volume per stroke</b>	90,78 t/m 0,80 cc
<b>Flow rate</b>	30 t/m 0,35 l/min

### Options:

<b>Portable</b>	Extra handles
	Wheels
<b>Test certificate</b>	Option
<b>Digital display</b>	Option
<b>Pressure transmitter</b>	Option

Model	Ratio	Maximum working pressure		Volume per stroke		Flow rate	
		Bar	PSI	Cc	in3	l/min	US gpm
<b>APU SC10-5-5</b>	5:1	35	464	90.78	5.54	30	7.93
<b>APU SC10-5-10</b>	10:1	70	1015	42	2.59	23	6.08
<b>APU SC10-5-12</b>	12:1	84	1218	36	2.21	18	4.76
<b>APU SC10-5-20</b>	20:1	140	2030	34	1.39	12	3.17
<b>APU SC10-5-25</b>	25:1	175	2610	16	0.981	9	2.38
<b>APU SC10-5-30</b>	30:1	210	3045	14	0.861	7.5	1.98
<b>APU SC10-5-35</b>	35:1	245	3553	12	0.751	6	1.59
<b>APU SC10-5-55</b>	55:1	385	5583	7.6	0.464	3.5	0.92
<b>APU SC10-5-70</b>	70:1	490	7107	6.29	0.384	3	0.79
<b>APU SC10-5-85</b>	85:1	595	8629	5	0.31	3	0.79
<b>APU SC10-5-105</b>	105:1	735	10660	4	0.245	1.9	0.5
<b>APU SC10-5-140</b>	140:1	980	14213	3	0.188	1.5	0.4
<b>APU SC10-5-195</b>	195:1	1365	19797	2.26	0.138	1.15	0.3
<b>APU SC10-5-280</b>	280:1	1960	28427	1.57	0.096	0.7	0.18
<b>APU SC10-5-440</b>	440:1	3080	44671	1	0.061	0.43	0.11
<b>APU SC10-5-555</b>	555:1	3850	55000	0.8	0.048	0.35	0.09