

JJ Marlex, Inc.

E-Z Bond™ Uber Bond™

8 McLaren, Suite O, Irvine, CA 92618

TEL: (888) 973-9029

www.jjmarlex.com

www.e-zbond.com

E-mail : letsbond@jjmarlex.com

sales@e-zbond.com

SAFETY DATA SHEET

Date Prepared : 1/15/2025
MSDS No : Cyanoacrylate
Date-Revised : 1/15/2025
Revision No : 22

1. PRODUCT AND COMPANY IDENTIFICATION

GENERAL USE: Cyanoacrylate adhesive product

PRODUCT DESCRIPTION: Cyanoacrylate (S-105, S-110, S-120, S-180, S-205, S-210, S-220, S-280, S-305, S-310, S-320, S-380, I-1605, I-1650, I-16100, I-16300, I-16700, I-161500 G-2510, G-2520)

Emergency Contact: JJ Marlex, Inc.

Emergency Phone: 888-973-9029

Alternate Emergency Phone: 949-499-5157

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2A

Skin Irritation, Category 2

Target Organ Toxicity (Single exposure), Category 3

Skin Sensitization, Category 1

Physical:

Flammable Liquids, Category 4

GHS LABEL ELEMENTS



Exclamation Mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.
H319: Causes serious eye irritation.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
H227: Combustible liquid.

PRECAUTIONARY STATEMENT(S)

Prevention:

P264: Wash skin and hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P271: Use only outdoors or in a well-ventilated area.
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Response:

P370: In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P313: Get medical advice/attention.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable breath.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Disposal:

7944L5O1: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name Wt.% CAS

Ingredients	CAS No.	%
Ethyl Cyanoacrylate	7085-85-0	99-100
HYDROQUINONE	123-31-9	0-0.5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Peel or roll skin apart.

INGESTION: Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

INHALATION: Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes serious eye irritation. Will bond eyelids. Will cause excessive tearing.

SKIN: Bonds skin in seconds. May cause skin irritation. May cause sensitization by skin contact. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin.

INGESTION: Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE TOXICITY: Avoid exposure to vapor concentration in confined areas.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash.

5. FIRE FIGHTING MEASURES

3

GENERAL HAZARD: Combustible liquid and vapor. Product polymerized to solid by water.

EXTINGUISHING MEDIA: Use dry chemical extinguisher or flush with large amounts of water.

HAZARDOUS COMBUSTION PRODUCTS: Can burn in fire, releasing irritating vapors

EXPLOSION HAZARDS: None Known.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: None Known.

SENSITIVE TO STATIC DISCHARGE: None Known.

SENSITIVITY TO IMPACT: None Known.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Polymerize with water. Solid material may be scraped from surface.

LARGE SPILL: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

4

STORAGE TEMPERATURE: Store below 72F.

SHELF LIFE: One year from the date of shipment, unless otherwise noted.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV) (OSHA PEL)	OTHER
Ethyl Cyanoacrylate	0.2ppmTWA	None	None
HYDROQUINONE	2mg/m3TWA	2mg/m3TWA	2mg/m3TWA 4mg/m3STEL

ENGINEERING CONTROLS: Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Use Nitrile gloves and aprons to prevent contact. Do not use PVC, Nylon or Cotton materials.

RESPIRATORY: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

WORK HYGIENIC PRACTICES: Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Characteristic odor, irritating.

ODOR THRESHOLD: Odor Threshold = 1 ppm

5

APPEARANCE:

pH: Not Applicable.

PERCENT VOLATILE: Not Available

FLASHPOINT AND METHOD: 80°C (176°F) to 93.4°C (200°F) TAG CC

FLAMMABLE LIMITS: Not Available

AUTOIGNITION TEMPERATURE: 485°C (905°F)

VAPOR PRESSURE: < 0.2 mm Hg

VAPOR DENSITY: Not Available

BOILING POINT: > 149°C (300°F)

FREEZING POINT: Not Available

MELTING POINT: Not Determined

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE: Not Established

DENSITY: Not Available

SPECIFIC GRAVITY:

VISCOSITY #1:

MOLECULAR WEIGHT: Not Available

(VOC): < 20.000 g/L Per SCAQMD Method 316B.

COEFF. OIL/WATER: Partition coefficient (octanol/water): Not applicable.

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Avoid temperatures above 176° F (80° C), moisture and alkalies.

6

POSSIBILITY OF HAZARDOUS REACTIONS: Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.

INCOMPATIBLE MATERIALS: Polymerized by water, alcohol, amines, alkaline materials.

COMMENTS: REACTIVITY: Rapid exothermic polymerization will occur in the presence of water , amines, alkalis and alcohols.

11. TOXICOLOGICAL INFORMATION

ACUTE

<u>Chemical Name</u>	<u>ORAL LD₅₀</u>	<u>DERMAL LD₅₀</u>
ETHYL-2-CYANOACRYLATE DERMAL LD ₅₀ : > 2000 mg/kg	> 5000 mg/kg	> 2000 mg/kg

Notes: (Estimated)

ORAL LD₅₀: > 5000 mg/kg

INHALATION LC₅₀: Vapors may be irritating. Recommended TWA 0.2ppm.

EYE EFFECTS: Bonds skin and eyes in seconds. Eye irritant.

SKIN EFFECTS: Irritating to skin. May cause allergic skin reaction with prolonged contact.

CARCINOGENICITY

IARC: None known

NTP: None known

OSHA: None known

SENSITIZATION: Possible skin sensitizer.

TARGET ORGANS:

<u>Ingredient</u>	<u>Health Effect/ Target Organ</u>
Ethyl cyanoacrylate	Irritant, Allergen/ Respiratory, Skin

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA:

This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not restricted

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted
AIR (ICAO/IATA)

SHIPPING NAME: Not regulated (less than 500 mL). AVIATION REGULATED LIQUID, N.O.S. (ETHYL CYANOACRYLATE), UN3334, 9.

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not restricted

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate Health, Delayed Health, Fire, Reactive.

313 REPORTABLE INGREDIENTS: None above reporting de minimus.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None above reporting de minimus.

8

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name CAS

ETHYL-2-CYANOACRYLATE 7085-85-0

Polymethyl methacrylate 9011-14-7

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Not applicable.

CALIFORNIA PROPOSITION 65: No California Proposition 65 ingredients are known to be in this product.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Combustible Liquid



Health Hazard

Class B3 - Combustible, D2B - Irritant.

WHMIS CLASS: B3 - combustible, D2B - irritant.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components are listed on or are exempt from listing on the Domestic Substances List.