

SentryLink Smart Intercom (STK001)

GBF SentryLink Video Intercom—Full IP smart intercom, has 10" touchscreen for both surface or in-wall versions.

Main Features:

- 1080P HD CMOS camera
- Access Code opening
- Local Card opening
- Visitor call and push notification
- Remote opening for authorized visitor
- Cloud record opening history
- Tempered glass panel, IP65 rated for dust, water and chemical resistance.
- Infrared sensors for motion detection and night vision
- Flush Mounted or Surface Mounted.
- Working temperature: from $-30^{\circ}\text{C} / -22^{\circ}\text{F}$ to $+60^{\circ}\text{C} / + 140^{\circ}\text{F}$
- Compatible with NVR and other smart home automation system.

General Specification:

- Touchscreen size: 10.1" TFT, Resolution: *1024 x 600*
- Operation System: Embedded Android 5.1
- Video Specification:

Video compression: H264

Image Sensor: $1/3"$ 2MP CMOS

Lens: 3.6mm

Angle of view: Vertical 120° , Horizontal 90° .

Day/Night: Color Image

- Audio Specification:

Audio compress: G.711/AAC

Audio Input: Omnidirectional Mic

Audio output: Built-in Speaker

Bidirectional Talk: Support two-way bidirectional talk

- Network Requirements:

Ethernet: 10M/100Mbps

Network protocol: TCP/IP

- Power requirement:

Power: 12V DC, 5A

Power consumption: Standby $\leq 1W$, Work $\leq 10W$