

Envirofoam™

Low Density™ | Medium Density™
| High Density™ | TRU-2™

Our full line of low odor, highyield spray polyurethane foam (SPF) insulation products are designed with wide application windows to make it easier for you and your SPF crew to succeed in the field.



DESIGNED WITH YOU IN MIND



Easy to apply, with wide application window and temperature tolerance



Excellent adhesion in a wide range of ambient conditions and applications



Thick passes overhead without dripping



Exceptional yield and reduced waste



Superior performance for lasting building efficiency

WE'RE COMMITTED TO BUILDING YOUR BUSINESS

Envirofoam boasts 15 years of product innovation and brand dominance. With a Large customer base, Envirofoam of America spray foam contractors are backed by superior products, a strong technical team and a brand that drives sales.

Become an Envirofoam spray foam contractor
Call 877.362.6552, or visit EnvirofoamOfAmerica.com



Envirofoam® Spray Foam Insulation

Envirofoam™ spray foam insulation products play a crucial role in ensuring your customer's building operates efficiently as a system, minimizing leaks and keeping conditioned air inside. When used with other responsible building practices, Envirofoam™ by Envirofoam of America™ can save your customers up to 50% on heating and cooling costs compared to traditionally insulated structures.*

Envirofoam™ Low Density



Envirofoam™ Low Density is a high yield, open cell, Class 1 fire rated, 100% waterblown spray polyurethane foam insulation designed for use in residential and commercial walls, attics and roof decks. When applied, Envirofoam™ Low Density expands to over 100 times in size in approximately 4 seconds, filling and sealing building cavities of any shape and size. It is sprayer friendly, offering a wide application window and temperature tolerance and excellent adhesion when installed in cold temperatures down to 15°F.

Envirofoam™ Low Density seals and insulates in one step, helping property owners reduce energy consumption by up to 50% when compared to conventional insulation systems. Its superior thermal insulation, sealant and sound attenuation properties contribute to a healthy, quiet and more energy efficient building.

Envirofoam™ Low density X



Envirofoam™ Low Density X is a fast set, open cell, Class I fire rated, Appendix X compliant, 100% waterblown spray polyurethane foam insulation system designed to reduce energy consumption in residential and commercial structures up to 50% by insulating and air sealing the thermal envelope in a single step.

Envirofoam™ Low Density X is applied as a liquid and then expands over 100x in seconds to fill and seal building cavities of any shape or size. It exhibits superior thermal insulation, air barrier, and sound attenuation properties compared to conventional insulation materials, and can be used in attics and crawlspaces without prescriptive ignition barrier, or intumescent coating. Once fully cured Envirofoam™ Low Density X remains soft and flexible allowing for movement of the substrate or building over time while maintaining proper insulation and air sealing of the building envelope.

Envirofoam™ Medium Density



Envirofoam™ Medium Density is an Hybrid cell, 100% water blown spray polyurethane foam insulation system with an initial R-value of 5.3 and effective R-4.7 per inch. When applied, Envirofoam™ Medium Density expands to over 50 times in size in approximately 8 seconds, filling and sealing building cavities of any shape and size. It achieves near twice the yield of 2.0 lb spray foam while reducing waste and cleanup time by up to 50% compared to that of a ½ lb spray foam insulation. Giving you the best of both the open cell foams High STC (Sound Transmission Control) and Closed cells high R-Value, this foam is gaining in popularity with knowledgeable installers. Envirofoam™ Medium Density satisfies energy code in most climate zones at less than 4 inches and is designed for use in wall, attic and roof deck applications where cavity depth is limited.

Envirofoam™ TRU-2



Envirofoam™ TRU-2 is a closed cell, 245fa blown spray polyurethane foam insulation that achieves exceptional yield and adhesion in a wide range of ambient conditions and applications. When applied, Envirofoam™ TRU-2 expands to 25 times its size in approximately 12 seconds to seal and insulate. It can safely be applied in lift thickness of up to 4 inches in a single pass with excellent control and a smooth finish, achieving Appendix X compliance without any additional coatings.

Envirofoam™ TRU-2 is designed for use in wall, attic and roof deck applications where it insulates, air seals and adds structural strength. It's also suitable for tank and pipeline insulation and as a below grade exterior insulation for foundation walls or slabs. Envirofoam™ TRU-2 is Class I fire rated and has an R-value of 6.85 per inch.

Envirofoam™ High Density



Envirofoam™ High Density is a fast set, closed cell, spray polyurethane foam insulation that utilizes an HFO (hydrofluorolefin) blowing agent. This blowing agent features a GWP of 1 and is an ideal, non hydrofluorocarbon blowing agent option that still delivers the performance that contractors demand.

Envirofoam™ High Density is designed for use in residential and commercial structures, exterior foundation or perimeter insulation, below grade applications, exterior tank/pipe insulation, and more. It is applied as a liquid and expands 25x in seconds to fill and seal building cavities of any shape and size. It exhibits superior thermal insulation, air barrier, and sound attenuation properties compared to conventional insulation materials. Once fully cured, Envirofoam™ High Density remains rigid maintaining significant structural strength and thermal insulation properties in adverse conditions across a wide variety of applications.



Become a Envirofoam spray foam contractor Call 877.362.6552, or visit EnvirofoamOfAmerica.com

Envirofoam Of America LLC | 136 Judd | Glenarm, Illinois 62536 | 877.362.6552 | <http://envirofoamofamerica.com>

*Based on case studies, modeling and project profiles at <http://envirofoamofamerica.com> Envirofoam SPF products are spray polyurethane foams. During application, precautions should be taken by applicators, helpers and building occupants to protect them from fumes, mists and spills. Product information and specifications subject to change without notice. For the most current product information, please consult <http://envirofoamofamerica.com> ©2020 Envirofoam Of America LLC All rights reserved.