

Push to Talk Over Cellular Product MSRP Price Book

For Hytera PoC Devices, HORIZON PoC Services and Systems
September 2026



HORIZON

Contents

MNC360 PoC Mobile Radio	3
MNC360 PoC Mobile Radio Accessories	4
PNC360S PoC Device	5
PNC360S PoC Device Accessories	6
PNC380S PoC Device	7
PNC380S PoC Device Accessories	8
PNC550 PoC Mobile Computer Accessories	10
PNC560S/PNC560 PoC Mobile Computer	11
PNC560S/PNC560 PoC Mobile Computer Accessories	12
VM780 PoC Body Worn Camera and PoC Radio ..	14
VM780 PoC Body Worn Camera and PoC Radio Accessories	15
Hytera HORIZON License Pricing	16
Hytera HORIZON Bridge Pricing	17
Hytera PoC Protection Plan Pricing	18
HORIZON Device Logo and Dispatcher Customized Logo / URL	18

Dealer Terms:

A Hytera PoC Dealer Agreement is required to sell Hytera PoC devices and HORIZON services.

All prices are Net/Net. Dealer rebates and marketing co-op do not apply.

*The PNC550 radio is End of Life but the accessories will continue to be sold.

Hytera US Inc.

8 Whatney Suite 200
Irvine, CA 92618
(954) 846-1011

www.hytera.us



MNC360 PoC Mobile Radio



The MNC360 is a compact and easy-to-operate Push-to-Talk over Cellular (PoC) Mobile Radio that supports nationwide instant group calling, dispatching, and location tracking. The Hytera MNC360 provides safe and reliable in-vehicle fleet communications.

Part Number	MSRP
MNC360	\$460.00

Specifications

Cellular Standards	FDD-LTE, TDD-LTE, WCDMA, GSM
Built-in Wi-Fi	Built-in Wi-Fi 2.4GHz 802.11 b/g/n
Bluetooth	Bluetooth 4.2
GPS	GPS (A-GPS)/BDS
Audio	Built-in Microphone and Handheld Mic and digital noise cancellation. High-volume forward-facing loudspeaker with 4W Rated Audio Power Output.
Display	2" LCD 320x240
Card Slots	2x Micro-SIM, 1x MicroSD TF
Ports	2x LTE Antenna Ports, SMA GPS Antenna Port, MicroUSB 2.0 connector, 3.5mm audio accessory port, secure 10-pin aviation port for handheld mic, power connector

Standard Accessories (Included with MNC360)

Part Number	Description
MNC360	PoC Mobile Radio
SM16A1	Handheld Mic with Mounting Bracket
AN1700W01	2x LTE Paddle Antenna
BRK33	Mounting Bracket and Screws
GPS04	GPS Antenna
PWC34	Power Cord

Warranty

Standard	2 Years
----------	---------

MNC360 PoC Mobile Radio Accessories

Part #	Image	Technical Specification		MSRP
SM16A1 Handheld Mic		VOX: PTT Key: Emergency Key: Connector Type: IP Rating:	N/A Yes N/A 10 Pin Connector IP54	\$69.10
AN1700W01 LTE Paddle Antennas		Dimensions: Frequency Range: Certification:	156.8 X 16mm 700-2700MHz RoHS, REACH	\$16.50
GPS04 GPS Antenna		Frequency Range: Connector Type: Cable Length: Certification:	1575MHz SMA 3000mm RoHS, REACH	\$19.30
PWC34 Power cable		Cable Length: Certification:	3000mm RoHS, REACH	\$40.60
BRK33 Mounting Bracket and Screws		Dimensions: Operating Temperature: Certification:	125 x 53 x 65mm -20°C ~ 60°C RoHS, REACH	\$28.60
SEC1223 External Desktop Power Supply		Dimensions: Weight: Input: Output: Amps: Certification:	7.28 x 8.19 x 2.40 (in) 1.6 kg 100-130 VAC 13.8 VDC 23 Amps UL, FCC	\$212.00
SM27W2 Bluetooth Speaker Mic and Mounting Bracket		Effective Range: Operation per Charge: Speaker power: Control buttons: Clip Mount: Certified:	10m 20h 2W (rated) 3W (max) PTT, Nav, Programmable Surface mount and belt clip FCC, IC	\$165.30
EHW08 Bluetooth Earpiece with Microphone		Dimensions: PTT Key: Bluetooth: Certification:	101 X 62 X 28mm Yes V4.1 RoHS, REACH	\$150.20
SM09C1 External Speaker		Dimensions: Speaker Sensitivity: Average Impedance: Speaker power: Operating Temp:	6' Cable, 2-pin 88dB ±2dB 600,700,800,900Hz 8Ω ±15% @500Hz 15 W (rated) / 20W (max) -30°C to +70°C	\$81.10
SM10A1 Table Microphone		Speaker sensitivity: Impedance: Speaker power: Operating temperature:	88dB ±2dB @ 600,700,800,900Hz Average 8Ω ±15% @500Hz 15W (rated) / 20W (Max) -30°C to +70°C	\$105.20

PNC360S PoC Device



The PNC360s is an ultra-compact, rugged, and easy-to-operate Push-to-Talk over Cellular (PoC) and Wi-Fi device that supports nationwide instant group calling, dispatching, and location tracking.

Part Number	MSRP
PNC360S	\$260.00

Specifications

Cellular Standards	FDD-LTE, TDD-LTE, WCDMA, GSM
Built-in Wi-Fi	2.4GHz 802.11 b/g/n
Bluetooth	Bluetooth 4.2
GPS	GPS/Galileo/AGPS
Audio	Digital Noise suppression, high-volume speaker, speaker power 2W (rated) 3W (max)
Keypad	Partial Keypad
Display	1 3/4" 160x128 TFT LCD Non-touch
Camera	N/A
Ruggedized Compliance	MIL-STD-810 H, IP67, ESD IEC 61000-4-2, -4 to +140 F Operating Temperature
Texting	Receive and view text messages sent from dispatcher and other Hytera PoC devices
Safety	Emergency (programmable) button, Stun and Revive
Battery	3100mAh Li-ion, ≥18h (5-5-90 working cycle)
SIM Card Slot	Nano SIM
Ports	USB Type C Charging Port, 3.5mm Audio Interface
Memory	1GB RAM, 8GB ROM

Standard Accessories (Included with PNC360S)

Part Number	Description
PNC360S	PoC Device
BP4008	Lithium Polymer Battery
PS2023	Power Adapter
PC158	USB Charging Cable
RO03	Carrying strap
BC66	Belt Clip

Warranty

Standard	2 Years
----------	---------

PNC360S PoC Device Accessories

Part #	Image	Technical Specification		MSRP
BP4008 Lithium Polymer Battery		Nominal Capacity:	4000mAh	\$31.50
		Nominal Voltage:	3.85V	
		Working Time (10/10/80):	48h	
		Battery Life Cycle:	500 charges	
PS2023 Power Adapter (US)		Operating Voltage:	90-264VAC	\$15.80
		Input:	100-120VAC	
		Output:	5VDC/2A	
		Certification:	UL	
PC158 Charging Cable		Interface:	USB to USB Type C	\$13.60
		Plug Type:	US standard	
		Cable Length:	1.0m	
BC66 Belt Clip		Applicable To Belts:	45 mm or less	\$5.80
		Material:	Polycarbonate	
		Swivel:	No	
RO03 Carrying Strap		Length:	25cm	\$3.90
		Material:	Nylon	
EAS07 Earpiece with in-line PTT & Transparent Acoustic Tube		VOX:	N/A	\$31.60
		PTT Key:	Yes	
		Emergency Key:	N/A	
		Connector Type:	3.5mm plug	
		Speaker Power:	20mW rated; 30mW max	
EHS26R C-Style Earset for Right Ear		VOX:	N/A	\$17.30
		PTT Key:	Yes	
		Connector Type:	3.5mm plug	
		Speaker Power:	10mW max	
POA121 Wireless PTT and Charging Cable		Connection Distance:	8~10m	\$127.60
		Certification:	CE, FCC, IC	
		Working Time (5/5/90):	≥100H	
		Charging Time:	<2H	
		IP Rating:	IP67	
SM27W2 Bluetooth Speaker Mic with Clip		Effective Range:	10m	\$165.30
		Operation per Charge:	20h	
		Speaker power:	2W (rated) 3W (max)	
		Control buttons:	PTT, Nav, Programmable	
		Clip Mount:	Surface mount and belt clip	
		Certified:	FCC, IC	
EHW08 Bluetooth Earpiece with Microphone		Dimensions:	101 X 62 X 28mm	\$150.20
		PTT Key:	Yes	
		Bluetooth:	V4.1	
		Certification:	RoHS, REACH	
EHS30 C-Style Earpiece with in-line PTT		VOX:	N/A	\$31.60
		PTT Key:	Yes	
		Connector Type:	3.5mm Jack	
		Speaker Power:	10mW max	

PNC380S PoC Device



The PNC380S is a compact, rugged, and easy-to-operate Push-to-Talk over Cellular (PoC) and Wi-Fi device. The PNC380S supports nationwide voice and video group calling, dispatching, and GPS location tracking. It is AT&T Network Ready, has T-Mobile IoT Network Certification, PTCRB certified and features an optional dash-mount car kit.

Part Number	MSRP
PNC380S	\$400.00

Specifications

Cellular Standards	FDD-LTE, WCDMA, GSM
Built-in Wi-Fi	Built-in Wi-Fi 2.4GHz and 5GHz, 802.11 b/g/n
Bluetooth	Bluetooth 4.2
GPS	GPS/A-GPS
Audio	Digital Noise suppression, high-volume speakers, 1W Rated Audio Power Output (Max 2W)
Keypad	Full Keypad
Display	2.0" 320x240 TFT Non-touch
Camera	8MP Rear Facing
Ruggedized Compliance	MIL-STD-810 G, IP67, ESD IEC 61000-4-2, -40 to +140 F Operating Temperature
Texting	Send, receive, and view text messages between dispatcher and other Hytera PoC devices
Safety	Emergency button, Stun and Revive, Flashlight
Battery	4000mAh Li-ion Polymer, ≥24h (5-5-90 working cycle)
SIM	Nano SIM (8.8mm x 12.3mm)
Ports	Micro USB 2.0, 3.5mm Audio, Dock Charger interface, Car Kit Connection Contacts
Memory	1GB RAM, 8GB ROM, Micro SD/TF card, up to 32GB

Standard Accessories (Included with PNC380S)

Part Number	Description
PNC380S	PoC Device
BP4008	Li-ion Battery
PS2023	Switching Power Adapter
PC80	USB Charging Cable
RO03	Nylon Strap
BC50	Belt Clip

Warranty

Standard	2 Years
----------	---------

PNC380S PoC Device Accessories

Part #	Image	Technical Specification		MSRP
BP4008 Lithium Polymer Battery		Nominal Capacity:	4000mAh	\$31.50
		Battery Life 5/5/90:	24h	
		Nominal Voltage:	3.85V	
		Battery Life Cycle:	500 charges	
PS2023 Power Adapter (US)		Operating Voltage:	90–264VAC	\$15.80
		Input:	100-120VAC	
		Output:	5VDC/2A	
		Certification:	UL	
PC80 Programming and Charging Cable		Connectors:	USB to Micro USB	\$19.10
		Length:	1 m	
		Connector Type:	USB to Micro USB	
MCL35-S Multi-unit Charger		Supported Battery Type:	Li-ion and Li-polymer batteries	\$429.00
		Charging Pockets:	6 batteries and 6 devices	
		Input:	100-240VAC or 12VDC/7A	
		Charging Current:	1400 mA (per pocket)	
		Charger Type:	Smart	\$150.20
		Certification:	CE	
EHW08 Bluetooth Earpiece with Microphone		Dimensions:	101 X 62 X 28mm	
		PTT Key:	Yes	
		Bluetooth:	V4.1	\$127.60
		Certification:	RoHS, REACH	
POA121 Wireless PTT and Charging Cable		Connection Distance:	8~10m	
		Certification:	CE, FCC, IC	
		Working Time (5/5/90):	≥100H	\$3.90
		Charging Time:	<2H	
		IP Rating:	IP67	
RO03 Nylon Strap		Length:	47.5cm	\$5.80
		Material:	Nylon	
BC50 Belt Clip		Applicable To Belts:	50mm or less	
		Swivel:	No	
		Material:	Polycarbonate	\$17.30
EHS26R C-Style Earset for Right Ear		VOX:	N/A	
		PTT Key:	Yes	
		Connector Type:	3.5mm plug	
		Speaker Power:	10mW max	
EHS30 C-Style Earpiece with in-line PTT		VOX:	N/A	\$31.60
		PTT Key:	Yes	
		Connector Type:	3.5mm Jack	
		Speaker Power:	10mW max	
SM27W2 Bluetooth Speaker Mic with Clip		Effective Range:	10m	\$165.30
		Operation per Charge:	20h	
		Speaker power:	2W (rated) 3W (max)	
		Control buttons:	PTT, Nav, Programmable	
		Clip Mount:	Surface mount and belt clip	
		Certified:	FCC, IC	

Part #	Image	Technical Specification	MSRP
CK10 Car Kit Body with Power Cable		The CK10 Car Kit is a rugged vehicle mounting assembly that enables the PNC380S to be installed in a vehicle and allows the PNC380S to be easily removed. The Car Kit also functions as a docking charger Dimensions: With locking bracket: 174 x 79 x 54mm, weight is 225g Without locking bracket: 174 x 79 x 45mm, weight is 165g Includes: Docking chassis, locking bracket, locking bracket key Controls: On/Off Power Button Ports: External speakers, microphones, and push-to-talk buttons Material: Polycarbonate Input: 12VDC	\$158.40
SM18A3 Palm Mic		VOX: N/A PTT Key: Yes Emergency Key: N/A Connector Type: 10 Pin Connector IP Rating: IP54	\$76.50
POA77 Visor Mic		Interface: 3.5 mm jack Cable length: 3.5m	\$31.60
SM09S1 External Amplified Speaker		Connector Type: 10 Pin Connector Speaker Power: 15W (rated) / 20W (max) IP Rating: IP55 Operating Temperature: - 30°C to 70°C	\$171.60

PNC550 PoC Mobile Computer Accessories

Part #	Image	Technical Specification	MSRP
BP4003 Li-ion Polymer Battery (4000 mAh)		Nominal Capacity: 4000mAh Nominal Voltage: 3.8V Working Time (5/5/90): >18h Battery Life Cycle: 500 charges	\$64.40
CH20L14 Dual Pocket Charger		Supported Battery Type: Li-ion battery and Li-Polymer Charging Pocket: 2 Input: 5VDC, 2 A Charging Current: 2000 mA (total) Certification: CE	\$21.50
PS2023 Power Adapter (US)		Operating Voltage: 90-264VAC Input: 100-120VAC Output: 5VDC/2A Certification: UL	\$15.80
PC158 Charging Cable		Connectors: USB to USB Type C Plug Type: US standard Cable Length: 1.0m	\$13.60
BC49 Case and Belt Clip		Dimensions: 163 x 82 x 33mm Fits Belts and Straps up to: 61mm or less Material: PC1414	\$25.80
EAS07 Earpiece with in-line PTT & Transparent Acoustic Tube		VOX: N/A PTT Key: Yes Emergency Key: N/A Connector Type: 3.5mm plug Speaker Power: 20mW rated; 30mW max	\$31.60
EHS30 C-Style Earpiece with in-line PTT		VOX: N/A PTT Key: Yes Connector Type: 3.5mm Jack Speaker Power: 10mW max	\$31.60
POA121 Wireless PTT and Charging Cable		Connection Distance: 8~10m Certification: CE, FCC, IC Working Time (5/5/90): ≥100H Charging Time: <2H IP Rating: IP67	\$127.60
SM27W2 Bluetooth Speaker Mic with Clip		Effective Range: 10m Operation per Charge: 20h Speaker power: 2W (rated) 3W (max) Control buttons: PTT, Nav, Programmable Clip Mount: Surface mount and belt clip Certified: FCC, IC	\$165.30
EHW08 Bluetooth Earpiece with Microphone		Dimensions: 101 X 62 X 28mm PTT Key: Yes Bluetooth: V4.1 Certification: RoHS, REACH	\$150.20

PNC560S/PNC560 PoC Mobile Computer



The PNC560 is a feature rich, easy-to-operate Push-to-Talk over Cellular (PoC) and Wi-Fi Mobile Computer with integrated Infrared Barcode/QR Code Scanner. The PNC560 supports nationwide voice and video group calling, dispatching, and location tracking. The PNC560S is a lower cost model without a scanner.

Part Number	Description	MSRP
PNC560S	Without Scanner	\$839.00
PNC560	With Scanner	\$1,365.00

Specifications

Cellular Standards	FDD-LTE, TDD-LTE, WCDMA, GSM, 5G
Built-in Wi-Fi	Built-in Wi-Fi 2.4/5.0 GHz 802.11b/g/n/ac
Bluetooth	Bluetooth 5.0
GPS	GPS/A-GPS/Galileo/BDS
Audio	AI-based noise suppression, high-volume speakers, 3W Max Audio Power Output
Keypad	Touch Display
Display	6.3" Gorilla Glass 2340 x 1080 FHD+, Dew Drop Notch, Capacitive Touch, Wet Touch, and Glove Touch
Camera	8MP Front Facing, 8MP Rear Facing Telephoto, and 48MP (via software algorithm) Wide Angle Rear Facing
Ruggedized Compliance	MIL-STD-810 G, IP68, ESD IEC 61000-4-2, -40 to +140 F Operating Temperature
Texting	Send, receive, and view text messages between dispatcher and other Hytera PoC devices
Safety	Emergency button, Stun and Revive, Flashlight
Battery	5040mAh Li-Ion Polymer, ≥15h use
SIM	2X Nano SIM, or 1X Nano SIM and 1X MicroSD 128Gb
Ports	USB Type C Charger Interface, 3.5mm Audio Interface
Memory	4GB RAM + 32GB ROM

Standard Accessories (Included with PNC560S/PNC560)

Part Number	Description
PNC560	PoC Mobile Computer
BP4901	Li-Ion Polymer Battery
PS3007	Power Adapter
PC158	USB Charging Cable
POA200	Tempered Glass Screen Protector

Warranty

Standard	2 Years
----------	---------

PNC560S/PNC560 PoC Mobile Computer Accessories

Part #	Image	Technical Specification	MSRP
BP4901 Li-ion Polymer Battery (5040mAh)		Nominal Capacity: 5040mAh Nominal Voltage: 3.8V Working Time (5/5/90): > 18h Battery Life Cycle: 500 charges	\$71.50
CH20L19 Desktop Charger		Supported Battery Type: Li-ion battery and Li-Polymer Charging Pocket: 2 Input: 5VDC, 2A Charging Current: 2000 mA (battery) Certification: CE/FCC	\$73.60
PS3007 Power Adapter (US)		Input Voltage: 100 – 240VAC/0.6A Output: 5VDC/3A Output Interface: USB A Certification: UL/FCC	\$31.50
PC158 Charging Cable		Connectors: USB A to USB Type C Cable Length: 1.0m	\$13.60
POA200 Tempered Glass Screen Protector		Dimensions: 157.17 x 71.7 x 0.2 mm Operating Temperature: 14°F-104°F Storage Temperature: -4°F-122°F	\$8.00
POA207 Protective Case with Hand Strap		Dimensions: 172 x 85 x 27 mm Material: Protective Case: PC Plastic + Silicone; Hand strap - Nylon Color: Black and Gray Weight: 55g	\$42.00
BC39 Belt Clip for use with POA207		Dimensions: 88 x 30mm Material: Plastic and Metal Swivel: Yes	\$10.60
EAS07 Earpiece with in-line PTT & Transparent Acoustic Tube		VOX: N/A PTT Key: Yes Emergency Key: N/A Connector Type: 3.5mm plug Speaker Power: 20mW rated; 30mW max	\$31.60
EHS30 C-Style Earpiece with in-line PTT		VOX: N/A PTT Key: Yes Connector Type: 3.5mm Jack Speaker Power: 10mW max	\$31.60

PNC560S/PNC560 PoC Mobile Computer Accessories

Part #	Image	Technical Specification	MSRP
POA121 Wireless PTT and Charging Cable		Connection Distance: 8~10m Certification: CE, FCC, IC Working Time (5/5/90): ≥100H Charging Time: <2H IP Rating: IP67	\$127.60
SM27W2 Bluetooth Speaker Mic with Clip		Effective Range: 10m Operation per Charge: 20h Speaker power: 2W (rated) 3W (max) Control buttons: PTT, Nav, Programmable Clip Mount: Surface mount and belt clip Certified: FCC, IC	\$165.30
EHW08 Bluetooth Earpiece with Microphone		Dimensions: 101 X 62 X 28mm PTT Key: Yes Bluetooth: V4.1 Certification: RoHS, REACH	\$150.20

VM780 PoC Body Worn Camera and PoC Radio



The VM780 Body Worn Camera integrates a body camera, a PoC radio, and a remote speaker mic into a single device that records, stores, and shares video and audio over cellular LTE and Wi-Fi networks. The VM780 supports nationwide voice and video group calling, dispatching, and location tracking. It features video management and evidence collection software applications.

Model	Part Number	Description	MSRP
VM780	SC00888	16G Memory	\$734.00
	SC00890	32G Memory	\$797.00
	SC00891	64G Memory	\$891.50
	SC00892	128G Memory	\$975.50

Specifications

Cellular Standards	FDD-LTE, TDD-LTE, WCDMA, GSM
Built-in Wi-Fi	Built-in Wi-Fi 2.4GHz 8, 02.11b/g/n
Bluetooth	Bluetooth 4.2
GPS	GPS/BDS/GLONASS
Audio	Dual Mics, Digital Noise suppression, Dual 1.5W high-volume speakers, 2W Max Audio Power Output
Keypad	Touch Display
Display	2.8" TFT-LCD color touch screen
Camera	216° rotating 16MP camera with LED lighting. 1080p mp4 (1080p@30fps, 720p@30/60fps, 480p@30fps), wide angle view, automatic night vision, H.265 compression, and AES256 encryption
Ruggedized Compliance	MIL-STD-810 G, IP67, ESD 6 kV (Air discharge 12 kV), -22 to +140 F Operating Temperature
Texting	Send, receive, and view text messages between dispatcher and other Hytera PoC devices
Safety	Emergency button with auto video record, 30 second pre and post recording buffer
Battery	3500 mAh Li-Ion, 8 hours continuous video at 720p@30fps
SIM	Nano SIM (8.8mm x 12.3mm)
Ports	Micro USB 2.0, 4-pin charging and video collection contacts
Memory	Available with 16GB, 32GB, 64 GB, or 128GB

Standard Accessories (Included with VM780)

Part Number	Description
BP3501	3500mAh Li-Ion Polymer Battery
PS2023	Switching Power Adapter
PC80	USB Charging Cable
RO01	Nylon Strap
BC40	Belt Clip

Warranty

Standard	1 Year
----------	--------

VM780 PoC Body Worn Camera and PoC Radio Accessories

Part #	Image	Technical Specification	MSRP
BP3501 Li-Ion Polymer Battery (3500mAh)		Nominal Capacity: 3500mAh Nominal Voltage: 3.85V Working Time (5/5/90): 8h Battery Life Cycle: 500 charges IP Rating: IP68	\$85.80
MCL30 Multi-Unit Charger with Data Interface		Supported Battery Type: Li-ion and Li-polymer battery Input: 100-240VAC or 12VDC/7A Charging Current: 1000 mA (per pocket) Charging Pockets: 6 devices and 6 batteries Charger Type: AC Power Adapter Certification: CE, FCC	\$552.20
CH20L15 Dual pocket charger		Supported Battery Type: Li-ion and Li-Ion polymer Charging Pocket: 2 Input: 5V DC, 2 A Charging Current: 2000 mA (total) Charger Type: PS2023	\$30.30
PS2023 Power Adapter (US)		Operating Voltage: 90–264VAC Input: 100-120VAC Output: 5VDC/2A Certification: UL	\$15.80
PC80 Programming and Charging Cable		Connectors: USB to Micro USB Length: 1 m Connector Type: USB to Micro USB	\$19.10
EHU03 C-Style Earpiece		VOX: N/A PTT Key: N/A Emergency Key: N/A Connector Type: Micro-USB Speaker Power: 5mW (rated), 10mW (max.)	\$11.50
BC40 Mounting Clip (to belt, vest, or uniform)		Applicable To Belts: 50mm or less Swivel: Yes Material: Polycarbonate	\$20.10
RO01 Nylon Strap		Length: 47.5cm Material: Nylon	\$3.90
RO04 Leather Strap		Length: 25cm Material: Leather	\$4.20

Hytera HORIZON License Pricing

Hytera HORIZON PoC Service Prices		
Model Number	Description	MSRP
Hytera HORIZON PoC Gateway Service Fee		
HORIZON-GW-AS	HORIZON Lite Subscription (voice only, per device), SIM data not included	Market Value Pricing
HORIZON-GW-2AS	HORIZON Standard Subscription (voice only, per device), SIM data 500MB/M included at no charge	Market Value Pricing
HORIZON-GW-3AS	HORIZON Elite Subscription (voice only, per device), SIM data 500MB/M included at no charge	Market Value Pricing
HORIZON-V-AS	HORIZON Video Standard Subscription (not applicable for PNC360S)	\$24 for 1-Year
HORIZON Web-Based Dispatcher		
HORIZON-D-AS	HORIZON Dispatcher Standard Subscription	Market Value Pricing
HORIZON-D-LOGO	HORIZON Dispatch logo customization (per placement). High resolution logo file must be provided.	\$250
BYOD (Bring Your Own Device) Android Service Fee		
HORIZON-AC-AS	HORIZON Lite Subscription (per device) - CPoC Android Client	Market Value Pricing
HORIZON-AC-2AS	HORIZON Standard Subscription (per device) - CPoC Android Client	Market Value Pricing
HORIZON-AC-3AS	HORIZON Elite Subscription (per device) - CPoC Android Client	Market Value Pricing
AT&T, T-Mobile or Tri-SIM Data 500MB SIM card available monthly without a contract for \$7 per month.		
SIM Cards: AT&T, T-Mobile and Tri-SIM cards include 500MB of data per month per device. Data is pooled between SIM cards and overage will be billed at \$5 per 500MB. Hytera provided AT&T, T-Mobile and Tri-SIM card does not support SMS. A \$5 Replacement Fee will be applied if there is a need to switch or cancel a SIM card for a previously registered device. AT&T: Roaming charges \$6 per MB apply if roaming usage outside U.S. territory (United States, Puerto Rico, the U.S. Virgin Islands and Guam), Mexico and Canada in incurred, regardless of whether roaming is permitted under the Pricing Schedule. T-Mobile & Tri-Sim can only be used In United States. HORIZON Customer Satisfaction Guarantee: If a customer is not satisfied with the HORIZON service, Hytera will refund the pro-rated remainder of the plan fee. No cancellation fees will be charged for customer cancellations within 3-days of initial purchase. Cancellation beyond 30-days will result in a minimum 90-day charge that includes both HORIZON Service and AT&T, T-Mobile or Tri-SIM data (if applicable).		

Hytera HORIZON Bridge Pricing

Hytera HORIZON Bridge Pricing		
Model Number	Description	MSRP
HORIZON-B2B	HORIZON Bridge PoC/DMR Back-to-Back Solution for Voice Communication Package. This kit contains: HM782 VHF Mobile radio operating in DMR T2 mode, None, or free Encryption, MNC360 Mobile Radio with special FW and Application, HM7 cabinet and power supply for the radios, All interconnection cables. Note: The HORIZON Bridge must include staging (below) and be quoted by Hytera Sales Engineering.	\$2,499.00
DT-SVCHRZNB2BSTG	HORIZON B2B Staging per channel	\$255.20

Hytera PoC Protection Plan Pricing

Hytera PoC Protection Plan		
Model Number	Device Covered	Price
PPP-PNC3	PNC360S, PNC380	\$100.00
PPP-MNC	MNC360	\$129.00
PPP-VM	VM780	\$200.00
PPP-PNC560	PNC560	\$399.00
The Hytera PoC Protection Plan covers one accidental damage instance within two years of purchase. Must be purchased at the time of initial purchase of the PoC unit. The customer is responsible for shipping the damaged unit to Hytera, and Hytera will pay for return shipping via two-day air. Units that show intentional abuse or tampering are not covered.		

HORIZON Device Logo and Dispatcher Customized Logo / URL

Hytera HORIZON Customized Logo / URL			
Model Number	Device	Pixel Size (Width * Height)	One-time Set-up Fee
HORIZON-LOGO-PNC360S	PNC360S	160 * 128 pixels	\$250.00
HORIZON-LOGO-PNC380S	PNC380S	320 * 240 pixels	\$250.00
HORIZON-LOGO-MNC360	MNC360	320 * 240 pixels	\$250.00
HORIZON-LOGO-PNC560	PNC560	1,080 * 2,340 pixels	\$250.00
HORIZON-D-LOGO	HORIZON Dispatch	34 * 48 pixels	\$250.00
Please contact your RSM for specific instructions to implement a customized device logo and/or Dispatcher logo/URL.			
There are two ways to implement and deploy the customized logo:			
1. With No Fee: The Dealer implements it themselves for free if you have SysOp and MDM (Mobile Device Management) training and certification. To gain access to MDM, request this through the RSM. 2. With Fee: Hytera will implement the logos for each device, for a service fee of \$5.25 per device. The Dealer must provide the S/N's of the units they want the logo sent to.			

Hytera US Inc.

8 Whatney Suite 200, Irvine, CA 92618
(954) 846-1011

www.hytera.us

sales@hytera.us

Copyright Hytera US Inc. 2026

