

Cam Follower Bearing New / Old	External dimensions(mm)			Relevant installation medium					Other sizes			
	Screw	Outer diameter	Length	Weight	Maximum locking Torque	Basic rated Dynamic load	Basic rated Static load	Maximum static capacity Allowable load	mm			
	M	D	L	G	N · m	C		N	C	L1	M/L2	S
						N						
CF3/KR10	M3*0.5	10	17	4.3	0.34	1500	1020	384	7	9	5	2
CF4/KR12	M4*0.7	12	20	7.4	0.78	2070	1590	834	8	11	6	2.5
CF5/KR13	M5*0.8	13	23	10.3	1.6	2520	2140	1260	9	13	7.5	3
CF6/KR16	M6*1.0	16	28.2	18.5	2.7	3660	3650	1950	11	16	8	3
CF8/KR19	M8*1.25	19	32.2	28.5	6.5	4250	4740	4620	11	20	10	4
CF10/KR22	M10*1.25	22	36.2	45	13.8	5430	6890	6890	12	23	12	4
CF10-1/KR26	M10*1.25	26	36.2	60	13.8	5430	6890	6890	12	23	12	4
CF12/KR30	M12*1.5	30	40.2	95	21.9	7910	9790	9790	14	25	13	6
CF12-1/KR32	M12*1.5	32	40.2	105	21.9	7910	9790	9790	14	25	13	6
CF16/KR35	M16*1.5	35	52.1	170	58.5	12000	18300	18300	18	32.5	17	6
CF18/KR40	M18*1.5	40	58.1	250	86.2	148000	25200	25200	20	36.5	19	8
CF20/KR52	M20*1.5	52	66.1	460	119	20700	34600	34600	24	40.5	21	8
CF20-	M20*1.5	47	66.1	385	119	20700	34600	34600	24	40.5	21	8
CF24/KR62	M24*1.5	62	80.1	815	215	30500	52600	52000	29	49.5	25	12
CF24-	M24*1.5	72	80.1	1140	215	30500	52600	52000	29	49.5	25	12
CF30/KR80	M30*1.5	80	100	1870	438	45400	85100	85100	35	63	32	17
CF30-	M30*1.5	85	100	2030	438	45400	85100	85100	35	63	32	17
CF30-	M30*1.5	90	100	2220	438	45400	85100	85100	35	63	32	17
CFS2V	M2*0.4	4.5	8	0.6	9.1	768	734	229	4	4	2	1.5
CFS2.5V	M2.5*0.45	5	9.5	1	18.7	1000	1080	360	4.5	5	2.5	1.5
CFS3V	M3*0.5	6	11.5	2	33.5	1420	1790	484	5.5	6	3	2
CFS4V	M4*0.7	8	15	4	77.7	2370	3000	919	7	8	4	2
CFS5V	M5*08	10	18	7	158	3180	4700	1570	8	10	5	3
CFS6V	M6*1.0	12	21.5	13	268	4610	6250	2150	9.5	12	6	3

