

Model	Inside diameter/mm	Inside diameter/in	Outside diameter/mm	Outside diameter/in	Breadth/mm	Breadth/in	Seal type	Dynamic radial load	Static radial load	Maximum speed (x1000)
R1-4	1.984	5/64	6.350	1/4	2.380	3/32	Open	279	89	67
R1-4zz	1.984	5/64	6.350	1/4	3.571	1/8	SPCC	279	89	67
R133	2.38	3/32	4.762	3/16	1.588	1/16	Open	188	60	80
R133zz	2.38	3/32	4.762	3/16	2.380	3/32	SPCC	188	60	80
R1-5	2.38	3/32	7.938	5/16	2.779	7/64	Open	392	147	53
R1-5zz	2.38	3/32	7.938	5/16	3.571	9/64	SPCC	392	147	53
R144	3.175	1/8	6.350	1/4	2.380	3/32	Open	294	98	67
R144zz	3.175	1/8	6.350	1/4	2.779	7/64	SPCC	294	98	67
R2-5	3.175	1/8	7.938	5/16	2.779	7/64	Open	560	179	60
R2-5zz	3.175	1/8	7.938	5/16	3.571	9/64	SPCC	560	179	60
R2-6	3.175	1/8	9.525	3/8	2.779	7/64	Open	640	224	49
R2-6zz	3.175	1/8	9.525	3/8	3.571	9/64	SPCC	640	224	49
R2	3.175	1/8	9.525	3/8	3.967	5/32	Open	560	226	56
R2zz/2rs	3.175	1/8	9.525	3/8	3.967	5/32	SPCC/Rubber	560	226	56
R2A	3.175	1/8	12.700	1/2	4.366	11/64	Open	640	225	53
R2Azz/2rs	3.175	1/8	12.700	1/2	4.366	11/64	SPCC/Rubber	640	225	53
R155	3.967	5/32	7.938	5/16	2.779	7/64	Open	360	149	53
R155zz/2rs	3.967	5/32	7.938	5/16	3.175	1/8	SPCC/Rubber	360	149	53
R156	4.762	3/16	7.938	5/16	2.779	7/64	Open	360	149	53
R156zz/2rs	4.762	3/16	7.938	5/16	3.175	1/8	SPCC/Rubber	360	149	53
R166	4.762	3/16	9.525	3/8	3.175	1/8	Open	710	270	50
R166zz/2rs	4.762	3/16	9.525	3/8	3.175	1/8	SPCC/Rubber	710	270	50
R3	4.762	3/16	12.700	1/2	3.967	5/32	Open	1300	485	43
R3zz/2rs	4.762	3/16	12.700	1/2	4.978	13/64	SPCC/Rubber	1300	485	43
R3A	4.762	3/16	15.875	5/8	4.978	13/64	Open	1310	485	43
R3Azz/2rs	4.762	3/16	15.875	5/8	4.978	13/64	SPCC/Rubber	1310	485	43
R168	6.350	1/4	9.525	3/8	3.175	1/8	Open	375	173	48
R168zz/2rs	6.350	1/4	9.525	3/8	3.175	1/8	SPCC/Rubber	375	173	48
R188	6.350	1/4	12.700	1/2	3.175	1/8	Open	1080	440	40
R188zz/2rs	6.350	1/4	12.700	1/2	4.762	3/16	SPCC/Rubber	1080	440	40
R4	6.350	1/4	15.875	5/8	4.978	13/64	Open	1610	660	38
R4zz/2rs	6.350	1/4	15.875	5/8	4.978	13/64	SPCC/Rubber	1610	660	38
R4A	6.350	1/4	19.050	3/4	5.558	7/32	Open	2340	885	36
R4Azz/2rs	6.350	1/4	19.050	3/4	7.142	9/32	SPCC/Rubber	2340	885	36
R1810	7.938	5/16	12.700	1/2	3.967	5/32	Open	540	276	40
R1810zz	7.938	5/16	12.700	1/2	3.967	5/32	SPCC	540	276	40
R6	9.525	3/8	22.225	7/8	5.558	7/32	Open	3350	1410	32
R6zz/2rs	9.525	3/8	22.225	7/8	7.142	9/32	SPCC/Rubber	3350	1410	32
R1038	9.525	3/8	15.875	5/8	3.967	5/32	Open	815	411	28
R1038zz	9.525	3/8	15.875	5/8	3.967	5/32	SPCC	815	411	28
R1212	12.700	1/2	19.050	3/4	3.967	5/32	Open	898	524	21
R1212zz	12.700	1/2	19.050	3/4	3.967	5/32	SPCC	898	524	21
R8	12.700	1/2	28.575	1 1/8	6.350	1/4	Open	3930	2230	24
R8zz/2rs	12.700	1/2	28.575	1 1/8	7.938	5/16	SPCC/Rubber	3930	2230	24

R10	15.875	5/8	34.925	1 3/8	7.144	9/32	Open	4620	2790	36
R10zz/2rs	15.875	5/8	34.925	1 3/8	8.731	11/32	SPCC/Rubber	4620	2790	36
R12	19.050	3/4	41.275	1 5/8	7.938	5/16	Open	7240	4463	41
R12zz/2rs	19.050	3/4	41.275	1 5/8	11.113	7/16	SPCC/Rubber	7240	4463	41
R14	22.225	7/8	47.625	1 7/8	9.525	3/8	Open	7740	4960	40
R14zz/2rs	22.225	7/8	47.625	1 7/8	12.700	1/2	SPCC/Rubber	7740	4960	40
R16	25.400	1	50.800	2	9.525	3/8	Open	7740	5160	38
R16zz/2rs	25.400	1	50.800	2	12.700	1/2	SPCC/Rubber	7740	5160	38
R18	28.575	1 1/8	53.975	2 1/8	9.525	3/8	Open	10180	6910	28
R18zz/2rs	28.575	1 1/8	53.975	2 1/8	12.700	1/2	SPCC/Rubber	10180	6910	28
R20	31.750	1 1/4	57.150	2 1/4	9.525	3/8	Open	10800	7520	28
R20zz/2rs	31.750	1 1/4	57.150	2 1/4	12.700	1/2	SPCC/Rubber	10800	7520	28
R22	34.925	1 3/8	63.500	2 1/2	11.112	7/16	Open	12280	8500	30
R22zz/2rs	34.925	1 3/8	63.500	2 1/2	14.288	9/16	SPCC/Rubber	12280	8500	30
R24	38.100	1 7/8	63.500	2 1/2	11.112	7/16	Open	14350	10240	32
R24zz/2rs	38.100	1 7/8	63.500	2 1/2	14.288	9/16	SPCC/Rubber	14350	10240	32