



# ACRYLIC CURE AND SEAL

Clear Acrylic Curing and Sealing Compound

---

## 1. Product Description

**a. Basic Use:** Acrylic Cure and Seal is a clear, sprayable, membrane-forming compound for new concrete, and a sealer for existing concrete.

### b. Features & Benefits:

- Will effectively seal water inside fresh concrete, allowing complete curing and hardening.
- Forms a tough, long-lasting flexible film on the concrete surface.
- Keeps out salt, dirt, grease, water, and oil.
- Allows for easy cleanup.
- Helps concrete resist spalling and dusting.
- Provides a clear, high-gloss finish that will not amber with age.
- Intended for both interior and exterior applications.

**c. Typical Application:** Use Acrylic Cure and Seal on floors, pavements, walls, exposed aggregate, warehouses, parking garages, and colored concrete.

## 2. Packaging

Acrylic Cure and Seal is packaged in a 1-gallon can, 4/1-gallon case, 5-gallon pail, or 55-gallon drum.

## 3. Coverage

- On fresh concrete: 200 square feet per gallon
- On old concrete: 200-500 square feet per gallon

## 4. Technical Data

**Drying Time:** One hour at 70°F (21.1°C)

**Weight per Gallon:** 6.87 lbs.

**Non-Volatile Content:** 20%

**Flash Point:** 105°F (40.5°C)

**Specifications:** Meets ASTM C-309 type 1

## 5. Directions for Use

**a. Application:** Mix well. Spray as soon as surface water disappears at a rate of 200 square feet per gallon. As a sealer for existing concrete, application rate will vary between 200-500 square feet per gallon. Use low pressure spray, roller, or brush. Apply only to clean, dry, dust-free concrete. Two coats works better than one heavy coat. Allow 8 hours between coats. Allow to dry overnight before permitting heavy traffic.

**b. Clean-Up:** Use solvent cleaner.

## 6. Warning

Combustible. Contains petroleum distillate. Harmful or fatal if swallowed. May cause skin and eye irritation. Keep away from heat, sparks, and open flames. Do not smoke while applying. Use adequate ventilation. If product comes into contact with eyes, flush immediately for 15 minutes with water. Contact a physician. If swallowed, do not induce vomiting. Call a physician immediately.

## **7. Availability**

Sealwall Acrylic Cure and Seal is normally available immediately from your local distributor or it will be shipped within 4 working days upon receipt of order. Please contact your local Sealwall representative or call Sealwall Products directly for more information.

## **8. Warranty**

Sealwall Acrylic Cure and Seal is manufactured in strict accordance with the quality control standards of Sealwall Products. It is guaranteed to perform as indicated on this data sheet when applied by competent applicators.