



MORTAR ACCELERATOR PELLETS

Cold Weather Admixture

1. Product Description

a. Basic Use: Sealwall Mortar Accelerator Pellets allows the placement of mortar in cold weather by accelerating the set time.

b. Features & Benefits:

- Will not effloresce or discolor.
- Premeasured package eliminates mistakes.
- Increases strength and workability of mortar.
- Eliminates downtime.
- Increases mortar density.
- Allows faster striking of joints.
- Lowers construction costs.

c. Typical Application: Use Mortar Accelerator in mortar mix when low temperatures prevail or are expected. Using Mortar Accelerator Liquid helps avoid freezing mortar joints while laying brick, block, structural tile, or glass block.

2. Packaging

Sealwall Mortar Accelerator Pellets is packaged in a 1.5-lb. bag and 20/1.5-lb. case.

3. Directions for Use

a. Mixing: Empty complete contents of bag into mortar mixer with all or part of mixing water. Rotate mixer blades for approximately 15 seconds until pellets have dissolved. Add cement, lime, and sand or add masonry cement and sand in normal manner.

- **For Masonry cement at 15°-32°F:** Add 1½ lbs. of pellets to each bag of masonry cement
- **For Portland cement at 15°-32°F:** Add 3 lbs. of pellets to each bag of Portland cement.
- **For Masonry cement above 32°F:** Add ¾ lbs. of pellets to each bag of masonry cement

c. Special Instructions:

1. No frozen materials or materials containing ice should be used.
2. Use only dry masonry units which will remove water and reduce damage due to freezing.
3. Use a windbreaker of tarps, etc. around mixing equipment and mortar boards to prevent rapid evaporation.
4. Masonry should be protected for 24 hours after covering with tarps, etc.
5. Wall areas adjacent to metal door frames must be kept dry and free from all water, ice, and snow.
6. Metal door frames should be painted with an asphalt paint or primer.

4. Note

Mortar Accelerator Pellets must be completely dissolved in water prior to the addition of masonry cement, lime, and sand. Use no more than the prescribed quantity of Sealwall Mortar Accelerator Pellets.

5. Availability

Sealwall Mortar Accelerator Pellets is normally available immediately from your local distributor or it will be shipped within 4 working days upon receipt of order. Please contact your local Sealwall representative or call Sealwall Products directly for more information.

6. Warranty

Sealwall Mortar Accelerator Pellets is manufactured in strict accordance with the quality control standards of Sealwall Products. It is guaranteed to perform as indicated on this data sheet when applied by competent applicators.