Little Row Training Sheets

		MGR	
	Trainee Name	BOATS	
		FIRE-E	
		SKY-F	
Trainer Name	Trainer Name	CYCLES	
Day 1	Day 2	SWINGS	
<u>-</u>	<u> </u>	TRUCKS	
Date	Date	CRUISER	
		KIDDIE-W	

Trainers: Please have your trainee initial each line and sign the bottom of each training sheet. You as the trainer should sign off on the bottom of each training sheet when completed.

General Safety Notes:

Never leave a ride loaded with riders. If you need to leave for any reason you should unload the riders and put up your ride closed sign. During normal operation, someone should always take your place before you leave a ride.
If you need assistance at your ride, press your help button, turn on your help light, wave a manager down or send someone for assistance.
In the event of an incident/accident, the operator should stay with the ride and use one of the above methods to get assistance.
If the ride has not been placed in operation for the day, has been turned off or has been taken out of service for any reason (ex. maintenance/weather) you are required to run a test ride without riders before returning the ride to service.
In the event of a power outage, stay with your ride. Turn off the ride power switch even though there is no power. Unload your riders and return ride tickets when possible. If the ride requires power to unload, remain calm, inform the riders that we will have them unloaded shortly but that you need assistance to unload without power. If the power returns, do not restart your ride without supervisor approval.
No food or drink is allowed on any ride at Funland.
Over time, you will get used to the normal operating sounds of each ride. If a ride doesn't sound right, or you hear a new sound, please inform your supervisor. We would rather double check than to have something important get ignored.

MERRY GO ROUND

Tickets: 3 tickets / wristband	Height Min: N/A	Height Max: N/A	
OPENING THE RIDE			INT
Walk around the ride area to maunits.	ke sure nothing is	obstructing the ride platform or the ride	
Turn the lights on at the control	panel located in th	ne center of the ride.	
Make sure the music is turned of	on. If it is not, plea	se ask the change person to turn it on.	
Place the wireless stop switch la	anyard around you	ır neck.	
•	. maintenance), yo	e day, has been turned off or has been taken ou are required to run a test ride without	
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facia	•	ne ride, creating eye contact, greeting them	
Communicate with all riders to "	'Please walk," as t	hey enter the ride area.	
There is no height minimum or r	naximum for this r	ide.	
As riders enter, please collect two Place all tickets in the ticket box	_	the correct afternoon wristband. (1-4:30pm)	
the child or stand next to them t	hey must also pro	o a horse but if they would like to ride with ovide tickets/wristband. Please determine are not riding ask them to use the exit gate	
		efore boarding. No items may be placed n. (Strollers, coolers, large bags, etc.)	
LOADING RIDERS			INT
Count the appropriate number of	of riders for a ride	group and only admit that number.	
_	_	begin your safety checks do not go back to riders you must start the entire safety check	
When you close the entrance ga	ate you must give	the gate a push/pull to confirm it is locked.	
		when possible. This allows the riders to see lifety checks in a methodical and consistent	

If a rider can not put their feet in the stirrups they must use the safety belt. If they can put their feet in the stirrups it is their choice if they want to use the safety belt.	
Visually check the ride for the appropriate number of riders, rider seating arrangement/ placement and rider posture. All children must sit properly on the horse facing forward. No side saddle for riders. If an adult needs to sit side saddle due to attire, please suggest a chariot.	
If using a belt, make sure the safety belt is tight and secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a safety belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until it is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
As you conduct your safety checks please look for anyone standing on the outside of the outer horse where they could fall off the ride when it is moving. Please have them move to the inside of the horse to hold a child.	
When you reach the yellow line painted on the floor at the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your safety checks. This process ensures you do not miss a ride unit.	
Any horse that is not being used should have the safety belt buckled around the horses neck or draped between the front legs of the horse. This will make sure that the belt is out of the way when not in use.	
STARTING THE RIDE	INT
When you finish your safety restraint checks return to the operator controls located in the	
center of the ride.	
, , , , , , , , , , , , , , , , , , ,	
center of the ride. Make sure you are in the defined safety zone next to the operator control station when starting	
center of the ride. Make sure you are in the defined safety zone next to the operator control station when starting the ride. From the controls, use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure.	
Center of the ride. Make sure you are in the defined safety zone next to the operator control station when starting the ride. From the controls, use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It	

If you can confirm that the ride platform is clear ring the warning bell once as your "ALL CLEAR" warning.	
After a third and final look ring the bell a third time as your "HERE WE GO!", warning. Press the START button.	
As the ride speeds, look out at the riders to make sure everyone is ok.	
Once the ride reaches full speed, leave the control area and board the ride at one of the chariots. Place your back on one of the outer poles looking inward at the riders.	

DURING THE RIDE	INT
Be prepared to stop the ride using the wireless stop switch lanyard around your neck.	
Keep your chin up and eyes out looking at your ride/riders the entire time it is running.	
All riders must stay seated. Watch for riders hopping on or off a horse or trying to move horses. Anticipate any trouble makers and stand near that group if needed.	
Do not allow spectators to reach over the fence for hi fives.	
Stand with your back against one of the outer poles while the ride is in operation, stay mentally focused and alert.	
STOPPING THE RIDE	INT
When the timer runs out, there ride will stop automatically.	
In the event of an emergency, press the stop button on the lanyard around your neck.	
AFTER THE RIDE	INT
When the ride comes to a complete stop assist riders off the horses and the platform.	
If you unbuckle a belt for a rider you need to assist that rider completely off the ride platform before assisting another rider.	
When the ride platform is completely empty you should start the loading process again.	
TWO PERSON OPERATION	INT
If there are two operators, one operator should collect tickets and engage riders at the entrance gate while the other operator assists riders onto the platform/horses.	
Both operators should wear wireless stop switch lanyards.	
Once the entrance gate has been closed and checked, both operators may begin the safety check process together meeting at the other side of the MGRT. This ensures that all riders have been checked.	

Once safety checks have been completed, one operator will go into the middle of the ride to begin the ride starting procedure. The other operator stands on the platform with the riders. When the operator in the middle of the ride begins the defined visual confirmation process using the bell, the second operator needs to extend their arm with the elbow locked and a thumbs up. As long as the second operator is ready for the ride to start they must keep their arm extended until the ride begins moving. If at any time they do not have their arm raised the operator in the middle of the ride should abort the ride starting procedure and determine why the second operator does not have their arm extended.	e
While the ride is moving, the two operators should stand on opposite sides of the ride with their backs against a pole to ensure full coverage of the rides. Do not stand together.	
CLOSING THE RIDE	INT
When instructed by your supervisor, place your ride closed sign on the fence.	
Turn off the lights at the controls in the middle of the ride.	
Flip the large black breaker on the bottom of the controls down towards the ground.	
Ask the change person to turn off the music for the ride.	
Place the wireless stop switch lanyards on the controls.	
Complete any other tasks assigned by your supervisor such as sweeping or reassignment to another area.	
When you are cleared to leave, take your ticket box back to the Swinger ride area and place the operator control key on the counter in the office before signing out.	
Trainee Signature Trainer Signature Date	f

BOATS

Tickets: 1 ticket / wristband	Height Min: N/A	Height Max: 48 inches	s
OPENING THE RIDE			INT
Walk around the ride area to macars.	ke sure nothing is obstructing the ride	e platform or the ride	
Make sure the ride breaker is or should be in the ON position.	n. The breaker is located on the opera	tor control panel and	
	the control panel and keep it with you bungee on your wrist and take it with	•	
	n operation for the day, has been turn a. weather), you are required to run a to ice.		
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facial	est as they enter the ride, creating eye al expression.	contact, greeting them	
As you prepare to load riders be either of the height checking sig	e prepared to check riders against the ins.	height maximum at	
If a riders is over the maximum ride option. No exceptions!	height of 48 inches they may not ride.	Please suggest another	
child is too small to ride please	rum height so you need to use your jur suggest another ride that they can po assistance please press the help butto	ssibly ride with an adult.	
No adults allowed on this ride.			
As riders are seated, collect one tickets in the ticket box.	e ticket or verify the correct afternoon	wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a	parent please help steady the boat if y	ou are able.	
Communicate with all riders to '	'Please walk," around the ride area.		
LOADING RIDERS			INT
	r safety checks please be aware of ar itional riders board after you begin yo	•	

Little Now Training Offeets	
Begin your safety checks in a clockwise direction. This allows the riders to see you approaching.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. Two per seat only.	
Make sure the lap belt is snug across the lap and secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
If there is an unused ride car, please put the safety belts inside the unit.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
STARTING THE RIDE	INT
When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel.	
Make sure you are in the defined safety zone next to the operator control station.	
Use defined visual confirmation from the designated safety zone to confirm: • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position.	
Do not allow anyone to sit on the edge of the boat pond.	
Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.	
After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	
Remove the rope from the engine car.	
If you can confirm that the riders are in position and ready announce "ALL SET".	
If you can confirm that the ride area is clear announce "ALL CLEAR".	
After a third and final look announce "HERE WE GO! while pressing the green start button. The ride timer light on the controls will illuminate.	
As the ride speeds up you you may lower your arm but must look at each rider to make sure they are ok.	
DURING THE RIDE	INT

Keep you	r finger over the stop button i	n case you need to stop the ride.		
Keep you	r chin up and eyes out looking	g at your ride the entire time it is ru	ınning.	
Watch for	riders standing up, rocking th	ne boat, sticking hands in the wate	er, etc.	
	our safety zone while the ride i to leave the safety zone you	s in operation, stay mentally focus should stop the ride.	ed. If at any point	
STOPPIN	G THE RIDE			INT
the engine	e car is at your 9pm position.	When the light goes out press the It takes 1/4 of a rotation for the ricar in front of the operator station.	•	
Hook the	rope on the engine car.			
	nt of an emergency, press the itch off which is located unde	e stop button, hit the red E-Stop pl r the stop switch.	unger or turn the	
AFTER T	HE RIDE			INT
	ride comes to a complete sto t riders off the ride.	op please remove your key from th	e operator controls	
	ouckle a belt for a rider you ne sisting the next rider.	ed to assist that rider completely o	out of the ride car	
When the	ride cars are completely emp	ty you should start the loading pro	ocess again.	
CLOSING	THE RIDE			INT
When inst	tructed by your supervisor, pla	ace your ride closed sign on the fe	nce.	
Turn off th	ne ride breaker on the control	panel by turning the black handle	to the off position.	
Complete another a		your supervisor such as sweeping	or reassignment to	
_		ur ticket box back to the Swinger or in the office before signing out.	ride area and place	
	Trainee Signature	Trainer Signature	Date	

FIRE ENGINES

Tickets: 2 tickets / wristband	Height Min: N/A	Height Max: 48 inches	S
OPENING THE RIDE			INT
Walk around the ride area to macars.	ke sure nothing is obstructing the ride	e platform or the ride	
Make sure the ride breaker is on and should be in the on position	. The breaker is located on the front o	of the operator controls	
•	the control panel and keep it with youngee on your wrist and take it with your		
•	n operation for the day, has been turn . weather), you are required to run a t ce.		
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facial	est as they enter the ride, creating eyeal expression.	e contact, greeting them	
	nrough the entrance gate, have your hat the height maximum on the entrance	•	
If a riders is over the maximum haride option. No exceptions!	neight of 48 inches they may not ride.	Please suggest another	
No adults/parents may ride this	ride.		
child is too small to ride please s	um height so you need to use your ju suggest another ride that they can po ssistance please press the help butto	ssibly ride with an adult.	
As riders enter, please collect or tickets in the ticket box.	ne ticket or verify the correct afternoo	n wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a p	parent please ask them to use the exi	t gate when finished.	
Communicate with all riders to "	Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number of seat.	of riders for a ride group and only adm	nit that number. One per	
If you have smaller riders, please	e suggest that they ride in the back of	f a fire engine.	

Load 9 Cal Once you also the entropes gets and begin your sefety about a not so beauty	
Load & Go! Once you close the entrance gate and begin your safety checks do not go back to admit additional riders. If you do admit additional riders you must start the entire safety check process again.	
When you close the entrance gate you give the gate a push/pull to confirm it is locked.	
Begin your safety checks in a clockwise direction. This allows the riders to see you approaching.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. One rider per seat.	
Make sure the lap belt is snug across the lap and secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
When you reach the small yellow line on the platform at the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your safety checks. This process ensures you do not miss a ride unit.	
OTA DTIMO THE DIDE	
STARTING THE RIDE	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel.	INT
When you finish your safety restraint checks, return to the control panel, insert your operator	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel.	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure.	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	INT
When you finish your safety restraint checks, return to the control panel, insert your operator key to active the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride. If you can confirm that the riders are in position and ready announce "ALL SET".	INT

As the ride they are of		ver your arm but must look at each	rider to make sure	
DURING 1	THE RIDE			INT
Keep your	finger over the stop button in	n case you need to stop the ride.		
Keep your	chin up and eyes out looking	g at your ride the entire time it is ru	nning.	
Do not allo	ow spectators to reach over the	he fence for hi fives.		
, ,	ur safety zone while the ride is to leave the safety zone you s	s in operation, stay mentally focuse should stop the ride.	ed. If at any point	
STOPPING	G THE RIDE			INT
the engine	e car is at your 2pm position.	When the light goes out press the It takes 3/4 of a rotation for the rid car in front of the operator station.		
In the ever	G 5 .	e stop button or hit the emergency	stop plunger in an	
AFTER TH	IE RIDE			INT
and assist	•	op please remove your key from the velcome to invite parents onto the rang their children.	•	
•	uckle a belt for a rider you ne sisting the next rider.	ed to assist that rider completely o	ut of the ride car	
When the	ride platform is completely er	mpty, you should start the loading	orocess again.	
CLOSING	THE RIDE			INT
When inst	ructed by your supervisor, pla	ace your ride closed sign on the fer	nce.	
	e ride breaker by turning it to e ride control box.	the OFF position. The ride breake	r is located on the	
Complete another ar		your supervisor such as sweeping	or reassignment to	
•		ur ticket box back to the Swinger rin the office before signing out.	de area and place	
-	Trainee Signature	Trainer Signature	 Date	

SKYFIGHTER

Tickets: 3 tickets / wristband	Height Min: N/A	Height Max: 54 inches	S
OPENING THE RIDE			INT
Walk around the ride area to macars.	ke sure nothing is obstructing the ride	e platform or the ride	
Make sure the ride breaker is on lever should be in the ON position	i. The breaker is located under the op on.	erator controls and the	
	the control panel and keep it with youngee on your wrist and take it with your		
·	n operation for the day, has been turn weather), you are required to run a t ice.		
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facial	est as they enter the ride, creating eyeal expression.	contact, greeting them	
	hrough the entrance gate have your h t the height maximum on the entrance	•	
If a riders is over the maximum ride option. No exceptions!	neight of 54 inches they may not ride.	Please suggest another	
No adults/parents may ride this	ride.		
child is too small to ride please s	um height so you need to use your ju suggest another ride that they can po assistance please press the help butto	ssibly ride with an adult.	
As riders enter, please collect twickets in the ticket box.	o tickets or verify the correct afternoon	on wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a p	parent please ask them to use the exi	t gate when finished.	
Communicate with all riders to "	Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number of	of riders for a ride group and only adm	nit that number.	
If you have smaller riders please	suggest that they ride in the back of	the Sky Fighter.	

Entire From Framing enests	
Load & Go! Once you close the entrance gate and begin your safety checks do not go back to admit additional riders. If you do admit additional riders you must start the entire safety check process again.	
When you close the entrance gate you give the gate a push/pull to confirm it is locked.	
Begin your safety checks in a clockwise direction. This allows the riders to see you approaching.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. There should only be one rider for each seat.	
Make sure the belt is snug across the lap and secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
When you reach the small yellow line on the platform at the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your	
safety checks. This process ensures you do not miss a ride unit.	
, , ,	INT
safety checks. This process ensures you do not miss a ride unit.	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel.	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure.	INT
STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Rider sare in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your right arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your right arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	INT
safety checks. This process ensures you do not miss a ride unit. STARTING THE RIDE When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. Make sure you are in the defined safety zone next to the operator control station. Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position. Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side. After completing your visual check, extend your right arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride. Pull the hydraulic hand lever back to the control panel with your left hand.	INT

_	Trainee Signature	Trainer Signature	Date	
_		ur ticket box back to the Swinger in the office before signing out.	r ride area and place	
Complete a		your supervisor such as sweepin	g or reassignment to	
Turn off the	e ride breaker on the control	panel by turning the black handle	e to the off position.	
When instr	ucted by your supervisor, pla	ace your ride closed sign on the f	ence.	
CLOSING	THE RIDE			INT
When the r	ide platform is completely en	mpty you should start the loading	g process again.	
•	ickle a belt for a rider you ne sting the next rider.	ed to assist that rider completely	out of the ride car	
the operate	or controls and assist riders	op release the hydraulic lever. Re off the ride. You are welcome to with unloading their children.	•	
AFTER TH	E RIDE			INT
		e stop button or hit the emergenc e ride with the ride units in the air		
toward the	•	When the light goes pull the hyd de units. When the ride cars retu to hold the hydraulic lever.		
STOPPING	THE RIDE			INT
	r safety zone while the ride i o leave the safety zone you s	s in operation, stay mentally focushould stop the ride.	used. If at any point	
Do not allo	w spectators to reach over t	he fence for hi fives.		
Keep your	chin up and eyes out looking	g at your ride the entire time it is i	running.	
Keep your	finger over the stop button in	n case you need to stop the ride.		
DURING T	HE RIDE			INT
When the raise into the	•	o of the hydraulic lever which will	allow the ride units to	
As the ride they are ok		ver your arm but must look at eac	ch rider to make sure	
	d and final look announce "H e ride timer light on the cont	IERE WE GO! Drop your right arn rols will illuminate.	n to press the start	

CYCLES

Tickets: 3 tickets / wristband	Height Min: N/A	Height Max: 54 inches	8
OPENING THE RIDE			INT
Walk around the ride area to malcars.	ke sure nothing is obstructing the ride	e platform or the ride	
next to the clown and the lights	e in the center of the ride. There are t in the middle to activate each. If they Il over a supervisor to turn on the mai	do not turn on the main	
•	the control panel and keep it with youngee on your wrist and take it with you	•	
•	n operation for the day, has been turn . Maintenance), you are required to ru o service.		
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facial	est as they enter the ride, creating eyeal expression.	contact, greeting them	
	nrough the entrance gate have your hat the height maximum near the entran	-	
If a riders is over the maximum haride option. No exceptions!	neight of 54 inches they may not ride.	Please suggest another	
No adults/parents may ride this	ride.		
	um height so you need to use your ju are not sure please press your help b	-	
As riders enter please collect two tickets in the ticket box.	o tickets or verify the correct afternoo	on wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a p	parent please ask them to use the exit	gate when finished.	
Communicate with all riders to "	Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number o	f riders for a ride group and only adm	it that number.	
motorcycle. A child needs at least	suggest that they ride in one of the c st three points of contact to ride on a at least one foot must be able to read	motorcycle. Both hands	

S S	
Load & Go! Once you close the entrance gate and begin your safety checks do not go back to admit additional riders. If you do admit additional riders you must start the entire safety check process again.	
When you close the entrance gate you give the gate a push/pull to confirm it is locked.	
Begin your safety checks in a clockwise direction. This allows the riders to see you approaching.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. There should only be one rider per motorcycle.	
If a child is on a motorcycle they need at least three points of contact. Both hands must reach the handlebars and at least one foot must reach the platform. If they can not do this they must choose a car or suggest they ride a different ride.	
Make sure the belt is snug across the lap and secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
When you reach the small yellow line on the platform next to the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your safety checks. This process ensures you do not miss a ride unit.	
STARTING THE RIDE	INT
When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel. This will illuminate the lights on the ride cars and the horns will work.	
Make sure you are in the defined safety zone next to the operator control station.	
Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position.	
Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.	
After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	

If you can confirm that the riders are in position and ready announce "ALL SET".	
If you can confirm that the ride area is clear announce "ALL CLEAR".	
After a third and final look announce "HERE WE GO! while pressing the green start button. A timer is activated and begins a countdown.	
As the ride speeds up you you may lower your arm but must look at each rider to make sure they are ok.	

DURING THE RIDE	INT
Keep your finger over the stop button in case you need to stop the ride.	
Keep your chin up and eyes out looking at your ride the entire time it is running.	
Do not allow spectators to reach over the fence for hi fives.	
Stay in your safety zone while the ride is in operation, stay mentally focused. If at any point you need to leave the safety zone you should stop the ride.	
STOPPING THE RIDE	INT
When the timer finishes the ride will come to a stop on its own.	
In the event of an emergency, press the stop button or hit the emergency stop button located on the control panel.	
AFTER THE RIDE	INT
Remove your key from the operator controls and assist riders off the ride. You are welcome to invite parents onto the ride platform through the exit to assist with unloading their children.	
If you unbuckle a belt for a rider you need to assist that rider completely out of the ride car and off the platform before assisting the next rider.	
When the ride platform is completely empty you should start the loading process again.	
CLOSING THE RIDE	INT
When instructed by your supervisor, place your ride closed sign on the fence.	
Complete any other tasks assigned by your supervisor such as sweeping or reassignment to another area.	
When you are cleared to leave, take your ticket box back to the Swinger ride area and place the operator control key on the counter in the office before signing out.	

Trainee Signature	Trainer Signature	Date

SWINGER

Tickets: 3 tickets / wristband Height Min: N/A Height Max: 52 inches		s	
OPENING THE RIDE			INT
Walk around the ride area to ma	ake sure nothing is obstructing the ride	e platform or the ride	
Make sure the ride lights are or main breaker for the ride.	. If they are not on you will need a sup	pervisor to turn on the	
•	t the control panel and keep it with you ungee on your wrist and take it with yo	<u> </u>	
•	in operation for the day, has been turnex. Maintenance), you are required to ruto service.		
RIDER SCREENING			INT
You should speak with each gu with a smile and a pleasant fac	est as they enter the ride, creating eye al expression.	contact, greeting them	
• • •	through the entrance gate have your heat the height maximum near the entran	•	
If a riders is over the maximum ride option. No exceptions!	height of 52 inches they may not ride.	Please suggest another	
No adults/parents may ride this	ride.		
	num height so you need to use your jud u are not sure please press your help b	-	
As riders enter please collect to tickets in the ticket box.	vo tickets or verify the correct afternoo	n wristband. Place all	
Ensure that riders remove or se	cure loose items before boarding.		
If a child is being assisted by a	parent please ask them to use the exit	gate when finished.	
Communicate with all riders to	"Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number	of riders for a ride group and only adm	it that number.	
•	rating a full ride. There are 20 swings, nce the ride by telling them to pick a s		
As children enter many will nee helping them at that moment is	d assistance. Please help when possil not your safety check.	ole but realize that	

Little Now Training Officers	
Lower the lap bar ensuring that you do not hit the the child on the head as you bring it down. Also, be careful not to pinch a finger. Then pull the bungee between the riders legs and fasten it to the lap bar.	
Load & Go! Once you close the entrance gate and begin your safety checks do not go back to admit additional riders. If you do admit additional riders you must start the entire safety check process again.	
When you close the entrance gate, give the gate a push/pull to confirm it is locked.	
Begin your safety checks in a clockwise direction. This allows the riders to see you approaching.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. There should only be one rider per seat.	
Make sure the lab bar is secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap bar it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
When you reach the small yellow line on the platform next to the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your safety checks. This process ensures you do not miss a ride unit.	
STARTING THE RIDE	INT
When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel.	
Make sure you are in the defined safety zone next to the operator control station.	
Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position.	
Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.	
After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	
If you can confirm that the riders are in position and ready announce "ALL SET". Use the mirror on the wall to view the area blocked behind the ride column.	

If you can confirm that the ride area is clear announce "ALL CLEAR".	
After a third and final look announce "HERE WE GO! while pressing the green start button. A timer is activated and begins a countdown.	
As the ride speeds up you you may lower your arm but must look at each rider to make sure they are ok.	
DURING THE RIDE	INT
Keep your finger over the stop button in case you need to stop the ride.	
Keep your chin up and eyes out looking at your ride the entire time it is running.	
Do not allow spectators to reach over the fence for hi fives.	
Stay in your safety zone while the ride is in operation, stay mentally focused. If at any point you need to leave the safety zone you should stop the ride.	
STOPPING THE RIDE	INT
When the ride timer completes its cycle the ride will stop on its own.	
As the ride comes to almost a full stop you may use the rope to bring it to a complete stop. Do NOT hang on the rope to stop the ride.	
In the event of an emergency, press the stop button or hit the emergency stop button located on the control panel.	
AFTER THE RIDE	INT
Remove your key from the operator controls and assist riders off the ride. You are welcome to invite parents onto the ride platform through the exit to assist with unloading their children.	
If you unbuckle a belt for a rider you need to assist that rider completely out of the ride car and off the platform before assisting the next rider.	
When the ride platform is completely empty you should start the loading process again.	
TWO PERSON OPERATION	INT
If there are two operators one operator should collect tickets and engage riders at the entrance gate while the other operator assists riders onto the platform/swings.	
Once the entrance/exit gates have been closed and checked, both operators may begin the safety check process starting next to each other. Each operator will work in opposite directions until they meet on the other side. This ensures that all riders have been thoroughly	
checked and no one was missed.	

CLOSING	THE RIDE			INT
When instr	ucted by your supervisor, pla	ace your ride closed sign on the f	ence.	
Complete a		your supervisor such as sweepin	g or reassignment to	
_		ur ticket box back to the Swinger by on the counter in the office bef		
_				
	Trainee Signature	Trainer Signature	Date	

TRUCKS

Tickets: 3 tickets / wristband	Height Min: N/A	Height Max: N/A	
OPENING THE RIDE			INT
Walk around the ride area to ma cars.	ke sure nothing is obstructing the ride	e platform or the ride	
Make sure the main power switch is in the ON position. This switch is located on the outside of the electrical box by the Jungle of Fun.			
	the control panel and keep it with youngee on your wrist and take it with you	, , , , , , , , , , , , , , , , , , ,	
If the ride has not been placed in operation for the day, has been turned off or has been taken out of service for any reason (ex. Maintenance), you are required to run a test ride without riders before returning the ride to service.			
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facial	est as they enter the ride, creating eyeal expression.	contact, greeting them	
There is no height minimum or n	naximum for this ride.		
Parents are allowed on this ride	but only one adult may sit in the back	of each ride car.	
	um height so you need to use your ju are not sure please press your help b	•	
As riders enter please collect the tickets in the ticket box.	ree tickets or verify the correct afterno	oon wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a p	parent please ask them to use the exit	gate when finished.	
Communicate with all riders to "	Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number of	of riders for a ride group and only adm	it that number.	
If you have smaller riders please	direct them to the front of a ride car.		
As children enter many will need helping them at that moment is	l assistance. Please help when possi not your safety check.	ble but realize that	
If a child is being assisted by a p	parent please ask them to use the exit	gate when finished.	
	entrance gate and begin your safety on admit additional riders you must sta	<u> </u>	

Little how Training Sheets	
When you close the entrance gate, give the gate a push/pull to confirm it is locked.	
Begin your safety checks starting at the first car near the control panel.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. There should be no more than two riders on a seat.	
Make sure the lap belt is secured with nothing between the rider and the restraint device.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
When you pass the exit gate you should step away to verify the gate is secure with a push and pull. Return behind the yellow line to continue your safety checks. This process ensures you do not miss a ride unit.	
STARTING THE RIDE	INT
When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel.	
Make sure you are in the defined safety zone next to the operator control station.	
Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position.	
Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.	
After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	
If you can confirm that the ride platform is clear announce "ALL CLEAR".	
If you can confirm that the riders are in position and ready announce "ALL SET".	
After a third and final look announce "HERE WE GO! while pressing the green start button.	
As the ride speeds up you you may lower your arm but must look at each rider to make sure they are ok.	
DURING THE RIDE	INT
Keep your finger over the stop button in case you need to stop the ride.	

Keep your	chin up and eyes out looking	at your ride the entire time it is ru	unning.	
Do not allo	ow spectators to reach over th	e fence for hi fives.		
	ur safety zone while the ride is to leave the safety zone you sh	in operation, stay mentally focus nould stop the ride.	sed. If at any point	
STOPPING	G THE RIDE			INT
When the	ride timer completes its cycle	the ride will stop on its own.		
	nt of an emergency, press the strol panel.	stop button or hit the emergency	stop button located	
AFTER TH	IE RIDE			INT
You are we		trols, close the cover and assist in the ride platform through the exit		
•	uckle a belt for a rider you nee e platform before assisting the	ed to assist that rider completely next rider.	out of the ride car	
When the	ride platform is completely em	pty you should start the loading	process again.	
TWO PER	SON OPERATION			INT
	•	should collect tickets and engage ssists riders onto the platform/tr		
check pro	_	d and checked, both operators me he last ride car and the other sta t no riders have been missed.		
while the of the control same. Bo	other operator goes to the seconds of the second of	hen go to the controls to begin the ond safety zone near the exit. Veir elbow locked the second operontact with each other as they go he ride has started will they lower	When the operator at rator must do the otherwise through the defined	
CLOSING	THE RIDE			INT
When inst	ructed by your supervisor, plac	ce your ride closed sign on the fe	ence.	
Complete another ar		our supervisor such as sweeping	g or reassignment to	
•	•	r ticket box back to the Swinger on the counter in the office before		
-	Trainee Signature	Trainer Signature	Date	

CRUISERS

Tickets: 4 tickets / wristband	Height Min: 36 inches	Height Max: N/A	
OPENING THE RIDE			INT
	e sure nothing is obstructing the ride k to make sure the platform is also d	•	
,	the control panel and keep it with youngee on your wrist and take it with you	-	
If the ride has not been placed in operation for the day, has been turned off or has been taken out of service for any reason (ex. Maintenance), you are required to run a test ride without riders before returning the ride to service.			
If the ride will not operate please	call a supervisor to make sure the ric	de breaker is turned on.	
RIDER SCREENING			INT
You should speak with each gues with a smile and a pleasant facial	st as they enter the ride, creating eye expression.	contact, greeting them	
There is a minimum height of 36 i the ride.	nches to ride. Do not allow parents	to carry children onto	
Parents are allowed on this ride.			
As riders enter please collect thre tickets in the ticket box.	ee tickets or verify the correct afterno	oon wristband. Place all	
Ensure that riders remove or secure loose items before boarding.			
If a child is being assisted by a pa	arent please ask them to use the exit	gate when finished.	
Communicate with all riders to "F	Please walk," as they enter the ride a	rea.	
LOADING RIDERS			INT
Count the appropriate number of	riders for a ride group and only adm	it that number.	
Balance the ride when not operat specific color ride car that you de	ing a full ride. This can be done by tesignate.	elling riders to pick a	
If you have smaller riders riding water	vith large riders please have the large	er rider sit closer to the	
_	ntrance gate and begin your safety of admit additional riders you must sta	_	
Begin your safety checks starting direction when possible so the ric	at the entrance gate. Proceed in a ders see you approaching.	counterclockwise	

Little flow fraining offeets	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check the ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture. There should be no more than two riders on a seat.	
Make sure the lap belt is secured with nothing between the rider and the restraint device. Rotate the grab bar toward the rider so they can also hold onto it durning the ride.	
If a ride car is empty please make sure the lap belts are inside the car.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
Do not pass a ride unit until the ride unit is fully checked & secured. In the event that a restraint device security check process is interrupted, the operator/attendant must begin the process again.	
Once you have returned to the yellow line on the platform you know you have checked each ride car.	
STARTING THE RIDE	INT
When you finish your safety restraint checks and return to the control panel, insert your operator key and turn on the panel.	
Make sure you are in the defined safety zone next to the operator control station.	
Use defined visual confirmation from the designated safety zone to confirm: • Entrance and exit gates are secure. • The ride area is clear. • Ride restraints are secure. • Riders are in proper riding position.	
Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.	
After completing your visual check, extend your arm out towards the ride locking out the elbow with a thumbs up. This visually alerts those around you that you are about to start the ride.	
If you can confirm that the riders are in position and ready announce "ALL SET". Press the timer button which will illuminate the red timer light and allow you to start the ride when ready.	
If you can confirm that the ride platform is clear announce "ALL CLEAR".	
After a third and final look announce "HERE WE GO! Turn the control knob to the forward position and hold the knob during the ride.	
As the ride speeds up you you may lower your arm but must look at each rider to make sure they are ok.	
Keep your chin up and eyes out looking at your ride the entire time it is running.	
Do not allow spectators to reach over the fence for hi fives.	

DURING THE RIDE	INT
When the timer expires the ride will begin to slow down even when the control knob is in the forward position. At this point let go of the control knob.	
As the ride begins to slow down, inform the riders that they are going to to backwards. Announce "GOING BACKWARDS" several times so that the all riders are aware and that they do not try to get out when the ride stops.	
Even when you announce "GOING BACKWARDS" it is very common for riders to begin unloading since the ride is slowing. This is a critical moment to make sure all riders are still in the proper position before you put the ride into reverse.	
When the ride has come to a COMPLETE stop, set the timer button again which will illuminate the red timer light. If all riders are still in the proper position turn the control knob toward the reverse position and hold the knob during the ride.	
When the timer goes out the ride will begin to slow on its own. At this point let go of the knob.	
Stay in your safety zone while the ride is in operation, stay mentally focused. If at any point you need to leave the safety zone you should stop the ride.	
STOPPING THE RIDE	INT
When the ride timer completes its cycle in forward or reverse the ride will stop on its own.	
In the event of an emergency, let go of the control knob and the ride will begin to slow down.	
AFTER THE RIDE	INT
Remove your key from the operator controls and assist riders off the ride.	
If you unbuckle a lap belt for a rider you need to assist that rider completely out of the ride car before assisting the next rider.	
When the ride platform is completely empty you should start the loading process again.	
TWO PERSON OPERATION	INT
If there are two operators one operator should collect tickets and engage riders at the entrance gate while the other operator assists riders onto the platform.	
Once the entrance/exit gates have been closed and checked, both operators may begin the safety check process starting next to each other. Each operator will work in opposite directions until they meet again on the other side. This ensures that all riders have been thoroughly checked and no one was missed.	
The operator with the operator key will then go to the controls to begin the starting process while the other operator goes to the second safety zone on the opposite side of the platform. When the operator at the controls puts their thumb up with their elbow locked, the second operator must do the same. Both operators must make eye contact with each other as they go through the defined visual confirmation checks. Only once the ride has started with either of them lower their arm.	

CLOSING THE RIDE	INT
When instructed by your supervisor, place your ride closed sign on the fence.	
Complete any other tasks assigned by your supervisor such as sweeping or reassignment another area.	to
When you are cleared to leave, take your ticket box back to the Swinger ride area outside t fence and place the operator control key on the counter in the office before signing out.	h
Trainee Signature Trainer Signature Date	

KIDDIE WHEEL

Tickets: 3 tickets / wristband	Height Min: N/A Under 3 must have adult	Height Max: N/A	
OPENING THE RIDE			INT
Walk around the ride area to mal cars.	ke sure nothing is obstructing the ride	e platform or the ride	
Make sure the ride lights are on. electrical box and turn the ride s	If they are not, walk behind the ride witch to ON.	platform to the tan	
•	the control panel. While loading and ach time you load/unload. If you leave with you.	•	
	n operation for the day, has been turn . Maintenance), you are required to ru o service.		
RIDER SCREENING			INT
You should speak with each gue with a smile and a pleasant facia	st as they enter the ride, creating eyell expression.	contact, greeting them	
	but only one adult may sit in each riden to sit in the middle of the ride car s		
ride with an adult. Use your judg	um height/maximum but children und gement and if you are not sure you sh ust also pay tickets/have a wristband	nould ask the parent. If	
•	ride alone and a parent will not accor ou need assistance from a superviso		
As riders enter please collect two tickets in the ticket box.	o tickets or verify the correct afternoo	on wristband. Place all	
Ensure that riders remove or sec	cure loose items before boarding.		
If a child is being assisted by a p	parent, please ask them to use the ex	it gate when finished.	
LOADING RIDERS			INT

Little Row Training Sneets	
Proper balancing of the ride cars is critical to the safe and efficient operation of the ride. Based on the number of riders in your Q line you need to evaluate how to best balance the cars. If you can only fill two cars, place them opposite each other. If you have a full ride you can unload/load the cars in consecutive order.	
When loading/unloading the ride cars, the ride will drift after the stop button is pressed. The amount the ride car will drift depends on the weight of passengers loaded and the speed the ride was traveling.	
If the ride car overshoots the platform wait until it comes to a complete stop. Flip the switch on the control panel labeled "change direction". Bring the ride car back to the proper position on the platform and then flip the "change position" switch back again. During general operation the ride should operate clockwise.	
Load & Go! Kiddie Wheel is different from other rides in the park. You load each ride individually which does not allow you to load everyone before starting your defined visual safety checks.	
When you are loading riders, the operator control key should be in the off position.	
If you ever need to leave the ride you must take the ride operator key with you.	
After you allow a ride car group onto the platform make sure that the entrance chain is latched.	
Make sure to steady each ride car as customers get in and out.	
Conducting security restraint safety checks in a methodical and consistent manner is key to safety.	
Visually check each ride unit for the appropriate number of riders, rider seating arrangement/placement and rider posture.	
Each child should have their lap belt buckled. Make sure the belt is snug across the lap and secured with nothing between the rider and the restraint device. Parents do not have to buckle.	
If a rider or a parent has buckled a lap belt it is your responsibility to double check the restraint. Do not assume it is buckled correctly.	
When you close the ride car entrance gate make sure the safety pin is fully engaged.	
In the event that a restraint device security check process is interrupted, the operator/ attendant must begin the process again.	
STARTING THE RIDE	INT
When you have finished your safety restraint checks on each ride car, return to the control panel, and turn the operator controls to the ON position.	
Make sure you are in the defined safety zone next to the operator control station.	

Use defined visual confirmation again from the designated safety zone to confirm:

- Entrance chain and exit gate are secure.
- The ride area is clear.
- Ride restraints are secure.
- Riders are in proper riding position.

Defined visual confirmation is an intentional visual check of each specific location observed. It is not a quick head swing from side to side.

After confirming the the defined visual confirmation criteria you can press the Start button and the timer button.

DURING THE RIDE	INT
Keep your finger over the stop button in case you need to stop the ride.	
Keep your chin up and eyes out looking at your ride the entire time it is running.	
Do not allow spectators to reach over the fence for hi fives.	
Stay in your safety zone while the ride is in operation, stay mentally focused. If at any point you need to leave the safety zone you should stop the ride.	
STOPPING THE RIDE	INT
When the timer light goes out this indicates that it is time to begin the unloading process.	
Bring one of the ride cars to the unloading area on the platform.	
In the event of an emergency, press the stop button or hit the emergency stop button located on the control panel.	
AFTER THE RIDE	INT
Bring a ride car to the platform, turn your operator key to the OFF position and assist riders out of the ride car.	
If you unbuckle a lap belt for a rider you need to assist that rider completely out of the ride car and off the platform before assisting the next rider.	
Make sure to steady the ride car as riders exit.	
Based on the number of riders in your Q line you need to evaluate how to best balance the ride. Please evaluate if you should reload that ride car or if you should leave it empty.	
Return to the controls, turn the ride controls back on and move to the next ride car.	
Repeat this process for each car until all riders have all been unloaded from the previous ride.	
If you only have a few riders please make sure to balance them opposite each other.	
CLOSING THE RIDE	INT
When instructed by your supervisor, place your ride closed sign on the fence.	

Complete any other tasks assigned by yo another area.	our supervisor such as sweeping	g or reassignment to	
When you are cleared to leave, take your ticket box back to the Swinger ride area and place the operator control key on the counter in the office before signing out.			
Trainee Signature	 Trainer Signature	 Date	

TRAINER NOTES: