USG

SAFETY DATA SHEET

1. Identification

Product identifier FIRECODE® Smoke-Sound Sealant

Other means of identification

SDS number 61000040002A

Synonyms Sound Blocking Sealant

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

 Telephone
 1-800-874-4968

 Website
 www.usg.com

 Emergency phone number
 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbolNone.Signal wordNone.Hazard statementNone.

Precautionary statement

PreventionObserve good industrial hygiene practices.ResponseGet medical attention/advice if you feel unwell.

Storage Store as indicated in Section 7.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	% > 50	
Calcium carbonate, synthetic	471-34-1		
Glycerol	56-81-5	< 5	
Iron oxide	1309-37-1	< 2	

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

Skin contactContact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists.

FIRECODE® Smoke-Sound Sealant

930874 Version #: 03 Revision date: 28-October-2020 Issue date: 12-November-2015

1 / 7

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical Eye contact

assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Dust may irritate eves and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. May cause allergic skin disorders in sensitive individuals.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

and precautions for firefighters

Special protective equipment

Fire fighting equipment/instructions

Specific methods

General fire hazards

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Not a fire hazard.

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Cool material exposed to heat with water spray and remove it if no risk is involved.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up For personal protection, see Section 8 of the SDS.

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

Filled 4.5 gallon pails of joint compound may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

Filled cartons of joint compound may be stacked a maximum of 3 layers high on a standard 42 x 42 or 42 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Glycerol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Iron oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.

SDS US 2/7 930874 Version #: 03 Revision date: 28-October-2020 Issue date: 12-November-2015

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	Form
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection

It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Skin protection

Other

Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Paste. Color Red. Acrylate. Odor **Odor threshold** Not applicable. 8 - 10 рH Not applicable. Melting point/freezing point

Initial boiling point and boiling Not applicable.

range

Flash point Not applicable. Not applicable. **Evaporation rate**

930874 Version #: 03 Revision date: 28-October-2020 Issue date: 12-November-2015 3/7 Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

(%)

Not applicable.

Not applicable.

Explosive limit - lower (%) Not applicable. Not applicable. Explosive limit - upper (%) Vapor pressure Not applicable.

Vapor density Not applicable. Relative density 1.6 (H2O=1)

Solubility(ies)

Miscible with water. Solubility (water) Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable.

Other information

Bulk density 13.4 lb/gal VOC 4 g/l

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition

products

Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Airborne dust may irritate throat and upper respiratory system causing coughing. Inhalation

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Airborne dust may cause mechanical eye irritation. Eve contact

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing

Information on toxicological effects

Acute toxicity Not expected to be a hazard under normal conditions of intended use.

Components **Species Test Results**

Calcium carbonate, synthetic (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

Glycerol (CAS 56-81-5)

Acute

Dermal

LD50 Rabbit > 18700 mg/kg

Issue date: 12-November-2015 4/7 930874 Version #: 03 Revision date: 28-October-2020

Species Test Results Components

Oral

LD50 Rat 27200 mg/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization The product contains a small amount of sensitizing substance which may provoke an allergic

reaction among sensitive individuals after repeated contact. For detailed information, see section

Data does not suggest that this product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Iron oxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

No data available, but none expected.

repeated exposure **Aspiration hazard** Not an aspiration hazard.

Prolonged exposure may cause chronic effects. For detailed information, see section 16. **Chronic effects**

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

Calcium carbonate, synthetic (CAS 471-34-1)

Aquatic Acute

LC50 Fish Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 Hours

Glycerol (CAS 56-81-5)

Aquatic

Acute

Crustacea EC50 Daphnia magna > 10000 mg/l, 24 Hours

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Partition coefficient n-octanol / water (log Kow)

Glycerol (CAS 56-81-5) -1.76

No data available. Mobility in soil Other adverse effects None expected.

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Dispose of in accordance with local regulations. Local disposal regulations

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components of this product are in compliance with the listing Requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Glycerol (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

Glycerol (CAS 56-81-5) Iron oxide (CAS 1309-37-1)

US. New Jersey Worker and Community Right-to-Know Act

Glycerol (CAS 56-81-5)

Iron oxide (CAS 1309-37-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Glycerol (CAS 56-81-5)

Iron oxide (CAS 1309-37-1)

US. Rhode Island RTK

Glycerol (CAS 56-81-5)

Iron oxide (CAS 1309-37-1)

FIRECODE® Smoke-Sound Sealant 6/7 Issue date: 12-November-2015

930874 Version #: 03 Revision date: 28-October-2020

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

16. Other information, including date of preparation or last revision

12-November-2015 Issue date **Revision date** 28-October-2020

Version #

Further information Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No.

4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer.

Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with

eczema.

NFPA Ratings: Health: 2 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



NFPA: National Fire Protection Association. List of abbreviations

Registry of Toxic Effects of Chemical Substances (RTECS) References

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.

SDS US 7/7 930874 Version #: 03 Revision date: 28-October-2020 Issue date: 12-November-2015