

# OSAIC

## WAVY Titanium Collection

Piece 1" x 1" • Piece 2.5x2.5cm. Sheet 12 ½" x 12 ½" • Panel 31,6 x 31,6 cm.

### SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

| Wall      | Floor       | Wet areas | Pools | Material |
|-----------|-------------|-----------|-------|----------|
| Int / Ext | Residential | Yes       | Yes   | Glass    |



#### PACKING SOLID COLORS ( MESH )

| SIZE / MESH                      | WEIGHT / BOX | M² / BOX | PIECES / BOX | M² / PALLET · | WEIGHT / PALLET · |
|----------------------------------|--------------|----------|--------------|---------------|-------------------|
| 31,6 x 31,6 cm.<br>12 ½" x 12 ½" | 17,33 kg     | 2 m²     | 20           | 126 m²        | 1.200 kg          |

### TECHNICAL CHARACTERISTICS

| Test<br>UNE-EN-ISO 10545-3<br>Water Absorption           | Test<br>UNE-EN-ISO-101-92=101<br>Surface hardness.<br>Mohs | Test<br>UNE-EN-ISO 10545-9<br>Resistance to<br>thermal shocks        | Test<br>UNE-EN-ISO<br>10545-12<br>Frost resistance                   | Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack |                                                    |                                              |                                                                                                               |
|----------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------|----------------------------------------------|---------------------------------------------------------------------------------------------------------------|
|                                                          |                                                            |                                                                      |                                                                      | Domestic products                                           | Pool water additives                               | Low acid and alkalins                        | High acid and alkalins                                                                                        |
| None                                                     | 4                                                          | Resistant                                                            | Resistant                                                            | GA                                                          | GA                                                 | GLA                                          | GHA                                                                                                           |
| Test<br>UNE-EN-ISO<br>10545-14<br>Resistance to staining | Test<br>UNE-EN-ISO<br>10545-11=1997<br>Cracking            | DIN 51094<br>Colour Stability on<br>exposure to light and<br>UV rays | DCOF<br>Wet Dynamic Coefficient of Friction<br>ANSI A 137.1 Standard |                                                             | DIN 51130:2004<br>SLIP Resistance<br>wearing shoes | DIN 51097<br>SLIP Resistance in<br>bare feet | Test UNE-ENV<br>12633:2003 (CTE) Anti<br>skid coefficient, suitable<br>for outdoor use and<br>swimming pools. |
| Class 5                                                  | Resistant                                                  | Resistant                                                            |                                                                      |                                                             |                                                    |                                              |                                                                                                               |

WWW.BYOSAIC.COM



RECYCLE  
PRODUCT

