


OSAIC


PROUD TITANIUM COLLECTION




2.5X2.5cm sheet size 31.6x31.6cm




SA 601




SA 602




SA 603



SA 604



SA 605



SA 606



SA 607




SA 608




SA 609




SA 610




SA 611



SA 612



SA 613




SA 614




SA 615




2.5X2.5cm sheet size 31.6x31.6cm




SA 616




SA 617




SA 618




SA 619



SA 620




SA 621



SA 622



SA 623



SA 624



OSAIC

PROUD Titanium Collection

Piece 1" x 1" • Piece 2.5x2.5cm. Sheet 12 ½" x 12 ½" • Panel 31,6 x 31,6 cm.

SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

Wall	Floor	Wet areas	Pools	Material
Int / Ext	Residential	Yes	Yes	Glass



PACKING SOLID COLORS (MESH)

SIZE / MESH	WEIGHT / BOX	M ² / BOX	PIECES / BOX	M ² / PALLET •	WEIGHT / PALLET •
31,6 x 31,6 cm. 12 ½" x 12 ½"	17,33 kg	2 m ²	20	126 m ²	1.200 kg

TECHNICAL CHARACTERISTICS

Test UNE-EN-ISO 10545-3 Water Absorption	Test UNE-EN-ISO-101-92=101 Surface hardness. Mohs	Test UNE-EN-ISO 10545-9 Resistance to thermal shocks	Test UNE-EN-ISO 10545-12 Frost resistance	Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack			
				Domestic products	Pool water additives	Low acid and alkalins	High acid and alkalins
None	4	Resistant	Resistant	GA	GA	GLA	GHA
Test UNE-EN-ISO 10545-14 Resistance to staining	Test UNE-EN-ISO 10545-11=1997 Cracking	DIN 51094 Colour Stability on exposure to light and UV rays	DCOF Wet Dynamic Coefficient of Friction ANSI A 137.1 Standard		DIN 51130:2004 SLIP Resistance wearing shoes	DIN 51097 SLIP Resistance in bare feet	Test UNE-ENV 12633:2003 (CTE) Anti skid coefficient, suitable for outdoor use and swimming pools.
Class 5	Resistant	Resistant					

WWW.BYOSAIC.COM



RECYCLE
PRODUCT

