

FUTURA
MARK DIFFERENT



F350L

**LASER
MARKING**

Subject to change without notice

BRIDGE[®]
SYNERGY BETWEEN EXCELLENCE

F350L

SPECIFICATIONS

FUTURA

MACHINE DESCRIPTION	
Footprint	1.000 x 1.450 x 1.770 mm
Weight	800 Kg
Control Unit	Proprietary – PC Based
HMI	24" Touch Screen, multilanguage
Color	RAL 9005 Frame, front door; RAL 7035 side covers, back doors
Codes	Data Matrix ECC200, Code 39, Code 128, 2/5 Interleaved, QR Code, Text

MACHINE CONFIGURATION	
Transport Height	950 mm +/- 25 mm
Max Transport Width	420 mm
Interface	SMEMA
Transfer Direction	Left to right (optional right to left or pass-back)

PANEL DIMENSIONS	
Panel Length	70 mm up to 655 mm
Panel Width	50 mm up to 420 mm
Panel Weight	Up to 3 Kg
Transport PCB	1 ÷ 5 mm ESD belt
Panel Clearance	20 mm up / 30 mm down
Panel Thickness	0.5 mm to 6 mm
Marking Area (LxW)	Up to 650 mm x 350 mm

LASER DESCRIPTION	
Laser Type	CO2 (fiber optional)
Laser Power	10 W CO2 (30 W optional) / 50 W fiber
Laser Spot	125 µm (5 mils)
Typical cycle time	2D code 3x3mm < than 0,35 s (pure marking time)

INSTALLATION REQUIREMENTS	
Power Supply	230 VAC monophase, 50 Hz (1P+N+PE)
Consumption	1 kW
Air Supply	6 Bar filtered, 200 slpm
Connectivity	Ethernet (Wifi and VPN as options) – Industry 4.0 Compliant