

miniDSP with Dirac Live Selection Guide

(Available through Deer Creek Audio)

	<u>DDRC-24</u>	<u>Flex RCA</u>	<u>Flex Balanced</u>	<u>SHD</u>
Bluetooth LDAC High Definition		X	X	
Built in Streamer Volumio				X
Balanced Analog I/O			X*	X**
RCA Single ended Analog I/O	X	X		X
TOSLINK Digital Input	X	X	X	X
USB Digital Input	X	X	X	X
SPDIF Digital Input		X	X	X
AES-EBU Digital Inputs				X
SPDIF Digital Outputs		***	***	X
TOSLINK Digital Outputs		***	***	
Front Panel Display and Control Knob		X	X	X
Remote Selectable Inputs, Volume & Tone Modes	X	X	X	X
Remote Streaming Playback Control				X
PEQ, X-over, Channel Level, Delay, Compression, 2x4 Routing	X	X	X	X
Number Input x Output Channels	2x4	2x4	2x4	2x4
Maximum Input Sample Rate	216 kHz	216 kHz	216 kHz	192 kHz
Internal Processing Bits & Sample Rate	32 bit / 48kHz	32 bit / 96kHz	32 bit / 96kHz	32 bit / 96kHz
Dirac Live Process Bits & Sample Rate	32 bit / 48kHz	32 bit / 48kHz	32 bit / 48kHz	32 bit / 96kHz
Input Voltage Maximum	2 - 4 Vrms	2 Vrms	4 Vrms	2 / 4 Vrms****
Output Voltage	2 Vrms	2 Vrms	4 Vrms	2 / 4/Vrms****
*TRS **XLR ***Only Flex Digital ****2 Vrms unbalanced, 4 Vrms balance				