



1027 S. LINWOOD AVE. SANTA ANA, CA 92705
TEL. 714.549.2015 | FAX. 714.549.2087

MAINTENANCE GUIDELINES FOR PLASTIC LAMINATE LOCKERS

WARNING:

- **AVOID** using cleaners that contain Sulfuric, Nitric, Oxalic, Muriatic or Hydrochloric acid. Such cleaners will cause discoloration and corrosion to all metals. When used in an enclosed area such as a public restroom, the fumes can cause corrosion and discoloration even if the acid is not in direct contact with the metal.
- **AVOID** using hose-down cleaning on plastic laminate products. These products have a particleboard core which will absorb water into the substrate causing swelling and delamination.
- **AVOID** using bleaches, sodium hydroxide, and sodium hypochlorite.

MAINTENANCE:

CLEAN BY WIPING WITH NON-ABRASIVE DETERGENT AND DAMP CLOTH OR SPONGE. DIFFICULT STAINS CAN BE REMOVED USING A MILD SOAP AND DETERGENT AND A SOFT-BRISTLED BRUSH.

DIFFICULT STAINS THAT RESIST ANY OF THE ABOVE CLEANING METHODS MAY REQUIRE THE USE OF LACQUER THINNER. DISCONTINUE APPLYING THINNER IF THE STAIN PERSISTS AND IF COLOR OF THE LAMINATE HAS BEEN ALTERED. EXTENDED CONTACT OF THE LAMINATE TO THE THINNER MAY CAUSE DISCOLORATION.