

CARE AND MAINTENANCE

Handling & Storage

- Lay material flat. Do not store against a wall or stack unevenly; improper storage can cause warping.
- Leave protective masking on panels and doors until installation is complete to prevent scratches.
- Use care when lifting parts; do not slide or drag across surfaces.
- When moving with a forklift, protect edges — forks can easily damage the material.
- If banding is used, apply protective corners to prevent indentations.
- Extreme heat warning: surface temperatures beyond normal indoor exposure may cause melting, sagging, warping, discoloration, or increased expansion/contraction.
- Protect from direct sunlight. Product is not intended for outdoor use; sunlight exposure voids warranty.
- Store products horizontally, flat, and indoors at room temperature until installation.
- Keep surfaces free from construction debris such as dust, sand, concrete, or tile residue.
- Do not use any HDPE material as a work surface.

Cleaning:

Dirt & Graffiti

- Clean with water and mild detergent.
- Avoid abrasive cleaners, pads, or brushes that may scratch the surface.
- Do not use cleaners containing acetic acid/vinegar.
- Always test new cleaners on a scrap piece or inconspicuous area before full use.

For stubborn stains, use:

- ½ cup household detergent + ⅔ cup trisodium phosphate + 1 gallon water, OR
- Non-abrasive industrial strength cleaners.
- For adhesive residue from masking, use mineral spirits or acetone (avoid hardware contact).

Cuts & Scratches

- Minor cuts and scratches can often be burnished by rubbing with a smooth, rounded object (such as a spoon handle).

To restore appearance, spray surfaces lightly with silicone polish for a bright, glossy finish.

Maintenance Note:

Accu Tec solid plastic partitions are low-maintenance and will not rust or delaminate. Like a new painted surface or automobile, regular cleaning ensures the best long-term appearance.