

Wood doors on your terms

## 20 MIN P-LAM DOOR CONSTRUCTION SPECS

Denton Door 5-Ply Premium Flush Door Construction:  
All Denton Door Company Premium Architectural Doors Type PC-5/FD-3 meet or exceed standards set forth by WDMA I.S.1-A and the AWI for PC-5 as tested per A.S.T.M. E-152 by Warnock Hersey International. DentonDoor is authorized through INTERTEK to construct and mark 20-minute rated fire doors.

- 
- Top and Bottom Rails:  
1-3/8" Thick SCL  
(Stranded Composite Lumber)
  - Core Type:  
Particle Board meets or exceeds ANSI A208.1  
for physical/mechanical properties  
For environmental properties meets or exceeds  
EPPS CPA-3-08 (100% Recycled Fiber)
  - Crossband:  
1/10" High Density Fiber Crossband
  - Stiles:  
Hard wood over Stranded Composite Lumber (SCL)  
Backer for stained edges  
1-3/8" thick = 7/8" Solid Maple + 1/2" SCL before pre-fit
  - Faces:  
Plastic Laminate available from  
Wilsonart, Formica, Nevamar, Arborite

Adhesives: Meet requirements of WDMA I.S.1A, C-6

Door Thickness: 1-3/4"

Maximum Size: 4' x 9'

Warranty: Premium Architectural Doors (Lifetime Warranty)  
Note: Interior use only. (Exterior use applications not warranted.)