

Wood doors on your terms

45 MIN WOOD VENEER DOOR CONSTRUCTION SPECS

Denton Door 5-Ply Premium Flush Door Construction:

All Denton Door Company Premium Architectural Doors Type PC-5/FD-3 meet or exceed standards set forth by WDMA I.S.1-A and the AWI for PC-5 as tested per A.S.T.M. E-152 by Warnock Hersey International. DentonDoor is authorized through INTERTEK to construct and mark 45-minute rated fire doors.

Top Rail:
1-3/8" Thick SCL (Stranded Composite Lumber) w/ Concealed Intumescent Fire Block

Core Type:
32-lb Density AFC (Agrifiber) Fire Core

Crossband:
1/10" High Density Fiber Crossband

Stiles:
1.474" Thick solid Maple over SCL w/Concealed Intumescent Fire Block

Faces:
White Maple, Red Oak, Birch, and more.
Premium, Grade A wood for wood face.

Bottom Rail:
1-3/8" Thick SCL

Adhesives: Meet requirements of WDMA I.S.1A, C-6

Door Thickness: 1-3/4"

Maximum Size: 4' x 9'

Warranty: Premium Architectural Doors (Lifetime Warranty)

Note: Interior use only. (Exterior use applications not warranted.)

