

READ THIS MANUAL CAREFULLY!
It contains important safety information.

168pgs

OWNER'S MANUAL

# YFM350FWBK(C) Big Bear 4x4

AWARNING

LIT-11626-10-98

Dear New Yamaha ATV Owner:

CONGRATULATIONS ON THE PURCHASE OF YOUR NEW YAMAHA ATV. You have purchased a quality Yamaha product that, with proper use and care, will provide hours of riding pleasure. **BEFORE YOU OPERATE YOUR NEW ATV, Yamaha recommends these important points:** 

- READ YOUR OWNER'S MANUAL
- A CHILD UNDER 12 YEARS OLD SHOULD NOT OPERATE AN ATV-WITH ENGINE SIZE 70CC OR GREATER
- A CHILD UNDER 16 YEARS OLD SHOULD NOT OPERATE AN ATV WITH ENGINE SIZE GREATER THAN 90CC

<u>.</u>

民国

• TAKE THE FREE HANDS-ON TRAINING COURSE OFFERED BY YAMAHA — ASK YOUR DEALER FOR DETAILS OR CALL 1-800-447-4700

If you have any questions about these points, or if you purchased your ATV from an authorized Yamaha dealership and were not informed of the age recommendation for your ATV by the dealership, please fill out the information below and mail this card to Yamaha today.

Name:		ATV Model:	Purchase Date:
Address:	5 15	Primary I.D. (Engine Number)	MO. DAY YR.
		David and Name of C. Address	
Telephone:	rant	Dealer Name & Address:	





FIRST CLASS

PERMIT NO. 4

CYPRESS, CA

POSTAGE WILL BE PAID BY ADDRESSEE

YAMAHA MOTOR CORPORATION U.S.A. P.O. BOX 6555 CYPRESS, CALIFORNIA 90630-9989

ATTN: SALES ADMINISTRATION

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES



# INTRODUCTION

Congratulations on your purchase of the Yamaha YFM350FWB. It represents the result of many years of Yamaha experience in the production of fine sporting, touring, and pace-setting racing machines. With the purchase of this Yamaha, you can now appreciate the high degree of craftsmanship and reliability that have made Yamaha a leader in these fields.

This manual will provide you with a good basic understanding of the features and operation of this machine. This manual includes important safety information. It provides information about special techniques and skills necessary to ride your machine. It also includes basic maintenance and inspection procedures. If you have any questions regarding the operation or maintenance of your machine, please consult a Yamaha dealer.

# AN IMPORTANT SAFETY MESSAGE:

- READ THIS MANUAL TOGETHER WITH TIPS FOR THE ATV RIDER CAREFULLY AND COMPLETELY BEFORE OPERATING YOUR MACHINE. MAKE SURE YOU UNDERSTAND ALL INSTRUCTIONS.
- PAY CLOSE ATTENTION TO THE WARNING AND CAUTION LABELS ON THE MACHINE.
- NEVER OPERATE AN ATV WITHOUT PROPER TRAINING OR INSTRUCTION. FREE TRAINING IS AVAILABLE TO ANYONE WHO BUYS A NEW ATV. CALL 1-800-447-4700 FOR MORE INFORMATION.
- THIS ATV, AND ANY OTHER ATV OVER 90cc, SHOULD NOT BE RIDDEN BY ANYONE UNDER 16 YEARS OF AGE.

#### IMPORTANT MANUAL INFORMATION

FAILURE TO FOLLOW THE WARNINGS CONTAINED IN THIS MANUAL CAN RESULT IN SERIOUS INJURY OR DEATH.

Particularly important information is distinguished in this manual by the following notations:

 $\triangle$ 

The Safety Alert Symbol means ATTENTION! BECOME ALERT! YOUR SAFETY IS INVOLVED!

**WARNING** 

Failure to follow WARNING instructions <u>could result in severe injury</u> or <u>death</u> to the machine operator, a bystander or a person inspecting or repairing the machine.

CAUTION:

A CAUTION indicates special precautions that must be taken to avoid damage to the machine.

NOTE:

A NOTE provides key information to make procedures easier or clearer.

## **IMPORTANT NOTICE**

This machine is designed and manufactured for OFF-ROAD use only. It is illegal and unsafe to operate this machine on any public street, road or highway.

This machine complies with all applicable OFF-ROAD noise level and spark arrester laws and regulations in effect at the time of manufacture.

Please check your local riding laws and regulations before operating this machine.

EDA00000		
1	AFFIX DEALER	I
	LABEL HERE	

EDA00100

OWNER'S MANUAL
© 1997 by Yamaha Motor Corporation,
U.S.A.
1st Edition, April 1997
All rights reserved. Any reprinting or
unauthorized use without the written
permission of
Yamaha Motor Corporation,
U.S.A. is expressly prohibited.
Printed in Japan

P/N LIT-11626-10-93

YFM350FWBK(C)

# **WARNING**

Indicates a potential hazard that could result in serious injury or death.

# **CONTENTS**

1	LOCATION OF THE "WARNING AND SPECIFICATION LABELS".	1-1
2	SAFETY INFORMATION	2-1
3	DESCRIPTION AND MACHINE IDENTIFICATION Identification numbers record Key identification number Vehicle identification number Model label	3-2 3-2 3-3

CONTROL FUNCTIONS	4-1
Main switch	4-
Indicator lights	4-2
Oil temperature indicator light	
checking method	4-3
Handlebar switches	4-4
Throttle lever	4-5
Speed limiter	4-6
Front brake lever	4-7
Rear brake pedal and lever	4-7
Parking brake	
Shift pedal	
Reverse knob	
Recoil starter	. 4-10
Fuel tank cap	. 4-11
Fuel cock	
Starter "CHOKE"	
Seat	
Storage box	
Front carrier	


	Rear carrier4-15	6	OPERATION	6-1
	Front shock absorber		Starting a cold engine	6-1
	adjustment4-16		Starting a warm engine	6-3
	Rear shock absorber		Warming up	6-3
	adjustment4-17		Reverse knob operation an	d
	Auxiliary DC terminal4-18		reverse driving	6-4
			Shifting	6-5
5	PRE-OPERATION CHECKS5-1		To start out and accelerate	6-5
	Front and rear brakes5-3		To decelerate	6-6
	Fuel5-5		Engine break-in	6-7
	Engine oil5-7		Parking	
	Final gear oil5-7		Parking on a slope	6-9
	Differential gear oil5-8		Accessories and loading	
	Throttle lever5-8		_	
	Fittings and Fasteners5-8	7	RIDING YOUR MOTO-4	7-1
	Lights5-8		Getting to know your MOTO	O-47-3
	Switches5-8		Ride with care and good	
	Battery5-8		judgement	7-4
	Tires5-9		Be careful where you ride	7-16
	How to measure tire pressure 5-11		Turning your MOTO-4	7-23
	Tire wear limit5-12		Climbing uphill	7-25


	Riding downhill 7-30	Carburetor adjustment	8-17
	Crossing a slope 7-32	Idle speed adjustment	8-18
	Crossing through shallow	Valve clearance adjustment	8-18
	water 7-34	Reverse lock release cable	
	Riding over rough terrain 7-36	adjustment	8-19
	Sliding and skidding 7-38	Throttle lever adjustment	8-19
	What to do if 7-40	Front brake shoe inspection	8-20
	What to do 7-40	Rear brake shoe inspection	8-20
		Inspecting the brake fluid	
8	PERIODIC MAINTENANCE AND	level	8-21
	ADJUSTMENT8-1	Brake fluid replacement	8-22
	Owner's manual and tool kit8-1	Front brake lever free play	
	Periodic maintenance/	adjustment	8-23
	lubrication8-3	Rear brake pedal and lever	
	Engine oil8-5	adjustment	8-25
	Final gear oil8-9	Clutch adjustment	8-28
	Differential gear oil	Cable inspection and	
	replacement8-11	lubrication	8-29
	Front axle boots 8-13	Brake and shift pedals/brake	
	Spark plug inspection 8-14	lever lubrication	8-29
	Air filter cleaning 8-15	Wheel removal	8-30

	Wheel installation8	3-30
	Battery8	3-31
	Replenishing the battery fluid8	3-33
	Fuse replacement8	3-35
	Replacing the headlight bulb8	3-37
	Headlight beam adjustment8	3-38
	Troubleshooting8	3-39
	Troubleshooting chart8	3-40
9	CLEANING AND STORAGE	.9-1
10	SPECIFICATIONS1	0-1
11	NOISE REGULATION1	1-1
12	MAINTENANCE RECORD1	2-1

	3-1
YAMAHA EXTENDED SERVICE (Y.E.S.)14	l-1

# LOCATION OF THE "WARNING AND SPECIFICATION LABELS"





Read and understand all of the labels on your machine. They contain important information for safe and proper operation of your MOTO-4.

Never remove any labels from your MOTO-4. If a label becomes difficult to read or comes off, a replacement label is available from your Yamaha dealer.

1

# LOAD LIMIT

40 kg (88 lbs)

YAMAHA 4GB-24877-00

2

# **A WARNING**

**NEVER** sit here

YAMAHA

3MX-24875-00

(5)

# **LOAD LIMIT**

80 kg (176 lbs)

**YAMAHA** 

4SH-24897-00

(3)

#### A WARNING

# IMPROPER TIRE PRESSURE OR OVERLOADING CAN CAUSE LOSS OF CONTROL.

# LOSS OF CONTROL CAN RESULT IN SEVERE INJURY OR DEATH.

#### **OPERATING TIRE PRESSURE:** Set with tires cold

 Recommended: FRONT: 25kPa, {0.25kgf/cm²}, 3.6psi REAR: 25kPa, {0.25kgf/cm²}, 3.6psi

Minimum : FRONT : 22kPa, {0.22kgf/cm²}, 3.2psi
 REAR : 22kPa, {0.22kgf/cm²}, 3.2psi

 Never set tire pressure below minimum. It could cause the tire to dislodge from the rim.

#### LOADING/TRAILER TOWING

- Cargo or a trailer can affect stability and handling. Read owner's manual before loading or towing.
- When loading with cargo or towing a trailer: Reduce speed and allow more room to stop. Avoid hills and rough terrain.
- Maximum Vehicle Load: 210kg, (463lbs) Includes weight of operator, cargo and accessories (and if applicable, trailer tongue weight).

YAMAHA

4SH-21696-00

**(4)** 

# **A WARNING**

NEVER ride as a passenger.

Passengers can cause a loss of control, resulting in SEVERE INJURY or DEATH.

4WU-2151H-00

6

# **A WARNING**

Improper ATV use can result in SEVERE INJURY or DEATH.









ALWAYS USE AN APPROVED HELMET AND PROTECTIVE GFAR

NEVER USE ON PUBLIC PASSENGERS WITH DRUGS OR ALCOHOL

#### **NEVER** operate:


- · without proper training or instruction.
- at speeds too fast for your skills or the conditions.
- on public roads-a collision can occur with another vehicle.
- with a passenger-passengers affect balance and steering and increase risk of losing control.

#### **ALWAYS:**

- use proper riding techniques to avoid vehicle overturns on hills and rough terrain and in turns.
- avoid paved surfaces-pavement may seriously affect handling and control.

LOCATE AND READ OWNER'S MANUAL. FOLLOW ALL INSTRUCTIONS AND WARNINGS. (For replacement manual, call 1-800-532-1558)

4WU-21568-00



8

## **A** WARNING



Operating this ATV if you are under the age of 16 increases your chance of severe injury or death.

**NEVER** operate this ATV if you are under age 16.

YAMAHA

3FA-2415A-00

# **A** SAFETY INFORMATION

AN ATV IS NOT A TOY AND CAN BE HAZARDOUS TO OPERATE. An ATV handles differently from other vehicles including motorcycles and cars. A collision or rollover can occur quickly, even during routine maneuvers such as turning and riding on hills or over obstacles, if you fail to take proper precautions.

SEVERE INJURY OR DEATH can result if you do not follow these instructions:

- Read this manual and all labels carefully and follow the operating procedures described.
- Never operate an ATV without proper training or instruction. <u>Take a Training Course</u>.
   Beginners should receive training from a certified instructor. Contact an authorized ATV dealer or call 1-800-447-4700 to find out about the training courses nearest you.
- Always follow the age recommendation:
  - A child under 16 years old should never operate an ATV with engine size greater than 90cc.
- Never allow a child under age 16 to operate an ATV without adult supervision, and never allow continued use of an ATV by a child if he or she does not have the abilities to operate it safely.
- Never carry passenger on an ATV.

- Always avoid operating an ATV on any paved surfaces, including sidewalks, driveways, parking lots and streets.
- Never operate an ATV on any public street, road or highway, even a dirt or gravel one.
- Never operate an ATV without wearing an approved motorcycle helmet that fits properly. You should also wear eye protection (goggles or face shield), gloves, boots, long-sleeved shirt or jacket, and long pants.
- Never consume alcohol or drugs before or while operating this ATV.
- Never operate at speeds too fast for your skills or the conditions. Always go at a speed that is proper for the terrain, visibility and operating conditions, and your experience.
- Never attempt wheelies, jumps, or other stunts.
- Always inspect your ATV each time you use it to make sure it is in safe operating condition. Always follow the inspection and maintenance procedures and schedules described in this manual.
- Always keep both hands on the handlebars and both feet on the footboards of the ATV during operation.
- Always go slowly and be extra careful when operating on unfamiliar terrain. Always be alert to changing terrain conditions when operating the ATV. Never operate on excessively rough, slippery or loose terrain until you have learned and practiced the skills necessary to control the ATV on such terrain. Always be especially cautious on these kinds of terrain.

- Always follow proper procedures for turning as described in this manual. Practice turning at low speeds before attempting to turn at faster speeds. Do not turn at excessive speed.
- Never operate the ATV on hills too steep for the ATV or for your abilities. Practice on smaller hills before attempting larger hills.
- Always follow proper procedures for climbing hills as described in this manual. Check
  the terrain carefully before you start up any hill. Never climb hills with excessively slippery or loose surfaces. Shift your weight forward. Never open the throttle suddenly or
  make sudden gear changes. Never go over the top of a hill at high speed.
- Always follow proper procedures for going down hills and for braking on hills as described in this manual. Check the terrain carefully before you start down any hill. Shift your weight backward. Never go down a hill at high speed. Avoid going down a hill at an angle that would cause the vehicle to lean sharply to one side. Go straight down the hill where possible.
- Always follow proper procedures for crossing the side of a hill as described in this manual. Avoid hills with excessively slippery or loose surfaces. Shift your weight to the uphill side of the ATV. Never attempt to turn the ATV around on any hill until you have mastered the turning technique described in this manual on level ground. Avoid crossing the side of a steep hill if possible.

- Always use proper procedures if you stall or roll backwards when climbing a hill. To
  avoid stalling, use proper gear and maintain a steady speed when climbing a hill. If
  you stall or roll backwards, follow the special procedure for braking described in this
  manual. Dismount on the uphill side or to a side if pointed straight uphill. Turn the ATV
  around and remount, following the procedure described in this manual.
- Always check for obstacles before operating in a new area.
   Never attempt to operate over large obstacles, such as large rocks or fallen trees. Always follow proper procedures when operating over obstacles as described in this manual.
- Always be careful when skidding or sliding. Learn to safely control skidding or sliding
  by practicing at low speeds and on level, smooth terrain. On extremely slippery surfaces, such as ice, go slowly and be very cautious in order to reduce the change of
  skidding or sliding out of control.
- Never operate an ATV in fast flowing water or in water deeper than that recommended in this manual. Remember that wet brakes may have reduced stopping ability. Test your brakes after leaving water. If necessary, apply them several times to let friction dry out the linings.
- Always be sure there are no obstacles or people behind you when you operate in reverse. When it is safe to proceed in reverse, go slowly.

- Always use the size and type tires specified in this manual. Always maintain proper tire pressure as described in this manual.
- Never modify an ATV through improper installation or use of accessories.
- Never exceed the stated load capacity for an ATV. Cargo should be properly distributed and securely attached. Reduce speed and follow instructions in this manual for carrying cargo or pulling a trailer. Allow greater distance for braking.

FOR MORE INFORMATION ABOUT ATV SAFETY, call the Consumer Products Safety Commission at 1-800-638-2772, or the ATV Distributor's Safety Hotline at 1-800-852-5344.

## **A** WARNING

#### **POTENTIAL HAZARD**

Improper handling of gasoline.

#### WHAT CAN HAPPEN

Gasoline can catch fire and you could be burned.

# **HOW TO AVOID THE HAZARD**

Always turn off the engine when refueling.

Do not refuel right after the engine has been running and is still very hot.

Do not spill gasoline on the engine or exhaust pipe/muffler when refueling. Never refuel while smoking, or while in the vicinity of sparks, open flames, or other sources of ignition such as the pilot lights of water heaters and clothes dryers.


When transporting the machine in another vehicle, be sure it is kept upright and that the fuel cock is in the "OFF" position. Otherwise, fuel may leak out of the carburetor or fuel tank.

# WHAT CAN HAPPEN

Gasoline is poisonous and can cause injuries.

## **HOW TO AVOID THE HAZARD**

If you should swallow some gasoline or inhale a lot of gasoline vapor, or get some gasoline in your eyes, see your doctor immediately. If gasoline spills on your skin, wash with soap and water. If gasoline spills on your clothing, change your clothes.



# **WARNING**

# POTENTIAL HAZARD

Starting or running the engine in a closed area.


## **WHAT CAN HAPPEN**


Exhaust fumes are poisonous and may cause loss of consciousness and death within a short time.


# **HOW TO AVOID THE HAZARD**

Always operate your machine in an area with adequate ventilation.

# **DESCRIPTION AND MACHINE IDENTIFICATION**







- 1. Rear carrier
- 2. Seat
- 3. Front carrier
- 4. Rear brake pedal
- 5. Headlight
- 6. Fuel cock
- 7. Starter "CHOKE"
- 8. Recoil starter
- 9. Battery
- 10. Rear wheel

- 11. Shift pedal
- 12. Front wheel
- 13. Rear brake lever
- 14. Parking brake lock plate
- 15. Main switch
- 16. Reverse knob
- 17. Front brake lever
- 18. Throttle lever
- 19. Handlebar switch

#### NOTE:\_

The machine you have purchased may differ slightly from those shown in the figures of this manual.

#### Identification numbers record

FD460301

Record the key identification number, vehicle identification number and model label information in the spaces provided for assistance when ordering spare parts from a Yamaha dealer or for reference in case the vehicle is stolen.

1. KEY IDENTIFICATION NUMBER:

2. VEHICLE IDENTIFICATION NUMBER:


3. MODEL LABEL INFORMATION:



EDA60201

#### Key identification number

The key identification number is stamped on the key as shown in the following illustration. This number can be used for ordering a new key.




1. Key identification number

EDA80000

#### Vehicle identification number

The vehicle identification number is stamped into the frame.



1. Vehicle identification number


NOTE:

The vehicle identification number is used to identify your machine.

EDA70100

#### Model label

The model label is affixed to the frame. Record the information on this label in the space provided. This information will be needed to order spare parts from your Yamaha dealer.



1. Model label

#### **CONTROL FUNCTIONS**

# **A** WARNING

Indicates a potential hazard that could result in serious injury or death.

EDB00100

#### Main switch


Functions of the respective switch positions are as follows:

#### ON:


Engine can be started only at this position and the headlight and taillight come on when the light switch is on.

#### OFF:

All electrical circuits are switched off. The key can be removed in this position.



#### Indicator lights



- 1. Reverse indicator light "REVERSE"
- 2. Neutral indicator light "NEUTRAL"
- 3. Oil temperature indicator light "OIL TEMP"

EDB10600

#### Reverse indicator light "REVERSE"

This indicator light comes on when the transmission is in reverse.

EDB10500

## Neutral indicator light "NEUTRAL"

This indicator light comes on when the transmission is in neutral.

EDB10800


# Oil temperature indicator light "OIL TEMP"

When the oil temperature reaches a specified level, this light comes on to warn that the engine has overheated. If the light comes on during operation, stop the engine as soon as it is safe to do so, and allow the engine to cool down for about 10 minutes.


## **CAUTION:**

- The light comes on mostly due to overload. Reduce the load to specification before restarting the engine.
- 2. Restart after making sure that the light is out. Continuous use while the light is on, may cause damage to the engine.

## Oil temperature indicator light checking method



#### Handlebar switches



- 1. Lights switch "LIGHTS"
- 2. Engine stop switch "ENG.STOP"
- 3. Start switch "START"

EDB55100

#### Engine stop switch "ENG.STOP"

Make sure that the engine stop switch is in the "RUN" position. The engine stop switch has been equipped to ensure safety in an emergency such as when the machine is upset or trouble takes place in the throttle system. The engine will not start or run when the engine stop switch is turned to "OFF". EDB55501

#### Start switch "START"

The starter motor cranks the engine when this switch is pushed.

#### **CAUTION:**

See starting instructions prior to starting engine. (see page 6-1 for details)

EDB55901

#### Lights switch "LIGHTS"

Turn the switch to "LO" for the low beam and taillight.

Turn the switch to "HI" for the high beam and taillight.


#### CAUTION:

Do not use the headlight with the engine turned off for more than thirty minutes. The battery may discharge to the point that the starter motor will not operate properly. If this should happen, remove the battery and recharge it. EDB60300

#### Throttle lever

Once the engine is running cleanly, movement of the throttle lever will increase the engine speed.

Regulate the speed of the machine by varying the throttle position. Because the throttle is spring-loaded, the machine will decelerate, and the engine will return to an idle any time the hand is removed from the throttle lever.



1. Throttle lever

Before starting the engine, check the throttle to be sure it is operating smoothly. Make sure it returns to the idle position as soon as the lever is released.

# **WARNING**

# POTENTIAL HAZARD

Malfunction of throttle.

## WHAT CAN HAPPEN


The throttle could be hard to operate, making it difficult to speed up or slow down when you need to. This could cause an accident.

#### **HOW TO AVOID THE HAZARD**

Check the operation of the throttle lever before you start the engine. If it does not work smoothly, check for the cause. Correct the problem before riding the ATV. Consult a Yamaha dealer if you can't find or solve the problem yourself.

#### Speed limiter

The speed limiter keeps the throttle from fully opening even when the throttle lever is pushed to the maximum. Screwing in the adjuster lowers the engine power available and decreases the maximum speed of the ATV.



1. Locknut

2. Adjuster

## WARNING

#### POTENTIAL HAZARD

Improper adjustment of the speed limiter and throttle.

#### WHAT CAN HAPPEN


The throttle cable could be damaged. Improper throttle operation could result. You could lose control, have an accident or be injured.

#### **HOW TO AVOID THE HAZARD**

Do not turn the speed adjuster out more than 12 mm (0.47 in). Always make sure the throttle lever free play is adjusted to  $3 \sim 5 \text{ mm}$  (0.12  $\sim 0.20 \text{ in}$ ). See page 8-19.

#### Front brake lever

The front brake lever is located on the right handlebar. Pull it toward the handlebar to apply the front brake.




1. Front brake lever


EDB90100

#### Rear brake pedal and lever

The brake pedal is located on the right side of the machine and the brake lever is located on the left handlebar. Push down on the pedal or pull the lever toward the handlebar to apply the rear brake.




1. Rear brake pedal



1. Rear brake lever

#### Parking brake

Use the parking brake when you have to start the engine or park the machine, especially on a slope. Apply the rear brake lever and push down the lock plate to apply the parking brake. Squeeze the rear brake lever to release the parking brake.



1. Lock plate

#### **WARNING**

#### **POTENTIAL HAZARD**

Improper use of the parking brake.

#### **WHAT CAN HAPPEN**


The ATV could start moving unexpectedly if the parking brake is not applied before starting the engine. This could cause loss of control or a collision. The brake could overheat if you ride the ATV without releasing the parking brake. You could lose braking performance which could cause an accident. You could also wear out the brakes prematurely.

#### **HOW TO AVOID THE HAZARD**

Always set the parking brake before starting the engine. Always be sure you have released the parking brake before you begin to ride.

# Shift pedal

This machine is equipped with a constantmesh 5-speed forward and 1-speed reverse transmission. The shift pedal is located on the left side of the engine. Reverse is at the bottom position. Neutral is one position above reverse.



1. Shiht pedal

N. Neutral


R. Reverse

EDB85200

#### Reverse knob

The reverse knob is used to shift into reverse gear.

Refer to section "Reverse driving" before operating this machine in reverse gear.




1. Reverse knob

EDC25000

#### Recoil starter

Firmly grasp the handle and pull slightly until engagement can be felt. Then pull forcefully, being careful not to pull the rope all the way out.



1. Recoil starter

## **A** WARNING

#### **POTENTIAL HAZARD**

Starting the engine in gear and/or starting the engine without setting the parking brake.

#### WHAT CAN HAPPEN

The ATV could start to move unexpectedly, which could cause an accident.


# **HOW TO AVOID THE HAZARD**

Put the transmission in neutral and set the parking brake before starting the engine.

EDC00000

# Fuel tank cap

Remove the fuel tank cap by turning it counterclockwise.



1. Fuel tank cap

#### **Fuel cock**


The fuel cock supplies fuel from the fuel tank to the carburetor.

The fuel cock has three positions.

OFF: With the lever in this position fuel will not flow. Always turn the lever to this position when the engine is not running.


ON: With the lever in this position, fuel flows to the carburetor. Normal riding is done with the lever in this position.

RES: This indicates reserve. If you run out of fuel while riding, turn the lever to this position. THEN FILL THE FUEL TANK AT THE FIRST OPPORTUNITY. After refuelling, return the fuel cock lever to the "ON" position.



#### Starter "CHOKE"

Starting a cold engine requires a richer airfuel mixture. A separate starter circuit supplies this mixture. Pull the starter "CHOKE" out to open the circuit for starting. When the engine has warmed up, push the starter "CHOKE" in to close the circuit. Refer to "Starting a cold engine" for proper operation.




- 1. Fully-open
- 3. Closed

- 2. Half open
- a. Starter "CHOKE"

#### EDC40001

#### Seat


To remove the seat, pull the seat lock lever upward and pull up the seat at the rear.



1. Seat lock lever

To install the seat, insert the lobe on the seat front into the receptacle on the frame and push down the seat at the rear.

NOTE:	_
Make sure that the seat is securely fitted.	




EDC55000

### Storage box

Maximum load limit: 2 kg (4.4 lbs)

## **CAUTION:**

To protect from damage, do not put metal products, like tools or sharply edged products directly in the storage box. If they must be stored, wrap them in appropriate cushion material.



EDD00000

#### Front carrier

Maximum load limit: 40 kg (88 lbs)

EDD00100

### Rear carrier

Maximum load limit: 80 kg (176 lbs)


### Front shock absorber adjustment

The spring preload can be adjusted to suit the rider's weight and riding conditions.

Spring preload adjustment

To increase the spring preload, turn the adjuster in direction ⓐ.

To decrease the spring preload, turn the adjuster in direction **(b)**.



a. Increase spring preload b. Decrease spring preload

Standard position: B

A - Minimum (Soft)

E – Maximum (Hard)

# **A** WARNING

### POTENTIAL HAZARD

Improper shock absorber adjustment.

### WHAT CAN HAPPEN

Uneven adjustment can cause poor handling and loss of stability, which could lead to an accident.

### **HOW TO AVOID THE HAZARD**

Always adjust the shock absorbers on the left and right side to the same setting.


### Rear shock absorber adjustment

The spring preload can be adjusted to suit the rider's weight and riding conditions.

Spring preload adjustment

To increase the spring preload, turn the adjuster in direction ⓐ.

To decrease the spring preload, turn the adjuster in direction **(b)**.



a. Increase spring preload b. Decrease spring preload

Standard position: B


A – Minimum (Soft)

E – Maximum (Hard)

#### **Auxiliary DC terminal**

The auxiliary DC terminal is located on the front carrier.

The auxiliary terminal can only be used when the main switch is on and the engine is running. Refer to the following chart for correct usage.



1. Auxiliary DC terminal

#### AMPERAGE CHART


	IDLING SPEED	RIDING SPEED (3,000 r/min. or more)
HEAD/TAIL LIGHT "ON"	Cannot be used.	12V, 5A
HEAD/TAIL LIGHT "OFF"	12V, 5A	12V, 10A

#### **CAUTION:**

- If accessories are used in excess of the above capacity, or if accessories are used with the engine not running, the battery will lose its charge and engine starting may become difficult.
- Do not use accessories requiring more than 12V, 10A. This may overload the circuit and cause a fuse to blow.

### Connecting accessory leads

- Strip off 5 mm of insulation from each accessory lead. Twist the stranded wires.
- 2. Pass the leads through the protective cover, then crimp a terminal onto each lead. Securely connect the leads.



a. 5 mm


1. Accessory plug

2. Cover

### CAUTION:

Take note of the marks embossed on the accessory plug. Make sure that the positive and negative lead are connected to the corresponding terminal. Make sure that neither terminal is shorted.

Put the protective cover over the accessory plug.




1. Accessory plug

2. Cover


### How to use the Auxiliary DC terminal

- 1. Start the engine (see page 6-1).
- 2. Remove the dust cap from the receptacle.



1. Dust cap

Insert the accessory plug into the receptacle and secure it with the screwon cap.



1. Receptacle

2. Accessory plug

4. When the accessory terminal is not being used, screw the dust cap onto the receptacle for protection.

EDE00001

# **A** WARNING

Indicates a potential hazard that could result in serious injury or death.

# **PRE-OPERATION CHECKS**

Before using this machine, check the following points:

ITEM	ROUTINE	PAGE	
Front brake	<ul> <li>Check operation, free play, fluid level and fluid leakage.</li> <li>Top-up with DOT 4 (or DOT 3) brake fluid if necessary.</li> </ul>	5-3 ~ 5-4, 8-20 ~ 8-27	
Rear brake	Check operation, lever/pedal free play and pedal height.	0-20 ~ 0-27	
Fuel tank	Check fuel level.     Top-up as required.	5-5 ~ 5-6	
Engine oil	Check oil level.     Top-up as required.	5-7, 8-5 ~ 8-8	
Final gear oil/ Differential gear oil  • Check for leakage.		5-7 ~ 5-8, 8-9 ~ 8-12	
Throttle • Check for proper throttle cable operation.		5-8, 8-19	
Wheels and tires	Check tire pressure, wear and damage.	5-9 ~ 5-12, 8-30 ~ 8-31	
Fittings and Fasteners	Check all fittings and fasteners.	5-8	
- Check for proper operation.		5-8, 8-37 ~ 8-38	
Battery	Check fluid level.     Top-up with distilled water if necessary.	5-8, 8-31 ~ 8-34	
Front axle boots	Front axle boots • Check for damage.		

# **WARNING**

### **POTENTIAL HAZARD**

Failure to inspect the ATV before operating.

Failure to properly maintain the ATV.

### WHAT CAN HAPPEN

Increases the possibility of an accident or equipment damage.

#### **HOW TO AVOID THE HAZARD**

Always inspect your ATV each time you use it to make sure the ATV is in safe operating condition.

Always follow the inspection and maintenance procedures and schedules described in the Owner's Manual.

#### Front and rear brakes

- Brake levers and brake pedal Check for correct free play in the brake levers and brake pedal. If the free play is incorrect, adjust it. See pages 8-23 ~ 8-27.
  - Check operation of the levers and pedal. They should move smoothly and there should be a firm feeling when the brake is applied. If not, have the machine inspected by a Yamaha dealer.
- Brake fluid level (Front brake)
   Check the brake fluid level. Add fluid if necessary. See pages 8-21 ~ 8-22.

R	ecor	nmer	nded	brake	fluid:	DO	Γ /
	COOL	1111161	IUGU	DIGNE	HUILLA.		

#### NOTE:

If DOT 4 is not available, DOT 3 can be used.

3. Brake fluid leakage

Check to see if any brake fluid is leaking out of the hose, joint or master cylinder of the front brake. Apply the brake firmly for one minute. If the lever moves slowly inward, there may be a leak in the brake system. If there is any leakage, the brake system should be inspected by a Yamaha dealer.

4. Brake operation

Test the brakes at slow speed after starting out to make sure they are working properly. If the brakes do not provide proper braking performance, inspect the brakes for wear (see page 8-20).

# **▲** WARNING

#### POTENTIAL HAZARD

Riding with improperly operating brakes.

#### WHAT CAN HAPPEN

You could lose braking ability, which could lead to an accident.

### **HOW TO AVOID THE HAZARD**

Always check the brakes at the start of every ride. Do not ride the ATV if you find any problem with the brakes. If a problem cannot be corrected by the adjustment procedures provided in this manual, have the ATV inspected by a Yamaha dealer.

FDF80000\*

#### Fuel

Make sure there is sufficient gasoline in the tank.

Recommended fuel: UNLEADED FUEL Fuel tank capacity:

Total:


10.0 L (2.2 Imp gal, 2.6 US gal) Reserve:

1.3 L (0.29 Imp gal, 0.34 US gal)

Your Yamaha engine has been designed to use regular unleaded gasoline with a pump octane number ((R+M)/2) of 86 or higher, or research octane number of 91 or higher. If knocking or pinging occurs, use a different brand of gasoline or premium unleaded fuel. Unleaded fuel will give you longer spark plug life and reduced maintenance cost. If unleaded gasoline is not available, then leaded regular gasoline can be used.

#### Gasohol

There are two types of gasohol; gasohol containing ethanol and that containing methanol. Gasohol containing ethanol can be used if ethanol content does not exceed 10%. Gasohol containing methanol is not recommended by Yamaha because it may cause fuel system damage or vehicle performance problems.



1. Fuel level

2. Filler tube

# **A** WARNING

### **POTENTIAL HAZARD**

Improper care when refueling.

### WHAT CAN HAPPEN

Fuel can spill, which can cause a fire and severe injury.

Fuel expands when it heats up. If the fuel tank is overfilled, fuel could spill out due to heat from the engine or the sun.

### **HOW TO AVOID THE HAZARD**


Do not overfill the fuel tank. Be careful not to spill fuel, especially on the engine or exhaust pipe. Wipe up any spilled fuel immediately. Be sure the fuel tank cap is closed securely.

Do not refuel right after the engine has been running and is still very hot.

FDF30203

### **Engine oil**

Make sure the engine oil is at the specified level. Add oil as necessary. (See page 8-5 ~ 8-8.)



Recommended engine oil classification: API Service "SE", "SF" type or equivalent (e.g. "SF-SE", "SF-SE-CC", "SF-SE-SD" etc.) Oil quantity:

Periodic oil change:

2.9 L (2.6 lmp qt, 3.1 US qt)

With oil filter replacement:

3.0 L (2.6 Imp qt, 3.2 US qt)

Total amount:

3.5 L (3.1 Imp gt, 3.7 US gt)

EDD40100

### Final gear oil

Make sure the final gear oil is at the specified level. Add oil as necessary (see page 8-9 ~ 8-10 for details).

Recommended oil:

SAE 80 API GL-4 Hypoid gear oil

If desired, an SAE 80W90 hypoid gear oil may be used for all conditions.

#### NOTE:

GL-4 is a quality and additive rating, GL-5 or GL-6 rated hypoid gear oils may also be used.

EDD40200

### Differential gear oil

Make sure the differential gear oil is at the specified level. Add oil as necessary (see page 8-11 ~ 8-12 for details).

Recommended oil:

SAE 80 or SAE 80W-90

API GL-5 Hypoid gear oil for L.S.D. (Limited Slip Differential)

EDE55000

#### Throttle lever

Check to see that the throttle lever operates correctly. It must open smoothly and spring back to idle position when released. Repair as necessary for proper operation.

EDE85001

#### **Fittings and Fasteners**

Always check the tightness of chassis fittings and fasteners before a ride. Take the machine to a Yamaha dealer or refer to the Service Manual for correct tightening torque.

EDE70000

### Lights

Check the headlight and taillight to make sure they are in working condition. Repair as necessary for proper operation.

EDE70100

#### **Switches**

Check the operation of the headlight switch, engine stop switch and any other switches. Repair as necessary for proper operation.

EDE70201

### **Battery**

Check fluid level and top-up if necessary. Use only distilled water if refilling is necessary. See pages 8-31 ~ 8-34.

### **A** WARNING

#### **POTENTIAL HAZARD**

Operating this ATV with improper tires, or with improper or uneven tire pressure.

### WHAT CAN HAPPEN

Use of improper tires on this ATV, or operation of this ATV with improper or uneven tire pressure, may cause loss of control, increasing your risk of accident.

### **HOW TO AVOID THE HAZARD**

The tires listed below have been approved by Yamaha Motor Co., Ltd. for this model. Other tire combinations are not recommended.

	Manufacturer	Size	Type
Front	DUNLOP	AT25 x 8-12	KT404
Rear	DUNLOP	AT25 x 10-12	KT405B

- 2. The tires should be set to the recommended pressure:
- Recommended tire pressure
   Front 25 kPa (0.25 kgf/cm², 3.6 psi)
   Rear 25 kPa (0.25 kgf/cm², 3.6 psi)
- Check and adjust tire pressures when the tires are cold.
- Tire pressures must be equal on both sides.
- 3. Tire pressure below the minimum specified could cause the tire to dislodge from the rim under severe riding conditions.

The following are minimums: Front 22 kPa (0.22 kgf/cm², 3.2 psi) Rear 22 kPa (0.22 kgf/cm², 3.2 psi) 4. Use no more than the following pressures when seating the tire beads. Front 250 kPa (2.5 kgf/cm², 36 psi) Rear 250 kPa (2.5 kgf/cm², 36 psi) Higher pressures may cause the tire to burst. Inflate the tires very slowly and carefully. Fast inflation could cause the tire to burst.

FDE90200


### How to measure tire pressure Use the low-pressure tire gauge.

_		_	
n		١,	E.
	J.	,,	_

The low-pressure tire gauge is included as standard equipment. Make two measurements of the tire pressure and use the second reading. Dust or dirt in the gauge could cause the first reading to be incorrect.

Set pressure with tires cold. Set tire pressures to the following specifications:


	Recommended pressure	Minimum	Maximum
Front	25 kPa	22 kPa	28 kPa
	(0.25 kgf/cm²,	(0.22 kgf/cm²,	(0.28 kgf/cm²,
	3.6 psi)	3.2 psi)	4.0 psi)
Rear	25 kPa	22 kPa	28 kPa
	(0.25 kgf/cm²,	(0.22 kgf/cm²,	(0.28 kgf/cm²,
	3.6 psi)	3.2 psi)	4.0 psi)



1. Low-pressure tire gauge

#### Tire wear limit

When the tire groove decreases to 3 mm (0.12 in) due to wear, replace the tire.



a. 3 mm (0.12 in)

### **OPERATION**

# **A** WARNING

Indicates a potential hazard that could result in serious injury or death.

### **WARNING**

#### **POTENTIAL HAZARD**

Operating ATV without being familiar with all controls.

### WHAT CAN HAPPEN

Loss of control, which could cause an accident or injury.

### **HOW TO AVOID THE HAZARD**

Read the Owner's Manual carefully. If there is a control or function you do not understand, ask your Yamaha dealer. EDF13001

### Starting a cold engine

### **WARNING**

### **POTENTIAL HAZARD**

Freezing control cables in cold weather.

### WHAT CAN HAPPEN

You could be unable to control the ATV, which could lead to an accident or collision.

### **HOW TO AVOID THE HAZARD**

When riding in cold weather, always make sure all control cables work smoothly before you begin riding.


- 1. Turn the fuel cock to "ON".
- 2. Turn the main switch to "ON" and the engine stop switch to "RUN".
- 3. Shift the transmission into neutral.

#### NOTE:

- When the transmission is in neutral, the neutral indicator light should come on. If the light does not come on, ask a Yamaha dealer to inspect it.
- The engine can be started in any gear if the rear brake lever is applied. However, it is recommended to shift into neutral before starting the engine.
- 4. Use the starter "CHOKE" in reference to the figure:

Position ①: Cold engine startambient temperature below 5°C (40°F).

Position ②: Cold engine startambient temperature at 0°C (30°F) ~ 30°C (90°F) and warming up position. Position ③: Cold engine startambient temperature above 25°C (80°F) and warm engine start position.



1. Fully-open

2. Half open

3. Closed

- a. Starter "CHOKE"
- 5. Completely close the throttle lever and start the engine by pushing the start switch.

#### NOTE:

- If the engine fails to start, release the start switch, then push the start switch again. Pause a few seconds before the next attempt. Each cranking should be as short as possible to preserve battery energy. Do not crank the engine more than 10 seconds on each attempt.
- If the battery is discharged, pull the recoil starter to start the engine.
- 6. If the engine is started at position ①, the starter "CHOKE" should be returned to position ② (half-open) to warm up the engine. If the engine is started at position ②, keep it at this position to warm up the engine.
- 7. Continue warming up the engine until it idles smoothly and return the starter "CHOKE" to position ③ (closed) before riding.

#### **CAUTION:**

See the "Engine break-in" section prior to operating engine for the first time.

EDF10502

### Starting a warm engine

To start a warm engine, refer to the "Starting a cold engine" section. The starter "CHOKE" should not be used. The throttle should be opened slightly.

EDF10701

## Warming up

To get maximum engine life, always warm up the engine before starting off. Never accelerate hard with a cold engine! To see whether or not the engine is warm, check if it responds to the throttle normally with the starter "CHOKE" turned off.

Reverse knob operation and reverse driving

### **CAUTION:**

Before shifting, stop the machine and return the throttle lever to its closed position. Otherwise the transmission may be damaged.

- Bring the machine to a complete stop and return the throttle lever to the closed position with the transmission in neutral.
- 2. While applying the rear brake lever, turn the reverse knob clockwise with your right hand.
- 3. Shift the transmission into reverse by pressing down on the shift pedal.

#### NOTE:

When in reverse, the reverse indicator light should be on. If the light does not come on, ask a Yamaha dealer to inspect the machine.

- 4. Check behind you for people or obstacles, then release the rear brake lever.
- Open the throttle lever gradually and continue to watch to the rear while backing.

### **WARNING**

### **POTENTIAL HAZARD**

Freezing control cables in cold weather.

### WHAT CAN HAPPEN


You could be unable to control the ATV, which could lead to an accident or collision.

#### **HOW TO AVOID THE HAZARD**

When riding in cold weather, always make sure all control cables work smoothly before you begin riding.

### **Shifting**

This model has a 5-speed forward and 1-speed reverse transmission with centrifugal automatic clutch. The transmission allows you to control the amount of power you have available at a given speed or for starting accelerating, climbing, etc. To shift into neutral, return the throttle lever to its original position and repeatedly depress the shift pedal until it stops.



### CAUTION:

Do not coast for long periods with the engine off, and do not tow the machine a long distance. Even with gears in neutral, the transmission is only properly lubricated when the engine is running. Inadequate lubrication may damage the transmission.

#### EDF20400

#### To start out and accelerate:

1. Release the throttle lever.

### CAUTION:

Always close the throttle while shifting gears. Otherwise, damage to the engine and drive train may result.

- 2. Shift into first gear and release the shift pedal.
- 3. Open the throttle gradually.

- 4. Once the machine has attained adequate speed, release the throttle lever.
- 5. Shift into second gear and release the shift pedal.
- 6. Open the throttle gradually.
- 7. Follow the same procedure when shifting to the next higher gear.

# **A** WARNING

#### **POTENTIAL HAZARD**

Opening the throttle before releasing the shift pedal.

#### WHAT CAN HAPPEN

The machine could wheelie. This would increase the chance of an accident, including overturn.

### **HOW TO AVOID THE HAZARD**

Release the shift pedal before opening the throttle. Open the throttle gradually. EDE20500

#### To decelerate:

When slowing down or stopping, release the throttle and apply the brakes smoothly and evenly. As you slow down, shift to a lower gear. Be sure that the engine has sufficiently slowed before engaging a lower gear. Improper use of the brakes or shifting can cause the tires to lose traction, reducing control and increasing the possibility of an accident.

# **WARNING**

### **POTENTIAL HAZARD**

Engaging a lower gear when the engine speed is too high.

### WHAT CAN HAPPEN

The wheels could stop rotating. This could cause loss of control, an accident and injury. It could also cause engine or drive train damage.

#### **HOW TO AVOID THE HAZARD**

Make sure the engine has sufficiently slowed before shifting to a lower gear.

FDF25100

#### Engine break-in

There is never a more important period in the life of your machine than the period between zero and 20 hours.

For this reason, we ask that you carefully read the following material. Because the engine is brand new, you must not put an excessive load on it for the first several hours of running. During the first 20 hours, the various parts in the engine wear and polish themselves to the correct operating clearances.

During this period, prolonged full throttle operation or any condition which might result in excessive engine heating must be avoided. However, momentary ( $2 \sim 3$  seconds maximum) full throttle operation under load does not harm the engine.

Each full throttle acceleration sequence should be followed with a substantial rest period for the engine by cruising at lower r/min so the engine can rid itself of the temporary build up of heat.

If any abnormality is noticed during this period, consult a Yamaha dealer.

### 1. $0 \sim 10$ hours:

Avoid continuous operation above half throttle. Allow a cooling off period of five to ten minutes after every hour of operation. Vary the speed of the machine from time to time. Do not operate it at one set throttle position.

#### 2. 10 ~ 20 hours:

Avoid prolonged operation above 3/4 throttle. Rev the machine freely through the gears but do not use full throttle at any time.


#### 3. After break-in:

Avoid prolonged full throttle operation. Vary speeds occasionally.

FDF40000

### **Parking**

When parking, stop the engine and shift into neutral. Turn the fuel cock to "OFF" and apply the parking brake.



1. Lock plate

#### Parking on a slope

### **A** WARNING

### **POTENTIAL HAZARD**

Parking on a hill or other incline.


#### WHAT CAN HAPPEN

The ATV could roll out of control, increasing the chance of an accident.

#### **HOW TO AVOID THE HAZARD**

Avoid parking on hills or other inclines. If you must park on an incline, put the machine in low gear, apply the parking brake, and block the front and rear wheels with rocks or other objects. Do not park the ATV at all on hills that are so steep you could not walk up them easily.

- 1. Bring the machine to a stop by applying the brakes in low gear.
- 2. Stop the engine.
- With the rear brake lever and pedal applied, apply the parking brake and slowly release the rear brake pedal.



### Accessories and loading

EDF50100

#### **Accessories**

Accessories can affect the handling and control of your ATV. Keep the following in mind when considering an accessory or operating an ATV which has accessories.

• Choose only accessories designed for your ATV. Your Yamaha dealer has a variety of genuine Yamaha accessories. Other accessories may also be available on the market. However, it is not possible for Yamaha to test all non-Yamaha accessories, nor have any control over the quality of suitability of them. Choose a genuine Yamaha accessory, or one that is equivalent in design and quality.

- Accessories should be rigidly and securely mounted. An accessory which can shift position or come off while you are riding could affect your ability to control the ATV.
- Do not mount an accessory where it could interfere with your ability to control the ATV. Examples include (but are not limited to) a heavy or bulky object attached to the handlebars which could make steering difficult, an accessory that limits your ability to move around on the seat, or one that limits your view.
- Use extra caution when riding an ATV with accessories. The ATV may handle differently than it does without accessories.

#### Loading

Cargo or a trailer can change the stability and handling of an ATV. You must use common sense and good judgement when carrying cargo or towing a trailer. Keep the following points in mind:

Never exceed the weight limits shown.
 An overloaded ATV can be unstable.

#### **MAXIMUM LOADING LIMIT**

- Vehicle loading limit (total weight of cargo, rider and accessories, and tongue weight): 210 kg (463 lbs)
- Front carrier: 40 kg (88 lbs)
- Rear carrier: 80 kg (176 lbs)
- Storage box: 2 kg (4.4 lbs)
- Trailer hitch:

Pulling load (total weight of trailer and cargo): 410 kg (904 lbs)

Tongue weight (vertical weight on trailer hitch point): 15 kg (33 lbs)

- Do not exceed the maximum tongue weight. You can measure tongue weight with a bathroom scale. Put the tongue of the loaded trailer on the scale with the tongue at hitch height. Adjust the load in the trailer, if necessary, to reduce the weight on hitch.
  - If you are carrying cargo and towing a trailer, include the tongue weight in the maximum vehicle load limit.
- Load cargo on the carrier as close to the center of the vehicle as possible. Put cargo at the front of the rear carrier. Center the load from side to side.
- Tie down cargo securely to the carriers.
   Make sure cargo in the trailer cannot move around. A shifting load can cause an accident.
- Make sure the load does not interfere with controls or your ability to see where you are going.

- Ride more slowly than you would without a load. The more weight you carry, the slower you should go. Although conditions vary, it is good practice not to exceed 2nd gear whenever you are carrying heavier loads or when towing a trailer.
- Allow more braking distance. A heavier vehicle takes longer to stop.
- Avoid making sharp turns unless at very slow speeds.
- Avoid hills and rough terrain. Choose terrain carefully. Added weight affects the stability and handling of the ATV.

### **⚠** WARNING

### **POTENTIAL HAZARD**

Overloading this ATV or carrying or towing cargo improperly.

# **WHAT CAN HAPPEN**

Could cause changes in vehicle handling which could lead to an accident.


### **HOW TO AVOID THE HAZARD**

Never exceed the stated load capacity for this ATV.

Cargo should be properly distributed and securely attached. Reduce speed when carrying cargo or pulling a trailer. Allow greater distance for braking. EDF55003



Indicates a potential hazard that could result in serious injury or death.



















Indicates a potential hazard that could result in serious injury or death.

#### **GETTING TO KNOW YOUR MOTO-4**

This MOTO-4 is mainly for utility use, but may also be used for recreation. This section, Riding your MOTO-4, provides general ATV riding instructions for recreational riding. The skills and techniques described in this section, however, are appropriate for all types of riding. Riding your MOTO-4 requires special skills acquired through practice over a period of time. Take the time to learn the basic techniques well before attempting more difficult maneuvers.

Riding your new MOTO-4 can be a very enjoyable activity, providing you with hours of pleasure. But it is essential to familiarize yourself with the operation of the MOTO-4

to achieve the skill necessary to enjoy riding safely. Before you begin to ride be sure you have read this Owner's Manual completely and understand the operation of the controls. Pay particular attention to the safety information on page 2-1 ~ 2-7. Please also read all caution and warning labels on your MOTO-4.

# RIDE WITH CARE AND GOOD JUDGEMENT

# Get training if you are inexperienced.

Beginners should get training from a certified instructor. Become familiar with this ATV at slow speeds first, even if you are an experienced operator. Do not attempt to operate at maximum performance until you are totally familiar with the machine's handling and performance characteristics.

# **A** WARNING

#### **POTENTIAL HAZARD**

Operating this ATV without proper instruction.

## WHAT CAN HAPPEN

The risk of an accident is greatly increased if the operator does not know how to operate the ATV properly in different situations and on different types of terrain.

## **HOW TO AVOID THE HAZARD**

Beginning and inexperienced operators should complete the certified training course offered by Yamaha. They should then regularly practice the skills learned in the course and the operating techniques described in this Owner's Manual. For more information about the training course, contact an authorized ATV dealer or call 1-800-447-4700.

Riding your machine requires skills acquired through practice over a period of time.

Take the time to learn the basic techniques well before attempting more difficult maneuvers.

Not recommended for children under 16 years of age.

# **A** WARNING

## **POTENTIAL HAZARD**

Failure to follow the age recommendations for this ATV.

## WHAT CAN HAPPEN

Use by children of ATVs that are not recommended for their age can lead to severe injury or death of the child.

#### **HOW TO AVOID THE HAZARD**

A child under 16 should never operate an ATV with engine size greater than 90cc.



This machine is designed to carry operator and cargo only - passengers prohibited.

## **WARNING**

#### **POTENTIAL HAZARD**


Carrying a passenger on this ATV.

## WHAT CAN HAPPEN

Greatly reduces your ability to balance and control this ATV. Could cause an accident, resulting in harm to you and/or your passenger.

## **HOW TO AVOID THE HAZARD**

Never carry a passenger. The long seat is to allow the operator to shift position as needed during operation. It is not for carrying passengers.



## **Apparel**


# **WARNING**

## **POTENTIAL HAZARD**

Operating this ATV without wearing an approved motorcycle helmet, eye protection and protective clothing.

## WHAT CAN HAPPEN

Operating without an approved motor-cycle helmet increases your chances of a severe head injury or death in the event of an accident.



Operating without eye protection can result in an accident and increases your chances of a severe injury in the event of an accident.

Operating without protective clothing increases your chances of severe injury in the event of an accident.

## **HOW TO AVOID THE HAZARD**

Always wear an approved motorcycle helmet that fits properly.

You should also wear:

eye protection

(goggles or face shield)

gloves


boots

long-sleeved shirt or jacket

long pants.

# Do not operate after consuming alcohol or drugs.

Operator's performance capability is reduced by the influence of alcohol or drugs.



## **WARNING**

#### **POTENTIAL HAZARD**

Operating this ATV after consuming alcohol or drugs.

## WHAT CAN HAPPEN

Could seriously affect your judgment. Could cause you to react more slowly. Could affect your balance and perception.

Could result in an accident.

## **HOW TO AVOID THE HAZARD**

Never consume alcohol or drugs before or while driving this ATV.

## **Pre-Operation checks**

Always perform the Pre-Operation checks listed on page 5-1 before riding for safety and proper care of the machine.

## **A** WARNING

## **POTENTIAL HAZARD**

Failure to inspect the ATV before operating.

Failure to properly maintain the ATV.

#### WHAT CAN HAPPEN

Increases the possibility of an accident or equipment damage.

# **HOW TO AVOID THE HAZARD**

Always inspect your ATV each time you use it to make sure the ATV is in safe operating condition. Always follow the inspection and maintenance procedures and schedules described in the Owner's Manual.

## **A** WARNING

#### **POTENTIAL HAZARD**

Operating this ATV with improper tires, or with improper or uneven tire pressure.

## WHAT CAN HAPPEN

Use of improper tires on this ATV, or operation of this ATV with improper or uneven tire pressure, may cause loss of control, increasing your risk of an accident.

## **HOW TO AVOID THE HAZARD**

Always use the size and type tires specified in the Owner's Manual for this vehicle on page 5-9 ~ 5-10.

Always maintain proper tire pressure as described in the Owner's Manual on page 5-11.

# **A** WARNING

Indicates a potential hazard that could result in serious injury or death.

Do not operate at speeds too fast for your skills or the conditions.

## **⚠** WARNING

#### **POTENTIAL HAZARD**

Operating this ATV at speeds too fast for your skills or the conditions.

#### WHAT CAN HAPPEN


Increases your chances of losing control of the ATV, which can result in an accident.

## **HOW TO AVOID THE HAZARD**

Always go at a speed that is proper for the terrain, visibility and operating conditions, and your experience.

## Speed limiter

For riders inexperienced with this model, this model is equipped with a speed limiter in the throttle lever housing. The speed limiter limits the power and top speed of the machine. Turning the screw in decreases top speed, and turning it out increases top speed.



1. Locknut

2. Adjuster

## Loading and accessories

Use extra caution when riding the machine with additional loads, such as accessories or cargo. The machine's handling may be adversely affected. Reduce your speed when adding additional loads.

## **MAXIMUM LOADING LIMIT**

- Vehicle loading limit (total weight of cargo, rider and accessories, and tongue weight): 210 kg (463 lbs)
- Front carrier: 40 kg (88 lbs)
- Rear carrier: 80 kg (176 lbs)
- Storage box: 2 kg (4.4 lbs)
- Trailer hitch:

Pulling load (total weight of trailer and

cargo): 410 kg (904 lbs)

Tongue weight (vertical weight on trailer hitch point): 15 kg (33 lbs)

## **A** WARNING

## POTENTIAL HAZARD

Overloading this ATV or carrying or towing cargo improperly.

## **WHAT CAN HAPPEN**

Could cause changes in vehicle handling which could lead to an accident.

## **HOW TO AVOID THE HAZARD**

Never exceed the stated load capacity for this ATV.


Cargo should be properly distributed and securely attached. Reduce speed when carrying cargo or pulling a trailer.

Allow greater distance for braking.

Always follow the instructions in your Owner's Manual for carrying cargo or pulling a trailer.

## **During operation**

Always keep your feet on the footboards during operation. Otherwise your feet may contact the rear wheels.



# **A** WARNING

## **POTENTIAL HAZARD**

Removing hands from handlebars or feet from footboards during operation.

#### WHAT CAN HAPPEN

Removing even one hand or foot can reduce your ability to control the ATV or could cause you to lose your balance and fall off of the ATV. If you remove a foot from a footboard, your foot or leg may come into contact with the rear wheels, which could injure you or cause an accident.

## **HOW TO AVOID THE HAZARD**

Always keep both hands on the handlebars and both feet on the footboards of your ATV during operation. Avoid wheelies and jumping. You may lose control of the machine or overturn.

# **A** WARNING

## **POTENTIAL HAZARD**


Attempting wheelies, jumps, and other stunts.

## WHAT CAN HAPPEN

Increases the chance of an accident, including an overturn.

## **HOW TO AVOID THE HAZARD**

Never attempt stunts, such as wheelies or jumps. Don't try to show off.



#### Modifications

## **A** WARNING

# **POTENTIAL HAZARD**

Operating this ATV with improper modifications.

## WHAT CAN HAPPEN

Improper installation of accessories or modification of this vehicle may cause changes in handling which in some situations could lead to an accident.

# **HOW TO AVOID THE HAZARD**

Never modify this ATV through improper installation or use of accessories. All parts and accessories added to this vehicle should be genuine Yamaha or equivalent components designed for use on this ATV and should be installed and used according to instructions. If you have questions, consult an authorized ATV dealer.

## **Exhaust system**

The exhaust system on the machine is very hot during and following operation. To prevent burns, avoid touching the exhaust system. Park the machine in a place where pedestrians or children are not likely to touch it.

## **WARNING**

## **POTENTIAL HAZARD**


Hot exhaust system.

## **WHAT CAN HAPPEN**

Someone touching the exhaust system during or after operation could be burned.

#### **HOW TO AVOID THE HAZARD**

Do not touch the hot exhaust system. Do not park the machine in a place where others might be likely to touch it.



#### **BE CAREFUL WHERE YOU RIDE:**

This machine is designed for off-road use only. Riding on paved surfaces can cause loss of control.

# **A** WARNING

#### **POTENTIAL HAZARD**


Operating this ATV on paved surfaces.

## WHAT CAN HAPPEN

ATV's are designed for off-road use only. Paved surfaces may seriously affect handling and control of the ATV, and may cause the vehicle to go out of control.

## **HOW TO AVOID THE HAZARD**

Always avoid paved surfaces, including sidewalks, driveways, parking lots and streets.



Do not ride on any public road, street, or highway.

Riding on public roads can result in collisions with other vehicles.

## **A** WARNING

## **POTENTIAL HAZARD**


Operating this ATV on public streets, roads or highways.

## WHAT CAN HAPPEN

You can collide with another vehicle.

#### **HOW TO AVOID THE HAZARD**

Never operate this ATV on any public street, road or highway, even a dirt or gravel one. In many states it is illegal to operate ATVs on public streets, roads and highways.



Know the terrain where you ride. Ride cautiously in unfamiliar areas. Stay alert for holes, rocks, or roots in the terrain, and other hidden hazards which may cause the machine to upset.

# **WARNING**

## **POTENTIAL HAZARD**


Failure to use extra care when operating this ATV on unfamiliar terrain.

## WHAT CAN HAPPEN

You can come upon hidden rocks, bumps, or holes, without enough time to react. Could result in the ATV overturning or going out of control.

# **HOW TO AVOID THE HAZARD**

Go slowly and be extra careful when operating on unfamiliar terrain. Always be alert to changing terrain conditions when operating the ATV.



## **A** WARNING

#### **POTENTIAL HAZARD**


Failure to use extra care when operating on excessively rough, slippery or loose terrain.

## WHAT CAN HAPPEN


Could cause loss of traction or vehicle control, which could result in an accident, including an overturn.

#### **HOW TO AVOID THE HAZARD**

Do not operate on excessively rough, slippery or loose terrain until you have learned and practiced the skills necessary to control the ATV on such terrain. Always be especially cautious on these kinds of terrain.



When riding in an area where you might not easily be seen, such as desert terrain, mount a caution flag on the machine. DO NOT use the flag pole bracket as a trailer hitch.



# **WARNING**

## **POTENTIAL HAZARD**

Operating in areas where you might not be seen by other off-road vehicles.


#### WHAT CAN HAPPEN

You could be in a collision. You could be injured.

## **HOW TO AVOID THE HAZARD**

Always mount a caution flag on the machine to make you more visible. Watch carefully for other vehicles.

Do not ride in areas posted "no trespassing". Do not ride on private property without getting permission.



Select a large, flat area off-road to become familiar with your MOTO-4. Make sure that this area is free of obstacles and other riders. You should practice control of the throttle, brakes, shifting procedures, and turning techniques in this area before trying more difficult terrain. Always avoid riding on paved surfaces: the MOTO-4 is designed for off-road use only, and handling maneuvers are more difficult to perform on pavement.

Set the parking brake and follow the instruction on page 6-1 to start the engine. Once it has warmed up you are ready to begin riding your MOTO-4. As you get on the MOTO-4, be sure not to accidentally move the shift pedal. Remember that the engine and exhaust pipe will be hot when riding and afterwards; do not allow skin or clothing to come in contact with these components.

With the engine idling, lift the shift pedal to the 1st gear position and then release the parking brake. Apply the throttle slowly and smoothly. The centrifugal clutch will engage and you will start to accelerate. Once the MOTO-4 has attained adequate speed, release the throttle and lift the shift pedal to the 2nd gear position. Release the shift pedal and apply the throttle smoothly. Use this same procedure as you move into the higher gears. Be sure to coordinate the use of the throttle and shift pedal properly. If the throttle is applied too abruptly or if the throttle is not released during shifting, or if the shift pedal is not released before applying the throttle, the front wheels may lift off the ground resulting in a loss of directional control. Avoid higher speeds until you are thoroughly familiar with the operation of your MOTO-4.

#### CAUTION:

Do not shift gears without releasing the throttle. Damage to the engine or drive train may occur.

When slowing down or stopping, release the throttle and apply the brakes smoothly and evenly. As you slow down, shift to a lower gear. Be sure that the engine has sufficiently slowed before engaging a lower gear. Improper use of the brakes or shifting can cause the tires to lose traction, reducing control and increasing the possibility of an accident.

# **WARNING**

## **POTENTIAL HAZARD**

Engaging a lower gear when the engine speed is too high.

## WHAT CAN HAPPEN

The wheels could stop rotating. This could cause loss of control, an accident and injury. It could also cause engine or drive train damage.

## **HOW TO AVOID THE HAZARD**

Make sure the engine has sufficiently slowed before shifting to a lower gear.

#### **TURNING YOUR MOTO-4**

To achieve maximum traction while riding off-road, the two rear wheels are mounted solidly on one axle and turn together at the same speed. Therefore, unless the wheel on the inside of the turn is allowed to slip or lose some traction, the MOTO-4 will resist turning. A special turning technique must be used to allow the MOTO-4 to make turns quickly and easily. It is essential that this skill be learned first at low speed.

# **WARNING**

## **POTENTIAL HAZARD**

Turning improperly.

## WHAT CAN HAPPEN


ATV could go out of control, causing a collision or overturn.

## **HOW TO AVOID THE HAZARD**

Always follow proper procedures for turning as described in this Owner's Manual.

Practice turning at low speeds before attempting to turn at faster speeds. Do not turn at speeds too fast for your skills or the conditions.

As you approach a curve, slow down and begin to turn the handlebars in the desired direction. As you do so, put your weight on the footboard to the outside of the turn (opposite your desired direction) and lean your upper body into the turn. Use the throttle to maintain an even speed through the turn. This maneuver will let the wheel on the inside of the turn slip slightly, allowing the MOTO-4 to make the turn properly.



This procedure should be practiced at slow speed many times in a large off-road area with no obstacles. If an incorrect technique is used, your MOTO-4 may continue to go straight. If the MOTO-4 doesn't turn, come to a stop and then practice the procedure again. If the riding surface is slippery or loose, it may help to position more of your weight over the front wheels by moving forward on the seat.

Once you have learned this technique you should be able to perform it at higher speeds or in tighter curves.

Improper riding procedures such as abrupt throttle changes, excessive braking, incorrect body movements, or too much speed for the sharpness of the turn may cause the MOTO-4 to tip. If the MOTO-4 begins to tip over to the outside while negotiating a turn, lean more to the inside. It may also be necessary to gradually let off on the throttle and steer to the outside of the turn to avoid tipping over.

Remember: Avoid higher speeds until you are thoroughly familiar with the operation of your MOTO-4.

#### **CLIMBING UPHILL**

Use proper riding techniques to avoid vehicle overturns on hills. Be sure that you can maneuver your MOTO-4 well on flat ground before attempting any incline and then practice riding first on gentle slopes. Try more difficult climbs only after you have developed your skill. In all cases avoid inclines with slippery or loose surfaces, or obstacles that might cause you to lose control.

## **A** WARNING

## **POTENTIAL HAZARD**

Operating on excessively steep hills.

## WHAT CAN HAPPEN

The vehicle can overturn more easily on extremely steep hills than on level surfaces or small hills.

## **HOW TO AVOID THE HAZARD**

Never operate the ATV on hills too steep for the ATV or for your abilities. Practice on smaller hills before attempting large hills.

It is important when climbing a hill to make sure that your weight is transferred forward on the MOTO-4. This can be accomplished by leaning forward and, on steeper inclines, standing on the footboards and leaning forward over the handlebars.

## **WARNING**

#### **POTENTIAL HAZARD**

Climbing hills improperly.

#### WHAT CAN HAPPEN

Could cause loss of control or cause ATV to overturn.

#### **HOW TO AVOID THE HAZARD**

Always follow proper procedures for climbing hills as described in this Owner's Manual.

Always check the terrain carefully before you start up any hill.

Never climb hills with excessively slippery or loose surfaces.


Shift your weight forward.

Never open the throttle suddenly or make sudden gear changes.

The ATV could flip over backwards.

Never go over the top of any hill at high speed.

An obstacle, a sharp drop, or another vehicle or person could be on the other side of the hill.



If you are climbing a hill and you find that you have not properly judged your ability to make it to the top, you should turn the MOTO-4 around while you still have forward motion (provided you have the room to do so) and go down the hill.

## **A** WARNING

#### **POTENTIAL HAZARD**

Improperly crossing hills or turning on hills.

## WHAT CAN HAPPEN

Could cause loss of control or cause ATV to overturn.

## **HOW TO AVOID THE HAZARD**


Never attempt to turn the ATV around on any hill until you have mastered the turning technique as described in the Owner's Manual on level ground. Be very careful when turning on any hill. Avoid crossing the side of a steep hill if possible.

# When crossing the side of a hill:

Always follow proper procedures as described in the Owner's Manual.

Avoid hills with excessively slippery or loose surfaces.

Shift your weight to the uphill side of the ATV.



If your MOTO-4 has stalled or stopped and you believe you can continue up the hill, restart carefully to make sure you do not lift the front wheels which could cause you to lose control. If you are unable to continue up the hill, dismount the MOTO-4 on the uphill side. Physically turn the MOTO-4 around and then descend the hill.

If you start to roll backwards, DO NOT use the rear brake to stop or try to put the MOTO-4 in gear. The MOTO-4 could easily tip over backwards. Instead, dismount the MOTO-4 immediately on the uphill side.

## **WARNING**

#### **POTENTIAL HAZARD**

Stalling, rolling backwards or improperly dismounting while climbing a hill.

## WHAT CAN HAPPEN

Could result in ATV overturning.

# **HOW TO AVOID THE HAZARD**

Use proper gear and maintain steady speed when climbing a hill.

## If you lose all forward speed:

Keep weight uphill.

Apply the brakes.

Lock parking brake, after you are stopped.

## If you begin rolling backwards:


Keep weight uphill.

Never apply the rear brake while rolling backwards.

Apply the front brake.

When fully stopped, apply rear brake as well, and then lock parking brake.

Dismount on uphill side or to a side if pointed straight uphill. Turn the ATV around and remount, following the procedure described in the Owner's Manual.



#### RIDING DOWNHILL

When riding your MOTO-4 downhill, shift your weight as far to the rear and uphill side of the MOTO-4 as possible. Move back on the seat and sit with your arms straight. Choose a low gear which will allow the engine compression to do most of the braking for you. Improper braking may cause a loss of traction.

Use caution while descending a hill with loose or slippery surfaces. Braking ability and traction may be adversely affected by these surfaces. Improper braking may also cause a loss of traction.

Whenever possible, ride your MOTO-4 straight downhill. Avoid sharp angles which could allow the MOTO-4 to tip or roll over. Carefully choose your path and ride no faster than you will be able to react to obstacles which may appear.

## **A** WARNING

## **POTENTIAL HAZARD**

Going down a hill improperly.

## WHAT CAN HAPPEN

Could cause loss of control or cause ATV to overturn.

## **HOW TO AVOID THE HAZARD**


Always follow proper procedures for going down hills as described in this Owner's Manual. Note: a special technique is required when braking as you go down a hill.

Always check the terrain carefully before you start down any hill.

Shift your weight backward.

Never go down a hill at high speed.

Avoid going down a hill at an angle that would cause the vehicle to lean sharply to one side. Go straight down the hill where possible.



#### **CROSSING A SLOPE**

Traversing a sloping surface on your MOTO-4 requires you to properly position your weight to maintain proper balance. Be sure that you have learned the basic riding skills on flat ground before attempting to cross a sloping surface. Avoid slopes with slippery surfaces or rough terrain that may upset your balance.

As you travel across a slope, lean your body in the uphill direction. It may be necessary to correct the steering when riding on loose surfaces by pointing the front wheels slightly uphill. When riding on slopes be sure not to make sharp turns either up or down hill.

If your MOTO-4 does begin to tip over, gradually steer in the downhill direction if there are no obstacles in your path. As you regain proper balance, gradually steer again in the direction you wish to travel.

## **WARNING**

# **POTENTIAL HAZARD**

Improperly crossing hills or turning on hills.

#### WHAT CAN HAPPEN

Could cause loss of control or cause ATV to overturn.

## **HOW TO AVOID THE HAZARD**


Never attempt to turn the ATV around on any hill until you have mastered the turning technique as described in the Owner's Manual on level ground. Be very careful when turning on any hill. Avoid crossing the side of a steep hill if possible.

# When crossing the side of a hill:

Always follow proper procedures as described in the Owner's Manual.

Avoid hills with excessively slippery or loose surfaces.

Shift your weight to the uphill side of the ATV.



#### **CROSSING THROUGH SHALLOW WATER**

The MOTO-4 can be used to cross slow moving, shallow water of up to a maximum of 35 cm (14 inches) in depth. Before entering the water, choose your path carefully. Enter where there is no sharp drop off, and avoid rocks or other obstacles which may be slippery or upset the MOTO-4. Drive slowly and carefully.

## **A** WARNING

#### **POTENTIAL HAZARD**

Operating this ATV through deep or fast flowing water.


#### WHAT CAN HAPPEN

Tires may float, causing loss of traction and loss of control, which could lead to an accident.


#### **HOW TO AVOID THE HAZARD**

Never operate this ATV in fast flowing water or in water deeper than that specified in your Owner's Manual.

Remember that wet brakes may have reduced stopping ability. Test your brakes after leaving water. If necessary, apply them several times to let friction dry out the linings.




Test your brakes after leaving the water. Do not continue to ride your MOTO-4 without verifying that you have regained proper braking ability.



## CAUTION:

After riding your MOTO-4 in water, be sure to drain the trapped water by removing the check hose at the bottom of the air filter case. Wash the MOTO-4 in fresh water if it has been operated in salt water or muddy conditions.



1. Check hose

#### **RIDING OVER ROUGH TERRAIN**

Riding over rough terrain should be done with caution. Look out for obstacles which could cause damage to the MOTO-4 or could lead to an upset or accident. Be sure to keep your feet firmly mounted on the footboards at all times. Avoid jumping the MOTO-4 as loss of control and damage to the MOTO-4 may result.

## **A** WARNING

## **POTENTIAL HAZARD**

Improperly operating over obstacles.

## WHAT CAN HAPPEN

Could cause loss of control or a collision. Could cause the ATV to overturn.

## **HOW TO AVOID THE HAZARD**


Before operating in a new area, check for obstacles.

Never attempt to ride over large obstacles, such as large rocks or fallen trees. When you go over obstacles, always follow proper procedures as described in the Owner's Manual.


#### **SLIDING AND SKIDDING**

Care should be used when riding on loose or slippery surfaces since the MOTO-4 may slide. If unexpected and uncorrected, sliding could lead to an accident.

To reduce the tendency for the front wheels to slide in loose or slippery conditions, positioning your weight over the front wheels will sometimes help.



If the rear wheels of your MOTO-4 start to slide sideways, control can usually be regained (if there is room to do so) by steering in the direction of the slide. Applying the brakes or accelerating is not recommended until you have corrected the slide.



With practice, over a period of time, skill at controlled sliding can be developed. The terrain should be chosen carefully before attempting such maneuvers, since both stability and control are reduced. Bear in mind that sliding maneuvers should always be avoided on extremely slippery surfaces such as ice, since all control may be lost.

## **WARNING**

## **POTENTIAL HAZARD**

Skidding or sliding improperly.

## WHAT CAN HAPPEN

You may lose control of this ATV. You may also regain traction unexpectedly, which may cause the ATV to overturn.

# **HOW TO AVOID THE HAZARD**

Learn to safely control skidding or sliding by practicing at low speeds and on level, smooth terrain.

On extremely slippery surfaces, such as ice, go slowly and be very cautious in order to reduce the chance of skidding or sliding out of control.

### WHAT TO DO IF ...

This section is designed to be a reference guide only. Be sure to read each section on riding techniques completely.

### WHAT TO DO ...

- If your MOTO-4 doesn't turn when you want it to:
  - Bring the MOTO-4 to a stop and practice the turning maneuvers again. Be sure you are putting your weight on the footboard to the outside of the turn. Position your weight over the front wheels for better control. (See pages 7-23 ~ 7-24)
- If your MOTO-4 begins to tip while turning:
  - Lean more into the turn to regain balance. If necessary, gradually let off the throttle and/or steer to the outside of the turn. (See pages 7-23 ~ 7-24)

- If your MOTO-4 starts to slide sideways: Steer in the direction of the slide if you have the room. Applying the brakes or accelerating is not recommended until you have corrected the slide. (See pages 7-38 ~ 7-39)
- If your MOTO-4 can't make it up a hill you are trying to climb:

Turn the MOTO-4 around if you still have forward speed. If not, stop, dismount on the uphill side of the MOTO-4 and physically turn the MOTO-4 around. If the MOTO-4 starts to slip backwards DO NOT USE THE REAR BRAKE - the MOTO-4 may tip over on top of you. Dismount the MOTO-4 on the uphill side. (See pages 7-25 ~ 7-29)

 If your MOTO-4 is traversing a sloping surface:

Be sure to ride with your weight positioned towards the uphill side of the MOTO-4 to maintain proper balance. If the MOTO-4 starts to tip, steer down the hill (if there are no obstacles in your way) to regain balance. If you discover that the MOTO-4 is going to tip over, dismount on the uphill side. (See pages 7-32 ~ 7-33)

If your MOTO-4 encounters shallow water:

Ride slowly and carefully through slow moving water, watching for obstacles. Be sure to let water drain from the MOTO-4 and CHECK YOUR BRAKES FOR PROPER OPERATION when you come out of the water. Do not continue to ride your MOTO-4 until you have regained adequate braking ability. (See pages 7-34 ~ 7-35)

# **A** WARNING

Indicates a potential hazard that could result in serious injury or death.

FDH00200

# PERIODIC MAINTENANCE AND ADJUSTMENT

Periodic inspection, adjustment, and lubrication will keep your machine in the safest and most efficient condition possible. Safety is an obligation of the machine owner. The most important points of machine inspection, adjustment, and lubrication are explained on the following pages.

# **A** WARNING

### POTENTIAL HAZARD

Servicing an engine while it is running.

# **WHAT CAN HAPPEN**

Moving parts can catch clothing or parts of the body, causing injury.

Electrical components can cause shocks or can start fires.

# **HOW TO AVOID THE HAZARD**


Turn off the engine when performing maintenance unless otherwise specified.

Have a Yamaha dealer perform service if you are not familiar with machine service.

FDH10700

### Owner's manual and tool kit

You are recommended to put this owner's manual and low-pressure tire gauge in the vinyl bag and always carry them in the storage box. Put the owner's tool kit in the space under the seat.



1. Tool kit

Owner's manual

2. Low-pressure tire gauge

The service information included in this manual is intended to provide you, the owner, with the necessary information for completing your own preventive maintenance and minor repairs. The tools provided in the Owner's tool kit are sufficient for this purpose, except that a torque wrench is also necessary to properly tighten nuts and bolts.

### NOTE:\_

If you do not have a torque wrench available during a service operation requiring one, take your machine to a Yamaha dealer to check the torque settings and adjust them as necessary.

# **⚠** WARNING

# **POTENTIAL HAZARD**

Operating this ATV with improper modifications.

# WHAT CAN HAPPEN

Improper installation of accessories or modification of this vehicle may cause changes in handling which in some situations could lead to an accident.

# **HOW TO AVOID THE HAZARD**

Never modify this ATV through improper installation or use of accessories. All parts and accessories added to this vehicle should be genuine Yamaha or equivalent components designed for use on this ATV and should be installed and used according to instructions. If you have questions, consult an authorized Yamaha ATV dealer.

# PERIODIC MAINTENANCE/LUBRICATION

			INITIAL	EVERY		
ITEM	ROUTINE	1 month	3 months	6 months	6 months	1 year
Valves*	Check valve clearance.     Adjust if necessary.	0		0	0	0
Spark plug	Check condition.     Adjust gap and clean.     Replace if necessary.	0	0	0	0	0
Air filter	Clean.     Replace if necessary.	(M	Every 20~40 hours (More often in wet or dusty areas.)			
Carburetor*	Check and adjust idle speed/starter operation.     Adjust if necessary.		0	0	0	0
Cylinderhead cover breather system*	Check breather hose for cracks or damage.     Replace if necessary.			0	0	0
Exhaust system*	Check leakage.     Retighten if necessary.     Replace gasket if necessary.			0	0	0
Fuel line*	Check fuel hose for cracks or damage.     Replace if necessary.			0	0	0
Engine oil	Replace (Warm engine before draining).	0		0	0	0
Engine oil filter	Replace.	0		0		0
Engine oil strainer	• Clean.	0		0		_ 0
Final gear oil Differential gear oil	Check oil level/oil leakage.     Replace every 12 months.	0				0
Front brake*	Check operation/fluid leakage/see NOTE page 8-4.     Correct if necessary.	0	0	0	0	0
Rear brake*	Check operation.     Adjust if necessary.	0	0	0	0	0
Clutch*	Check operation.     Adjust if necessary.	0		0	0	0

			EVERY			
ITEM	ROUTINE	1 month	1 -		6 months	1 year
Reverse release cable*	Check operation.     Adjust if necessary.			0	0	0
Wheels*	Check balance/damage/run out.     Repair if necessary.	0		0	0	0
Wheel bearings*	Check bearing assembly for looseness/damage.     Replace if damaged.	0		0	0	0
Steering system*	Check operation. Replace if damaged. Check toe-in. Adjust if necessary.	0	0	0	0	0
Front axle boots*	Check operation.     Replace if damaged.	0				0
Fittings and Fasteners*	Check all chassis fittings and fasteners.     Correct if necessary.	0	0	0	0	0
Battery*	<ul> <li>Check specific gravity.</li> <li>Check that the breather pipe is working properly.</li> <li>Correct if necessary.</li> </ul>	0	0	0	0	0

<sup>\*</sup> It is recommended that these items be serviced by a Yamaha dealer.

ľ	V١	U	ı	ᆮ	:	 

Brake fluid replacement:


- When disassembling the master cylinder or caliper cylinder, replace the brake fluid. Normally check the brake fluid level and add fluid as required.
- 2. On the inner parts of the master cylinder and caliper cylinder, replace the oil seals every two years.
- 3. Replace the brake hoses every four years, or if cracked or damaged.



Indicates a potential hazard that could result in serious injury or death.

# **Engine oil**

- 1. Engine oil level measurement
- a. Place the machine on a level place.
- b. Warm up the engine for several minutes and stop it.
- c. Remove the dipstick and wipe it off with a clean rag. Insert the dipstick in the filler hole without screwing it in.



1. Dipstick


### NOTE:

Wait a few minutes until the oil level settles before checking.

- d. Remove the dipstick and inspect the oil level.
- e. The oil level should be between the maximum and minimum marks. If the level is low, add oil to raise it to the proper level.

# **CAUTION:**

Be sure no foreign material enters the crankcase.




- 1. Maximum level mark
- 2. Minimum level mark

- 2. Engine oil replacement and oil filter element cleaning
- a. Place the machine on a level place.
- b. Warm up the engine for several minutes and stop it.
- c. Place a container under the engine.
- d. Remove the dipstick and drain plug to drain the oil.


# **CAUTION:**

When removing the drain plug, the compression spring, oil strainer and O-ring will fall out. Take care not to lose these parts.



Drain plug

- 2. O-ring
- 3. Compression spring
- 4. Oil strainer
- e. Remove the oil filter cover and oil filter.




1. Filter cover

2. Filter cover bolt (x 3)

- f. Clean the oil strainer and oil filter with solvent.
- g. Inspect the O-ring and replace if damaged.
- h. Reinstall the oil filter, O-ring, oil filter cover, oil strainer and drain plug. Tighten the drain plug to specification.

# **CAUTION:**

Before reinstalling the drain plug, be sure to install the O-ring, compression spring and oil strainer.



1. O-ring

Tightening torque:

Drain plug (engine):

32 Nm (3.2 m·kg, 23 ft·lb)

Filter cover bolt:

8 Nm (0.8 m·kg, 6.0 ft·lb)

 Fill the engine with oil and install the dipstick.

Recommended oil: See page 5-7.

Oil quantity:

Periodic oil change:

2.9 L (2.6 Imp qt, 3.1 US qt)

With oil filter replacement:

3.0 L (2.6 Imp qt, 3.2 US qt)

Total amount:

3.5 L (3.1 Imp qt, 3.7 US qt)

### CAUTION:


Be sure no foreign material enters the crankcase.

j. Warm up the engine for several minutes at idle speed. Check for oil leakage while warming up.

C					

If oil leakage is found, stop the engine immediately and check for the cause.

- 3. Oil pressure check
- a. Put a cloth around the cylinder.
- b. Slightly loosen the oil gallery bolt in the cylinder head.
- c. Start the engine and keep it idling until oil begins to seep from the oil gallery. If no oil comes out after one minute, turn the engine off so it will not seize and find the cause.
- d. Restart the engine and check the oil pressure.
- e. After checking, tighten the oil gallery bolt to the specified torque.



1. Oil gallery bolt

2. Cloth

Tightening torque:
Oil gallery bolt:
7 Nm (0.7 m·kg, 5.1 ft·lb)

### CAUTION:

Be sure to inspect the oil pressure after replacing the engine oil.

### Final gear oil

- 1. Final gear oil measurement
- a. Place the machine on a level place.
- b. Remove the oil filler bolt and check the oil level. It should be up to the brim of the hole. If the level is low, add oil to raise it to the proper level.

# **CAUTION:**


Be sure no foreign material enters the final gear case.

c. Install the oil filler bolt and tighten to the specified torque.


Tightening torque:

Oil filler bolt:


23 Nm (2.3 m·kg, 17 ft·lb)



- 1. Final gear oil
  - 2. Correct oil level 3. Oil
- 3. Oil filler bolt
- 2. Final gear oil replacement
- a. Remove the final gear case cover.



- b. Place the machine on a level place.
- c. Place a container under the final gear case.
- d. Remove the oil filler bolt and the drain plug to drain the oil.



- 1. Drain plug
  - e. Install the drain plug and tighten to the specified torque.

Tightening torque:

Drain plug (final gear case):

23 Nm (2.3 m·kg, 17 ft·lb)

f. Fill the final gear case with oil.

Recommended oil:

SAE 80 API "GL-4" Hypoid gear oil Oil quantity:

Periodic oil change:

0.19 L (0.17 Imp qt, 0.20 US qt)

Total amount:

0.25 L (0.22 Imp qt, 0.26 US qt)

### CAUTION:

Be sure no foreign material enters the final gear case.

g. Install the filler bolt and tighten to the specified torque.

Tightening torque:


Filler bolt (final gear case):


23 Nm (2.3 m·kg, 17 ft·lb)

- h. Check for oil leakage. If oil leakage is found, check for the cause.
- i. Reinstall the final gear case cover.


## Differential gear oil replacement

- 1. Place the machine on a level place.
- 2. Remove the differential gear case cover.






- 3. Place a container under the differential gear case.
- 4. Remove the filler bolt and drain plug to drain the oil.



1. Filler bolt



- 1. Drain plug
- 5. Install the drain plug and tighten to specification.

Tightening torque:

Drain plug (differential gear case): 12 Nm (1.2 m·kg, 8.7 ft·lb)

6. Fill the differential gear case with oil.

Recommended oil:

SAE 80 or SAE 80W-90

API "GL-5" Hypoid gear oil for L.S.D. (Limited Slip Differential)

Oil quantity:

Periodic oil change:

0.18 L (0.16 lmp qt, 0.19 US qt)

Total amount:

0.2 L (0.18 lmp qt, 0.21 US qt)

### CAUTION:

Be sure no foreign material enters the final gear case.

7. Install the filler bolt and tighten to specification.

Tightening torque:


Filler bolt (differential gear case): 12 Nm (1.2 m·kg, 8.7 ft·lb)

8. Check for oil leakage. If oil leakage is found, check for the cause.


### EDH55001

### Front axle boots

Check the protective boots for holes or tears. If any damage is found, have them replaced by a Yamaha dealer.



1. Boot  $(\times 2)$ 



1. Boot (× 2)

EDH20000

### Spark plug inspection

The spark plug is an important engine component and is easy to inspect. The condition of the spark plug can indicate the condition of the engine.

For example, a very white center electrode porcelain color could indicate an intake air leak or carburetion problem for that cylinder. Do not attempt to diagnose such problems yourself.

Instead, take the machine to a Yamaha dealer. You should periodically remove and inspect the spark plug because heat and deposits will cause the spark plug to slowly break down and erode. If electrode erosion becomes excessive, you should replace the spark plug with one of the proper type.


Standard spark plug: D8EA (NGK) or

X24ES-U (DENSO)

Before installing the spark plug, measure the electrode gap with a feeler gauge and adjust to specification.

Spark plug gap:

0.6 ~ 0.7 mm (0.024 ~ 0.028 in)



1. Spark plug gap

When installing the spark plug, always clean the gasket surface and use a new gasket. Wipe off any grime from the threads and tighten to specification.


Spark plug torque:

17.5 Nm (1.75 m·kg, 12.5 ft·lb)


# Air filter cleaning

### NOTE:\_


There is a check hose at the bottom of the air filter case. If dust or water collects in this hose, empty the hose and clean the air filter element and air filter case.



- 1. Check hose
- 1. Remove the seat.
- 2. Remove the air filter case cover.



- 1. Air cleaner case cover
- 3. Remove the air filter element, and separate it from the guide.



1. Air filter element

4. Wash the element gently but thoroughly in solvent.

### **A** WARNING

### **POTENTIAL HAZARD**

Using low flash point solvents or gasoline to clean the air filter element.

### WHAT CAN HAPPEN

Low flash point solvents or gasoline can catch fire or explode.

### **HOW TO AVOID THE HAZARD**

Use parts cleaning solvent to clean the air filter element.

5. Squeeze the excess solvent out of the filter and let it dry.

### CAUTION:

Do not twist the filter element when squeezing it.

- 6. Inspect the element. If damaged, replace it.
- Apply Yamaha foam air filter oil or other quality foam air filter oil to the element. If foam air filter oil is not available, motor oil may be used.

### NOTE:

The element should be wet but not dripping.

- 8. Reinstall the element to the element guide.
- 9. Reinstall the element assembly and parts removed for access.

### NOTE:\_

The air filter element should be cleaned every 20 ~ 40 hours. It should be cleaned and lubricated more often if the machine is operated in extremely dusty areas. Each time filter element maintenance is performed, check the air inlet to the filter case for obstructions. Check the air cleaner rubber joint to the carburetor and manifold fittings for an airtight seal. Tighten all fittings securely to avoid the possibility of unfiltered air entering the engine.

# **CAUTION:**

Never operate the engine with the air filter element removed. This will allow unfiltered air to enter, causing rapid engine wear and possible engine damage. Additionally, operation without the filter element will affect carburetor jetting with subsequent poor performance and possible engine overheating.

FDH90501

### Carburetor adjustment

The carburetor is a vital part of the engine and requires very sophisticated adjustment. Most adjusting should be left to a Yamaha dealer who has the professional knowledge and experience to do so. However, the idling speed may be performed by the owner as a part of the usual maintenance routine.

# **CAUTION:**

The carburetor was set at the Yamaha factory after many tests. If the settings are disturbed by someone without sufficient technical knowledge, poor engine performance and damage may result.

### Idle speed adjustment


### NOTE:

A diagnostic tachometer must be used for this procedure.

- Start the engine and warm it up for a few minutes at approximately 1,000 to 2,000 r/min. Occasionally rev the engine to 4,000 to 5,000 r/min. The engine is warm when it quickly responds to the throttle.
- Connect the tachometer and set the idle to the specified idling speed by adjusting the throttle stop screw. Turn the screw in to increase engine speed, and out to decrease engine speed.

Specified idle speed:

1,450 ~ 1,550 r/min



1. Throttle stop screw


#### EDH90701

# Valve clearance adjustment

The correct valve clearance changes with use, resulting in improper fuel/air supply or engine noise. To prevent this, the valve clearance must be adjusted regularly. This adjustment however, should be left to a professional Yamaha service technician.

# Reverse lock release cable adjustment

The reverse lock release cable stretches with use, resulting in improper function. To prevent this, the cable must be adjusted regularly. This adjustment, however, should be left to a Yamaha dealer.



1. Locknut

2. Adjuster


#### EDH90300

### Throttle lever adjustment

### NOTE:

Adjust the engine idling speed before adjusting the throttle lever free play.

- 1. Loosen the locknut.
- 2. Turn the adjuster until the throttle lever free play is 3 ~ 5 mm (0.12 ~ 0.20 in).
- 3. Tighten the locknut.




1. Locknut

- 2. Adjuster
- a. 3 ~ 5 mm (0.12 in ~ 0.20 in)

### Front brake shoe inspection

- Rotate the front wheel so that the rubber plug is positioned at the top or bottom of the wheel hub.
- 2. Remove the wheel assembly.
- Remove the rubber plug from the wheel hub and check the lining thickness.



1. Rubber plug

- a. Wear limit: 1mm (0.04 in)
- 4. If the lining is worn beyond the wear limit, ask a Yamaha dealer to replace the shoes as a set.


Specified thickness: 4 mm (0.16 in)
Wear limit: 1 mm (0.04 in)

EDH86100

### Rear brake shoe inspection

A wear indicator is provided on the rear brake. This indicator allows checking of brake shoe wear without disassembling the brake.

Apply the rear brake and check the position of the indicator. If the indicator reaches the wear limit line, ask a Yamaha dealer to replace shoes as a set.



1. Wear indicator

2. Wear limit

# Inspecting the brake fluid level

Insufficient brake fluid may let air enter the brake system, possibly causing the brakes to become ineffective.

Before riding, check that the brake fluid is above the lower level and replenish when necessary.


Observe these precautions:

- 1. When checking the fluid level, make sure the top of the master cylinder is level by turning the handlebars.
- Use only the designated quality brake fluid. Otherwise, the rubber seals may deteriorate, causing leakage and poor brake performance.

Recommended brake fluid: DOT 4

### NOTE:

If DOT 4 is not available, DOT 3 can be used.



1. Minimum level mark "LOWER"

- 3. Refill with the same type of brake fluid. Mixing fluids may result in a harmful chemical reaction and lead to poor brake performance.
- Be careful that water does not enter the master cylinder when refilling. Water will significantly lower the boiling point of the fluid and may result in vapor lock.

- 5. Brake fluid may deteriorate painted surfaces or plastic parts. Always clean up spilled fluid immediately.
- 6. Have a Yamaha dealer check the cause if the brake fluid level goes down.

EDH86400

### **Brake fluid replacement**

- Complete fluid replacement should be done only by trained Yamaha service personnel.
- Have a Yamaha dealer replace the following components during periodic maintenance or when they are damaged or leaking.
- a. Replace all rubber seals every two years.
- b. Replace all hoses every four years.

# Front brake lever free play adjustment


### NOTE:

Before adjusting the brake, inspect the front brake shoes.

- 1. Brake lever free play is the distance of brake lever movement before the adjusting bolt touches the master cylinder. The front brake lever free play @ should be adjusted to 2 ~ 5 mm (0.08 ~ 0.19 in).
  - If the free play is incorrect, adjust as follows:
- a. Loosen the locknut.
- b. Turn the adjusting bolt until specified free play is obtained.


# Specified free play:

- $2 \sim 5 \text{ mm} (0.08 \sim 0.19 \text{ in})$
- c. After adjusting, tighten the locknut.



- Locknut
- 2. Adjusting bolt a. 2 ~ 5 mm (0.08 ~ 0.19 in)

2. Brake lever position (while applied)
If the brake lever position (b) exceeds
more than 30 mm (1.18 in) before
braking takes effect, ask a Yamaha
dealer to adjust the brake or replace
the shoes.



b. 30 mm (1.18 in)

### **A** WARNING

### POTENTIAL HAZARD

Operating with improperly serviced or adjusted brakes.

# WHAT CAN HAPPEN

You could lose braking ability, which could lead to an accident.

# **HOW TO AVOID THE HAZARD**


After servicing:

- Make sure the brakes operate smoothly and that the free play is correct.
- Make sure the brakes do not drag.
- Make sure the brakes are not spongy.
   All air must be bled from the brake system.

Replacement of brake components requires professional knowledge. These procedures should be performed by Yamaha dealer.


# Rear brake pedal and lever adjustment

- 1. Brake pedal free play adjustment
- a. Fully loosen the adjusting nut on the brake cable.




- 1. Adjusting nut (brake cable)
- 2. Adjusting nut (brake rod)

b. Turn the adjusting nut on the brake rod until free play is 20 ~ 30 mm (0.8 ~ 1.18 in).



a. 20 ~ 30 mm (0.8 ~ 1.18 in)


- 2. Brake lever free play adjustment
- a. Loosen the locknut and fully turn in the adjusting bolt at the brake lever.



1. Locknut

2. Adjusting bolt


b. Screw in the adjusting nut on brake cable to provide a gap of 0 ~ 1 mm (0 ~ 0.04 in) between the lever and the pin.



1. Adjusting nut (brake cable)

a. 0 ~ 1 mm (0 ~ 0.04 in)

c. Turn the adjusting bolt until free play at the brake lever pivot is  $4 \sim 8$  mm  $(0.16 \sim 0.32 \text{ in})$ .



1. Locknut

- 2. Adjusting bolt
- a. 4 ~ 8 mm (0.16 ~ 0.32 in)
  - d. Tighten the locknut.

# **A** WARNING

### **POTENTIAL HAZARD**

Operating with improperly serviced or adjusted brakes.

# WHAT CAN HAPPEN

You could lose braking ability, which could lead to an accident.


### **HOW TO AVOID THE HAZARD**

After servicing:

- Make sure the brakes operate smoothly and that the free play is correct.
- Make sure the brakes do not drag. Replacement of brake components requires professional knowledge. These procedures should be performed by a Yamaha dealer.

### Clutch adjustment

- 1. Loosen the locknut.
- 2. Slowly turn the adjusting bolt counterclockwise until resistance is felt. Then, turn it 1/8 turn clockwise.



1. Locknut

2. Adjusting bolt

3. Tighten the locknut to specification.

Tightening torque: 15 Nm (1.5 m·kg, 11 ft·lb)

### NOTE:

Turn the adjusting bolt counterclockwise to decrease the clutch free play and turn it clockwise to increase the free play.

# Cable inspection and lubrication

# **WARNING**

### **POTENTIAL HAZARD**

Damaged control cables.

# WHAT CAN HAPPEN

Corrosion can result when the outer covering of control cables becomes damaged. Cables can also become frayed or kinked. Operation of controls could be restricted, which could cause an accident or injury.

### **HOW TO AVOID THE HAZARD**

Inspect cables frequently. Replace damaged cables.

Lubricate the inner cable and the cable end. If they do not operate smoothly, ask a Yamaha dealer to replace them.

Recommended lubricant:

Yamaha chain and cable lube or SAE 10W30 motor oil

EDI25101

# Brake and shift pedals/brake lever lubrication


Lubricate the pivoting parts of each lever and pedal.

Recommended lubricant:

Yamaha chain and cable lube or SAE 10W30 motor oil

### Wheel removal

- 1. Elevate the wheel by placing a suitable stand under the frame.
- 2. Remove the nuts from the wheel.
- 3. Remove the wheel assembly.




EDJ20301

### Wheel installation

When installing the wheel, reverse the removal procedure. Pay attention to the following.


### NOTE:\_

The arrow mark  $\Im$  on the tire must point toward the rotating direction of the wheel.



1. Arrow mark

 Tapered wheel nuts are used for both front and rear wheels. Install the nut with its tapered side towards the wheel.



- 1. Tapered nut
- 2. Tighten the wheel nuts.

Wheel nut torque:

Front: 55 Nm (5.5 m·kg, 40 ft·lb)

Rear: 55 Nm (5.5 m·kg, 40 ft·lb)


EDI70100

### **Battery**

Check the level of the battery fluid and see if the terminals are tight. Add distilled water if the fluid level is low.

### CAUTION:

Do not leave or store the battery on its side. When inspecting the battery, be sure the breather pipe is routed correctly. If it touches the frame or exists in such a way as to cause battery electrolyte or gas to exit onto the frame, structural and cosmetic damage to the machine can occur.



Battery 2. Battery breather hose

3. Guide

# **M** WARNING

### **POTENTIAL HAZARD**

Failure to handle batteries or battery electrolyte carefully.

### WHAT CAN HAPPEN

You could be poisoned. You could be severely burned by the sulfuric acid in battery electrolyte.

Batteries produce explosive gases.

### **HOW TO AVOID THE HAZARD**

Avoid contact with skin, eyes or clothing. Always shield eyes when working near batteries. Keep out of reach of children.

Antidote:

**EXTERNAL: Flush with water.** 


INTERNAL: Drink large quantities of water or milk. Follow with milk of magnesia, beaten egg or vegetable oil. Get prompt medical attention.

EYES: Flush with water for 15 minutes and get prompt medical attention. Keep batteries away from sparks, flames, cigarettes or other sources of ignition. Ventilate when charging or using in a closed space.


# Replenishing the battery fluid

A poorly maintained battery will corrode and discharge quickly. The battery fluid should be checked at least once a month.

 The level should be between the upper and lower level marks. Use only distilled water if refilling is necessary.



- 1. Maximum level mark
- 2. Minimum level mark
- 3. Positive (+) lead
- 4. Negative (-) lead
- 2. Disconnect the negative (–) lead and remove the battery bracket.



- 1. Bolt (x 2)
- 3. Disconnect the positive (+) lead and remove the battery.

# **CAUTION:**


Normal tap water contains minerals which are harmful to a battery. Therefore, refill only with distilled water.

- 4. When the machine is not to be used for a month or longer, remove the battery and store it in a cool, dark place. Completely recharge the battery before reusing.
- If the battery is to be stored for a longer period than the above, check the specific gravity at least once a month and recharge the battery when it is too low.
- Always make sure the connections are correct when putting the battery back in the machine. Make sure the breather pipe is properly connected and is not damaged or obstructed.

#### Fuse replacement


- The main fuse case is located under the seat and the auxiliary DC terminal fuse case is located under the left rear fender.
- 2. If a fuse is blown, turn off the main switch and install a new fuse of the specified amperage. Then turn on the switches. If the fuse immediately blows again, consult a Yamaha dealer.

Specified fuse:
Main 30A
Auxiliary 10A



1. Main fuse

2. Spare fuse



1. Auxiliary fuse

2. Spare fuse

### **WARNING**

#### **POTENTIAL HAZARD**

Using an improper fuse.

#### **WHAT CAN HAPPEN**

An improper fuse can cause damage to the electrical system which could lead to a fire.

#### **HOW TO AVOID THE HAZARD**

Always use a fuse of the specified rating. Never use a material in place of the proper fuse.


#### **CAUTION:**

To prevent accidental short-circuiting, turn off the main switch when checking or replacing a fuse.


#### Replacing the headlight bulb

If the headlight bulb burns out, replace the bulb as follows:

1. Remove the headlight cover together with the headlight unit assembly.



- 1. Headlight cover
- 2. Remove the cover, turn the bulb holder counterclockwise and remove the defective bulb.



1. Cover

2. Bulb holder

#### **WARNING**

#### POTENTIAL HAZARD

The headlight bulb is hot when it is on and immediately after it is turned off.

#### **WHAT CAN HAPPEN**

You can be burned, or a fire could start if the bulb touches something flammable.

#### **HOW TO AVOID THE HAZARD**

Wait for the bulb to cool before touching or removing it.

- 3. Put a new bulb into position and secure it in place with the bulb holder.
- 4. Reinstall the light unit assembly in the headlight body. Adjust the headlight beam if necessary.

EDI80600

#### Headlight beam adjustment


۰									
	00					00		53	
		ж.		ш.			20		

It is advisable to have a Yamaha dealer make this adjustment.

1. Vertical adjustment:

To raise the beam, turn the adjusting screw clockwise.

To lower the beam, turn the screw counterclockwise.



1. Adjusting screw (× 2)

#### **Troubleshooting**

Although Yamaha machines receive a rigid inspection before shipment from the factory, trouble may occur during operation. Any problem in the fuel, compression, or ignition systems can cause poor starting and loss of power. The trouble-shooting chart describes a quick, easy procedure for making checks. If your machine requires any repair, take it to a Yamaha dealer.

The skilled technicians at a Yamaha dealership have the tools, experience, and know-how to properly service your machine. Use only genuine Yamaha parts on your machine. Imitation parts may look like Yamaha parts, but they are often inferior. Consequently, they have a shorter service life and can lead to expensive repair bills.

## **WARNING**

#### **POTENTIAL HAZARD**

Checking the fuel system while smoking or near an open flame.


#### WHAT CAN HAPPEN

Fuel can ignite or explode, causing severe injury or property damage.

#### **HOW TO AVOID THE HAZARD**

Do not smoke when checking the fuel system. Make sure there are no open flames or sparks in the area, including pilot lights from water heaters or furnaces.

#### **Troubleshooting chart**



#### **CLEANING AND STORAGE**

#### A. CLEANING

Frequent, thorough cleaning of your machine will not only enhance its appearance but will improve its general performance and extend the useful life of many components.

- 1. Before cleaning the machine:
- a. Block off the end of the exhaust pipe to prevent water entry. A plastic bag and strong rubber band may be used.
- b. Make sure the spark plug and all filler caps are properly installed.
- If the engine case is excessively greasy, apply degreaser with a paint brush. Do not apply degreaser to the wheel axles.
- 3. Rinse the dirt and degreaser off with a garden hose. Use only enough pressure to do the job.

#### **CAUTION:**

Excessive water pressure may cause water seepage and deterioration of wheel bearings, brakes, transmission seals and electrical devices. Many expensive repair bills have resulted from improper high pressure detergent applications such as those available in coin-operated car washers.

- 4. Once the majority of the dirt has been hosed off, wash all surfaces with warm water and mild, detergent-type soap. An old toothbrush or bottle brush is handy for hard-to-get-at places.
- Rinse the machine off immediately with clean water and dry all surfaces with a chamois, clean towel or soft absorbent cloth.

- Clean the seat with a vinyl upholstery cleaner to keep the cover pliable and glossy.
- 7. Automotive type wax may be applied to all painted and chrome plated surfaces. Avoid combination cleanerwaxes. Many contain abrasives which may mar the paint or protective finish. When finished, start the engine and let it idle for several minutes.

#### **A** WARNING

#### **POTENTIAL HAZARD**

Operation with wet brakes after washing.

#### WHAT CAN HAPPEN

Wet brakes may have reduced stopping ability, increasing the chance of an accident.

#### **HOW TO AVOID THE HAZARD**

Test the brakes after washing. Apply the brakes several times at slow speeds to let friction dry out the linings.

#### **B. STORAGE**

Long term storage (60 days or more) of your machine will require some preventive procedures to guard against deterioration. After thoroughly cleaning the machine, prepare for storage as follows:

- 1. Drain the fuel tank, fuel lines and carburetor float bowl.
- Remove the spark plug, pour about one tablespoon of SAE 10W30 or 20W40 motor oil in the spark plug hole and reinstall the spark plug. Turn the engine over several times (ground spark plug wire) to coat the cylinder wall with oil.
- 3. Lubricate all control cables.
- 4. Block up the frame to raise all wheels off the ground.
- Tie a plastic bag over the exhaust pipe outlet to prevent moisture from entering.

- If storing in a humid or salt-air atmosphere, coat all exposed metal surfaces with a light film of oil. Do not apply oil to any rubber parts or the seat cover.
- Remove the battery and charge it. Store it in a dry place and recharge it once a month. Do not store the battery in an excessively warm or cold place (less than 0°C (30°F) or more than 30°C (90°F)).

#### NOTE:

Make any necessary repairs before storing the machine.

# **SPECIFICATIONS**

MODEL	YFM350FWB
Dimension: Overall length Overall width Overall height Seat height Wheel base Minimum ground clearance Minimum turning radius	1,945 mm (76.6 in) 1,095 mm (43.1 in) 1,165 mm (45.9 in) 835 mm (32.9 in) 1,236 mm (48.7 in) 245 mm (9.65 in) 3,400 mm ( 134 in)
Basic weight: With oil and full fuel tank	259kg (571 lb)
Engine:     Engine type     Cylinder arrangement:     Displacement     Bore × Stroke     Compression ratio     Starting system     Lubrication system	Air cooled, 4-stroke, SOHC Single cylinder, Forward inclined 348 cm <sup>3</sup> 83.0 × 64.5 mm (3.27 × 2.54 in) 8.6 : 1 Electric starter and recoil starter Wet sump
Oil type or grade: Engine oil/Transfer gear oil Final gear oil Differential gear oil	See page 5-7. SAE 80 API "GL-4" Hypoid gear oil SAE80 or SAE80W-90 API GL-5 Hypoid gear oil for L.S.D.

MODEL	YFM350FWB
Oil capacity: Engine oil: Periodic oil change With oil filter replacement Total amount Final gear case oil: Periodic oil change Total amount Differential gear case oil: Periodic oil change	2.9 L (2.6 lmp qt, 3.1 US qt) 3.0 L (2.6 lmp qt, 3.2 US qt) 3.5 L (3.1 lmp qt, 3.7 US qt)  0.19 L (0.17 lmp qt, 0.20 US qt) 0.25 L (0.22 lmp qt, 0.26 US qt)  0.18 L (0.16 lmp qt, 0.19 US qt)
Total amount Air filter	0.20 L (0.18 Imp qt, 0.21 US qt)  Wet type element
Fuel: Type Tank capacity Reserve amount	UNLEADED FUEL 10.0 L (2.2 Imp gal, 2.6 US gal) 1.3 L (0.29 Imp gal, 0.34 US gal)
Carburetor: Type/Manufacturer	BST34/MIKUNI
Spark plug: Type/Manufacturer Gap	D8EA/NGK or X24ES-U/DENSO 0.6 ~ 0.7 mm (0.024 ~ 0.028 in)
Clutch type	Wet, centrifugal automatic

MODEL	YFM350FWB
Transmission: Primary reduction system Primary reduction ratio Secondary reduction system Secondary reduction ratio Transmission type Operation Gear raito:  1st 2nd 3rd 4th 5th Reverse gear	Spur gear 76/24 (3.167) Shaft drive 27/25 × 24/18 × 33/09 (5.280) Constant mesh 5-speed forward, 1-speed reverse Left foot operation 38/13 (2.923) 34/18 (1.889) 30/22 (1.364) 26/25 (1.040) 25/33 (0.758) 22/17 × 35/15 (3.020)
Chassis: Frame type Caster angle Trail	Steel tube 2° 11 mm (0.43 in)
Tire: Type Size: Front Size: Rear	Tubeless AT25 × 8-12 AT25 × 10-12
Brake: Front brake type Operation Rear brake type Operation	Drum brake Right hand operation Drum brake Left hand and right foot operation

MODEL	YFM350FWB
Suspension: Front Rear	Double wishbone Swingarm (monocross)
Shock absorber: Front Rear	Coil spring/Oil damper Coil spring/Oil damper
Wheel travel: Front wheel travel Rear wheel travel	150 mm (5.91 in) 150 mm (5.91 in)
Electrical: Ignition system Generator system Battery type/voltage, capacity	C.D.I. AC Magneto GM14AZ-4A/12V, 14AH
Headlight type	Bulb
Bulb voltage, wattage × quantity: Headlight Taillight Indicator light: Neutral	12V, 25W/25W × 2 12V, 7.5W × 1
Reverse Oil temparature	12V, 3.4W × 1 12V, 3.4W × 1 12V, 3.4W × 1

#### **NOISE REGULATION**

#### TAMPERING WITH NOISE CONTROL SYSTEM PROHIBITED:

Federal law prohibits the following acts or the causing thereof: (1) The removal or rendering inoperative by any person other than for purposes of maintenance, repair, or replacement of any device or element of design incorporated into any new vehicle for the purpose of noise control prior to its sale or delivery to the ultimate purchaser or while it is in use or (2) the use of the vehicle after such device or element of design has been removed or rendered inoperative by any person.

"AMONG THOSE ACTS PRESUMED TO CONSTITUTE TAMPERING ARE THE ACTS LISTED BELOW."

These acts include tampering with the following systems; i.e., modification, removal, etc.

Exhaust system	Muffler Exhaust pipe Silencer			
Intake system	Air cleaner case Air cleaner element Intake duct			

#### **MAINTENANCE RECORD**

Copies of work orders and/or receipts for parts you purchase and install will be required to document maintenance done in accordance with the warranty. The chart below is printed only as a reminder to you that the maintenance work is required. It is not acceptable proof of maintenance work.

MAINTENANCE INTERVAL	DATE OF SERVICE	MILEAGE	SERVICING DEALER NAME AND ADDRESS	REMARKS
1 Month				
3 Months				
6 Months				
12 Months				
18 Months				
24 Months				
30 Months				
36 Months				
42 Months				
48 Months				
54 Months				
60 Months				

# YAMAHA MOTOR CORPORATION, U.S.A. MOTO-4 LIMITED WARRANTY

Yamaha Motor Corporation, U.S.A. hereby warrants that new Yamaha Moto-4 purchased from an authorized Yamaha Moto-4 dealer in the continental United States will be free from defects in material and workmanship for the period of time stated herein, subject to certain stated limitations.

THE PERIOD OF WARRANTY for Yamaha Moto-4s shall be six (6) months from the date of purchase.

DURING THE PERIOD OF WARRANTY any authorized Yamaha Moto-4 dealer will, free of charge, repair or replace any part adjudged defective by Yamaha due to faulty workmanship or material from the factory. Parts used in warranty repairs will be warranted for the balance of the product's warranty period. All parts replaced under warranty become property of Yamaha Motor Corp. U.S.A.

**GENERAL EXCLUSIONS** from this warranty shall include any failures caused by:

- a. Competition or racing use.
- Installation of parts or accessories that are not qualitatively equivalent to genuine Yamaha parts.
- c. Abnormal strain, neglect, or abuse.
- d. Lack of proper maintenance.
- e. Accident or collision damage.
- f. Modification to original parts.
- Damage due to improper transportation.

SPECIFIC EXCLUSIONS from this warranty shall include parts replaced due to normal wear or routine maintenance; such as spark plugs, oil, oil filter, air filter, and brake shoes.

THE CUSTOMER'S RESPONSIBILITY under this warranty shall be to:

- Operate and maintain the Moto-4 as specified in the appropriate owner's manual;
- Give notice to an authorized Yamaha Moto-4 dealer of any and all apparent defects within ten ten (10) days after discovery, and make the machine available at that time for inspection and repairs at such dealer's place of business.

WARRANTY TRANSFER: To transfer the warranty from the original purchaser to any subsequent purchaser(s), it is imperative that the machine be inspected and registered for warranty by an authorized Yamaha Moto-4 dealer. In order for this warranty to remain in effect, this inspection and registration must take place within (10) days after transfer. An inspection and registration fee will be charged for this service.

YAMAHA MOTOR CORPORATION, U.S.A. MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PAR-TICULAR PURPOSE WHICH EXCEED THE OBLIGA- TIONS AND TIME LIMITS STATED IN THIS WARRAN-TY ARE HEREBY DISCLAIMED BY YAMAHA MOTOR CORPORATION, U.S.A. AND EXCLUDED FROM THIS WARRANTY.

SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS. SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. ALSO EXCLUDED FROM THIS WARRANTY ARE ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES INCLUDING LOSS OF USE. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE EXCLUSION MAY NOT APPLY TO YOU.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

YAMAHA MOTOR CORPORATION, U.S.A. P.O. Box 6555 Cypress, California 90630

#### WARRANTY QUESTIONS AND ANSWERS

- Q. What costs are my responsibility during the warranty period?
- A. The customer's responsibility includes all costs of normal maintenance services, non-warranty repairs, accident and collision damages, and oil, oil filters, air filters, spark blues, and brake shoes.
- Q. What are some examples of "abnormal" strain, neglect, or abuse?
- A. These terms are general and overlap each other in areas. Specific examples include: Running the machine out of oil, sustained high-rpm, full-throttle, operating the machine with a broken or damaged part which causes another part to fail, damage or failure due to improper or careless transporation and or tie down. If you have any specific questions on operation or maintenance, please contact your dealer for advice.
- Q. Does the warranty cover incidental costs such as towing or transportation due to a failure?
- A. No. The warranty is limited to repair of the machine itself.
- Q. May I perform any or all of the recommended maintenance shown in the Owner's Manual instead of having the dealer do them?
- A. Yes, if you are a qualified mechanic and follow the procedures specified in the Owner's and Service Manual. We do recommend, however, that items requiring special tools or equipment be done by a Yamaha Moto-4 dealer.
- Q. Will the warranty be void or cancelled if I do not operate or maintain my new Moto-4 exactly as specified in the Owner's Manual?
- A. No. The warranty on a new Moto-4 cannot be "voided" or "cancelled." However, if a particular failure is caused by operation or maintenance other than as shown in the Owner's Manual, that failure may not be covered under warranty.
- Q. What responsibility does my dealer have under this warranty?
- A. Each Yamaha Moto-4 dealer is expected to:
  - 1. Completely set up every new machine before sale.
  - Explain the operation, maintenance, and warranty requirements to your satisfation at the time of sale, and upon your request at any later date.
  - Each Yamaha Moto-4 dealer is held responsible for his setup, service and warranty repair work.
- Q. Is the warranty transferable to second owners?
- A. Yes. The remainder of the existing warranty can be transferred upon request. The unit has to be inspected and re-registered by an authorized Yamaha Moto-4 dealer for the policy to remain effective.

#### CUSTOMER SERVICE

If your machine requires warranty service, you must take it to any authorized Yamaha Moto-4 dealer within the continental United States. Be sure to bring your warranty registration card or other valid proof of the original date of purchase. If a question or problem arises regarding warranty, first contact the owner of the dealership. Since all warranty matters are handled at the dealer level, this person is in the best position to help you. If you are still not satisfied and require additional assistance, please write:

# YAMAHA MOTOR CORPORATION U.S.A. CUSTOMER RELATIONS DEPARTMENT P.O. Box 6555 Cypress, California 90630

When contacting Yamaha Motor Corporation, U.S.A. don't forget to include any important information such as names, addresses, model, engine serial number, dates, and receipts.

#### CHANGE OF ADDRESS

The federal government requires each manufacturer of a motor vehicle to maintain a complete, up-to-date list of all first purchasers against the possibility of a safety-related defect and recall. This list is compiled from the purchase registrations sent to Yamaha Motor Corporation, U.S.A. by the selling dealer at the time of your purchase.

If you should move after you have purchased your new Moto-4, please advise us of your new address by sending a postcard listing your Moto-4 model name, engine serial number, dealer number (or dealer's name) as it is shown on your warranty card, your name and new mailing address. Mail to:

YAMAHA MOTOR CORPORATION, U.S.A. P.O. Box 6555 Cypress, California 90630 Attention: Warranty Department

This will ensure that Yamaha Motor Corporation, U.S.A. has an up-to-date registration record in accordance with federal law.

#### YAMAHA EXTENDED SERVICE (Y.E.S.)

Keep your Yamaha protected even after your warranty expires with genuine Yamaha Extended Service (Y.E.S.).

- Y.E.S. is designed and administered by Yamaha Motor Corporation to provide maximum owner satisfaction. You get uninterrupted factory-backed coverage for extra peace of mind.
- Y.E.S. is flexible. You choose the plan that's right for you: 12 months, 24 months, or 36 months beyond your warranty period.
- Y.E.S. is designed and administered by the same Yamaha people who handle your warranty — and it shows in the comprehensive coverage benefits. There are no mileage limitations. Coverage isn't limited to "moving parts" or the "drive train" like many other plans. And Y.E.S. covers manufacturing defects just like the warranty. See the sample contract at your Yamaha dealer to see how comforting uninterrupted factorybacked protection can be.
- You don't have to pay anything for covered repairs.
   There's no deductible to pay, and repairs aren't "pro-rated." You don't have any "out-of-pocket" expenses for covered repairs.

- In addition, Travel and Recreation Interruption Protection (TRIP) is included at no extra cost. TRIP gives you up to \$150 reimbursement per occurrence for any reasonable expenses you incur because your Yamaha needs covered service: replacement vehicle rental, emergency towing, phone calls, even food and lodging when you are away from home. This superb coverage goes into effect when you purchase Y.E.S., so it applies to any warranty repairs as well as covered repairs during your entire Y.E.S. plan period.
- Y.E.S. coverage is honored at any authorized Yamaha dealer nationwide.
- Y.E.S. coverage is transferrable to a new owner if you sell or trade-in. That can make your Yamaha much more valuable!

This excellent Y.E.S. plan coverage is only available to Yamaha owners like you, and only while your Yamaha is still within the Yamaha Limited Warranty period. So visit your authorized Yamaha dealer to get all the facts. He can show you how easy it is to protect your investment with Yamaha Extended Service.

We urge you to act now. You'll get the excellent benefits of TRIP coverage right away, and you'll rest easy knowing you'll have strong factory-backed protection even after your Yamaha Limited Warranty expires. You can also save money: Y.E.S. costs less within the first 90 days after you buy your Yamaha. See your dealer today!

#### A special note:

If visiting your dealer isn't convenient, contact Yamaha with your Primary ID number (your engine number). We'll be happy to help you get the Y.E.S. coverage you need.

Yamaha Service Marketing P.O. Box 6555 Cypress, CA 90630 (714) 761-7631







YAMAHA EXTENDED SERVICE

EDL20000



Indicates a potential hazard that could result in serious injury or death.

# PROTECT YOUR INVESTMENT Use **Genuine YAMAHA** Parts And Accessories

See your Authorized YAMAHA Dealer for a Genuine YAMAHA Service Manual.

# **AWARNING**

Improper ATV use can result in SEVERE INJURY or DEATH.









R USE ORUGS COHOL

4/29/2000

# DO NOT REMOVE THIS ITEM FROM THE YAMAHA LIBRARY!

LIT-11626-10-93



YFM350FWBK(C) 1998

) avoid ough terrain

ent may ontrol.

**Owner's Manual** 

LOCATE AND READ OWNER'S MANUAL. FOLLOW ALL INSTRUCTIONS AND WARNINGS. (For replacement manual, call 1-800-532-1558)





