

Electric Scissor Lift

Models	GTJZ05	GTJZ06A	GTJZ06	GTJZ08A	GTJZ08	GTJZ10	GTJZ12	GTJZ14
Platform height maximum	4.5m	6.00m	6.00m	8.00m	8.00m	10.00m	12.00m	13.80m
MAX working height	6.5m	8m	8m	10m	10m	12m	14m	15.8m
platform size outside(m)	1.34*0.75	1.68*0.74	2.27*1.12	2.27*0.86	2.27*1.12	2.27*1.12	2.27*1.12	2.7*1.11
Extend platform	0.6m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m
Overall size(fold) (m)	1.51*0.8*1.45	1.85*0.79*1.67	2.43*1.21*1.67	2.43*0.89*1.9	2.43*1.21*1.8	2.43*1.21*1.93	2.43*1.21*2.06	2.85*1.31*2.06
Overall size(unfold) (m)	1.51*0.8*2.06	1.85*0.79*2.20	2.43*1.21*2.22	2.43*0.89*2.35	2.43*1.21*2.35	2.43*1.21*2.47	2.43*1.21*2.6	2.85*1.31*2.6
Ground clearance	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.015m	0.1/0.015m
Wheelbase	1.14m	1.39m	1.87m	1.87m	1.87m	1.87m	1.89m	2.28m
Capacity	230kg	230kg	450kg	320kg	450kg	320kg	320kg	230kg
Drive height	full height	full height	full height	full height	full height	full height	full height	full height
Drive speed - stowed	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Drive speed - raised	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Gradeability-stowed	25%	25%	25%	25%	25%	25%	25%	25%
Inside Turning Radius	0.25m	0.3m	0	0	0	0	0	0
Outside Turning Radius	1.4m	1.75m	2.4m	2.4m	2.4m	2.4m	2.4m	2.7m
Raise / lower speed	100 / 80 sec	100 / 80 sec	100 / 80 sec	100 / 80 sec	100 / 80 sec	100 / 80 sec	100 / 80 sec	100 / 80 sec
Tyres - solid non-marking	Φ254×76mm	Φ305×114mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm
Power source	24V/1.7kw	24V/3.3kw	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw
Battery	4×6V/80ah	4×6V/200ah	4×6V/200ah	4×6V/200ah	4×6V/200ah	4×6V/200ah	4×6V/200ah	4×6V/240ah
Charger	24V/15A	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A
Max safe working angle	1.5° /3°	1.5° /3°	1.5° /3°	1.5° /3°	1.5° /3°	1.5° /3°	1.5° /3°	1.5° /3°
Weight	1050kg	1430kg	2250kg	2260kg	2350kg	2550kg	3000kg	3670kg

Features

Proportional control	Automatic braking system	Buzzer	Extension platform
Automatic pothole protection	Emergency descent system	Horn	Charging protection system
Platform self-locking door	Emergency stop button	Work schedule	Strobe light
Fully self-propelled	Fuel line explosion-proof system	Safe passage support bar	
Non-marking tires	Troubleshooting system	Standard forklift holes	
4*2 drive	Tilt protection system	Folding fence	

