



Portable Dissolved Oxygen Meter LMDO4P





Portable Dissolved Oxygen Meter

LMDO4P



SALIENT FEATURES

- ✦ Polarographic Dissolved Oxygen Electrode easy to use.
- ✦ Portable Dissolved Oxygen meter is equipped with a backlight LCD display.
- ✦ 1 or 2 points calibration using the air-saturated water or zero oxygen solution.
- ✦ Salinity and barometric pressure compensations eliminate the measurement errors.
- ✦ Automatic temperature compensation ensures accurate readings over the entire range.
- ✦ Auto-read function senses and locks the measurement endpoint.
- ✦ Auto-power OFF effectively conserves battery life.
- ✦ Setup menu allows setting the number of calibration points, temperature unit, etc.
- ✦ Reset function automatically resumes all settings back to the factory defaults.
- ✦ Expanded memory stores or recalls up to 100 data sets.
- ✦ USB communication interface for data transfer or connecting a power adapter to the meter.
- ✦ Battery Life : Approximately 150 hours without backlight.
- ✦ Automatic shutdown - After 15 minutes, If not in use
- ✦ Carrying Case is Standard Supply.

Portable Dissolved Oxygen Meter

HSN : 90275090

SPECIFICATIONS

MODEL	LMDO4P
Dissolved Oxygen Range	0.00 to 20.00 mg/L, (ppm)
Dissolved Oxygen Resolution	0.01 mg/L, (ppm)
Dissolved Oxygen Accuracy	±0.5 mg/L, (ppm)
Saturation Range %	0.0 to 200.0%
Saturation Resolution	0.1%
Saturation Accuracy	±2.0%
Calibration	1 or 2 points
Temperature Compensation	0 to 50°C / 32 to 122°F, automatic
Pressure Correction	60.0 to 113.3 kPa / 450 to 850 mmHg, manual
Salinity Correction	0.0 to 50.0 ppt, manual
Display	LCD
Hold Function	Selectable - Manual or Automatic hold after measurement end point
Auto-Power OFF	15 minutes, if not in use
Carrying Case	Available
Reset Function	Yes
Date & Time	Yes
Memory	Upto 100 data readings
Connector	6-pin mini-DIN
Communication	USB Interface
Power Supply	3 × 1.5V AA batteries or 5V DC power adapter
Packing Dimension (LxWxH)	345 × 85 × 300mm
Gross Weight	1kg


* Specifications are subject to change without Notice

Standard Accessories : Main Instrument, DO Electrode, Electrolyte Solution, Membrane Cap, Instruction Manual, Test Certificate.


LABMAN Product Range 2025-26

LMFD61, 62, 63, 64 Lyophilizer Freeze Dryer (-60°C)	LMFD83, 84 Lyophilizer Freeze Dryer (-80°C)	LMRE25 Rotary Evaporator	ADM3 Automatic Density Meter	MSOD6 Microvolume Spectrophotometer
NAE32 Nucleic Acid Extractor	EMR4 Elisa Microplate Reader	GPTC96 Gradient PCR Thermal Cycler	HO30 Hybridization Oven	UVCL254 UV - Crosslinker
TGH12, 24 Tissue Grinder Homogenizer	PBH80T Paddle Blender Homogenizer	TOC2NDir Total Organic Carbon Analyzer	TOC1CD Total Organic Carbon Analyzer	LMDS600, 1200 Microwave Digestion System
HPLC1IS, HPLC2GS High Performance Liquid Chromatography	APT1800 Automatic Potential Titrator	KFT250VC Karl Fischer Titrator	COD1500 COD Analyzer with Digestor	BOD4000 BOD Analyzer
MTVM50 Multi Tube Vortex Mixer	LMVM60D Vortex Mixer	OS20 Orbital Shaker	TRM6 Tube Roller Mixer	DBNE12, 24 Dry Bath Nitrogen Evaporator





LABMAN Product Range 2025-26

DBI11T  Dry Bath Incubator	DBI15SH, DBI16SC  Dry Bath Incubator	IRS14, 35  Infrared Sterilizer	GGA200  Air Generator	GGA301, 302  Hydrogen Generator
GGN303  Nitrogen Generator	GHA304  Hydrogen Air Generator(2 in 1)	LMVP10  Vacuum Pump	LMVP20  Vacuum Pump	LMCO1  Column Oven
LMIO6  Mini Thermostatic Incubator	GHP400  Graphite Hotplate	LOBMS5  Oil Bath Magnetic Stirrer	LMMS4LC, 20LC  Ceramic Hotplate Magnetic Stirrer	LMMS300  Hotplate Magnetic Stirrer
MMS15S  Multiposition Magnetic Stirrer	MMS12H  Multiposition Magnetic Stirrer	WBMS3  Water Bath Magnetic Stirrer	LMWB2H, 4H, 6H, 8H  Digital Water Bath	HOS20L  Overhead Stirrer
LMHH160  Hand Held Homogenizer	PS1565  Peltier / Sipper System	LUV6HG  PMT Spectrophotometer	LUV2000T, 2100T  Single / Double Beam UV-Vis. Spectrophotometer with 21CFR	LMSPUV SERIES  Double Beam UV-Vis. Spectrophotometer

LABMAN Product Range 2025-26

LMSPUV1200  UV-Vis. Single Beam Spectrophotometer	LMSPV320, 325  Visible Spectrophotometer	ADP100CFR, 95CFR  Automatic Digital Polarimeter with CFR	ADP45, 50  Automatic Digital Polarimeter (±45°)	ADP75, 90  Automatic Digital Polarimeter (±90°)
ADP40  Automatic Digital Polarimeter	LMPM180  Manual Polarimeter	MAR100  Manual ABBE Refractometer	RFM100CFR  Digital Refractometer CFR	RFM950, 970  Digital Refractometer
LMAR1317T  ABBE Refractometer	LMDV300H  Digital Viscometer with Thermosel	LMDV60, 100, 200  Digital Viscometer (L Series)	LMDV400R  Digital Viscometer (R Series)	LMKV2  Krebs Viscometer
LMDV111, 222  Digital Viscometer with SSA	LVA30  Low Viscosity Adaptor	LMCR80F  Visual Colorimeter	LMUC2D  Ultrasonic Cleaner	LMUC3D, 6D, 9D, 12D, 25D  Ultrasonic Cleaner - Degas
LMUC50, 100  Industrial Ultrasonic Cleaner	LMPH15  pH Meter with Printer	LMPH12, LMPH10H  pH Meter	LMPH9  pH Meter - Basic	LMCM20H  Conductivity / TDS Meter

LABMAN Product Range 2025-26

LMCM20H  Conductivity / TDS Meter	LMMP30, 32  Multiparameter (7 in 1 / 9 in 1)	LMION40  Ion Meter	LMDO50  Dissolved Oxygen Meter	LMHD60  Water Hardness Meter
OPH11  Online pH Controller	OCM21  Online Conductivity Controller	LMTB200  Turbidity Meter	RCB1010T, 1020T, 1030T  Refrigerated Circulating Bath	RCB620T  Refrigerated Circulating Bath
RWC320  Recirculating Water Chiller	LMDO4P  Portable DO Meter	LMPH1P  Portable pH / ORP Meter	LMCM2P  Portable Conductivity / TDS Meter	LMTB5P  Portable Turbidity Meter
PRO656, 900, 1200, 1800  Probe Sonicator	PRO660R  Probe Sonicator with Remote	PRO650  Probe Sonicator	LMIF30T, 50T, 100T  Ice Flaker	LMIF200T  Ice Flaker
LMIM15  Ice Maker	LMIM20C  Ice Maker with Crusher	ISE19, 62  Nitrate / Fluoride ISEs	ER SERIES  pH Electrode / DO Electrode	CC1, CC2, CC3  Conductivity Cell