



**Turbidity Meter
LMTB200**



Turbidity Meter

LMTB200



Turbidity meter LMTB200 with a Total Suspended Solids measurement mode, 2 to 7 points calibration, selectable 4 turbidity units, the meter is suitable for laboratory use.

SALIENT FEATURES

- ✦ Turbidity meter with TSS measurement mode, selectable four turbidity units
- ✦ Turbidity meter is equipped with a 4.5" TFT display.
- ✦ 2 to 7 points calibration using the Formazin Standards.
- ✦ Selectable four turbidity units, including the NTU, FNU, EBC and ASBC.
- ✦ TSS conversion factor ensures accurate measurement for Total Suspended Solids
- ✦ Continuous measurement mode that can be used for indexing and matching the sample vials
- ✦ Hold function freezes current reading for easy viewing and recording
- ✦ Password protection prevents the unauthorized calibration and settings
- ✦ Help message as an operational guide that helps user quickly begin using the meter
- ✦ System menu allows setting the 9 parameters, including the date and time, resolution, etc
- ✦ Reset feature automatically resumes all settings back to factory default settings.

STANDARD ACCESSORIES: Main Instrument, Empty Vial - 1no, Calibration Standards - 3(200NTU, 500NTU, 1000NTU), Cloth, Power Adaptor, Test Certificate.


Turbidity Meter

HSN Code : 90275090

SPECIFICATIONS

MODEL	LMTB200
Make	LABMAN
Measurement Range	1~2000 NTU
Resolution	0.01 (1~100 NTU), 0.1 (100~999 NTU), 1 (999~2000 NTU)
Accuracy	±5%
Calibration Points Options	2 to 7 points (0.02, 10.00, 200, 500, 1000, 1500, 2000 NTU)
TSS range	depending on the TSS conversion factor
Resolution	0.0 / 1
TSS Accuracy	±3% of reading
Light Source	Infrared-emitting diode (850nm Wavelength)
Detector	Silicon Photodiode
Stray Light	<0.02 NTU
Sample Vials	60 (H) x 25 (Dia)mm
Memory	Stores up to 200 data sets
Display	4.5" TFT Display
Password Protection	Yes
Operating Temperature	0~50°C
Power Requirements	DC Adaptor, Using AC 220V, 50/60Hz
Packing Dimension (L x W x H)	310 x 255 x 190mm
Gross Weight	2kg

★ Specifications are subject to change without notice.




Applications: • Industrial wastewater plants • Municipal water and other industrial applications

STANDARD ACCESSORIES: Main Instrument ,Empty Vial - 1no, Calibration Standards - 3(200NTU, 500NTU, 1000NTU), Cloth, Power Adaptor, Instruction Manual, Test Certificate.

LABMAN Product Range 2025-26

LMFD61, 62, 63, 64 Lyophilizer Freeze Dryer (-60°C)	LMFD83, 84 Lyophilizer Freeze Dryer (-80°C)	LMRE25 Rotary Evaporator	ADM3 Automatic Density Meter	MSOD6 Microvolume Spectrophotometer
NAE32 Nucleic Acid Extractor	EMR4 Elisa Microplate Reader	GPTC96 Gradient PCR Thermal Cycler	HO30 Hybridization Oven	UVCL254 UV - Crosslinker
TGH12, 24 Tissue Grinder Homogenizer	PBH80T Paddle Blender Homogenizer	TOC2NDir Total Organic Carbon Analyzer	TOC1CD Total Organic Carbon Analyzer	LMDS600, 1200 Microwave Digestion System
HPLC1IS, HPLC2GS High Performance Liquid Chromatography	APT1800 Automatic Potential Titrator	KFT250VC Karl Fischer Titrator	COD1500 COD Analyzer with Digestor	BOD4000 BOD Analyzer
MTVM50 Multi Tube Vortex Mixer	LMVM60D Vortex Mixer	OS20 Orbital Shaker	TRM6 Tube Roller Mixer	DBNE12, 24 Dry Bath Nitrogen Evaporator





LABMAN Product Range 2025-26

DBI11T  Dry Bath Incubator	DBI15SH, DBI16SC  Dry Bath Incubator	IRS14, 35  Infrared Sterilizer	GGA200  Air Generator	GGA301, 302  Hydrogen Generator
GGN303  Nitrogen Generator	GHA304  Hydrogen Air Generator(2 in 1)	LMVP10  Vacuum Pump	LMVP20  Vacuum Pump	LMCO1  Column Oven
LMIO6  Mini Thermostatic Incubator	GHP400  Graphite Hotplate	LOBMS5  Oil Bath Magnetic Stirrer	LMMS4LC, 20LC  Ceramic Hotplate Magnetic Stirrer	LMMS300  Hotplate Magnetic Stirrer
MMS15S  Multiposition Magnetic Stirrer	MMS12H  Multiposition Magnetic Stirrer	WBMS3  Water Bath Magnetic Stirrer	LMWB2H, 4H, 6H, 8H  Digital Water Bath	HOS20L  Overhead Stirrer
LMHH160  Hand Held Homogenizer	PS1565  Peltier / Sipper System	LUV6HG  PMT Spectrophotometer	LUV2000T, 2100T  Single / Double Beam UV-Vis. Spectrophotometer with 21CFR	LMSPUV SERIES  Double Beam UV-Vis. Spectrophotometer

LABMAN Product Range 2025-26

LMSPUV1200  UV-Vis. Single Beam Spectrophotometer	LMSPV320, 325  Visible Spectrophotometer	ADP100CFR, 95CFR  Automatic Digital Polarimeter with CFR	ADP45, 50  Automatic Digital Polarimeter (±45°)	ADP75, 90  Automatic Digital Polarimeter (±90°)
ADP40  Automatic Digital Polarimeter	LMPM180  Manual Polarimeter	MAR100  Manual ABBE Refractometer	RFM100CFR  Digital Refractometer CFR	RFM950, 970  Digital Refractometer
LMAR1317T  ABBE Refractometer	LMDV300H  Digital Viscometer with Thermosel	LMDV60, 100, 200  Digital Viscometer (L Series)	LMDV400R  Digital Viscometer (R Series)	LMKV2  Krebs Viscometer
LMDV111, 222  Digital Viscometer with SSA	LVA30  Low Viscosity Adaptor	LMCR80F  Visual Colorimeter	LMUC2D  Ultrasonic Cleaner	LMUC3D, 6D, 9D, 12D, 25D  Ultrasonic Cleaner - Degas
LMUC50, 100  Industrial Ultrasonic Cleaner	LMPH15  pH Meter with Printer	LMPH12, LMPH10H  pH Meter	LMPH9  pH Meter - Basic	LMCM20H  Conductivity / TDS Meter

LABMAN Product Range 2025-26

LMCM20H  Conductivity / TDS Meter	LMMP30, 32  Multiparameter (7 in 1 / 9 in 1)	LMION40  Ion Meter	LMDO50  Dissolved Oxygen Meter	LMHD60  Water Hardness Meter
OPH11  Online pH Controller	OCM21  Online Conductivity Controller	LMTB200  Turbidity Meter	RCB1010T, 1020T, 1030T  Refrigerated Circulating Bath	RCB620T  Refrigerated Circulating Bath
RWC320  Recirculating Water Chiller	LMDO4P  Portable DO Meter	LMPH1P  Portable pH / ORP Meter	LMCM2P  Portable Conductivity / TDS Meter	LMTB5P  Portable Turbidity Meter
PRO656, 900, 1200, 1800  Probe Sonicator	PRO660R  Probe Sonicator with Remote	PRO650  Probe Sonicator	LMIF30T, 50T, 100T  Ice Flaker	LMIF200T  Ice Flaker
LMIM15  Ice Maker	LMIM20C  Ice Maker with Crusher	ISE19, 62  Nitrate / Fluoride ISEs	ER SERIES  pH Electrode / DO Electrode	CC1, CC2, CC3  Conductivity Cell