



## 16K GOOSENECK TRAILER



### STANDARD FEATURES

- 33" Deck Height
- 2 5/16" Adjustable Gooseneck Coupler
- Brakes on Both Axles
- Oil Bath Hubs
- 8K Axles
- 235/80R16 14 Ply Radial Tires
- Side Step
- Checkered Plate Wheel Covers
- Engineered I-Beam Neck and Main Frame
- 8 Bolt Rims
- 6" Channel Lace Rail
- 4" Channel Crossmembers, 16" O.C.
- 4" Stake Pockets with Rub Rail
- Spare Tire Mount
- Dual 12K Drop Leg Front Jack
- Brown All Weather Treated Deck Boards
- LED Lights
- Braided Wiring Harness
- Drop Stands

### **Pete's Standard Build INCLUDES:**

**Aluminum Rims**  
**Custom Cabinet Style Front Toolbox**  
**Steel Rim Spare Tire**  
**3 3/8 Brake Upgrade**  
**3" Rub Rail**

### SIZES

- 102" Wide x 25'-30' Long

### COUPLERS

- 2 5/16" Adjustable Gooseneck Coupler
- 25K King Pin Gooseneck Coupler

### AXLES

- 2- 8,000# Axles

### TAIL OPTIONS

- 5' Dovetail w/ 5' Mega Style Ramps

### ADDITIONAL OPTIONS

- Aluminum Rims
- Custom Cabinet Style Front Toolbox
- 3" Rub Rail
- Spare Tire
- 3 3/8 Brake Upgrade
- Hydraulic Jack
- Winch Plate

