

DL 14K LOW-PROFILE DUMP PRO

STANDARD FEATURES

THESE ARE THE DEFAULT FEATURES THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

Inside Bed Width: 83"	Deck Height: 28" (24" Optional)	Cargo Capacity: 7.2 yd³ (up to 16.4 yd³)	Dump Angle: 40°
Lengths: 12', 14', 16'	Couplers: Bumper Pull, Gooseneck, & Pintle	Axles: Tandem (2 x 7,000 lb. or 8,000 lb.) or Triple (3 x 7,000 lb.)	Choose the optional 7,000 lb. Electric Drop Axles for an ultra-low 24" bed height.
GVWR: 14,000 - 21,000 lbs.	Load Capacity: 10,400 - 16,750 lbs.	Dump Side Height: 24" (36" & 48" Optional)	



With its sturdy construction and reliable performance, the Seamless I-Beam creates a more robust and dependable frame, ensuring that your dump trailer can handle even the most demanding jobs.

SEAMLESS I-BEAM FRAME DESIGN



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNIWALL STEEL TECHNOLOGY



The Optional Drop Axles provide an additional 4" lower deck height for your dump trailer. With this feature, you can quickly load and unload heavy materials with greater ease and efficiency.

DROP AXLES (OPTIONAL)



The Scissor-Lift Hydraulic System provides efficient lifting capabilities, a stable lifting platform and power-up/power-down functionality for quick dump cycles.

SCISSOR LIFT WITH POWERFUL CYLINDER

PJ TRAILERS

Visit pjtrailers.com for a complete list of trailer options.