



24K GOOSENECK TRAILER



STANDARD FEATURES

- 33" Deck Height
- 2 5/16" Adjustable Gooseneck Coupler
- Brakes on Both Axles
- Oil Bath Hubs
- Tandem Axles
- 215/7R17.5 16 Ply Radial Tires
- Side Step
- Checkered Plate Wheel Covers
- Engineered I-Beam Neck and Main Frame
- 17.5" Galvanized Rims
- 6" Channel Lace Rail
- 4" Channel Crossmembers, 16" O.C.
- 4" Stake Pockets with Rub Rail
- Spare Tire Mount
- Dual 12K Drop Leg Front Jack
- Brown All Weather Treated Deck Boards
- LED Lights
- Braided Wiring Harness
- Drop Stands

SIZES

- 102" Wide x 25'-35' Long

COUPLERS

- 2 5/16" Adjustable Gooseneck Coupler
- 25K King Pin Gooseneck Coupler

AXLES

- 2- 10,000# Axles
- 2- 12,000# Axles

TAIL OPTONS

- 5' Dovetail w/ 5' Mega Style Ramps

ADDITIONAL OPTIONS

- Custom Cabinet Style Front Toolbox
- 3" Rub Rail
- Spare Tire
- Hydraulic Jack
- Winch Plate

Pete's Standard Build INCLUDES:

**Custom Cabinet Style Front Toolbox
Galvanized Rim Spare Tire
3" Rub Rail**

