



14K GOOSENECK TRAILER



STANDARD FEATURES

- 33" Deck Height
- 2 5/16" Adjustable Gooseneck Coupler
- Brakes on Both Axles
- Easy Lube Hubs
- 7K Axles
- 235/80R16 10 Ply Radial Tires
- Side Step
- Checkered Plate Wheel Covers
- Engineered I-Beam Neck and Main Frame
- 8 Bolt Rims
- 6" Channel Lace Rail
- 4" Channel Crossmembers, 16" O.C.
- 4" Stake Pockets with Rub Rail
- Spare Tire Mount
- Dual 12K Drop Leg Front Jack
- Brown All Weather Treated Deck Boards
- LED Lights
- Braided Wiring Harness
- Drop Stands

Pete's Standard Build INCLUDES:

Aluminum Rims
Custom Cabinet Style Front Toolbox
Steel Rim Spare Tire
3" Rub Rail

SIZES

- 102" Wide x 25'-30' Long

COUPLERS

- 2 5/16" Adjustable Gooseneck Coupler
- 25K King Pin Gooseneck Coupler

AXLES

- 2- 7,000# Axles

TAIL OPTIONS

- 5' Dovetail w/ 5' Mega Style Ramps

ADDITIONAL OPTIONS

- Aluminum Rims
- Custom Cabinet Style Front Toolbox
- 3" Rub Rail
- Spare Tire
- 14 Ply Tires
- Hydraulic Jack
- Winch Plate

