

# **GULF FIRE**<sup>®</sup>

## **FIRE EXTINGUISHERS**



**KM 553375**



**0036**

**GULF FIRE FIGHTING EQUIPMENTS FZE**

**P.O.Box 262329 Jebel Ali Free Zone, Dubai , United Arab Emirates**





**Tel: +971 4880 7127 - Fax: +971 4880 7604**

**Email: [gulffirefze@yahoo.com](mailto:gulffirefze@yahoo.com) [www.gulffire.com](http://www.gulffire.com)**







| Model |  |  |  |  |
|-------|---|---|---|---|
| GFP1  | 8 A   | 34 B  | ●   | ●   |
| GFP2  | 13 A  | 70 B  | ●   | ●   |
| GFP4  | 21 A  | 113 B   | ●   | ●   |
| GFP6  | 34 A  | 183 B   | ●   | ●   |
| GFP9  | 43 A  | 233 B   | ●   | ●   |
| GFP12 | 55 A  | 233 B   | ●   | ●   |



The **GULF FIRE®** Dry Powder Fire Extinguishers are manufactured according to the Specifications of **BS EN 3** Part 7, 8, 10 Standard and got certified by **BSI** for **KITEMARK**. The cylinder itself complies with 97/23/EC (PED). It is very efficient in Knocking out the fire and each model has achieved the best Fire rating. All Models comes with wall mounting bracket and models from 4 Kg have strong plastic base.

| ABC DRY POWDER EXTINGUISHER |                             |           |            |            |            |            |
|-----------------------------|-----------------------------|-----------|------------|------------|------------|------------|
| MODEL                       | GFP1                        | GFP2      | GFP4       | GFP6       | GFP9       | GFP12      |
| CAPACITY                    | 1 KG                        | 2 KG      | 4 KG       | 6 KG       | 9 KG       | 12 KG      |
| FIRE RATINGS                | 8A / 34B                    | 13A / 70B | 21A / 113B | 34A / 183B | 43A / 233B | 55A / 233B |
| DISCHARGE TIME (sec)        | 6                           | 11        | 13         | 17         | 29         | 34         |
| DISCHARGE RANGE, APPROX     | 4 -5 m                      | 4 -5 m    | 6 -7 m     | 6 -7 m     | 6 - 8 m    | 6 - 8 m    |
| DIMENSION (H X D)mm         | 333 x 85                    | 400 x 110 | 492 x 135  | 512 x 162  | 585 x 182  | 736 x 182  |
| EXTINGUISHANT               | ABC 40% DRY CHEMICAL POWDER |           |            |            |            |            |
| PROPELLANT                  | NITROGEN                    |           |            |            |            |            |
| TYPE                        | STORED PRESSURE             |           |            |            |            |            |
| CLASS OF FIRE               | A, B, C & ELECTRICAL FIRES  |           |            |            |            |            |
| CYLINDER BODY               | COLD ROLL STEEL SHEET       |           |            |            |            |            |
| OPERATING VALVE             | BRASS                       |           |            |            |            |            |
| TEST PRESSURE               | 27 BAR                      |           |            |            |            |            |
| WORKING PRESSURE            | 14 BAR                      |           |            |            |            |            |
| WORKING TEMPERATURE         | -20° C TO+ 60° C            |           |            |            |            |            |





### Technical Specification:

- Multipurpose Application
- Body Made of Cold Rolled Mild Steel sheet
- Easy Squeeze grip operation
- Controlled Discharge
- High Quality Powder coating with Polyester finish
- Suitable for A, B, C classes of Fires. Safe to use on electrical fires
- Easy to operate as well as to recharge

### Application:

- Warehouse
- Industries
- Commercial Building
- Residential Buildings
- Schools
- Offices
- Automobiles



| Model |  |  |  |  |
|-------|---|---|---|---|
| GFW6  | 13 A  |   |   |   |
| GFW9  | 21 A  |   |   |   |
| GFF6  | 13 A  | 144 B   |   |   |
| GFF9  | 21 A  | 183 B   |   |   |



The **GULF FIRE®** Water based Portable Fire Extinguishers are manufactured & Tested according to the Specifications of **BS EN 3** Part 7, 8,10 & got certified by **BSI** for **KITEMARK**. The cylinder itself complies with 97/23/EC (PED). All Models comes with wall mounting bracket as well as strong plastic base.

| WATER BASED FIRE EXTINGUISHER |                       |           |              |           |
|-------------------------------|-----------------------|-----------|--------------|-----------|
| MODEL                         | GFW6                  | GFW9      | GFF6         | GFF9      |
| CAPACITY                      | 6 L                   | 9 L       | 6 L          | 9 L       |
| FIRE RATINGS                  | 13A                   | 21A       | 13A/144B     | 21A/183B  |
| DISCHARGE TIME (sec)          | 29                    | 35        | 21           | 34        |
| DISCHARGE RANGE, APPROX       | 5 m                   | 6 m       | 5 m          | 6 m       |
| DIMENSION (H X D)mm           | 512 X 162             | 585 X 182 | 512 X 162    | 585 X 182 |
| EXTINGUISHANT                 | WATER                 |           | 3% AFFF FOAM |           |
| PROPELLANT                    | NITROGEN              |           |              |           |
| TYPE                          | STORED PRESSURE       |           |              |           |
| CLASS OF FIRE                 | A                     |           | A , B        |           |
| CYLINDER BODY                 | COLD ROLL STEEL SHEET |           |              |           |
| OPERATING VALVE               | BRASS                 |           |              |           |
| TEST PRESSURE                 | 27 BAR                |           |              |           |
| WORKING PRESSURE              | 14 BAR                |           |              |           |
| WORKING TEMPERATURE           | +5° C TO +60° C       |           |              |           |

### FEATURES:

- Body Made of Cold Rolled Mild Steel sheet
- High Quality Powder coating with Polyester finish
- Polyethylene Internal Lining prevent it from corrosion
- Easy to Operate and also to recharge
- Suitable for fires involving Live electrical equipment

### APPLICATION:





#### WATER GAS FIRE EXTINGUISHERS:

Schools, Industries, Warehouse residential buildings etc.

#### FOAM FIRE EXTINGUISHERS:

Refineries, Oil Storage, Power Plants Paint storage etc.



| Model |  |  |  |  |
|-------|---|---|---|---|
| GFC2  |   | 34 B  |   | •   |
| GFC5  |   | 55B   |   | •   |

The **GULF FIRE®** CO<sub>2</sub> Portable Fire Extinguishers are manufactured & Tested according to the Specifications of **BS EN 3** Part 7, 9 & 10 Standard. It also got certified by **BSI** for **KITEMARK**. Carbon dioxide is a colourless, odourless, non toxic gas which acts as a clean agent while fighting against fire. This specific character made it the best to put off fires in offices which involve computers or other Electronic equipments.

| CO2 FIRE EXTINGUISHER   |                        |             |
|-------------------------|------------------------|-------------|
| MODEL                   | <b>GFC2</b>            | <b>GFC5</b> |
| CAPACITY                | 2 KG                   | 5 KG        |
| FIRE RATINGS            | 34B                    | 55B         |
| DISCHARGE TIME (sec)    | 10                     | 15          |
| DISCHARGE RANGE, APPROX | 4-5 m                  | 5-6 m       |
| DIMENSION (H X D)mm     | 575 x 103              | 750 x 136   |
| EXTINGUISHANT           | CARBON DIOXIDE         |             |
| CLASS OF FIRE           | B & ELECTRICAL FIRES   |             |
| CYLINDER BODY           | CARBON STEEL (34CrMo4) |             |
| OPERATING VALVE         | BRASS                  |             |
| TEST PRESSURE           | 250 BAR                |             |
| WORKING PRESSURE        | 60 BAR                 |             |
| WORKING TEMPERATURE     | -20° C TO +60° C       |             |

### FEATURES:

- Controlled Discharge
- Body Made of Carbon Molybdenum Steel (Seamless)
- High Quality Powder coating with Polyester finish which fight against corrosion
- Suitable for Fires due to Oil, Gas. Safe to use on electrical fires
- Comes with Wall Mounting Bracket
- Easy to Recharge

### APPLICATION:

- Offices
- Restaurants
- Commercial Building
- Residential Buildings
- Laboratories
- Warehouse