Product Model: INNOFLEX F220

Redispersible <u>polymer powder</u> produced by spray-drying special water-based emulsion, mostly based on vinyl acetate and ethylene. It dissolves in water easily and quickly forms emulsion.

Application

- Waterproof mortar
- Tile Adhesive/Tile joint filler
- Flexible waterproof putty

Key properties

- Higher flexural strength
- Excellent waterproof
- Improved workability
- Increased impact and abrasion resistance
- Improve abrasion resistance, durability, wetherability

INNOFLEX F220 is redispersible polymer powder based on vinyl acetate and ethylene copolymer. It provides excellent dispersibility and good compatibility to all kinds of inorganic binders. It can improve the workability in wet mortar. After mortar hardens, it can greatly improve the adhesion and cohesion strength, abrasion resistance, increase flexibility and reduce the crack tendency of mortar.

INNOFLEX F220 is recommended to be used in skim coat, cementitious tile adhesive and tile grout, plaster and render, thin-bed mortar, self-leveling compound and gypsum based compound etc. Recommended dosage is 0.5~3% by total dry mortar weight.

Product properties

Appearance	Free-flow white powder
Bulk density	450 - 650 kg/m ³

PH value of 20% solution	6 - 9
Moisture content	≤ 2.0%
Ash content (calcined at 950°C)	< 15%