**Product Model**: INNOFLEX F418

Redispersible polymer powder produced by spray-drying special water-based emulsion,

mostly based on vinyl acetate and ethylene. It dissolves in water easily and quickly forms

emulsion.

Application

- Waterproof mortar

- Tile Adhesive/Tile joint filler

- Flexible waterproof putty

Key properties

- Higher flexural strength

- Excellent waterproof

- Improved workability

- Increased impact and abrasion resistance

- Improve abrasion resistance, durability, wetherability

INNOFLEX F418 is redispersible polymer powder based on vinyl acetate and ethylene

copolymer. It provides excellent dispersibility and good compatibility to all kinds of

inorganic binders. It can improve the workability in wet mortar. After mortar hardens, it can

greatly improve the adhesion and cohesion strength, abrasion resistance, increase

flexibility and reduce the crack tendency of mortar.

INNOFLEX F418 is highly recommended to be used in high end tile adhesive, which shows

excellent adhesion strength under all kinds of conditions. It can also be used in skim coat,

plaster and render, thin-bed mortar, self-leveling compound and gypsum based compound

etc. Recommended dosage is 0.5~10% by total dry mortar weight.

**Product properties** 

Appearance	Free-flow white powder
Bulk density	450 - 650 kg/m <sup>3</sup>
PH value of 20% solution	6 - 9
Moisture content	≤ 2.0%
Ash content (calcined at 950°C)	12±2%