

Baudouin 400-550 kVA

50 Hz Diesel Generator Set



Power



Images are for illustration purpose only

### ENGINE

BAUDOUIN heavy duty diesel engine  
4-cycle, water cooled, turbocharged

Direct injection

12/24 Volt starter and charge  
alternator with battery, rack and  
cables

Replaceable air, fuel and oil filter

Industrial type radiator

Flexible fuel piping

Oil sump drain valve and extension  
pipe

Industrial/Residential type exhaust  
silencer.

Jacket Water Heater

Diesel gen-set maintenance and  
operating instructions and electrical  
circuit diagram

### ALTERNATOR

Brushless, single bearing, 4-pole  
alternator coupled with flexible disc  
coupling

H type insulation class

IP 23 protection

Self exciting

Electronic AVR

### CONTROL PANEL

DeepSea mains sensing or remote  
start control module

Emergency stop push button

Output circuit breaker

Static battery charger

Ready for remote monitoring

### CANOPY

Modular type sound-proof canopy

Built from galvanized steel and epoxy,  
polyester powder painted

Lockable doors on both sides of  
canopy designed for easy access to  
essential replacement parts

Emergency stop push button

Control Panel viewing window

Bunded base fuel tank (Optional)

Forklift Pockets (Optional)

Power cable entry with a gland plate

### Standby Power

Applicable for supplying  
power to varying electrical  
load for the duration of  
power interruption of a  
reliable utility source,  
Overload is not allowed.

### Prime Power

The maximum power  
which a generating set is  
capable of delivering con-  
tinuously whilst supplying  
a variable electrical load.  
Average load should be  
70%.The generator can  
be overloaded 10% for 1  
hour per 12 hrs.

### Base Power

Continuous power rating  
is used in applications  
where supplying power is  
at a constant 100% load  
for an unlimited number  
of hours each year.



EA Power Systems reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice

EA Power Systems Ltd.

207 Dominion Rd. LE36QA Leicester United Kingdom

www.eapowers.com +44(0)1163180570

Registered in England & Wales No:11023250

MOTEURS  
**Baudouin**



| MODEL      |  | EAB400   | EAB440             | EAB500             | EAB550             |                    |
|------------|--|----------|--------------------|--------------------|--------------------|--------------------|
| OUTPUT     | Standby                                | kVA      | 400                | 440                | 500                | 550                |
|            |  | kW       | 320                | 352                | 400                | 440                |
|            | Prime                                  | kVA      | 364                | 400                | 450                | 500                |
|            |  | kW       | 291                | 320                | 360                | 400                |
| ENGINE     | Engine                                 |          | BAUDOUIN           | BAUDOUIN           | BAUDOUIN           | BAUDOUIN           |
|            | Model                                  |          | 6M21G385/5         | 6M21G440/5         | 6M21G500/5         | 6M26G550/5         |
|            | Configuration                          |          | INLINE             | INLINE             | INLINE             | INLINE             |
|            | No. of Cylinders                       |          | 6                  | 6                  | 6                  | 6                  |
|            | Speed                                  | rpm      | 1500               | 1500               | 1500               | 1500               |
|            | Displacement                           | l        | 12.54              | 12.54              | 12.54              | 15.9               |
|            | Bore x Stroke                          | mm       | 127 x 165          | 127 x 165          | 127 x 165          | 150 x 150          |
|            | Compression Ratio                      |          | 16:1               | 16:1               | 16:1               | 15.7:1             |
|            | Aspiration                             |          | Turbocharged       | Turbocharged       | Turbocharged       | Turbocharged       |
|            | Governor Type                          |          | Electronic         | Electronic         | ECU                | Electronic         |
|            | Cooling                                |          | Water              | Water              | Water              | Water              |
|            | Coolant Capacity                       | l        | 55                 | 55                 | 55                 | 110.7              |
|            | Lubrication Oil Capacity               | l        | 30                 | 30                 | 30                 | 52                 |
|            | Fuel Consumption l/h                   | 100%Load | 82                 | 85.5               | 110.2              | 106.8              |
| 75% Load   |  | 61       | 63.5               | 82.65              | 79.8               |                    |
| 50%Load    |  | 41       | 43.2               | 55.1               | 54.5               |                    |
| ALTERNATOR | Phase                                  |          | 3                  | 3                  | 3                  | 3                  |
|            | Pole                                   |          | 4                  | 4                  | 4                  | 4                  |
|            | No. of Leads                           |          | 12                 | 12                 | 12                 | 12                 |
|            | Excitation System                      |          | AVR                | AVR                | AVR                | AVR                |
|            | Insulation Class                       |          | H                  | H                  | H                  | H                  |
|            | IP Protection                          |          | IP23               | IP23               | IP23               | IP23               |
|            | Power Factor                           |          | 0.8                | 0.8                | 0.8                | 0.8                |
|            | Frequency                              | Hz       | 50                 | 50                 | 50                 | 50                 |
|            | Voltage                                | V        | 400                | 400                | 400                | 400                |
| SIZE       | Canopy Set Dimensions (LxWxH) & Weight | mm       | 3705 x 1400 x 2645 | 3705 x 1400 x 2645 | 4400 x 1700 x 2960 | 4400 x 1700 x 2960 |
|            |  | kg       | 4291               | 4427               | 5425               | 6756               |
|            | Open Set Dimensions (LxWxH) & Weight   | mm       | 3450 x 1400 x 1885 | 3450 x 1400 x 1885 | 4000 x 1700 x 2210 | 4000 x 1700 x 2210 |
|            |  | kg       | 3844               | 3980               | 4685               | 6016               |
|            | Fuel Tank Capacity                     | l        | 880                | 880                | 1272               | 1272               |

EA Power Systems reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice

EA Power Systems Ltd.

207 Dominion Rd. LE36QA Leicester United Kingdom

www.eapowers.com +44(0)1163180570

Registered in England & Wales No:11023250



### CONTROL MODULE

DSE 7 Series Control Module

State of the art, microprocessor controlled

4line, 64 x 132 pixel display LCD display

Automatic mains failure sensing

Front panel manual programming

User friendly setup and button layout

Remote start

Event logging, showing date and time

Stop/Reset, Manual

#### Displays

Engine Speed (rpm)

Oil pressure

Fuel Level (%)

Coolant temperature

Running Hours

Battery voltage monitoring

Generator Voltage (LL. LN)

Generator Current (L1-L2-L3)

Generator Frequency (Hz)

Generator Load & Power Monitoring (kW. kVA. kVAR.

pf)

Mains Voltage (LL. LN)

Mains Frequency

Generator Set Ready

Mains Ready



#### Alarms

High coolant temperature

Low Fuel Level

Low oil pressure

Charge failure

Battery Low/High voltage

Fail to start

Fail to stop

High/Low Generator voltage

Generator Over/Under frequency

Generator Over/Under Speed