



SCAN TOOL POSITION STATEMENT

FCA US LLC vehicles, systems and components are engineered, tested and manufactured to help protect vehicle occupants. They are engineered to meet or exceed both government mandated and internal corporate requirements relative to durability, NVH (noise vibration and harshness) and vehicle safety. Use of the Mopar® wiTECH vehicle diagnostic tester (Mopar Scan Tool) is an important part of FCA US vehicle service and maintenance. This tool contains software that aftermarket tools may not contain and can assess whether any FCA US vehicle's safety and security systems contain active or stored Diagnostic Trouble Codes (DTCs).

Safety and security related systems, such as antilock brakes, supplemental restraint systems (SRS - air bags), occupant restraint controller (ORC), seat belts, active head restraints, forward facing camera and radar, blind spot monitoring, and other automated electronic driver assistance systems, **MUST** be tested for fault codes (DTCs) that could be active (current) or stored following a collision. Use of the Mopar wiTECH vehicle diagnostic tester is necessary before and after collision repair.

ANY of the following conditions could trigger DTCs prior to or during collision repairs, which could result in improper vehicle performance:

- ▶ Vehicle is involved in an accident or collision, even though the damage may appear minor
- ▶ Vehicle has been in an accident with or without air bag deployment
- ▶ Voltage loss, including battery disconnects and hybrid battery disabling
- ▶ Significant vehicle disassembly including, but not limited to, bumpers, door handles, headlamps and mirrors
- ▶ Interior trim repair or removal
- ▶ Glass removal and replacement operations

Any repairs performed without using Mopar parts and not following published repair guidelines and procedures, may expose current or future vehicle owners and occupants to unnecessary risk.

If faults were stored in the DTC memory for any safety or security system, then these systems **MUST** be serviced according to the repair procedures in Service Information. After performing repairs, recheck the system to determine if any active or stored DTCs remain; if so, take appropriate service action to ensure proper function.

SRS AIR BAG SQUIB STATUS

Multistage air bags with multiple initiators (squibs) **MUST** be checked to determine that all squibs were used during the deployment event. The Driver Air Bag (DAB) and Passenger Air Bag (PAB) are deployed by electrical signals generated by the Occupant Restraint Controller (ORC) through the driver or passenger squib circuits (up to 3) to the initiators in the air bag inflators. Typically, all initiators are exhausted and all potentially hazardous chemicals are burned during an air bag deployment event.

However, it is possible for only one initiator to be exhausted; therefore, you **MUST** always confirm that all initiators have been cycled to minimize the risk of improper handling or disposal of potentially live pyrotechnic or hazardous materials. This procedure must be performed using the Mopar wiTECH diagnostic scan tool or at a company such as Collision Diagnostic Services that diagnostically remotely scans the vehicle using FCA US scan tools in conjunction with their patented asTech device, to verify the status of all air bag squibs, prior to removing deployed air bags from the vehicle for disposal.

- ▶ Service Information can be obtained at www.oem1stop.com
- ▶ Mopar wiTECH scan tools can be purchased from <https://mopar.snapon.com>

