

4619 S. 139th Street | Omaha, NE. | 68137 402.550.8873 | 402.203.8916

www.velcondrumfilling.com

SHEET 1 OF 2 (SELECT TAB AT BOTTOM WHEN COMPLETE)

LIQUID FILLING SYSTEMS APPLICATION FORM						
COMPANY NAME:			NAME:			
ADDRESS 1:			PHONE:			
ADDRESS 2:			FAX:			
CITY/STATE/ZIP:			EMAIL:			
FILLING METHOD (Check all that apply)						
SINGLE		PALLETIZED			TOTE/	
CONTAINER		CONTAINER			IBC	
WETTED PARTS (Check all that apply)						
316SS		316SS			CORROSIVE	
PIPE		SANITARY			PRODUCTS	
PRODUCT CHARACTERISTICS (Check all that apply)						
FLAMMABLE		FOAMY			HIGH	
FLAMMABLE		POAMI			TEMPERATURE	
PRODUCTION AREA ELECTRICAL CLASSIFICATION (Check all that apply)						
GENERAL		CLASS-I			CLASS-I	
PURPOSE		DIVISION-II			DIVISION-I	
PRODUCTION AREA ENVIRONMENT (Check all that apply)						
INDOORS		WASHDOWN			CLEAN	
INDOOKS		WASHDOWN			ROOM	
SAFETY REQUIREMENTS (Check all that apply)						
CONTAINER		NITROGEN			VAPOR	
GROUNDING		INERTING			COLLECTION	
PRODUCTS VISCOSITY RANGES Cp (Check all that apply)						
1 TO 15	WATER	200 TO 500		40W. OIL	3,000 TO 5,000	
15 TO 100	10W. OIL	500 TO 2,000		60W. OIL	5,000 TO 10,000	
100 TO 200	30W. OIL	2,000 TO 3,000		HONEY	10,000 TO 25,000	
PRODUCTION REQUIREMENTS						
REQUIRED PRODUCTION RATE: (GAL/HR)			NUMBER OF PRODUCTS:			
COMMENTS						

List any special requirements and product characteristics under "COMMENTS".

electronic: velcon@velcondrumfilling.com Return completed form

402.550.8873 printed: