



- Superior sound attenuation & shock insulation
- Tight seam lines provide superior aesthetics
- Drop free weights directly onto the floor!
- Maintenance Free



Engineered for PERSONAL BESTS.

Virtually indestructible, duraTRAIN rubber fitness flooring tiles are designed for a range of applications, from heavy use fitness facilities to high impact health clubs, offering superior sound insulation. Our interlocking design and proprietary manufacturing process are the result of extensive testing and engineering backed by a best-in-industry Limited Lifetime Warranty.





You built your facility to last. Protect your investment with duraTRAIN rubber fitness flooring tiles by sofSURFACES. When we developed our fitness tile nine years ago, we set our sights on a sophisticated interlocking yet attractive flooring solution to handle any heavy use environment. Today, duraTRAIN rubber fitness tiles (formerly DuraFLEX) are being rigorously tested in Division 1 schools, fitness gyms and crossfit facilities all over the world. At 1.25" thick, duraTRAIN delivers the best in sound and shock insulation backed by the muscle of sofSURFACES' new industry-leading Lifetime Guarantee.

- Superior sound attenuation and shock insulation
- New Best-In-Industry Lifetime Warranty
- Available in 6 standard colors and an infinite range of premium custom color blends
- Innovative Patented KROSLOCK Tile-Locking System
- Maintenance Free
- Drop free weights directly onto the floor
- Tight seam lines provide superior aesthetics



PHYSICAL DIMENSIONS

Size	Thickness	Weight (lbs.) Ea.	sofRAMP Length
24" x 24"	1.25" <small>(other thicknesses available)</small>	PLUS - 19.30 HYBRID - 19.90 <small>(with 40% TPV)</small>	47.75"

PHYSICAL PROPERTIES

Test Description	ASTM Ref.	Results	Test Lab	Test Date
Acoustical A09-009	EC423/E795	SAA=0.14, NRC=0.15	RAL	01-09
Acoustical TL08-363	E90/E413	STC=53	RAL	12-08
Acoustical E492/E989	E492/E989	IIC=59	RAL	12-08
Acoustical IFC09-002	E2179	Delta IIC 26 IICc 54	RAL	01-09
Freeze/Thaw	C67	No deterioration	SGS	12-98
Rubber Deterioration/Air Oven	D573	No deterioration	SGS	12-98
Slip Resistance	E303	Dry 102/Wet 62	SGS	09-98
Slip Resistance	D2047	Dry 0.81/Wet 0.82	SGS	02-99
Compression Deflection	D1667	29.5 PSI to 25% Compression	NWL	01-95
Compression Set	D395	4.37% Permanent Set	NWL	01-95
Tensile Strength	D412	107 PSI	SGS	02-99
Elongation at Break	D412	165%	SGS	02-99
Tear Strength	D624	33.1 Lbs/Inch	SGS	02-99
Wear Surface Density (Durability)		>60 lbs/CuFt		

duraTRAIN is manufactured to a dimension of 24" x 24" and compressed during installation to a dimension of 23 15/16" x 23 15/16".

Available in 6 standard colors and an infinite range of hybrid custom color blends. **Customer-Favorite Hybrid color blends shown above** (choose from 15 colors).

Visit our new custom color mixer at:
sofSURFACES.com

* **FloorScore®** is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesives products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.