

VAPOR STRYKER SLAT TREADMILL



TRUE heritage and engineering come together to provide your facility with the TRUE Stryker Slat Treadmill. The Stryker features a running surface of vulcanized rubber slats that are more durable and require less maintenance than the conventional conveyor belt system of traditional treadmills. The individual shock-absorbing slats provide a running surface closer to the natural feel of outdoor running for those looking for a more realistic training experience.

FEATURES

- Less downtime and overall lower cost-of-ownership than traditional treadmill
- Requires less maintenance; no need for tracking adjustments, waxing, or flipping of deck with slat system
- Ergonomic pistol-grip handles with thumb controls and center pod with quick speed and incline keys
- Over-molded rubber slat belt with 62 individual slats and running surface of 22"/55 cm x 60"/152 cm
- Three emergency stops for safety (on console, center pod, and safety key)

SPECIFICATIONS

DIMENSIONS (L X W X H)
72" L x 35" W x 64" H /
182 cm x 89 cm x 163 cm

SPEED
1 to 12.0 MPH / 1.6 to 19.3 KPH (0.5 increments)

INCLINE/DECLINE RANGE
0% to 25% (-3% to 22% with Decline Kit)

PRODUCT WEIGHT
599 lbs / 271.7 kg

COLOR
Matte Black

CONSOLE OPTIONS



**UNITE 16"
TOUCHSCREEN**




**UNITE 10"
TOUCHSCREEN**



**UNITE LED
LED CONSOLE**



Easy-access quick-touch keys



Running Surface

VAPOR STRYKER SLAT TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	120V ₁₆ A Dedicated (NEMA 5-20 Receptacle) 220-240V ₆ A Option Available	
	Cord Length	12' / 3.7 M	
	Power Factor Correction (PFC)	Standard	
	Resistance Source	Double-Braking System	
	Incline Motor	1,200 lbs. of thrust	
	Speed Sensor	Optical	
	Slat	62 vulcanized rubber slats - durometer of 75 shore	
	End Rollers	58 mm diameter with shielded bearings	
	Slatbelt Support Bearings	22 mm diameter with sealed bearings	
	Frame Construction	Robotically Welded Heavy-Gauge Steel	
	Speed Range	1 to 12.0 MPH / 1.6 to 19.3 KPH	
	Incline/Decline Range	0% to 25% (-3% to 22% with Decline)	
	Quick Access Control	Mechanical thumb switches and center pod with quick keys (speed and incline) as well as emergency stop	
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips	
	Contact Heart Rate Monitoring	Yes	
	Wireless Heart Rate Monitoring	Polar® Compatible Bluetooth	
	User Detection	Person Present Detection	
	AVAILABLE CONSOLES	Unite 16", Unite 10", and Unite LED	
	WORKOUTS	Unite 16" and Unite 10" Consoles	10K, 5K, AIR FORCE, ARMY, CALORIE GOAL, CARDIO CHALLENGE, DISTANCE GOAL, DRAW YOUR OWN, GERKIN, HALF MARATHON, HILL INTERVALS, HRC CRUISE CONTROL, LEG SHAPER, MARINES, MONUMENT WORKOUT, NAVY, PEB, QUICK START, ROLLING HILLS, SINGLE HILL, SPEED INTERVALS, TARGET HRC, TIME GOAL VIRTUAL RUNS, WEIGHT LOSS HILL
		LED Console	10K, 5K, CALORIE GOAL, CARDIO CHALLENGE, DISTANCE GOAL, GERKIN, HALF MARATHON, HILL INTERVALS, HRC CRUISE CONTROL, LEG SHAPER, QUICK START ROLLING HILLS, SINGLE HILL, TARGET HRC, TIME GOAL, and WEIGHT LOSS HILL
EXTRAS	Accessories	Water Bottle Holders, Accessory Tray, Reading Rack/Tablet Holder	
PHYSICAL SPECIFICATIONS	Dimensions	72" L x 35" W x 64" H / 182 cm x 89 cm x 163 cm	
	Running Surface	22" / 55 cm x 60" / 152 cm	
	Machine Weight	599 lbs / 271.7 kg	
	Shipping Weight	649 lbs / 294.3 kg	
	Maximum User Weight	500 lbs / 226.7 kg	
	Deck Step-Up Height	13" / 33.02 cm	
	Portability	Rear Retractable	
WARRANTY	Frame	7 Years	
	Parts	3 Years	
	Labor	2 Years	

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

